



United States Nuclear Regulatory Commission

Protecting People and the Environment

NUREG/CR-7028

Volume 2

Engineered Covers for Waste Containment: Changes in Engineering Properties and Implications for Long-Term Performance Assessment – Appendices

**AVAILABILITY OF REFERENCE MATERIALS
IN NRC PUBLICATIONS**

NRC Reference Material

As of November 1999, you may electronically access NUREG-series publications and other NRC records at NRC's Public Electronic Reading Room at <http://www.nrc.gov/reading-rm.html>. Publicly released records include, to name a few, NUREG-series publications; *Federal Register* notices; applicant, licensee, and vendor documents and correspondence; NRC correspondence and internal memoranda; bulletins and information notices; inspection and investigative reports; licensee event reports; and Commission papers and their attachments.

NRC publications in the NUREG series, NRC regulations, and *Title 10, Energy*, in the Code of *Federal Regulations* may also be purchased from one of these two sources.

1. The Superintendent of Documents
U.S. Government Printing Office
Mail Stop SSOP
Washington, DC 20402-0001
Internet: bookstore.gpo.gov
Telephone: 202-512-1800
Fax: 202-512-2250
2. The National Technical Information Service
Springfield, VA 22161-0002
www.ntis.gov
1-800-553-6847 or, locally, 703-605-6000

A single copy of each NRC draft report for comment is available free, to the extent of supply, upon written request as follows:

Address: U.S. Nuclear Regulatory Commission
Office of Administration
Publications Branch
Washington, DC 20555-0001
E-mail: DISTRIBUTION.RESOURCE@nrc.gov
Facsimile: 301-415-2289

Some publications in the NUREG series that are posted at NRC's Web site address <http://www.nrc.gov/reading-rm/doc-collections/nuregs> are updated periodically and may differ from the last printed version. Although references to material found on a Web site bear the date the material was accessed, the material available on the date cited may subsequently be removed from the site.

Non-NRC Reference Material

Documents available from public and special technical libraries include all open literature items, such as books, journal articles, and transactions, *Federal Register* notices, Federal and State legislation, and congressional reports. Such documents as theses, dissertations, foreign reports and translations, and non-NRC conference proceedings may be purchased from their sponsoring organization.

Copies of industry codes and standards used in a substantive manner in the NRC regulatory process are maintained at—

The NRC Technical Library
Two White Flint North
11545 Rockville Pike
Rockville, MD 20852-2738

These standards are available in the library for reference use by the public. Codes and standards are usually copyrighted and may be purchased from the originating organization or, if they are American National Standards, from—

American National Standards Institute
11 West 42nd Street
New York, NY 10036-8002
www.ansi.org
212-642-4900

Legally binding regulatory requirements are stated only in laws; NRC regulations; licenses, including technical specifications; or orders, not in NUREG-series publications. The views expressed in contractor-prepared publications in this series are not necessarily those of the NRC.

The NUREG series comprises (1) technical and administrative reports and books prepared by the staff (NUREG-XXXX) or agency contractors (NUREG/CR-XXXX), (2) proceedings of conferences (NUREG/CP-XXXX), (3) reports resulting from international agreements (NUREG/IA-XXXX), (4) brochures (NUREG/BR-XXXX), and (5) compilations of legal decisions and orders of the Commission and Atomic and Safety Licensing Boards and of Directors' decisions under Section 2.206 of NRC's regulations (NUREG-0750).

DISCLAIMER: This report was prepared as an account of work sponsored by an agency of the U.S. Government. Neither the U.S. Government nor any agency thereof, nor any employee, makes any warranty, expressed or implied, or assumes any legal liability or responsibility for any third party's use, or the results of such use, of any information, apparatus, product, or process disclosed in this publication, or represents that its use by such third party would not infringe privately owned rights.



United States Nuclear Regulatory Commission

Protecting People and the Environment

NUREG/CR-7028
Volume 2

Engineered Covers for Waste Containment: Changes in Engineering Properties and Implications for Long-Term Performance Assessment – Appendices

Prepared by:

C.H. Benson¹, W.H. Albright², D.O. Fratta¹, J.M. Tinjum¹,
E. Kucukkirca¹, S.H. Lee¹, J. Scalia¹, P.D. Schlicht¹, and X. Wang¹,

¹Geological Engineering
University of Wisconsin-Madison
1415 Engineering Drive
Madison, WI 53706

²Desert Research Institute
2215 Raggio Parkway
Reno, NV 89512

Manuscript Completed: July 2010

Date Published: December 2011

Jacob Philip, NRC Project Manager

NRC Job Code N6366

Office of Nuclear Regulatory Research

ABSTRACT

This peer-reviewed study demonstrates that engineering properties of cover soils change while in service and that long-term engineering properties should be used as input to models employed for performance assessments. Recommendations for appropriate input are made based on the data that were collected. Increases in the saturated hydraulic conductivity, saturated volumetric water content, and the air entry suction (as characterized by van Genuchten's α parameter) occurred due to formation of soil structure, regardless of climate, cover design, or service life. Substantial changes in hydraulic conductivity were observed in some geosynthetic clay liners (GCLs) that did not hydrate completely and underwent cation exchange. Changes in geomembranes and geosynthetic drainage layers were modest or small, and computations based on antioxidant depletion rates suggest that the minimum service life of geomembranes is on the order of 50-125 yrs (the actual service life will be longer). The findings indicate that covers should be monitored to ensure that they are functioning as intended. Monitoring using pan lysimeters combined with secondary measurements collected for interpretive purposes is recommended. Future research investments should include an evaluation of remote sensing technologies for cover monitoring and analog studies to estimate properties of earthen and geosynthetic cover materials corresponding to service lives of 100s to 1000s of years.

CONTENTS

Abstract.....	iii
Executive Summary	xv
Acknowledgement.....	xvii
Abbreviations	xix
1. Introduction	1-1
2. Background: ACAP Test Sections.....	2-1
2.1 ACAP Lysimeters.....	2-6
2.2 Data Collection.....	2-6
2.3 Calibration and Data Quality Control.....	2-8
2.4 Cover Soils.....	2-8
2.5 Geosynthetics.....	2-8
3. Exhumations	3-1
3.1 Soil Sampling and Field Testing	3-1
3.2 Sampling of Geosynthetics.....	3-6
3.3 Geomorphological Surveys.....	3-6
3.4 Geophysical Surveys	3-6
4. Field Test Methods.....	4-1
4.1 Sealed Double-Ring Infiltrometer Tests	4-1
4.2 Borehole Tests	4-1
4.3 Hydraulic Conductivity from Peak Lysimeter Flow Rates	4-2
5. Laboratory Test Methods	5-1
5.1 Hydraulic Properties of Earthen Materials.....	5-1
5.2 Properties of Geosynthetic Clay Liners.....	5-1
5.2.1 Saturated Hydraulic Conductivity	5-1
5.2.2 Swell Index	5-2
5.2.3 Soluble Cations, Bound Cations, and Cation Exchange Capacity	5-2
5.2.4 Subgrade Soils	5-3
5.3 Properties of Geomembranes and Geosynthetic Drainage Layers	5-3
5.3.1 Tensile Strength of Geomembranes.....	5-3
5.3.2 Ply Adhesion of Geosynthetic Drainage Layers	5-3
5.3.3 Interface Shear Strength	5-3
5.3.4 Hydraulic Properties	5-4
5.3.5 Melt Flow Index and Oxidation Induction Time	5-4
6. Earthen Barrier and Storage Layers.....	6-1
6.1 Soil Characteristics.....	6-1
6.2 Field Hydraulic Conductivity	6-6
6.3 Laboratory Hydraulic Conductivity	6-10
6.4 Comparison of In-Service and As-Built Hydraulic Conductivity	6-12
6.5 Factors Affecting Changes in Hydraulic Conductivity.....	6-18

6.5.1 Service Life	6-18
6.5.2 Climate	6-18
6.5.3 Soil Composition	6-22
6.5.4 Compaction Conditions	6-22
6.5.5 Effect of Freeze-Thaw and Wet-Dry Cycles	6-28
6.6 Soil Water Characteristic Curves	6-31
6.7 Summary of Findings for Earthen Storage and Barrier Layers	6-38
7. Geosynthetic Clay Liners	7-1
7.1 Background on GCLs	7-3
7.2 Properties of Exhumed GCLs	7-4
7.2.1 GCL Water Content and Cation Exchange	7-4
7.2.2 Hydraulic Conductivity	7-8
7.2.3 Effect of Subgrade Condition	7-11
7.2.4 Service Life and Cover Soil Thickness	7-15
7.3 Key Factors to Successful GCL Performance	7-15
7.4 Summary of Findings for GCLs	7-22
8. Geomembranes and Geosynthetic Drainage Layers	8-1
8.1 Properties of Geomembranes	8-1
8.1.1 Tensile Strength	8-1
8.1.2 OIT and MFI	8-6
8.2 Properties of Geocomposite Drainage Layer	8-11
8.2.1 Transmissivity	8-11
8.2.2 Permittivity	8-16
8.2.3 Ply Adhesion	8-16
8.3 Interface Shear Strength	8-21
8.4 Reduction Factors for Design	8-21
8.5 Summary of Findings for Geomembranes and Drainage Layers	8-26
9. Geophysical Evaluation	9-1
9.1 Electrical Resistivity Surveys	9-1
9.2 Ground Penetrating Radar Surveys	9-8
9.3 Summary of Findings from Geophysical Surveys	9-15
10. Practical Implications for Design, Performance Assessment, and Monitoring	10-1
10.1 Design Conditions	10-2
10.2 Parameters for Performance Assessments	10-3
10.3 Monitoring	10-4
10.3.1 Performance Monitoring	10-5
10.3.2 Interpretive Monitoring	10-8
10.3.3 Recommended Practice for Final Cover Monitoring	10-11
11. Conclusions and Recommendations	11-1
12. References	12-1
Appendices (Volume 2)	
Appendix A Exhumation Photo Gallery	A-1
Appendix B Sealed Double-Ring Infiltrometer (SDRI) Data	B-1
Appendix C TSB Data	C-1

Appendix D	Laboratory Hydraulic Conductivity Data	D-1
Appendix E	Soil Water Characteristic Curve Test Data	E-1
Appendix F	Statistical Analyses of Hydraulic Conductivity Data	F-1
Appendix G	Methods Used in Chemical Analyses of Geosynthetic Clay Liners	G-1
Appendix H	Test Methods for Measuring Soluble Cations, Bound Cations, and Cation Exchange Capacity	H-1
Appendix I	Schematic and Photograph of Hydraulic Conductivity Test Set-Up for Geosynthetic Clay Liners (GCLs)	I-1
Appendix J	Exhumed Subgrade Porewater Chemistries	J-1
Appendix K	Exhumed GCLs Water Content, Bound Cations, and Soluble Cations	K-1
Appendix L	Hydraulic Conductivity Records for Exhumed GCLs	L-1
Appendix M	Field Exhumation Photographs and Observations	M-1
Appendix N	Laboratory Testing Photography and Observations	N-1
Appendix O	Exploration of GCL Laboratory Testing Methods	O-1
Appendix P	Supplemental Graphs and Tables from Geosynthetic Membrane (GM) and Geosynthetic Drainage Layer (GDL) Tests	P-1
Appendix Q	Photographs of GM and GDL Testing Data	Q-1
Appendix R	GM Test Data	R-1
Appendix S	GDL Test Data	S-1

List of Figures

Fig. 2.1.	Locations of ACAP field sites. Sites exhumed in this study marked with a star.	2-2
Fig. 2.2.	Profiles of conventional covers evaluated by ACAP.	2-3
Fig. 2.3.	Profiles of store-and-release covers evaluated by ACAP.	2-4
Fig. 2.4.	Schematic of ACAP lysimeter (not to scale).	2-7
Fig. 3.1.	Profiles of the final covers at full-scale MSW landfills in Wisconsin (Site E) and Michigan (Site F). GDL = geosynthetic drainage layer, GM = geomembrane, and GCL = geosynthetic clay liner. Service life of Wisconsin site is 4.7-5.8 yr (depending on test pit). Service life of Michigan site is 3.1 yr.	3-2
Fig. 3.2.	BH test conducted during exhumation of ACAP test section in Helena, MT.	3-3
Fig. 3.3.	SDRI test conducted at ACAP test facility in Polson, MT. Upper photograph shows inner and outer rings after installation. Lower photograph shows filled SDRI with Mariotte bottle in the rear.	3-4
Fig. 3.4.	Block sample being collected at ACAP test facility in Underwood, ND. Upper photograph shows sample partially trimmed into ring. Lower photograph shows sample in ring and ready for separation from subgrade.	3-5
Fig. 3.5.	Removing cover soils over a composite barrier layer (a) and removing a sample of geosynthetic drainage layer (b). Both photographs are from final cover at Wisconsin MSW landfill.	3-7
Fig. 3.6.	Exhumation of GCL samples: cutting around perimeter with razor knife (a) and delicately sliding sample onto rigid plastic plate (b).	3-8
Fig. 3.7.	Typical setup for evaluating punctures in geomembranes using electrical resistivity measurements (after Frangos 1997, Darilek and Miller 1998).	3-9
Fig. 3.8.	Typical voltage drop over a hole in a geomembrane hole: experimental measurements and theoretical response (from Parra 1988).	3-11
Fig. 3.9.	Common mid-point (a) and reflection survey (b) setup configuration for GPR.	3-12
Fig. 3.10.	Downhole setup for GPR.	3-13
Fig. 6.1.	Plasticity chart showing Atterberg limits of storage and barrier layers evaluated in this study.	6-3
Fig. 6.2.	Field hydraulic conductivity determined by SDRIs and BHs from each cover type (a) and hydraulic conductivity from SDRIs versus hydraulic conductivity from BHs for individual test sections (b).	6-8

Fig. 6.3. Saturated hydraulic conductivity from SDRI and BH tests (a) and laboratory tests on 305, 150 and 75 mm diameter specimens for each cover type (b). The solid line within the box represents the median, the box encloses 50% of the data, and outliers are indicated with a circle. 6-9

Fig. 6.4. Saturated hydraulic conductivity of large-scale (305 mm) laboratory specimens versus small-scale (150 and 75-mm-diameter) laboratory specimens. 6-13

Fig. 6.5. Field hydraulic conductivity from SDRI and BH versus large-scale (305 mm) laboratory saturated hydraulic conductivity (a) and small scale (150 and 75-mm) laboratory saturated hydraulic conductivity (b). 6-14

Fig. 6.6. Saturated hydraulic conductivity versus effective diameter for t Altamont store-and-release cover (a) and Apple Valley clay barrier (b). Trend lines drawn by hand. 6-15

Fig. 6.7. In-service saturated hydraulic conductivity (K_{si}) versus as-built hydraulic conductivity (K_{sa}) by site (a) and cover type (b). “?” signifies apparent outliers. 6-17

Fig. 6.8. Saturated hydraulic conductivity ratio (K_{si}/K_{sa}) versus as-built saturated hydraulic conductivity (K_{sa}). Trend lines drawn by hand. “?” signifies outliers. 6-19

Fig. 6.9. Saturated hydraulic conductivity ratio versus service life of test section. Trend lines drawn by hand. 6-20

Fig. 6.10. Saturated hydraulic conductivity ratio versus climate presented by cover type. 6-21

Fig. 6.11. Saturated hydraulic conductivity ratio versus plasticity index (a), clay content ($< 2 \mu\text{m}$) (b), and activity (c). $\text{PI} = 0$ indicates soil is non plastic. . 6-23

Fig. 6.12. Saturated hydraulic conductivity versus coarse fraction ($\% > 75 \mu\text{m}$) over clay content ($\% < 2 \mu\text{m}$) (a) and ratio of silt content ($\%$ between 2 and 75 μm) to fines content ($\% < 75 \mu\text{m}$) (b). 6-25

Fig. 6.13. Saturated hydraulic conductivity ratio versus as-built compacted dry unit weight by site (a) and cover type (b). 6-27

Fig. 6.14. Saturated hydraulic conductivity ratio versus water content relative to optimum water content. 6-29

Fig. 6.15. Saturated hydraulic conductivity ratio versus number of freeze-thaw cycles (a) and number of wet-dry cycles (b). 6-30

Fig. 6.16. In-service α parameter versus as-built α parameter (a) and in-service n parameter versus as-built n parameter (b). 6-35

Fig. 6.17.	In-service saturated volumetric water content versus as-built saturated volumetric water content.	6-36
Fig. 6.18.	The ratio of α (a) and n (b) from large-scale testing (254 or 150 mm) to small scale testing (75 mm).	6-37
Fig. 7.1.	Profiles of final covers evaluated by Meer and Benson (2007). The service life varied from 4.1 to 11.1 yr.	7-2
Fig. 7.2.	Swell index in DW (a) and mole fraction monovalent bound cations (b) for GCL-only and composite GCL covers. Data are from this study (open symbols) and Meer and Benson (2007) (closed symbols).	7-7
Fig. 7.3.	Water content of exhumed GCLs (a) and subgrades (b) for covers where GCLs were in composite barriers or the sole barrier layer. Data are from this study (open symbols) and Meer and Benson (2007) (closed symbols).	7-9
Fig. 7.4.	Hydraulic conductivity of exhumed GCLs from covers where GCLs were in composite barriers or the sole barrier layer. Data are from this study (open symbols) and Meer and Benson (2007) (closed symbols). Circles represent hydraulic conductivity to SW; shaded boxes represent hydraulic conductivity to DW. GCLs permeated with DW at Wisconsin site (W-02) are duplicates of GCLs that had high hydraulic conductivity to SW.	7-10
Fig. 7.5	Hydraulic conductivity versus (a) swell index in DW and (b) mole fraction bound sodium for exhumed GCLs from composite barriers. Data for new GCL are from Meer and Benson (2007).	7-12
Fig. 7.6.	Hydraulic conductivity of exhumed GCLs vs. water content (a) and water content of exhumed GCLs versus corresponding water content of subgrade (b). GCLs with lower K had hydraulic conductivities $< 5 \times 10^{-11}$ m/s, whereas GCLs with higher K had hydraulic conductivities $> 1 \times 10^{-9}$ m/s.	7-13
Fig. 7.7.	TCM (a) and X_m (b) of GCL versus water content of subgrade. GCLs with lower K had hydraulic conductivities $< 5 \times 10^{-11}$ m/s, whereas GCLs with higher K had hydraulic conductivities $> 1 \times 10^{-9}$ m/s.	7-14
Fig. 7.8.	TCM of GCL vs. TCM of subgrade (a) and MDR of GCL vs. MDR of subgrade (b). GCLs with lower K had hydraulic conductivities $< 5 \times 10^{-11}$ m/s, whereas GCLs with higher K had hydraulic conductivities $> 1 \times 10^{-9}$ m/s.	7-16
Fig. 7.9.	Hydraulic conductivities of GCLs exhumed in this study as a function of USCS classification of subgrade. Compilation of data from Meer and Benson (2007) Site S and from this study.	7-17
Fig. 7.10.	Hydraulic conductivity of exhumed GCLs permeated with SW and DW vs. service life (a) and thickness of overlying soil (b). Data are from this study and Site S in Meer and Benson (2007).	7-18

Fig. 7.11. Cross-sections of exhumed GCLs from Site E-02 (a) and Site B (b). Vertical scale in mm. 7-20

Fig. 7.12. Cross-sections of exhumed GCLs from Site S (a) and Site F-03 (b). Photo of GCL from Site S is from Meer (2004). Photo of GCL from Site F-03 is from after permeation with rhodamine WT dye. Vertical scale in mm. 7-21

Fig. 8.1. Profiles of covers at sites where geosynthetics were exhumed. GCL = geosynthetic clay liner, GDL = geosynthetic drainage layer, GM = geomembrane, GX = geotextile, RB = root barrier. 8-2

Fig. 8.2. Narrow strip break strengths for the geomembrane samples. Horizontal bars in each column represent the average for the data in the column. Polymer types are noted at the top of each column. Two headed arrows represent manufacturer's MARV. 8-4

Fig. 8.3. Strains at narrow strip yield strength (a) and break strength (b). Horizontal bars in each column represent the average for the data in the column. Two headed arrows represent manufacturers' MARV. 8-5

Fig. 8.4. Comparison between narrow-strip and wide-strip yield strengths (a) and narrow strip break and narrow strip yield strengths (b). 8-7

Fig. 8.5. Oxidation induction time (OIT) (a) and melt flow index (MFI) (b) for the geomembrane. OIT and MFI were measured by TRI Environmental, Inc. of Austin, Texas. Horizontal bars in each column represent the average for the data in the column. Solid line at 130 min in OIT graph represents the manufacturers' MARV. Two headed arrows represent the OIT estimates of the exhumed samples calculated by the Arrhenius equation. 8-9

Fig. 8.6. OIT of exhumed geomembranes normalized by MARV and OIT as a function of time. OIT_e = exhumed OIT. OIT_o = MARV OIT. 8-10

Fig. 8.7. Transmissivity of GDL under normal stress of 24 kPa (a) and 480 kPa (b). Horizontal bars in each column represent the average for data in the column. 8-13

Fig. 8.8. Transmissivity of exhumed GDLs as a function of stress and MARV transmissivities for Altamont (a), Boardman (b), Cedar Rapids (c), and Omaha (d). 8-14

Fig. 8.9. Site average transmissivity of GDL as a function of percent fines of the cover soil. Error bars represent one standard deviation from the mean. .. 8-15

Fig. 8.10. Permittivity of GDL using 10 mm head (a) and 50 mm head (b). Horizontal bars in each column represent the average for the data in the column. Two headed arrows represent manufacturers' MARV. 8-17

Fig. 8.11. Site average permittivity as a function of percent fines of the cover soil. Error bars represent one standard deviation from the mean. 8-18

Fig. 8.12.	Ply adhesion of GDL. Horizontal bars in each column represent the average the average for the data in the column. Two headed arrows represent manufacturers' MARV.	8-19
Fig. 8.13.	Site average ply adhesion as a function of service life (a) and number of freeze- thaw cycles (b). Error bars represent one standard deviation from = mean.	8-22
Fig. 8.14.	Peak interface shear strength envelope of GM-GDL interface for geosynthetics sampled from the Wisconsin site.	8-24
Fig. 9.1.	Configuration for the electrical resistivity survey used at the Altamont site.	9-2
Fig. 9.2.	Placement of current electrode under the GM at the Altamont site.	9-3
Fig. 9.3.	Raw (a) and smoothed (b) distribution of voltage drop from electrical resistivity survey of conventional cover at Altamont site (scale in mV).	9-4
Fig. 9.4.	Contour (a) and surface plots (b) of electrical resistivity data from conventional cover at Polson site. Suspect areas marked with red circles and location of intentional defect shown with solid yellow circle.	9-5
Fig. 9.5.	Contour and surface plots of electrical resistivity survey of conventional cover at Omaha site (more detailed maps are presented on right). Suspect areas are marked with red oval; green box shows location of gash in GM in Fig. 9.6 (voltage amplitudes in mV).	9-6
Fig. 9.6.	Gash in GM at Omaha site that was detected from electrical resistivity survey (lip balm container shown for scale).	9-7
Fig. 9.7.	Antennae (200 MHz) used for GPR surveys at Altamont and Omaha sites.	9-9
Fig. 9.8.	GPR reflection survey at Altamont site along survey line in Fig. 9.1. Profile shows both point reflector above ground (e.g., tools, cables, etc. on surface) and below ground (sensor cables, etc.).....	9-10
Fig. 9.9.	EM wave traces collected along survey line shown in Fig. 9.1.	9-11
Fig. 9.10.	Tomographic images of EM wave velocity at Altamont site.	9-12
Fig. 9.11.	GPR reflection survey across all three cover sections at Omaha site.	9-13
Fig. 9.12.	Photograph of thick store-and-release cover at Omaha site showing thick upper storage layer, sand layer for capillary break (white layer), and lower interim cover layer. Note uniformity of layers and moist condition of storage layer and topsoil.	9-14
Fig. 9.13.	Tomographic images of downhole EM wave velocity from the thick store-and-release cover at the Omaha site.	9-16

Fig. 10.1	Daily precipitation and percolation record (a) and water content vs. time at various depths (b) in first quarter of 1995 for the final cover test section in Wenatchee, WA described in Khire et al. (1997).....	10-6
Fig. 10.2	Schematic of flux meter used to monitor a final cover (adapted from Malusis and Benson 2006).	10-7
Fig. 10.3	Storage and percolation (a) and water contents at various depths (b) as a function of time for thin store-and-release cover evaluated by ACAP in Sacramento, CA.	10-10
Fig. 10.4.	Typical profile of a sensor nest used for interpretive data (adapted from Benson et al. 2009). Labels to right of profile describe layers in cover profile. No sensors were placed in rip rap layer due to the large particle sizes and the negligible storage anticipated in this layer.	10-12
Fig. 10.5.	Moderate frequency TDR sensor ready to be pushed into cover profile. Type-T thermocouple (blue wire) is taped head of TDR sensor.	10-13
Fig. 10.6	Water balance quantities for ACAP test sections near Grand Junction, CO (from Benson et al. 2009).	10-15
Fig. 10.7.	Water contents in frost protection layer and radon barrier measured at same depth in up slope and down slope nests of Test Section A (adapted from Benson et al. 2009).	10-17
Fig. 10.8.	Comparison of water contents in frost protection layer in upslope (Probe 5) and down slope (Probe 12) interpretive monitoring nests in duplicate test sections (Test Sections A and B).	10-18

List of Tables

Table 2.1.	Climatic characteristics and slopes of ACAP sites.	2-5
Table 6.1.	Site characteristics and soil index properties for storage and barrier layers evaluated in this study.	6-2
Table 6.2.	Average as-built compaction and water content for storage and barrier layers evaluated in this study.	6-4
Table 6.3.	As-built hydraulic properties for storage and barrier layers evaluated in this study.	6-5
Table 6.4.	Field hydraulic conductivity for storage and barrier layers.	6-7
Table 6.5.	Saturated hydraulic conductivity measured in laboratory on specimens from in-service storage and barrier layers.	6-11
Table 6.6.	In-service saturated hydraulic conductivity for storage and barrier.	6-16
Table 6.7.	In-service dry unit weight and relative compaction for storage layers. ...	6-26
Table 6.8.	SWCC parameters for storage and barrier layers from 75-mm-diameter specimens.	6-32
Table 6.9.	SWCC parameters for storage and barrier layers from 150-mm-diameter specimens.	6-33
Table 6.10	SWCC parameters for storage and barrier layers from 254-mm-diameter specimens.	6-34
Table 7.1.	Physical and chemical properties of exhumed GCLs.	7-5
Table 7.2.	Water Content, TCM, and MDR of exhumed GCLs.	7-6
Table 7.3.	USCS Classification and Arithmetic Mean Water Content, TCM, and MDR of Subgrade Soils.	7-6
Table 8.1.	Tensile properties of exhumed GMs (average reported, range of property in parenthesis).	8-3
Table 8.2.	Melt flow index (MFI) and oxidation induction time (OIT) of exhumed GMs (average reported, range of property in parenthesis).	8-8
Table 8.3.	Transmissivities and permittivities of exhumed GDLs (average reported, range of property in parenthesis.	8-12

Table 8.4. Ply adhesions of exhumed GDLs (average reported range of property in parenthesis)..... 8-20

Table 8.5 Shear strength parameters for the interface between the exhumed GDLs and GMs (average reported, range of property in parenthesis). 8-23

Table 8.6 Summary of reduction factors from previous studies and current study of exhumed geosynthetics. 8-25

Table 10.1. Water balance quantities for two ACAP test sections near Grand Junction, CO (from Benson et al. 2009). 10-16

EXECUTIVE SUMMARY

In this peer-reviewed study, final covers at test facilities and operating waste containment facilities were exhumed to evaluate how the properties of the cover materials changed 4.0-8.9 yr after installation (6.3 yr on average). Field tests were conducted, samples were collected, laboratory testing was performed, and data analyses were conducted. The findings demonstrate that engineering properties of cover soils change while in service and that long-term engineering properties should be used as input to models employed for performance assessments. Recommendations for appropriate input are made based on the data that were collected.

Changes in hydraulic properties occurred in all cover soils evaluated due to the formation of soil structure, regardless of climate, cover design, or service life. The saturated hydraulic conductivity and the α parameter for the soil water characteristic curve (SWCC) increased, which reflects formation of larger pores due to pedogenic processes such as wet-dry and freeze-thaw cycling. Larger changes were observed for soils with lower as-built saturated hydraulic conductivity and soils with a greater proportion of clay particles in the fines fraction. Hydraulic properties of the cover soils were similar when exhumed, regardless of the as-built condition. Test scale had a significant effect on the hydraulic properties, with conditions near field-scale obtained using 0.3-m test specimens.

Substantial changes were also observed in some geosynthetic clay liners (GCLs). Analysis showed that GCLs have very low saturated hydraulic conductivity ($< 5 \times 10^{-11}$ m/s) when placed on a moist subgrade (water content $> 10\%$) and covered with a geomembrane and cover soil soon after installation. GCLs installed under other conditions can be much more permeable. GCLs that underwent and maintained complete hydration with osmotic swell retained low hydraulic conductivity even when Na was replaced by Ca and Mg provided they did not dehydrate. GCLs that undergo osmotic swell and are covered with a geomembrane surcharged with cover soils are expected to retain low hydraulic conductivity provided the geomembrane remains intact.

Changes in geomembranes and geosynthetic drainage layers were modest or small. Analysis of antioxidants in geomembranes showed that antioxidant depletion was reasonably consistent with expectations based on first-order kinetics and laboratory-measured depletion rates. Based on antioxidant depletion, the minimum service life of geomembranes is on the order of 50-125 yrs. Actual service lives may be longer but are difficult to predict based on the limited information available today.

Because changes in the engineering properties of cover materials are commonplace, and significant in some cases, monitoring of covers should be conducted to ensure they are functioning as intended. Monitoring using pan lysimeters combined with secondary measurements collected for interpretive purposes (water content, temperature, vegetation surveys, etc.) is recommended. Future research investments should explore how remote sensing technologies can be used for cover monitoring.

This study represents a snap shot in the evolution of final covers approximately 5 to 10 yr after construction. Additional research investments are needed to more accurately and completely define very long-term properties of earthen and geosynthetic cover materials corresponding to 100s or 1000s of years. These research investments should include analog studies of natural environments where earthen and natural polymeric materials exist as well as accelerated laboratory experiments that can be used to develop predictive degradation models.

ACKNOWLEDGEMENT

This research study was funded by a consortium consisting of the U.S. Nuclear Regulatory Commission's Office of Nuclear Regulatory Research (through a grant to the University of Wisconsin-Madison Water Resources Institute under an interagency agreement, IA-RES-08-132, with the U. S. Geological Survey State Water Resources Research Institute Program), the National Science Foundation (Grant No. CMMI-0625850), the U.S. Environmental Protection Agency, the U.S. Department of Energy, the Environmental Research and Education Foundation, Colloid Environmental Technologies Corporation, Veolia Environmental Services, and Waste Connections, Inc. This support is gratefully acknowledged.

The research report was peer reviewed by an expert panel consisting of Charles D. Shackelford, John D. McCartney, and George R. Koerner. The authors of the research report considered and incorporated their comments and suggestions when finalizing the report.

ABBREVIATIONS

Acronyms

ACAP	Alternative Cover Assessment Program
BC	bound cations
CEC	cation exchange capacity
CMH	chilled mirror hygrometer
CMP	common midpoint
D	diameter
DW	deionized water
ET	evapotranspiration
GCL	geosynthetic clay liner
GDL	geosynthetic drainage layer
GM	geomembrane
GPR	ground penetrating radar
H	depth of water in outer ring of SDRI
HDPE	high density polyethylene
H _b	height of water in bubbling tube in BH relative to base of borehole
I	infiltration rate
ICP-OES	inductively coupled plasma – optical emissions spectrometry
I _s	ionic strength
K	hydraulic conductivity
L _f	depth of the wetting front
LLDPE	linear low density polyethylene
MARV	minimum average role value
MDR	charge ratio of monovalent to divalent soluble cations
MFI	melt flow index

MSW	municipal solid waste
OIT	oxidation induction time
PET	potential evapotranspiration
Q	volumetric flow rate
RMD	ratio of monovalent to divalent cations in a solution
SC	soluble cations
SDRI	sealed double-ring infiltrometer
SI	swell index
SW	standard water (0.01 M CaCl ₂)
SWCC	soil water characteristic curve
TDR	time domain reflectometry
BH	borehole permeameter
TCM	total soluble cations charge per mass
USCS	Unified Soil Classification System
USEPA	US Environmental Protection Agency

Western Symbols

Ca	calcium
Cl	chlorine
K	potassium
K _F	field-measured saturated hydraulic conductivity
K _s	saturated hydraulic conductivity
K _{sa}	as-built saturated hydraulic conductivity
K _{SDRI}	field-measured hydraulic conductivity with SDRI
K _{si}	in-service saturated hydraulic conductivity
K _{BH}	field-measured hydraulic conductivity with BH permeameter

n	shape parameter in van Genuchten's equation
n_{LS}	shape parameter in van Genuchten's equation from large-scale tests
n_{SS}	shape parameter in van Genuchten's equation from small-scale tests
n_a	shape parameter in van Genuchten's equation from as-built test section
Na	sodium
Mg	magnesium
p	p statistic from t-test
t	t statistic from t-test
X_m	mole fraction of monovalent cations

Greek Symbols

α	shape parameter in van Genuchten's equation
α_a	shape parameter in van Genuchten's equation from as-built test section
α_{LS}	shape parameter in van Genuchten's equation from large-scale tests
α_{SS}	shape parameter in van Genuchten's equation from small-scale tests
γ_{dmax}	maximum dry unit weight on compaction curve
θ	volumetric water content
θ_r	residual volumetric water content
θ_s	saturated volumetric water content
Θ	effective saturation
σ	standard deviation

APPENDIX A – EXHUMATION PHOTO GALLERY



Fig. A.1. Test field prior to decommissioning.




Fig A.2. Decommissioning weather station.




Fig A.3. Constant head TSBs in operation.



Fig A.4. Investigating soil paedogenesis.




Fig A.5. Sampling GDL in section with composite barrier.



Fig A.6. Constructed defect in GM.




Fig A.7. Removing GCL sample from composite barrier.




Fig A.8. Delicately plating GCL to avoid disturbance.



Fig A.9. Removing GCL samples from composite barrier.

APPENDIX A.1 – EXHUMATION OF HELENA, MONTANA SITE




Fig. A.10. Test field prior to decommissioning.



Fig. A.11. Cover soil removed prior to SDRI installation.




Fig. A.12. Cutting trenches for SDRI installation.



Fig. A.13. Adding granular bentonite to seal SDRI.




Fig. A.14. Filling SDRI, inner cap visible.



Fig. A.15. Constant head TSB in operation.



Fig. A.16. Exhumation of block sample.



Fig. A.17. Supervision during block sample exhumation.




Fig. A.18. Removing lysimeter GDL for laboratory analysis.




Fig. A.19. Operating SDRI with constant head inner ring.

APPENDIX A.2 – EXHUMATION OF POLSON, MONTANA SITE




Fig. A.20. Test field (in fence) prior to decommissioning.



Fig. A.21 Digging block sample for laboratory analysis.



Fig. A.22. Macroscopic in-situ flow path.



Fig. A.23. Close-up of macroscopic in-situ flow path.



Fig. A.24 Geophysical investigation prior to excavations.



Fig. A.25. Geophysical investigation prior to excavations.



Fig. A.26. Horizontal plane of roots found during block sampling.



Fig. A.27. Close up of root plane.




Fig. A.28. Installing SDRI under GM into CCL.



Fig. A.29. Installation of SDRI seating trenches.



Fig. A.30. SDRI inner ring after assembly but prior to filling.




Fig. A.31. Digging subsurface block sample.



Fig. A.32. Vertical root planes.



Fig. A.33. Alternative (ET) cover profile, veg. barrier visible.



Fig. A.34. Sampling ET cover for water content profile.




Fig. A.35. Running SDRI in ET cover.




Fig. A.36. Failure along vertical root planes during trenching.



Fig. A.37. Water removal from completed SDRI.




Fig. A.38. Location of Polson, MT ACAP test section.

APPENDIX A.3 – EXHUMATION OF OMAHA, NEBRASKA SITE



Fig. A.39. ACAP signage.




Fig. A.40 Test field prior to decommissioning.



Fig. A.41. Initial geophysical investigation.



Fig. A.42. Constant head TSBs during operation.



Fig. A.43. Installing TSB, rough bottom to avoid smearing.




Fig. A.44. Grouting TSB with bentonite paste.



Fig. A.45. Installing Mariette bottle for constant head testing.



Fig. A.46. TSB data collection with narrow Mariette bottle.



Fig. A.47. Conventional cover profile (soil above GM).



Fig. A.48. Conventional cover profile (CCL below GM).



Fig. A.49. In-situ water content reflectometer.



Fig. A.50. Soil overlying GM in conventional cover (flipped).



Fig. A.51. Soil underlying GM in conventional cover.



Fig. A.52. Unintentional hole from installation found via geophysical investigation.



Fig. A.53 Close-up of unintentional hole from installation found via geophysical investigation.



Fig. A.54. AO1 (Capillary barrier) cover profile.



Fig. A.55. Close up of capillary barrier in AO1.



Fig. A.56. Roots extending into course layer in AO1.



Fig. A.57. Close-up of undisturbed roots extending across capillary barrier and into course layer in AO1.




Fig. A.58. AO2 (Capillary barrier) cover profile.



Fig. A.59. Close-up of capillary barrier in AO2.



Fig. A.60. Close-up of vegetation barrier in AO2.



Fig. A.61. AO2 (capillary barrier) cover profile.

APPENDIX A.4 – EXHUMATION OF UNDERWOOD, NORTH DAKOTA SITE



Fig. A.62. ACAP sign at Coal Creek Station.



Fig. A.63. Lysimeter and instrumentation trailer.



Fig. A.64. Interior of lysimeters and instrumentation trailer.



Fig. A.65. In situ instrumentation data logger.




Fig. A.66. Test field prior to decommissioning.




Fig. A.68. TSBs in operation, and test pits.



Fig. A.67. Digging block sample for laboratory analysis.



Fig. A.69. Mixing bentonite grout for TSB installation.



Fig. A.70. Thicker (3 ft) CCL profile (desiccated across profile).




Fig. A.71. Digging block sample in thicker CCL.



Fig. A.72. Roots visible down to veg. barrier in all profiles.



Fig. A.73. Root planes visible on ped removed from bottom of desiccated CCL.




Fig. A.74 Discussing observations with regulators.




Fig. A.75. Thicker CCL (5 ft), desiccation and roots visible throughout profile.

APPENDIX A.5 – EXHUMATION OF MONTICELLO, UTAH SITE




Fig. A.76. Repository marker.



Fig. A.77. Test field prior to testing.



Fig. A.78. Vegetation layer removed for SDRI installation.



Fig. A.79. Preparation of site for SDRI installation.




Fig. A.80. Measuring in-situ density prior to sampling.




Fig. A.81. Cleaning site for SDR1 installation.



Fig. A.82. Sealing upper TSB section with granular bentonite.



Fig. A.83. Close-up of granular bentonite .



Fig. A.84. Constant head TSBs in operation.



Fig. A.85. Setting SDRI in trenches.




Fig. A.86. Sealing SDRI perimeter with granular bentonite.



Fig. A.87. Installing bentonite grout for inner TSB ring.



Fig. A.88. Installed TSB prior to operation.



Fig. A.89. Macroscopic flow path visible at bottom of TSB.



Fig. A.90. Block sample ring prior to sampling.




Fig. A.91. Removing vegetation prior to sampling.



Fig. A.92. Excavating additional soil during sampling.



Fig. A.93. Continued soil excavation for sampling.



Fig. A.94. Lower block sampling.



Fig. A.95. Trench for examination of soil structure.



Fig. A.96. Analysis of soil structure.




Fig. A.97. Re-compacting soil after sampling.



Fig. A.98. Ensuring re-compaction to initial dry density.

APPENDIX B - SEALED DOUBLE-RING INFILTROMETER (SDRI) DATA


SDRI Test - Altamont - Composite Cover

Date: 4/2/2007 Installer: XW
 Project: Altamont Analyst: CHB

Fixed variables:
 L = 150 cm Assume Unit Gradient in Analysis
 A = 22500 cm²
 a = 77.69 cm²
 Dp = 30.48 cm

Temporal Variables:

Time	Reading (cm)	Δ Time (s)	Time (h)	i	I (cm/s)	K (cm/s)
4/3/07 16:16	56.5					
4/3/07 16:33	54.0	1020	0.28	1.94	4.35E-06	
4/3/07 16:52	50.8	1140	0.60	1.94	4.98E-06	
4/3/07 17:13	47.3	1260	0.95	1.94	4.93E-06	
4/3/07 17:37	43.4	1440	1.35	1.94	4.81E-06	
4/3/07 17:57	40.1	1200	1.68	1.94	4.88E-06	
4/3/07 18:30	35.4	1980	2.23	1.94	4.21E-06	
4/3/07 18:45	33.7	900	2.48	1.94	3.35E-06	
4/3/07 19:00	31.6	900	2.73	1.94	4.14E-06	
4/3/07 19:15	29.9	900	2.98	1.94	3.35E-06	
4/3/07 19:30	28.0	900	3.23	1.94	3.75E-06	
4/3/07 19:32	56.5	120	3.27	1.94		
4/4/07 9:50	3.0	51480	17.57	1.94	1.85E-06	
4/4/07 9:58	58.0	480	17.70	1.94		
4/4/07 10:32	55.7	2040	18.27	1.94	2.00E-06	
4/4/07 11:34	51.0	3720	19.30	1.94	2.24E-06	
4/4/07 12:19	46.5	2700	20.05	1.94	2.96E-06	
4/4/07 12:37	57.5	1080	20.35	1.94		
4/4/07 13:34	50.7	3420	21.30	1.94	3.53E-06	
4/4/07 14:50	42.0	4560	22.57	1.94	3.39E-06	
4/4/07 15:50	33.0	3600	23.57	1.94	4.44E-06	
4/4/07 16:50	25.0	3600	24.57	1.94	3.95E-06	4.1E-06
4/4/07 17:50	18.0	3600	25.57	1.94	3.45E-06	4.1E-06
4/4/07 18:50	9.4	3600	26.57	1.94	4.24E-06	4.1E-06
4/4/07 19:30	3.0	2400	27.23	1.94	4.73E-06	4.1E-06



SDRI Test - Altamont - Store-and-Release Cover

Date: 4/2/2007
 Project: Altamont

Installer: XW
 Analyst: CHB


Fixed variables:

L = 150 cm Assume Unit Gradient in Analysis
 A = 22500 cm²
 a = 77.69 cm²
 Dp = 22.86 cm

Temporal Variables:

Time	Reading (cm)	Δ Time (s)	Time (h)	K (cm/s)
15:48	49.0			
15:50	40.0	120	0.03	2.59E-04
15:52	32.5	120	0.07	2.16E-04
15:54	24.0	120	0.10	2.45E-04
15:56	15.0	120	0.13	2.59E-04
15:57	10.5	60	0.15	2.59E-04
16:02	52.0	300	0.23	
16:04	49.0	120	0.27	8.63E-05
16:06	41.8	120	0.30	2.07E-04
16:08	33.8	120	0.33	2.30E-04
16:10	25.8	120	0.37	2.30E-04
16:14	9.5	240	0.43	2.35E-04
16:24	50.0	600	0.60	
16:26	40.5	120	0.63	2.73E-04
16:28	30.5	120	0.67	2.88E-04
16:30	22.0	120	0.70	2.45E-04
16:40	55.0	600	0.87	
16:42	48.0	120	0.90	2.01E-04
16:44	40.4	120	0.93	2.19E-04
16:46	33.0	120	0.97	2.13E-04
16:48	25.5	120	1.00	2.16E-04
16:50	18.5	120	1.03	2.01E-04
16:52	12.0	120	1.07	1.87E-04
17:03	57.0	660	1.25	
17:05	50.0	120	1.28	2.01E-04
17:07	42.0	120	1.32	2.30E-04
17:10	31.0	180	1.37	2.11E-04
17:12	23.5	120	1.40	2.16E-04
17:14	16.5	120	1.43	2.01E-04
17:16	9.0	120	1.47	2.16E-04
9:27	58.5		1.47	
9:29	56.0	120	1.50	7.19E-05
9:31	53.0	120	1.53	8.63E-05
9:33	50.0	120	1.57	8.63E-05
9:36	46.0	180	1.62	7.67E-05
9:38	43.1	120	1.65	8.34E-05
9:41	38.0	180	1.70	9.78E-05
9:47	30.0	360	1.80	7.67E-05
9:51	21.0	240	1.87	1.29E-04
9:54	16.7	180	1.92	8.25E-05
9:56	14.0	120	1.95	7.77E-05
9:58	11.1	120	1.98	8.34E-05
10:00	8.2	120	2.02	8.34E-05
10:08	58.2	480	2.15	
10:11	54.7	180	2.20	6.71E-05
10:15	49.8	240	2.27	7.05E-05
10:19	44.8	240	2.33	7.19E-05
10:24	38.4	300	2.42	7.37E-05
10:28	33.1	240	2.48	7.63E-05

10:32	28.0	240	2.55	7.34E-05	
10:37	21.8	300	2.63	7.14E-05	
10:41	16.6	240	2.70	7.48E-05	
10:46	10.0	300	2.78	7.60E-05	
10:49	6.0	180	2.83	7.67E-05	
11:03	57.2	840	3.07		
11:05	54.7	120	3.10	7.19E-05	
11:07	52.1	120	3.13	7.48E-05	
11:09	49.5	120	3.17	7.48E-05	
11:11	46.9	120	3.20	7.48E-05	
11:13	44.1	120	3.23	8.06E-05	
11:15	41.5	120	3.27	7.48E-05	
11:17	38.9	120	3.30	7.48E-05	
11:19	36.0	120	3.33	8.34E-05	
11:21	33.4	120	3.37	7.48E-05	
11:23	30.3	120	3.40	8.92E-05	
11:25	27.8	120	3.43	7.19E-05	
11:27	25.2	120	3.47	7.48E-05	
11:29	23.0	120	3.50	6.33E-05	K (cm/s)
11:31	20.5	120	3.53	7.19E-05	7.0E-05
11:33	18.0	120	3.57	7.19E-05	
11:35	15.5	120	3.60	7.19E-05	



SDRI Test - Apple Valley - Clay Cover

Date: 3/30/2007 **Installer:** XW
Project: Apple Valley **Analyst:** CHB


Fixed variables:

L = 150 cm
A = 22500 cm²
a = 77.69 cm²
Dp = 33.02 cm

Temporal Variables:

Time	Reading (cm)	Δ Time (s)	Time (h)	K (cm/s)
10:40	41.0			
10:45	37.0	300	0.08	4.60E-05
10:50	31.8	300	0.17	5.99E-05
10:55	26.6	300	0.25	5.99E-05
11:00	21.7	300	0.33	5.64E-05
11:05	16.6	300	0.42	5.87E-05
11:10	11.0	300	0.50	6.45E-05
11:13	55.0	180	0.55	-8.44E-04
11:16	50.4	180	0.60	8.82E-05
11:20	46.0	240	0.67	6.33E-05
11:25	40.3	300		
11:30	35.0	300	0.83	6.10E-05
11:35	30.0	300	0.91	5.75E-05
11:40	24.6	300	1.00	6.22E-05
11:45	19.8	300	1.08	5.52E-05
11:50	14.9	300	1.16	5.64E-05
11:55	9.8	300	1.25	5.87E-05
12:05	49.5	600		
12:10	44.5	300	1.50	5.75E-05
12:15	39.5	300	1.58	5.75E-05
12:20	34.5	300	1.67	5.75E-05
12:25	29.5	300	1.75	5.75E-05
12:30	24.6	300	1.83	5.64E-05
12:35	19.8	300	1.92	5.52E-05
12:40	15.0	300	2.00	5.52E-05

5.56E-05




SDRI Test - Cedar Rapids - Clay Cover

L = 610 cm i = 1.04
 A = 372100 cm²
 a = 77.69 cm²
 Dp = 25.4 cm

Date	Time	Bag On	Bag Off	Δ Time (s)	Time (h)	I (cm/s)	K (cm/s)
6-Jun-06	15:10	2503.6					
	15:51		828.1	2460	0.68	3.03E-05	2.91E-05
	16:24	2724.4					
7-Jun-06	18:07		2450.1	6180	2.40	1.97E-06	1.89E-06
	8:35	2449.3					
	10:36		2042.2	7260	4.42	2.49E-06	2.39E-06
	10:42	2042.2					
	11:35		1928.3	3180	5.30	1.59E-06	1.53E-06
	11:39	1928.3					
	13:39		1731.3	7200	7.30	1.22E-06	1.17E-06
	13:42	1731.3					
	15:45		1604.3	7380	9.35	7.65E-07	7.34E-07
	15:51	1604.3					
8-Jun-06	17:20		1421.9	5340	10.83	1.52E-06	1.46E-06
	8:29	2448.3					
	9:58		1980.9	5340	12.32	3.89E-06	3.73E-06
	10:04	1980.9					
	11:50		1787.0	6360	14.08	1.35E-06	1.30E-06
	11:52	1787.0					
	13:58		1535.0	7560	16.18	1.48E-06	1.42E-06
	14:05	1535.0					
15:04		1446.0	3540	17.17	1.12E-06	1.07E-06	

Avg K
1.27E-06




SDRI Test - Cedar Rapids - Composite Cover

L = 610 cm i = 1.04
 A = 372100 cm²
 a = 77.69 cm²
 Dp = 25.4 cm

Date	Time	Bag On	Bag Off	Δ Time (s)	Time (h)	I (cm/s)	K (cm/s)
7-Jun-06	8:40	2508.6					
	10:16		2315.0	5760	1.60	1.49E-06	1.43E-06
	10:33	2315.0					
	11:35		2224.5	3720	2.63	1.08E-06	1.04E-06
	11:39	2224.5					
	13:27		1906.4	6480	4.43	2.18E-06	2.09E-06
	13:37	1906.4					
	15:31		1746.8	6840	6.33	1.04E-06	9.96E-07
	15:46	1746.8					
	17:17		1671.9	5460	7.85	6.10E-07	5.85E-07
8-Jun-06	8:28	2636.7					
	10:06		2474.0	5880	9.48	1.23E-06	1.18E-06
	10:11	2474.0					
	11:53		2187.0	6120	11.18	2.08E-06	2.00E-06
	11:55	2187.0					
	13:54		1815.0	7140	13.17	2.32E-06	2.22E-06
	14:03	1815.0					
15:03		1631.0	3600	14.17	2.27E-06	2.18E-06	

Avg K
 2.13E-06



SDRI Hydraulic Conductivity - Helena - Store-and-Release Cover


Inner Ring Side Length (ft) 5.00
 Inner Ring Side Length (cm) 152.40
 Inner Ring Area (cm²) 23225.76

Average Head (in) 14.00
 Average Head (cm) 35.56

Standpipe Diameter (cm) 5.00
 Standpipe Area (cm²) 19.63

Date, Time	Inflow Reading (cm)	Inflow (mL)	Δt (sec)	t (sec)	Q (mL/s)	K (cm/s)
9:15	34		0.0			
9:52	41	137.44468	2220.0	2220.0	0.0619	2.7E-06
10:02	50	176.71459	600.0	2820.0	0.2945	1.3E-05
10:10	57.5	147.26216	480.0	3300.0	0.3068	1.3E-05
10:17	65	147.26216	420.0	3720.0	0.3506	1.5E-05
10:26	73.1	159.04313	540.0	4260.0	0.2945	1.3E-05
10:34	80.5	145.29866	480.0	4740.0	0.3027	1.3E-05
10:42	87.7	141.37167	480.0	5220.0	0.2945	1.3E-05
10:49	93.5	113.88273	420.0	5640.0	0.2711	1.2E-05
10:55	40.5	-1040.6526	360.0	6000.0	-2.8907	-1.2E-04
11:02	49.5	176.71459	420.0	6420.0	0.4207	1.8E-05
11:10	55.8	123.70021	480.0	6900.0	0.2577	1.1E-05
11:19	64.4	168.86061	540.0	7440.0	0.3127	1.3E-05
11:25	69.9	107.99225	360.0	7800.0	0.3000	1.3E-05
11:31	76	119.77322	360.0	8160.0	0.3327	1.4E-05
11:38	83.0	137.44468	420.0	8580.0	0.3272	1.4E-05
11:46	92.6	188.49556	480.0	9060.0	0.3927	1.7E-05
11:53	98.5	115.84623	420.0	9480.0	0.2758	1.2E-05
11:58	29.0	-1364.6293	300.0	9780.0	-4.5488	-2.0E-04
12:02	34.1	100.13827	240.0	10020.0	0.4172	1.8E-05
12:09	41.2	139.40817	420.0	10440.0	0.3319	1.4E-05
12:16	48.0	133.51769	420.0	10860.0	0.3179	1.4E-05

Average 1.4E-05



SDRI Test - Monticello - Store-and-Release Cover

Date: 7/24/2007
 Project: Monticello

Installer: XW
 Analyst: CHB


Fixed variables:

L = 150 cm
 A = 22500 cm²
 a = 77.69 cm²
 Dp = 35.56 cm

Temporal Variables:

Time	Reading (cm)	Δ Time (s)	Time (h)	K (cm/s)
10:45	57.0			
10:49	51.0	240	0.07	8.63E-05
10:56	40.5	420	0.18	8.63E-05
10:59	34.9	180	0.23	1.07E-04
11:02	30.0	180	0.28	9.40E-05
11:05	25.3	180	0.33	9.02E-05
11:08	20.8	180	0.38	
11:11	15.8	180	0.43	9.59E-05
11:14	11.2	180	0.48	8.82E-05
11:17	6.3	180	0.53	9.40E-05
11:25	53.5	480	0.67	
11:28	47.5	180	0.72	1.15E-04
11:33	39.6	300	0.80	
11:35	36.5	120	0.83	8.92E-05
11:38	32.0	180	0.88	8.63E-05
11:41	27.0	180	0.93	9.59E-05
11:44	22.5	180	0.98	
11:47	18.0	180	1.03	8.63E-05
11:50	13.5	180	1.08	8.63E-05
11:53	8.5	180	1.13	9.59E-05
11:56	56.2	180	1.18	
11:59	51.8	180	1.23	8.44E-05
12:02	47.2	180	1.28	8.82E-05
12:05	43.0	180	1.33	
12:08	38.5	180	1.38	8.63E-05
12:11	34.0	180	1.43	8.63E-05
12:14	29.5	180	1.48	8.63E-05
12:18	23.5	240	1.55	8.63E-05
12:21	20.0	180	1.60	6.71E-05
12:24	15.0	180	1.65	9.59E-05
12:27	10.5	180	1.70	
12:30	6.0	180	1.75	8.63E-05

Avg K
8.50E-05



Alt. SDRI Hydraulic Conductivity - Polson - Store-and-Release Cover


Inner Ring Side Length (ft) 5.00
 Inner Ring Side Length (cm) 152.40
Inner Ring Area (cm²) 23225.76

Average Head (in) 14.00
Average Head (cm) 35.56

Standpipe Diameter (cm) 5.00
Standpipe Area (cm²) 19.63

Date, Time	Inflow Reading (cm)	Inflow (mL)	Dt (sec)	t (sec)	Q (mL/s)	K (cm/s)
9:12	59		0.0			
9:36	52.1	135.48118	1440.0	1440.0	0.0941	4.1E-06
9:51	48.8	64.795348	900.0	2340.0	0.0720	3.1E-06
10:00	46.2	51.050881	540.0	2880.0	0.0945	4.1E-06
10:13	41.5	92.284284	780.0	3660.0	0.1183	5.1E-06
10:23	36.6	96.211275	600.0	4260.0	0.1604	6.9E-06
10:33	31.4	102.10176	600.0	4860.0	0.1702	7.3E-06
10:43	25.9	107.99225	600.0	5460.0	0.1800	7.7E-06
10:54	19.5	125.66371	660.0	6120.0	0.1904	8.2E-06
11:04	13.2	123.70021	600.0	6720.0	0.2062	8.9E-06
11:14	6.9	123.70021	600.0	7320.0	0.2062	8.9E-06
11:23	58.5	-1013.1636	540.0	7860.0	-1.8762	-8.1E-05
11:33	53.7	94.24778	600.0	8460.0	0.1571	6.8E-06
11:49	45.9	153.15264	960.0	9420.0	0.1595	6.9E-06
12:08	35.4	206.16702	1140.0	10560.0	0.1808	7.8E-06
12:18	29.0	125.66371	600.0	11160.0	0.2094	9.0E-06
12:28	22.5	127.6272	600.0	11760.0	0.2127	9.2E-06
12:38	16.1	125.66371	600.0	12360.0	0.2094	9.0E-06
12:51	8.2	155.11614	780.0	13140.0	0.1989	8.6E-06

Average 8.9E-06



Conv. SDRI Hydraulic Conductivity - Polson - Composite Cover


Inner Ring Side Length (ft) 5.00
 Inner Ring Side Length (cm) 152.40
Inner Ring Area (cm²) 23225.76

Average Head (in) 14.00
Average Head (cm) 35.56

Standpipe Diameter (cm) 5.00
Standpipe Area (cm²) 19.63

Date, Time	Inflow Reading (cm)	Inflow (mL)	Dt (sec)	t (sec)	Q (mL/s)	K (cm/s)
9:34	55.5		0.0			
9:50	52.5	58.904862	960.0	960.0	0.0614	2.6E-06
10:01	50.5	39.269908	660.0	1620.0	0.0595	2.6E-06
10:14	46.7	74.612826	780.0	2400.0	0.0957	4.1E-06
10:24	44.6	41.233404	600.0	3000.0	0.0687	3.0E-06
10:34	42.5	41.233404	600.0	3600.0	0.0687	3.0E-06
10:44	40	49.087385	600.0	4200.0	0.0818	3.5E-06
10:55	37.7	45.160394	660.0	4860.0	0.0684	2.9E-06
11:05	35.5	43.196899	600.0	5460.0	0.0720	3.1E-06
11:21	31.7	74.612826	960.0	6420.0	0.0777	3.3E-06
11:34	28.9	54.977871	780.0	7200.0	0.0705	3.0E-06
11:50	25	76.576321	960.0	8160.0	0.0798	3.4E-06
12:08	20.6	86.393798	1080.0	9240.0	0.0800	3.4E-06
12:29	15.5	100.13827	1260.0	10500.0	0.0795	3.4E-06
12:51	10.5	98.17477	1320.0	11820.0	0.0744	3.2E-06

Average 3.4E-06



SDRI Test - Sacramento - Thin Store-and-Release Cover

Date:
Project: Sacramento

Installer: XW
Analyst: CHB

Fixed variables:


L = 150 cm
A = 22500 cm²
a = 77.69 cm²
Dp = cm

Assume Unit Gradient in Analysis

Temporal Variables:

Time	Reading (cm)	Δ Time (s)	Time (h)	K (cm/s)
3:50	59			
3:52	56.5	120	0.03	7.19E-05
3:53	51.5	60	0.05	2.88E-04
3:54	46	60	0.07	3.17E-04
3:55	40.5	60	0.08	3.17E-04
3:56	34.5	60	0.1	3.45E-04
3:57	29	60	0.12	3.17E-04
3:58	23	60	0.13	3.45E-04
3:59	17.5	60	0.15	3.17E-04
4:00	12	60	0.17	3.17E-04
4:06	55.5	360	0.27	
4:07	50	60	0.28	3.17E-04
4:08	44.5	60	0.3	3.17E-04
4:09	39	60	0.32	3.17E-04
4:10	33.5	60	0.33	3.17E-04
4:11	27.5	60	0.35	3.45E-04
4:12	22	60	0.37	3.17E-04
4:13	16.5	60	0.38	3.17E-04
4:14	11	60	0.4	3.17E-04

Avg K
3.2E-04



SDRI Test - Sacramento - Thick Store-and-Release Cover

Date:
Project: Sacramento


Installer: XW
Analyst: CHB

Fixed variables:
 L = 150 cm Assume Unit Gradient in Analysis
 A = 22500 cm²
 a = 77.69 cm²
 Dp = cm

Temporal Variables:

Time	Reading (cm)	Δ Time (s)	Time (h)	K (cm/s)
11:03	56			
11:07	50.7	240	0.07	7.63E-05
11:10	45	180	0.12	1.09E-04
11:13	39	180	0.17	1.15E-04
11:16	33.8	180	0.22	9.98E-05
11:19	28.7	180	0.27	9.78E-05
11:22	23.2	180	0.32	1.06E-04
11:25	18	180	0.37	9.98E-05
11:28	12.6	180	0.42	1.04E-04
11:31	7.4	180	0.47	9.98E-05
11:40	51.5	540	0.62	
11:43	46	180	0.67	1.06E-04
11:46	40.2	180	0.72	1.11E-04
11:49	35	180	0.77	9.98E-05
11:52	29.5	180	0.82	1.06E-04
11:55	25.6	180	0.87	7.48E-05
11:58	19.2	180	0.92	1.23E-04
12:01	14.5	180	0.97	9.02E-05
12:06	53.8	480	1.1	
12:09	49.5	180	1.15	8.25E-05
12:12	44	180	1.2	1.06E-04
12:15	38.9	180	1.25	9.78E-05
12:18	33.8	180	1.3	9.78E-05
12:21	28.6	180	1.35	9.98E-05
12:24	23.4	180	1.4	9.98E-05
12:27	18.2	180	1.45	9.98E-05

Avg K
 9.85E-05



APPENDIX C - TSB DATA

Single-Stage Constant Head Borehole Test - Altamont - Composite Cover

Project: Altamont Decommissioning
Date: 04/03/07
Test ID: TSB-C1

Installer: XW
Analyst: CHB

Fixed Variables:

Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R_s (cm): 10
 L (cm): 30.48


Analysis using Horslev's isotropic constant head solution

Temporal Variables:


Time	R (cm)
4/3/07 15:03	29.2
4/3/07 15:51	41.1
4/3/07 16:18	42.1
4/3/07 16:52	43.1
4/3/07 17:13	43.8
4/3/07 17:38	44.6
4/3/07 17:57	45.1
4/3/07 18:30	46.0
4/3/07 18:45	46.5
4/3/07 19:00	47.0
4/3/07 19:15	47.5
4/3/07 19:30	48.0
4/4/07 9:44	73.4
4/4/07 10:31	75.0
4/4/07 11:34	77.0
4/4/07 12:34	78.6
4/4/07 13:34	80.5
4/4/07 14:50	82.5
4/4/07 15:50	84.5
4/4/07 16:50	86.0
4/4/07 17:50	87.8
4/4/07 18:50	89.3
4/4/07 19:30	90.5

Computations:

Q (cm ³ /s)	Time (d)	K (cm/s)
3.30E-01	0.033	9.72E-05
4.93E-02	0.052	1.45E-05
3.91E-02	0.076	1.15E-05
4.43E-02	0.090	1.31E-05
4.26E-02	0.108	1.25E-05
3.50E-02	0.121	1.03E-05
3.63E-02	0.144	1.07E-05
4.43E-02	0.154	1.31E-05
4.43E-02	0.165	1.31E-05
4.43E-02	0.175	1.31E-05
4.43E-02	0.185	1.31E-05
3.96E-02	0.778	1.17E-05
4.53E-02	0.811	1.33E-05
4.22E-02	0.855	1.24E-05
3.55E-02	0.897	1.05E-05
4.21E-02	0.938	1.24E-05
3.50E-02	0.991	1.03E-05
4.43E-02	1.033	1.31E-05
3.32E-02	1.074	9.80E-06
3.99E-02	1.116	1.18E-05
3.33E-02	1.158	9.80E-06
3.99E-02	1.185	1.18E-05



K (cm/s)
1.1E-05



Single-Stage Constant Head Borehole Test - Altamont - Composite Cover

Project: Altamont Decommissioning
Date: 03/30/07
Test ID: TSB-C2

Installer: XW
Analyst: CHB

Fixed Variables:

Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R_a (cm): 10
 L (cm): 30.48


Analysis using Horslev's isotropic constant head solution

Temporal Variables:


Time	R (cm)
4/3/07 15:03	29.5
4/3/07 15:51	31.0
4/3/07 16:18	31.8
4/3/07 16:52	32.7
4/3/07 17:13	33.4
4/3/07 17:38	34.0
4/3/07 17:57	34.4
4/3/07 18:30	35.4
4/3/07 18:45	35.7
4/3/07 19:00	36.1
4/3/07 19:15	36.7
4/3/07 19:30	37.0
4/4/07 9:44	61.2
4/4/07 10:31	62.8
4/4/07 11:34	64.6
4/4/07 12:34	66.0
4/4/07 13:34	67.6
4/4/07 14:50	69.7
4/4/07 15:50	71.5
4/4/07 16:50	72.6
4/4/07 17:50	74.4
4/4/07 18:50	75.7
4/4/07 19:30	76.6

Computations:

Q (cm ³ /s)	Time (d)	K (cm/s)
4.16E-02	0.033	1.22E-05
3.94E-02	0.052	1.16E-05
3.52E-02	0.076	1.04E-05
4.43E-02	0.090	1.31E-05
3.19E-02	0.108	9.41E-06
2.80E-02	0.121	8.25E-06
	0.144	
2.66E-02	0.154	7.84E-06
3.55E-02	0.165	1.05E-05
5.32E-02	0.175	1.57E-05
2.66E-02	0.185	7.84E-06
3.77E-02	0.778	1.11E-05
4.53E-02	0.811	1.33E-05
3.80E-02	0.855	1.12E-05
3.10E-02	0.897	9.15E-06
3.55E-02	0.938	1.05E-05
3.68E-02	0.991	1.08E-05
3.99E-02	1.033	1.18E-05
2.44E-02	1.074	7.19E-06
3.99E-02	1.116	1.18E-05
2.88E-02	1.158	8.49E-06
2.99E-02	1.185	8.82E-06



K (cm/s)
9.1E-06





Single-Stage Constant Head Borehole Test - Altamont - Composite Cover

Project: Altamont Decommissioning **Installer:** XW
Date: 04/03/07 **Analyst:** CHB
Test ID: TSB-C3

Fixed Variables:
 Casing Diameter (cm): 30.48 **Analysis using Horslev's isotropic**
 Standpipe Area (cm²): 79.8 **constant head solution**
 R_s (cm): 10
 L (cm): 30.48

Temporal Variables:		Computations:		
Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
4/3/07 15:03	46.7			
4/3/07 15:51	49.0	6.37E-02	0.03333	1.88E-05
4/3/07 16:18	50.0	4.93E-02	0.05208	1.45E-05
4/3/07 16:52	51.3	5.09E-02	0.07569	1.50E-05
4/3/07 17:13	52.1	5.07E-02	0.09028	1.49E-05
4/3/07 17:38	53.2	5.85E-02	0.10764	1.72E-05
4/3/07 17:57	53.7	3.50E-02	0.12083	1.03E-05
4/3/07 18:30	54.8	4.43E-02	0.14375	1.31E-05
4/3/07 18:45	55.4	5.32E-02	0.15417	1.57E-05
4/3/07 19:00	55.9	4.43E-02	0.16458	1.31E-05
4/3/07 19:15	56.4	4.43E-02	0.17500	1.31E-05
4/3/07 19:30	56.9	4.43E-02	0.18542	1.31E-05
4/4/07 9:44	80.0	3.60E-02	0.77847	1.06E-05
4/4/07 10:31	81.2	3.40E-02	0.81111	1.00E-05
4/4/07 11:34	82.7	3.17E-02	0.85486	9.33E-06
4/4/07 12:34	84.2	3.33E-02	0.89653	9.80E-06
4/4/07 13:34	85.4	2.66E-02	0.93819	7.84E-06
4/4/07 14:50	87.2	3.15E-02	0.99097	9.28E-06
4/4/07 15:50	88.6	3.10E-02	1.03264	9.15E-06
4/4/07 16:50	89.7	2.44E-02	1.07431	7.19E-06
4/4/07 17:50	91.1	3.10E-02	1.11597	9.15E-06
4/4/07 18:50	92.1	2.22E-02	1.15764	6.53E-06
4/4/07 19:30	93.0	2.99E-02	1.18542	8.82E-06

K (cm/s)
7.9E-06




Single-Stage Constant Head Borehole Test - Altamont - Composite Cover


Project: Altamont Decommissioning **Installer:** XW
Date: 04/03/07 **Analyst:** CHB
Test ID: TSB-C4

Fixed Variables:
 Casing Diameter (cm): 30.48 **Analysis using Horslev's isotropic**
 Standpipe Area (cm²): 79.8 **constant head solution**
 R_s (cm): 10
 L (cm): 30.48

Temporal Variables:		Computations:		
Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
4/3/07 15:03	30.0			
4/3/07 15:51	30.7	1.94E-02	0.03333	5.72E-06
4/3/07 16:52	31.5	1.74E-02	0.07569	5.14E-06
4/3/07 17:38	32.2	2.02E-02	0.10764	5.96E-06
4/3/07 18:30	32.9	1.79E-02	0.14375	5.28E-06
4/3/07 19:00	33.2	1.33E-02	0.16458	3.92E-06
4/3/07 19:30	33.6	1.77E-02	0.18542	5.23E-06
4/4/07 9:44	47.0	2.09E-02	0.77847	6.15E-06
4/4/07 10:31	47.9	2.55E-02	0.81111	7.51E-06
4/4/07 11:34	48.9	2.11E-02	0.85486	6.22E-06
4/4/07 12:34	49.8	2.00E-02	0.89653	5.88E-06
4/4/07 13:34	50.8	2.22E-02	0.93819	6.53E-06
4/4/07 14:50	51.9	1.93E-02	0.99097	5.67E-06
4/4/07 15:50	53.2	2.88E-02	1.03264	8.49E-06
4/4/07 16:50	54.0	1.77E-02	1.07431	5.23E-06
4/4/07 17:50	54.9	2.00E-02	1.11597	5.88E-06
4/4/07 18:50	55.6	1.55E-02	1.15764	4.57E-06



K (cm/s)
5.2E-06





Single-Stage Constant Head Borehole Test - Altamont - Store-and-Release Cover

Project: Altamont Decommissioning Installer: XW
 Date: 04/02/07 Analyst: CHB
 Test ID: TSB-A1

Fixed Variables:
 Casing Diameter (cm): 30.48 Analysis using Horslev's isotropic
 Standpipe Area (cm²): 79.8 constant head solution
 R₀ (cm): 10
 L (cm): 60.96

Temporal Variables:		Computations:		
Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
14:03:00	33.3			
14:11:00	38.2	8.15E-01	0.0056	1.37E-04
14:20:00	42.7	6.65E-01	0.0118	1.12E-04
14:31:00	47.2	5.44E-01	0.0194	9.15E-05
14:41:00	50.8	4.79E-01	0.0264	8.05E-05
14:56:00	55.5	4.17E-01	0.0368	7.01E-05
15:37:00	65.1	3.11E-01	0.0653	5.24E-05
15:58:00	69.2	2.60E-01	0.0799	4.37E-05
16:32:00	75.1	2.31E-01	0.1035	3.88E-05
16:53:00	78.1	1.90E-01	0.1181	3.19E-05
17:24:00	82.2	1.76E-01	0.1396	2.96E-05
17:35:00	83.6	1.69E-01	0.1472	2.85E-05
17:47:00	85.0	1.55E-01	0.1556	2.61E-05
17:53:00	85.7	1.55E-01	0.1597	2.61E-05
18:11:00	87.7	1.48E-01	0.1722	2.48E-05
9:34:00	31.0			
10:01:00	33.9	1.43E-01	0.1910	2.40E-05
10:20:00	35.8	1.33E-01	0.2042	2.24E-05
10:52:00	39.1	1.37E-01	0.2264	2.31E-05

K (cm/s)
2.4E-05



Single-Stage Constant Head Borehole Test - Altamont - Store-and-Release Cover

Project: Altamont Decommissioning
 Date: 04/02/07
 Test ID: TSB-A2


Installer: XW
 Analyst: CHB

Fixed Variables:
 Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R_s (cm): 10
 L (cm): 60.96


Analysis using Horslev's isotropic
 constant head solution

Temporal Variables:

Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
14:12:00	31.0			
14:21:00	34.1	4.58E-01	0.006	7.70E-05
14:32:00	38.1	4.84E-01	0.014	8.13E-05
14:42:00	41.2	4.12E-01	0.021	6.93E-05
14:56:00	46.0	4.56E-01	0.031	7.67E-05
15:37:00	57.5	3.73E-01	0.059	6.27E-05
15:58:00	63.7	3.93E-01	0.074	6.60E-05
16:32:00	72.6	3.48E-01	0.097	5.85E-05
16:53:00	77.9	3.36E-01	0.112	5.64E-05
17:24:00	85.7	3.35E-01	0.133	5.63E-05
17:35:00	88.6	3.51E-01	0.141	5.90E-05
17:47:00	91.4	3.10E-01	0.149	5.22E-05
17:53:00	93.2	3.99E-01	0.153	6.71E-05
18:11:00	97.8	3.40E-01	0.166	5.71E-05
9:35:00	34.0	1.64E-01		2.76E-05
9:48:00	37.8	3.89E-01	0.175	6.54E-05
10:01:00	41.7	3.99E-01	0.184	6.71E-05
10:21:00	47.4	3.79E-01	0.198	6.37E-05
10:52:00	56.4	3.86E-01	0.219	6.49E-05



K (cm/s)
 6.5E-05



Single-Stage Constant Head Borehole Test - Altamont - Store-and-Release Cover

Project: Altamont Decommissioning
 Date: 04/02/07
 Test ID: TSB-A3

Installer: XW
 Analyst: CHB

Fixed Variables:
 Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R₀ (cm): 10
 L (cm): 60.96


Analysis using Horslev's isotropic
 constant head solution

Temporal Variables:

Time	R (cm)
14:25:00	31.5
14:27:00	41.2
14:30:00	56.1
14:33:00	70.1
14:35:00	79.2
14:37:00	88.1
14:39:00	96.7
15:30:55	30.0
15:31:50	32.4
15:33:00	35.4
15:34:40	40.2
15:35:30	42.9
15:38:35	51.4
15:40:15	56.2
15:44:15	67.2
15:46:00	72.1
15:49:15	81.0
15:50:30	84.5
15:51:30	87.2
15:52:30	89.9
15:53:30	93.1
15:54:30	95.4
15:55:30	98.0
15:56:17	100.0
15:27:00	32.0
15:30:00	37.6
15:32:00	45.6
15:34:00	50.9
15:36:00	56.2
15:40:00	66.8
15:42:00	71.8
15:44:00	76.7
15:46:00	81.8
15:48:00	86.8
15:50:00	91.8
15:52:00	96.8


Computations:

Q (cm ³ /s)	Time (d)	K (cm/s)
6.45E+00	0.001	1.08E-03
6.61E+00	0.003	1.11E-03
6.21E+00	0.006	1.04E-03
6.05E+00	0.007	1.02E-03
5.92E+00	0.008	9.95E-04
5.72E+00	0.010	9.62E-04
	0.011	
3.48E+00	0.012	5.85E-04
3.42E+00	0.012	5.75E-04
3.83E+00	0.014	6.44E-04
4.31E+00	0.014	7.24E-04
3.67E+00	0.016	6.16E-04
3.83E+00	0.017	6.44E-04
3.66E+00	0.020	6.15E-04
3.72E+00	0.021	6.26E-04
3.64E+00	0.024	6.12E-04
3.72E+00	0.025	6.26E-04
3.59E+00	0.025	6.04E-04
3.59E+00	0.026	6.04E-04
4.26E+00	0.027	7.16E-04
3.06E+00	0.027	5.14E-04
3.46E+00	0.028	5.81E-04
3.40E+00	0.029	5.71E-04
2.48E+00	0.031	4.17E-04
5.32E+00	0.032	8.94E-04
3.52E+00	0.033	5.93E-04
3.52E+00	0.035	5.93E-04
3.52E+00	0.038	5.93E-04
3.33E+00	0.039	5.59E-04
3.26E+00	0.040	5.48E-04
3.39E+00	0.042	5.70E-04
3.33E+00	0.043	5.59E-04
3.33E+00	0.045	5.59E-04
3.33E+00	0.046	5.59E-04



9:46:00	30.3			
9:50	35.1	1.60E+00	0.049	2.68E-04
9:55	40.5	1.44E+00	0.052	2.41E-04
10:02	46.9	1.22E+00	0.057	2.04E-04
10:09	53.5	1.25E+00	0.062	2.11E-04
10:16	59.4	1.12E+00	0.067	1.88E-04
10:22	64.2	1.06E+00	0.071	1.79E-04
10:29	69.8	1.06E+00	0.076	1.79E-04
10:44	81.2	1.01E+00	0.086	1.70E-04
10:53	87.5	9.31E-01	0.093	1.57E-04
11:01	93.9	1.06E+00	0.098	1.79E-04
11:28	30.0		0.117	
11:30	31.9	1.26E+00	0.118	2.12E-04
11:34	35.1	1.06E+00	0.121	1.79E-04
11:37	37.5	1.06E+00	0.123	1.79E-04
11:40	40.0	1.11E+00	0.125	1.86E-04
11:43	42.3	1.02E+00	0.127	1.71E-04
11:46	44.6	1.02E+00	0.129	1.71E-04
11:52	49.0	9.75E-01	0.133	1.64E-04
12:00	55.0	9.98E-01	0.139	1.68E-04
12:09	61.7	9.90E-01	0.145	1.66E-04
12:19	68.6	9.18E-01	0.152	1.54E-04
12:29	75.8	9.58E-01	0.159	1.61E-04
12:37	81.5	9.48E-01	0.165	1.59E-04
12:51	91.0	9.03E-01	0.174	1.52E-04

K (cm/s)
1.6E-04





Single-Stage Constant Head Borehole Test - Altamont - Store-and-Release Cover

Project: Altamont Decommissioning Installer: XW
 Date: 04/02/07 Analyst: CHB
 Test ID: TSB-A4

Fixed Variables:
 Casing Diameter (cm): 30.48 Analysis using Horslev's isotropic
 Standpipe Area (cm²): 79.8 constant head solution
 R_s (cm): 10
 L (cm): 60.96

Temporal Variables:		Computations:		
Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
14:22:00	32.7			
14:24:00	36.5	2.53E+00	0.00139	4.25E-04
14:29:00	43.1	1.76E+00	0.00486	2.95E-04
14:34:00	49.4	1.68E+00	0.00833	2.82E-04
14:36:00	51.7	1.53E+00	0.00972	2.57E-04
14:38:00	54.1	1.60E+00	0.01111	2.68E-04
14:42:00	58.7	1.53E+00	0.01389	2.57E-04
14:47:00	64.0	1.41E+00	0.01736	2.37E-04
14:52:00	70.0	1.60E+00	0.02083	2.68E-04
14:56:00	73.2	1.06E+00	0.02361	1.79E-04
15:01:00	78.5	1.41E+00	0.02708	2.37E-04
15:28:00	35.4			
15:33:00	39.1	9.84E-01	0.049305556	1.65E-04
15:39:00	43.0	8.65E-01	0.05347	1.45E-04
15:44:00	46.8	1.01E+00	0.05694	1.70E-04
15:49:00	50.2	9.04E-01	0.06042	1.52E-04
15:53:00	52.8	8.65E-01	0.06319	1.45E-04
15:57:00	54.9	6.98E-01	0.06597	1.17E-04
16:28:00	74.2	8.28E-01	0.08750	1.39E-04
16:34:00	78.1	8.64E-01	0.09167	1.45E-04
16:45:00	84.7	7.98E-01	0.09931	1.34E-04
16:52:00	88.8	7.79E-01	0.10417	1.31E-04
17:12:00	99.6	7.18E-01	0.11806	1.21E-04
9:37:00	31.0			
9:49:00	36.9	6.54E-01	0.12639	1.10E-04
10:02:00	42.6	5.83E-01	0.13542	9.80E-05
10:10:00	46.2	5.99E-01	0.14097	1.01E-04
10:23:00	51.6	5.52E-01	0.15000	9.29E-05
10:31:00	55.0	5.65E-01	0.15556	9.50E-05
10:45:00	60.7	5.42E-01	0.16528	9.10E-05
10:52:00	64.0	6.27E-01	0.17014	1.05E-04
11:24:00	76.2	5.07E-01	0.19236	8.53E-05
11:36:00	81.0	5.32E-01	0.20069	8.94E-05
11:44:00	84.2	5.32E-01	0.20625	8.94E-05
12:09:00	94.1	5.27E-01	0.22361	8.85E-05
12:18:00	97.5	5.02E-01	0.22986	8.45E-05

K (cm/s)
8.7E-05



Single-Stage Constant Head Borehole Test - Apple Valley - Clay Cover

Project: Apple Valley Decommissioning Installer: XW
 Date: 03/30/07 Analyst: CHB
 Test ID: C-2



Fixed Variables:

Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R_s (cm): 10
 L (cm): 30.48

Temporal Variables:

Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
10:00:00	35.0			
10:00:08	45.0	9.98E+01	0.00009	2.94E-02
10:00:16	55.0	9.98E+01	0.00019	2.94E-02
10:00:25	65.0	8.87E+01	0.00029	2.61E-02
10:00:34	75.0	8.87E+01	0.00039	2.61E-02
10:00:43	85.0	8.87E+01	0.00050	2.61E-02
10:00:56	100.0	9.21E+01	0.00065	2.71E-02
10:01:00	30.0		0.00069	
10:01:08	40.0	9.98E+01	0.00079	2.94E-02
10:01:16	50.0	9.97E+01	0.00088	2.94E-02
10:01:25	60.0	8.87E+01	0.00098	2.61E-02
10:01:36	70.0	7.25E+01	0.00111	2.14E-02
10:01:45	80.0	8.87E+01	0.00122	2.61E-02
10:01:55	90.0	7.98E+01	0.00133	2.35E-02
10:02:05	100.0	7.98E+01	0.00145	2.35E-02
10:03:00	30.0		0.00208	
10:03:09	40.0	8.87E+01	0.00219	2.61E-02
10:03:20	50.0	7.25E+01	0.00231	2.14E-02
10:03:30	60.0	7.98E+01	0.00243	2.35E-02
10:03:40	70.0	7.98E+01	0.00255	2.35E-02
10:03:50	80.0	7.98E+01	0.00266	2.35E-02
10:04:00	90.0	7.98E+01	0.00278	2.35E-02
10:04:10	100.0	7.98E+01	0.00289	2.35E-02
10:05:00	35.0		0.00347	
10:05:10	45.0	7.98E+01	0.00359	2.35E-02
10:05:20	55.0	7.98E+01	0.00370	2.35E-02
10:05:31	65.0	7.25E+01	0.00383	2.14E-02
10:05:41	75.0	7.98E+01	0.00395	2.35E-02
10:05:51	85.0	7.98E+01	0.00406	2.35E-02
10:06:08	100.0	7.04E+01	0.00426	2.08E-02

AVG
2.28E-02



Single-Stage Constant Head Borehole Test - Apple Valley - Clay Cover

Project: Apple Valley Decommissioning
 Date: 03/30/07
 Test ID: C-3

Installer: XW
 Analyst: CHB



Fixed Variables:

Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R_s (cm): 10
 L (cm): 30.48

Temporal Variables:

Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
11:00:00	39.5			
11:05:00	42.0	6.65E-01	0.003	1.96E-04
11:13:00	45.6	5.99E-01	0.009	1.76E-04
11:27:00	51.5	5.61E-01	0.019	1.65E-04
11:35:00	54.6	5.15E-01	0.024	1.52E-04
11:46:00	58.6	4.84E-01	0.032	1.43E-04
12:06:00	65.6	4.66E-01	0.046	1.37E-04
12:17:00	69.4	4.59E-01	0.053	1.35E-04
12:36:00	75.5	4.27E-01	0.067	1.26E-04
13:08:00	85.3	4.07E-01	0.089	1.20E-04
13:34:00	93.2	4.04E-01	0.107	1.19E-04
14:07:00	101.0	3.14E-01	0.130	9.26E-05
14:11:00	32.0		0.133	
14:44:00	43.6	4.68E-01	0.156	1.38E-04
15:17:00	54.8	4.51E-01	0.178	1.33E-04
15:26:00	57.5	3.99E-01	0.185	1.18E-04
16:43:00	81.0	4.06E-01	0.238	1.20E-04
17:07:00	88.0	3.88E-01	0.255	1.14E-04
17:15:00	90.0	3.33E-01	0.260	9.80E-05
17:25:00	93.0	3.99E-01	0.267	1.18E-04
17:32:00	94.8	3.42E-01	0.272	1.01E-04

Average
1.22E-04




Single-Stage Constant Head Borehole Test - Apple Valley - Clay Cover


Project: Apple Valley Decommissioning Installer: XW
 Date: 03/30/07 Analyst: CHB
 Test ID: C-4

Fixed Variables:
 Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R_s (cm): 10
 L (cm): 30.48

Temporal Variables:		Computations:		
Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
10:00:07	37.0			
10:00:21	43.0	3.42E+01	0.000	1.01E-02
10:00:42	50.0	2.66E+01	0.000	7.84E-03
10:01:12	60.0	2.66E+01	0.001	7.84E-03
10:01:35	70.0	3.47E+01	0.001	1.02E-02
10:02:07	80.0	2.49E+01	0.001	7.35E-03
10:02:36	90.0	2.75E+01	0.002	8.11E-03
10:10:00	30.0		0.007	
10:10:26	40.0	3.07E+01	0.007	9.05E-03
10:10:53	50.0	2.96E+01	0.007	8.71E-03
10:11:20	60.0	2.96E+01	0.008	8.71E-03
10:11:45	70.0	3.19E+01	0.008	9.41E-03
10:12:16	80.0	2.57E+01	0.008	7.59E-03
10:12:43	90.0	2.96E+01	0.009	8.71E-03
10:20:00	30.0		0.014	
10:20:23	40.0	3.47E+01	0.014	1.02E-02
10:20:46	50.0	3.47E+01	0.014	1.02E-02
10:21:11	60.0	3.19E+01	0.015	9.41E-03
10:21:35	70.0	3.32E+01	0.015	9.80E-03
10:22:02	80.0	2.96E+01	0.015	8.71E-03
10:22:26	90.0	3.33E+01	0.015	9.80E-03
10:30:00	35.0		0.021	
10:30:11	40.0	3.63E+01	0.021	1.07E-02
10:30:35	50.0	3.32E+01	0.021	9.80E-03
10:30:59	60.0	3.33E+01	0.021	9.80E-03
10:31:25	70.0	3.07E+01	0.022	9.05E-03
10:31:49	80.0	3.32E+01	0.022	9.80E-03
10:32:14	90.0	3.19E+01	0.022	9.41E-03
10:40:00	30.0		0.028	
10:40:24	40.0	3.32E+01	0.028	9.80E-03
10:40:49	50.0	3.19E+01	0.028	9.41E-03
10:41:14	60.0	3.19E+01	0.029	9.41E-03
10:41:40	70.0	3.07E+01	0.029	9.05E-03
10:42:04	80.0	3.33E+01	0.029	9.80E-03
10:42:31	90.0	2.96E+01	0.029	8.71E-03



AVG
 9.60E-03




Single-Stage Constant Head Borehole Test - Apple Valley - Clay Cover


Project: Apple Valley Decommissioning Installer: XW
 Date: 03/30/07 Analyst: CHB
 Test ID: C-5

Fixed Variables:
 Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R_s (cm): 10
 L (cm): 30.48

Temporal Variables:		Computations:		
Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
10:00:00	40.0			
10:00:12	55.0	9.97E+01	0.00014	2.94E-02
10:00:22	70.0	1.20E+02	0.00025	3.53E-02
10:00:32	85.0	1.20E+02	0.00037	3.53E-02
10:00:45	100.0	9.21E+01	0.00052	2.71E-02
10:01:00	35.0		0.00069	
10:01:10	50.0	1.20E+02	0.00081	3.53E-02
10:01:15	60.0	1.60E+02	0.00087	4.70E-02
10:01:20	70.0	1.60E+02	0.00093	4.70E-02
10:01:30	80.0	7.98E+01	0.00104	2.35E-02
10:01:39	90.0	8.87E+01	0.00115	2.61E-02
10:01:46	100.0	1.14E+02	0.00123	3.36E-02
10:02:00	30.0		0.00139	
10:02:07	40.0	1.14E+02	0.00147	3.36E-02
10:02:14	50.0	1.14E+02	0.00155	3.36E-02
10:02:21	60.0	1.14E+02	0.00163	3.36E-02
10:02:30	70.0	8.87E+01	0.00174	2.61E-02
10:02:38	80.0	9.97E+01	0.00183	2.94E-02
10:02:43	90.0	1.60E+02	0.00189	4.70E-02
10:02:54	100.0	7.25E+01	0.00201	2.14E-02
10:03:00	30.0		0.00208	
10:03:06	40.0	1.33E+02	0.00215	3.92E-02
10:03:13	50.0	1.14E+02	0.00223	3.36E-02
10:03:21	60.0	9.97E+01	0.00233	2.94E-02
10:03:28	70.0	1.14E+02	0.00241	3.36E-02
10:03:35	80.0	1.14E+02	0.00249	3.36E-02
10:03:42	90.0	1.14E+02	0.00257	3.36E-02
10:03:50	100.0	9.98E+01	0.00266	2.94E-02
10:04:00	30.0		0.00278	
10:04:07	40.0	1.14E+02	0.00286	3.36E-02
10:04:15	50.0	9.98E+01	0.00295	2.94E-02
10:04:21	60.0	1.33E+02	0.00302	3.92E-02
10:04:30	70.0	8.87E+01	0.00312	2.61E-02
10:04:38	80.0	9.97E+01	0.00322	2.94E-02



AVG
3.15E-02



Single-Stage Constant Head Borehole Test - Apple Valley - Clay Cover

Project: Apple Valley Decommissioning **Installer:** XW
Date: 03/30/07 **Analyst:** CHB
Test ID: C-7


Fixed Variables:

Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R_s (cm): 10
 L (cm): 30.48


Temporal Variables:

Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
10:58:00	35.9			
11:05:00	36.9	1.90E-01	0.005	5.60E-05
11:14:00	38.2	1.92E-01	0.011	5.66E-05
11:35:00	41.4	2.03E-01	0.026	5.97E-05
11:50:00	43.5	1.86E-01	0.036	5.49E-05
12:17:00	47.2	1.82E-01	0.055	5.37E-05
12:36:00	49.6	1.68E-01	0.068	4.95E-05
13:10:00	54.4	1.88E-01	0.092	5.53E-05
13:35:00	57.6	1.70E-01	0.109	5.02E-05
14:11:00	62.5	1.81E-01	0.134	5.34E-05
14:43:00	66.5	1.66E-01	0.156	4.90E-05
15:17:00	71.0	1.76E-01	0.180	5.19E-05
15:25:00	72.0	1.66E-01	0.185	4.90E-05
16:42:00	81.9	1.71E-01	0.239	5.04E-05

Computations:



AVG
 5.17E-05



Single-Stage Constant Head Borehole Test - Apple Valley - Store-and-Release Cover

Project: Apple Valley Decommissioning Installer: XW
 Date: 05/30/07 Analyst: CHB
 Test ID: ALT-1



Fixed Variables:

Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R_s (cm): 10
 L (cm): 30.48

Temporal Variables:

Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
9:29:00	34.0			
9:30:00	37.4	4.52E+00	0.0007	1.33E-03
9:30:55	39.9	3.63E+00	0.0013	1.07E-03
9:31:40	42.0	3.72E+00	0.0019	1.10E-03
9:32:45	44.8	3.44E+00	0.0026	1.01E-03
9:33:40	47.3	3.63E+00	0.0032	1.07E-03
9:34:35	49.5	3.19E+00	0.0039	9.41E-04
9:35:35	51.9	3.19E+00	0.0046	9.41E-04
9:36:35	54.3	3.19E+00	0.0053	9.41E-04
9:37:35	56.5	2.93E+00	0.0060	8.62E-04
9:38:35	58.8	3.06E+00	0.0067	9.02E-04
9:39:35	61.1	3.06E+00	0.0073	9.02E-04
9:40:35	63.4	3.06E+00	0.0080	9.02E-04
9:41:35	65.6	2.93E+00	0.0087	8.62E-04
9:42:35	68.0	3.19E+00	0.0094	9.41E-04
9:43:35	70.1	2.79E+00	0.0101	8.23E-04
9:44:35	72.3	2.93E+00	0.0108	8.62E-04
9:45:35	74.5	2.93E+00	0.0115	8.62E-04
9:46:35	76.9	3.19E+00	0.0122	9.41E-04
9:47:35	78.8	2.53E+00	0.0129	7.45E-04
9:48:35	81.0	2.93E+00	0.0136	8.62E-04
9:49:35	82.9	2.53E+00	0.0143	7.45E-04
9:50:35	85.1	2.93E+00	0.0150	8.62E-04
9:51:35	87.2	2.79E+00	0.0157	8.23E-04
9:52:35	89.2	2.66E+00	0.0164	7.84E-04
9:53:35	91.2	2.66E+00	0.0171	7.84E-04
9:54:35	93.4	2.93E+00	0.0178	8.62E-04
9:55:35	95.4	2.66E+00	0.0185	7.84E-04
9:56:35	97.4	2.66E+00	0.0192	7.84E-04
9:57:35	99.3	2.53E+00	0.0198	7.45E-04

AVG
8.10E-04




Single-Stage Constant Head Borehole Test - Apple Valley - Store-and-Release Cover


Project: Apple Valley Decommissioning Installer: XW
 Date: 03/30/07 Analyst: CHB
 Test ID: ALT-2

Fixed Variables:
 Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R_s (cm): 10
 L (cm): 30.48

Temporal Variables:		Computations:		
Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
10:06:00	32.5			
10:07:00	35.0	3.33E+00	0.001	9.80E-04
10:08:00	37.5	3.33E+00	0.001	9.80E-04
10:09:00	39.6	2.79E+00	0.002	8.23E-04
10:10:00	41.7	2.79E+00	0.003	8.23E-04
10:11:00	44.0	3.06E+00	0.003	9.02E-04
10:12:00	46.1	2.79E+00	0.004	8.23E-04
10:13:00	48.0	2.53E+00	0.005	7.45E-04
10:14:00	50.0	2.66E+00	0.006	7.84E-04
10:15:00	51.9	2.53E+00	0.006	7.45E-04
10:16:00	53.8	2.53E+00	0.007	7.45E-04
10:17:00	55.8	2.66E+00	0.008	7.84E-04
10:18:00	57.7	2.53E+00	0.008	7.45E-04
10:19:00	59.5	2.39E+00	0.009	7.06E-04
10:20:00	61.5	2.66E+00	0.010	7.84E-04
10:21:00	63.3	2.39E+00	0.010	7.06E-04
10:22:00	65.2	2.53E+00	0.011	7.45E-04
10:23:00	66.9	2.26E+00	0.012	6.66E-04
10:24:00	68.5	2.13E+00	0.013	6.27E-04
10:25:00	70.4	2.53E+00	0.013	7.45E-04
10:26:00	72.0	2.13E+00	0.014	6.27E-04
10:27:00	73.8	2.39E+00	0.015	7.06E-04
10:28:00	75.5	2.26E+00	0.015	6.66E-04
10:29:00	77.3	2.39E+00	0.016	7.06E-04
10:30:00	79.1	2.39E+00	0.017	7.06E-04
10:31:00	80.8	2.26E+00	0.017	6.66E-04
10:32:00	82.4	2.13E+00	0.018	6.27E-04
10:33:00	84.1	2.26E+00	0.019	6.66E-04
10:34:00	85.6	2.00E+00	0.019	5.88E-04
10:35:00	87.4	2.39E+00	0.020	7.06E-04
10:36:00	89.0	2.13E+00	0.021	6.27E-04
10:37:00	90.8	2.39E+00	0.022	7.06E-04
10:38:00	92.5	2.26E+00	0.022	6.66E-04
10:39:00	94.1	2.13E+00	0.023	6.27E-04
10:41:00	97.7	2.39E+00	0.024	7.06E-04
10:42:00	99.2	2.00E+00	0.025	5.88E-04



AVG
6.27E-04



Single-Stage Constant Head Borehole Test - Boardman - Thin Store-and-Release Cover

Project: Boardman
 Date: 08/20/07
 Test ID: TH-1

Installer: XW
 Analyst: CHB


Fixed Variables:
 Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R_s (cm): 10
 L (cm): 60.96

Temporal Variables:


Time	R (cm)
2:49:00	32.0
2:50:00	33.0
2:52:00	35.5
2:53:00	37.0
2:54:00	38.0
2:56:00	41.5
2:58:00	43.0
2:59:00	44.5
3:00:00	45.5
3:01:00	47.0
3:02:00	48.0
3:03:00	49.0
3:04:00	50.5
3:05:00	52.0
3:06:00	53.0
3:07:00	54.5
3:08:00	55.5
3:09:00	56.5
3:10:00	58.0
3:11:00	59.0
3:12:00	60.5
3:13:00	61.5
3:16:00	65.5

Computations:

Q (cm ³ /s)	Time (d)	K (cm/s)
1.33E+00	0.0007	2.24E-04
1.66E+00	0.0021	2.80E-04
2.00E+00	0.0028	3.35E-04
1.33E+00	0.0035	2.24E-04
2.33E+00	0.0049	3.91E-04
9.98E-01	0.0063	1.68E-04
2.00E+00	0.0069	3.35E-04
1.33E+00	0.0076	2.24E-04
2.00E+00	0.0083	3.35E-04
1.33E+00	0.0090	2.24E-04
1.33E+00	0.0097	2.24E-04
1.99E+00	0.0104	3.35E-04
2.00E+00	0.0111	3.35E-04
1.33E+00	0.0118	2.24E-04
2.00E+00	0.0125	3.35E-04
1.33E+00	0.0132	2.24E-04
1.33E+00	0.0139	2.24E-04
2.00E+00	0.0146	3.35E-04
1.33E+00	0.0153	2.24E-04
2.00E+00	0.0160	3.35E-04
1.33E+00	0.0167	2.24E-04
1.77E+00	0.0188	2.98E-04



AVG
 2.98E-04



Single-Stage Constant Head Borehole Test - Boardman - Thin Store-and-Release Cover

Project: Boardman
 Date: 08/20/07
 Test ID: TH-2


Installer: XW
 Analyst: CHB

Fixed Variables:


Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R_s (cm): 10
 L (cm): 30.48

Temporal Variables:

Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
2:44:00	33.0			
2:45:00	35.0	2.66E+00	0.001	7.84E-04
2:46:00	37.0	2.66E+00	0.001	7.84E-04
2:47:00	39.0	2.66E+00	0.002	7.84E-04
2:48:00	41.0	2.66E+00	0.003	7.84E-04
2:52:00	48.0	2.33E+00	0.006	6.86E-04
2:53:00	50.0	2.66E+00	0.006	7.84E-04
2:54:00	52.0	2.66E+00	0.007	7.84E-04
2:56:00	56.5	2.99E+00	0.008	8.82E-04
2:58:00	58.5	1.33E+00	0.010	3.92E-04
2:59:00	60.5	2.66E+00	0.010	7.84E-04
3:00:00	62.0	2.00E+00	0.011	5.88E-04
3:01:00	63.5	2.00E+00	0.012	5.88E-04
3:02:00	65.5	2.66E+00	0.013	7.84E-04
3:03:00	67.0	2.00E+00	0.013	5.88E-04
3:04:00	69.0	2.66E+00	0.014	
3:05:00	70.5	2.00E+00	0.015	5.88E-04
3:06:00	72.0	2.00E+00	0.015	5.88E-04
3:07:00	74.0	2.66E+00	0.016	7.84E-04
3:08:00	75.5	2.00E+00	0.017	5.88E-04
3:09:00	77.5	2.66E+00	0.017	7.84E-04
3:10:00	79.0	2.00E+00	0.018	5.88E-04
3:11:00	80.5	2.00E+00	0.019	5.88E-04
3:12:00	82.5	2.66E+00	0.019	7.84E-04
3:13:00	84.0	2.00E+00	0.020	5.88E-04



AVG
 6.53E-04




Single-Stage Constant Head Borehole Test - Boardman - Thin Store-and-Release Cover

Project: Boardman
 Date: 08/20/07
 Test ID: TH-3


Installer: XW
 Analyst: CHB

Fixed Variables:
 Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R_s (cm): 10
 L (cm): 30.48

Temporal Variables:		Computations:		
Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
2:56:00	34.0			
2:58:00	39.5	3.66E+00	0.001	1.08E-03
2:59:00	43.0	4.66E+00	0.002	1.37E-03
3:00:00	46.0	3.99E+00	0.003	1.18E-03
3:01:00	49.0	3.99E+00	0.003	1.18E-03
3:02:00	52.0	3.99E+00	0.004	1.18E-03
3:03:00	55.0	3.99E+00	0.005	1.18E-03
3:04:00	58.0	3.99E+00	0.006	1.18E-03
3:05:00	61.0	3.99E+00	0.006	1.18E-03
3:06:00	64.0	3.99E+00	0.007	1.18E-03
3:07:00	66.5	3.33E+00	0.008	9.80E-04
3:08:00	70.0	4.66E+00	0.008	1.37E-03
3:09:00	72.5	3.33E+00	0.009	9.80E-04
3:10:00	75.0	3.33E+00	0.010	9.80E-04
3:11:00	78.0	3.99E+00	0.010	1.18E-03
3:12:00	81.0	3.99E+00	0.011	1.18E-03
3:13:00	84.0	3.99E+00	0.012	1.18E-03



AVG
 1.18E-03



Single-Stage Constant Head Borehole Test - Boardman - Thin Store-and-Release Cover

Project: Boardman
 Date: 08/20/07
 Test ID: TH-4

Installer: XW
 Analyst: CHB

Fixed Variables:

Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R_s (cm): 10
 L (cm): 60.96



Temporal Variables:

Time	R (cm)
14:22:00	32.7
14:24:00	36.5
14:29:00	43.1
14:34:00	49.4
14:36:00	51.7
14:38:00	54.1
14:42:00	58.7

Computations:

Time (d)	Q (cm ³ /s)	K (cm/s)
36.5	1.68E+04	2.82E+00
79.6	1.68E+04	2.82E+00
129	1.60E+04	2.70E+00
180.7	1.68E+04	2.82E+00
234.8	2.41E+04	4.05E+00
293.5	2.48E+04	4.17E+00

AVG
2.79E+00



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis
Boardman - Thick Store-and-Release Cover

TRIAL 1

Test ID: TK-1 Installer: XW
 Project: Boardman Analyst: CHB

FIXED VARIABLES


d (cm) = 10.16
 D (cm) = 30.48
 R_a (cm) = 0
 Final Time: 1/1/00 10:58:30

FITTED VARIABLES

a (s⁻¹) = 0.0000839
 H* (m) = 0.49
 H₀ (m) = 0.82
 MSE (m²) = 1.33E-06
 Bias (m) = -3.34E-08

SOLUTION - TRIAL 1

K (m/s) = 8.12E-07 8.12E-05
 Total Time (d) = 0.07 1.7 hrs



TEMPORAL VARIABLES

Time (m/d/yr h:m)	R (cm)
1/1/1900 9:17:17	33
1/1/1900 9:22:30	30.9
1/1/1900 9:27:30	28.9
1/1/1900 9:32:30	26.9
1/1/1900 9:37:30	25
1/1/1900 9:42:30	23.1
1/1/1900 9:47:30	21.2
1/1/1900 9:52:30	19.6
1/1/1900 9:57:30	17.8
1/1/1900 10:02:30	16.2
1/1/1900 10:07:30	14.6
1/1/1900 10:12:30	13.1
1/1/1900 10:18:30	11.2
1/1/1900 10:28:30	8.5
1/1/1900 10:38:30	5.6
1/1/1900 10:48:30	2.7
1/1/1900 10:58:30	0

Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	ε (m)	ε ² (m)
0.33	0.00	0.329	-9.01E-04	8.11E-07
0.31	313	0.308	-1.11E-03	1.23E-06
0.29	613	0.288	-9.24E-04	8.53E-07
0.27	913	0.269	-2.44E-04	5.94E-08
0.25	1213	0.250	-8.34E-05	6.96E-09
0.23	1513	0.232	5.45E-04	2.98E-07
0.21	1813	0.214	1.63E-03	2.66E-06
0.20	2113	0.196	1.62E-04	2.64E-08
0.18	2413	0.179	1.13E-03	1.27E-06
0.16	2713	0.163	5.17E-04	2.68E-07
0.15	3013	0.146	3.20E-04	1.02E-07
0.13	3313	0.131	-4.75E-04	2.26E-07
0.11	3673	0.112	8.86E-05	7.86E-09
0.09	4273	0.083	-2.43E-03	5.89E-06
0.06	4873	0.055	-1.49E-03	2.23E-06
0.03	5473	0.028	8.20E-04	6.73E-07
0.00	6073	0.002	2.44E-03	5.97E-06

Chiasson Solution:

Chiasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.


$$Z_t = H_0 e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	0.329
304	0.309
607	0.288
911	0.269
1215	0.250
1518	0.231
1822	0.213
2126	0.195
2429	0.178
2733	0.161
3037	0.145
3340	0.129
3644	0.114
3947	0.098
4251	0.084
4555	0.069
4858	0.055
5162	0.041
5466	0.028
5769	0.015
6073	0.002

Δt (s) = 304



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis Boardman - Thick Store-and-Release Cover

TRIAL 1

Test ID: TK-2 Installer: XW
Project: Boardman Analyst: CHB

FIXED VARIABLES

d (cm) = 10.16
D (cm) = 30.48
R_a (cm) = 0
Final Time: 1/0/00 9:14:37

FITTED VARIABLES

a (s⁻¹) = 0.0047384
H* (m) = 0.92
H₀ (m) = 1.50
MSE (m²) = 7.78E-06
Bias (m) = -6.04E-08

SOLUTION - TRIAL 1


K (m/s) = 4.58E-05
Total Time (d) = 0.00 0.0 hrs

TEMPORAL VARIABLES

Time (m/d/yr h:m)	R (cm)
1/0/00 9:12:54	58
1/0/00 9:13:02	53
1/0/00 9:13:07	49
1/0/00 9:13:13	45
1/0/00 9:13:21	40
1/0/00 9:13:30	35
1/0/00 9:13:38	30
1/0/00 9:13:47	25
1/0/00 9:13:55	20
1/0/00 9:14:05	15
1/0/00 9:14:15	10
1/0/00 9:14:27	5
1/0/00 9:14:37	0

Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	ε (m)	ε ² (m)
0.58	0.00	0.582	1.76E-03	3.10E-06
0.53	8	0.526	-4.19E-03	1.76E-05
0.49	13	0.492	-1.90E-03	3.59E-06
0.45	19	0.452	2.25E-03	5.06E-06
0.40	27	0.401	1.11E-03	1.24E-06
0.35	36	0.346	-4.15E-03	1.72E-05
0.30	44	0.299	-1.33E-03	1.76E-06
0.25	53	0.248	-2.31E-03	5.34E-06
0.20	61	0.204	4.16E-03	1.73E-05
0.15	71	0.152	2.02E-03	4.08E-06
0.10	81	0.102	2.29E-03	5.25E-06
0.05	93	0.046	-4.35E-03	1.89E-05
0.00	103	0.001	8.42E-04	7.10E-07



Chiasson Solution:
Chiasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.


$$Z_t = H_0 e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	0.582
5	0.545
10	0.510
15	0.476
21	0.442
26	0.409
31	0.377
36	0.346
41	0.315
46	0.285
51	0.256
57	0.228
62	0.200
67	0.173
72	0.146
77	0.121
82	0.096
88	0.071
93	0.047
98	0.024
103	0.001

Δt (s) = 5



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis Boardman - Thick Store-and-Release Cover

TRIAL 2

Test ID: TK-2 Installer: XW
Project: Boardman Analyst: CHB

FIXED VARIABLES

d (cm) = 30.48
D (cm) = 10.16
R_s (cm) = 0
Final Time: 1/0/1900 9:16:23


FITTED VARIABLES

a (s⁻¹) = 0.0056544
H* (m) = 0.93
H₀ (m) = 1.53
MSE (m²) = 4.41E-06
Bias (m) = 2.30E-09

SOLUTION - TRIAL 1

K (m/s) = 1.48E-03

Total Time (d) = 0.00 0.0 hrs



TEMPORAL VARIABLES

Time (m/d/yr h:m)	R (cm)
1/0/1900 9:15:08	60
1/0/1900 9:15:14	55
1/0/1900 9:15:20	50
1/0/1900 9:15:26	45
1/0/1900 9:15:33	40
1/0/1900 9:15:40	35
1/0/1900 9:15:46	30
1/0/1900 9:15:54	25
1/0/1900 9:15:59	20
1/0/1900 9:16:08	15
1/0/1900 9:16:16	10
1/0/1900 9:16:23	5

Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	ε (m)	ε ² (m)
0.60	0	0.600	4.65E-04	2.16E-07
0.55	6	0.549	-6.84E-04	4.68E-07
0.50	12	0.500	-1.27E-04	1.62E-08
0.45	18	0.452	2.08E-03	4.32E-06
0.40	25	0.398	-1.67E-03	2.78E-06
0.35	32	0.347	-3.33E-03	1.11E-05
0.30	38	0.304	3.99E-03	1.59E-05
0.25	46	0.249	-7.18E-04	5.16E-07
0.20	51	0.216	1.63E-02	2.67E-04
0.15	60	0.159	9.31E-03	8.66E-05
0.10	68	0.111	1.10E-02	1.21E-04
0.05	75	0.070	2.05E-02	4.20E-04

Chiasson Solution:

Chiasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.


$$Z_t = H_0 e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	0.600
4	0.568
7	0.537
11	0.506
15	0.476
19	0.446
22	0.417
26	0.389
30	0.361
34	0.334
37	0.307
41	0.281
45	0.256
49	0.231
52	0.207
56	0.183
60	0.159
64	0.136
67	0.114
71	0.092
75	0.070

Δt (s) = 4




**Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis
Boardman - Thick Store-and-Release Cover**

Equilibrium Evaluation & Steady Hydraulic Conductivity Determination

Trial	Time (d)	Total Time (d)	K (m/s)	
1	0.001	0.001	4.58E-05	TK-2
2	0.001	0.002	1.48E-03	
3	0.017	0.019	1.13E-04	

Field Hydraulic Conductivity

5.45E-04 m/s
5.45E-02 cm/s



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis
Boardman - Thick Store-and-Release Cover

TRIAL 1

Test ID: TK-3 Installer: XW
 Project: Boardman Analyst: CHB

FIXED VARIABLES


d (cm) = 10.16
 D (cm) = 30.48
 R_s (cm) = 0
 Final Time: 1:58:05

FITTED VARIABLES

a (s⁻¹) = 0.0000208
 H* (m) = 3.50
 H₀ (m) = 4.00
 MSE (m²) = 1.24E-04
 Bias (m) = -1.89E-09

SOLUTION -TRIAL 1

K (m/s) = 2.01E-07 2.01E-05
 Total Time (d) = 0.08 2.0 hrs



TEMPORAL VARIABLES

Time (m/d/yr h:m)	R (cm)
0:00:00	48.5
0:04:18	46.3
0:16:57	40.5
0:22:05	38.1
0:27:05	35.8
0:32:05	33.7
0:37:05	31.6
0:42:05	29.4
0:47:05	27.2
0:52:05	25.2
0:57:05	23.2
1:02:05	21.2
1:07:05	19.2
1:12:05	17.2
1:18:05	14.9
1:28:05	11.1
1:38:05	7.5
1:48:05	3.6
1:58:05	0

Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	ε (m)	ε ² (m)
0.49	0.00	0.500	1.50E-02	2.25E-04
0.46	258	0.479	1.56E-02	2.43E-04
0.41	1017	0.416	1.13E-02	1.27E-04
0.38	1325	0.391	1.02E-02	1.05E-04
0.36	1625	0.367	9.03E-03	8.16E-05
0.34	1925	0.343	5.97E-03	3.57E-05
0.32	2225	0.319	3.06E-03	9.37E-06
0.29	2525	0.295	1.30E-03	1.69E-06
0.27	2825	0.272	-3.14E-04	9.84E-08
0.25	3125	0.248	-3.78E-03	1.43E-05
0.23	3425	0.225	-7.10E-03	5.04E-05
0.21	3725	0.202	-1.03E-02	1.06E-04
0.19	4025	0.179	-1.33E-02	1.77E-04
0.17	4325	0.156	-1.62E-02	2.62E-04
0.15	4685	0.129	-2.05E-02	4.19E-04
0.11	5285	0.084	-2.75E-02	7.56E-04
0.08	5885	0.039	-3.59E-02	1.29E-03
0.04	6485	-0.005	-4.08E-02	1.67E-03
0.00	7085	-0.048	-4.82E-02	2.32E-03

Chiasson Solution:

Chiasson, P. (2005). Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.


$$Z_t = H_0 e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	0.500
354	0.471
709	0.441
1063	0.413
1417	0.384
1771	0.355
2126	0.327
2480	0.299
2834	0.271
3188	0.243
3543	0.216
3897	0.189
4251	0.161
4605	0.135
4960	0.108
5314	0.081
5668	0.055
6022	0.029
6377	0.003
6731	-0.023
7085	-0.048

Δt (s) = 354



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis
Boardman - Thick Store-and-Release Cover

TRIAL 2

Test ID: TK-3 Installer: XW
 Project: Boardman Analyst: CHB

FIXED VARIABLES

d (cm) = 10.16
 D (cm) = 30.48
 R_o (cm) = 0
 Final Time: 3:12:30

FITTED VARIABLES

a (s⁻¹) = 0.0000477
 H* (m) = 1.12
 H_o (m) = 1.34
 MSE (m²) = 2.38E-06
 Bias (m) = 6.37E-08

SOLUTION - TRIAL 1


K (m/s) = 4.61E-07 4.61E-05
 Total Time (d) = 0.04 1.0 hrs

TEMPORAL VARIABLES

Time (m/d/yr h:m)	R (cm)
2:11:00	21.7
2:45:45	9.3
3:12:30	0

Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	ε (m)	ε ² (m)
0.22	0.00	0.218	8.45E-04	7.14E-07
0.09	2085	0.091	-2.16E-03	4.68E-06
0.00	3690	0.001	1.32E-03	1.74E-06



Chiasson Solution:

Chiasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.


$$Z_t = H_o e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	0.218
185	0.206
369	0.194
554	0.183
738	0.171
923	0.160
1107	0.149
1292	0.138
1476	0.127
1661	0.116
1845	0.105
2030	0.094
2214	0.083
2399	0.073
2583	0.062
2768	0.052
2952	0.042
3137	0.031
3321	0.021
3506	0.011
3690	0.001

Δt (s) = 185



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis


Boardman - Thick Store-and-Release Cover

Equilibrium Evaluation & Steady Hydraulic Conductivity Determination

Trial	Time (d)	Total Time (d)	K (m/s)	
1	0.082	0.082	2.01E-07	TK-3
2	0.043	0.125	4.61E-07	

Field Hydraulic Conductivity

3.31E-07 m/s
3.31E-05 cm/s



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis
Boardman - Thick Store-and-Release Cover

TRIAL 1

Test ID: TK-4 Installer: XW
 Project: Boardman Analyst: CHB

FIXED VARIABLES


d (cm) =	10.16
D (cm) =	30.48
R ₀ (cm) =	0
Final Time:	1:03:00

FITTED VARIABLES

a (s ⁻¹) =	0.0001269
H* (m) =	4.08
H ₀ (m) =	4.57
MSE (m ²) =	8.45E-07
Bias (m) =	3.08E-09

SOLUTION -TRIAL 1

K (m/s) = 1.23E-06 1.23E-04
 Total Time (d) = 0.01 0.3 hrs



TEMPORAL VARIABLES

Time (m/d/yr h:m)	R (cm)
0:48:00	49.5
0:49:00	46.1
0:50:30	40.7
0:51:30	37.4
0:53:30	30.7
0:55:30	24.1
0:56:30	20.8
0:58:00	15.9
0:59:30	11.3
1:01:00	6.5
1:03:00	0

Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	ε (m)	ε ² (m)
0.50	0.00	0.495	-3.87E-04	1.50E-07
0.46	60	0.460	-1.05E-03	1.11E-06
0.41	150	0.408	1.44E-03	2.07E-06
0.37	210	0.374	4.28E-04	1.83E-07
0.31	330	0.307	1.75E-04	3.07E-08
0.24	450	0.241	-6.08E-05	3.69E-09
0.21	510	0.208	1.98E-04	3.90E-08
0.16	600	0.160	5.50E-04	3.03E-07
0.11	690	0.111	-1.54E-03	2.39E-06
0.07	780	0.064	-1.09E-03	1.20E-06
0.00	900	0.001	1.35E-03	1.82E-06

Chiasson Solution:

Chiasson, P. (2005). Method of interpretation of borehole falling-head tests performed in compacted clay liners. *Canadian Geotechnical J.*, 42, 79-90.


$$Z_t = H_0 e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	0.495
45	0.469
90	0.443
135	0.417
180	0.391
225	0.366
270	0.341
315	0.316
360	0.291
405	0.266
450	0.241
495	0.216
540	0.192
585	0.168
630	0.143
675	0.119
720	0.096
765	0.072
810	0.048
855	0.025
900	0.001

Δt (s) = 45



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis Boardman - Thick Store-and-Release Cover

TRIAL 2

Test ID: TK-4 Installer: XW
Project: Boardman Analyst: CHB

FIXED VARIABLES


d (cm) = 10.16
D (cm) = 30.48
R₀ (cm) = 0
Final Time: 1:36:00

FITTED VARIABLES

a (s⁻¹) = 0.0001768
H* (m) = 1.56
H₀ (m) = 2.14
MSE (m²) = 6.77E-06
Bias (m) = 2.50E-10

SOLUTION - TRIAL 1

K (m/s) = 1.71E-06 1.71E-04
Total Time (d) = 0.02 0.5 hrs



TEMPORAL VARIABLES

Time (m/d/yr h:m)	R (cm)
1:06:15	58.1
1:08:00	54
1:10:00	49.2
1:13:00	42.7
1:19:30	29.7
1:21:30	25.9
1:25:30	18.6
1:29:00	12.2
1:32:00	6.2
1:36:00	0

Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	ϵ (m)	ϵ^2 (m)
0.58	0.00	0.578	-2.78E-03	7.75E-06
0.54	105	0.539	-1.15E-03	1.32E-06
0.49	225	0.495	2.75E-03	7.55E-06
0.43	405	0.430	3.32E-03	1.10E-05
0.30	795	0.298	5.69E-04	3.24E-07
0.26	915	0.259	-4.70E-04	2.21E-07
0.19	1155	0.183	-3.11E-03	9.66E-06
0.12	1365	0.119	-2.71E-03	7.34E-06
0.06	1545	0.067	4.62E-03	2.14E-05
0.00	1785	-0.001	-1.04E-03	1.09E-06

Chausson Solution:

Chausson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.


$$Z_t = H_0 e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	0.578
89	0.545
179	0.512
268	0.479
357	0.447
446	0.416
536	0.385
625	0.354
714	0.324
803	0.295
893	0.266
982	0.237
1071	0.209
1160	0.181
1250	0.154
1339	0.127
1428	0.101
1517	0.075
1607	0.049
1696	0.024
1785	-0.001

Δt (s) = 89



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis
Boardman - Thick Store-and-Release Cover

TRIAL 3

Test ID: TK-4
Project: Boardman

Installer: XW
Analyst: CHB

FIXED VARIABLES


d (cm) =	10.16
D (cm) =	30.48
R _a (cm) =	0
Final Time:	2:17:30

FITTED VARIABLES

a (s ⁻¹) =	0.0000595
H* (m) =	4.49
H ₀ (m) =	5.13
MSE (m ²) =	2.02E-06
Bias (m) =	2.40E-09

SOLUTION - TRIAL 1

K (m/s) = 5.75E-07 5.75E-05
Total Time (d) = 0.03 0.6 hrs



TEMPORAL VARIABLES

Time (m/d/yr h:m)	R (cm)
1:40:30	63.8
1:46:00	53.6
1:51:00	44.8
1:56:00	36
2:02:30	25
2:10:00	12.1
2:17:30	0

Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	ε (m)	ε ² (m)
0.64	0.00	0.636	-2.00E-03	4.01E-06
0.54	330	0.536	2.87E-04	8.25E-08
0.45	630	0.447	-6.75E-04	4.56E-07
0.36	930	0.360	-6.39E-05	4.08E-09
0.25	1320	0.249	-1.36E-03	1.86E-06
0.12	1770	0.123	2.38E-03	5.68E-06
0.00	2220	0.001	1.44E-03	2.06E-06

Chiasson Solution:

Chiasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.


$$Z_t = H_0 e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	0.636
111	0.602
222	0.569
333	0.535
444	0.502
555	0.469
666	0.437
777	0.404
888	0.372
999	0.340
1110	0.308
1221	0.277
1332	0.245
1443	0.214
1554	0.183
1665	0.152
1776	0.122
1887	0.091
1998	0.061
2109	0.031
2220	0.001

Δt (s) = 111



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis Boardman - Thick Store-and-Release Cover

Equilibrium Evaluation & Steady Hydraulic Conductivity Determination


Trial	Time (d)	Total Time (d)	K (m/s)
1	0.001	0.001	1.23E-06
2	0.001	0.002	1.71E-06
3	0.017	0.019	5.75E-07

TK-4

Field Hydraulic Conductivity

1.17E-06 m/s

1.17E-04 cm/s



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis

Cedar Rapids - Clay Cover

TRIAL 1

Test ID: TSB CR Clay1-NW
Project: Cedar Rapids

Installer: XW
Analyst: CHB

FIXED VARIABLES

d (cm) = 1.905
D (cm) = 29.845
R_o (cm) = 44.45
Final Time: 16:42:00

FITTED VARIABLES

a (s⁻¹) = 0.0000053
H* (m) = 0.60
H_o (m) = 1.48
MSE (m²) = 3.73E-04
Bias (m) = 1.29E-09


TEMPORAL VARIABLES

Time (m/d/yr h:m)	R (cm)
10:41:26	46.8
10:55:11	44.7
11:05:00	41.8
11:48:21	39.4
12:58:00	34.7
13:41:45	32.3
14:03:00	36
15:11:00	32.3
15:27:00	31
16:42:00	29.4

Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	ε (m)	ε ² (m)
0.91	0.00	0.883	-2.94E-02	8.64E-04
0.89	825	0.877	-1.49E-02	2.22E-04
0.86	1414	0.872	9.46E-03	8.94E-05
0.84	4015	0.852	1.32E-02	1.74E-04
0.79	8194	0.820	2.82E-02	7.94E-04
0.77	10819	0.800	3.24E-02	1.05E-03
0.80	12094	0.790	-1.40E-02	1.97E-04
0.77	16174	0.761	-6.97E-03	4.86E-05
0.75	17134	0.754	-9.17E-04	8.41E-07
0.74	21634	0.721	-1.70E-02	2.89E-04

SOLUTION - TRIAL 1
K (m/s) = 1.86E-09
Total Time (d) = 0.25 6.0 hrs



Chiasson Solution:
Chiasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.

$$Z_t = H_o e^{-at} - H^*$$


$$K = \frac{a \pi d^2}{11 D}$$

9:16:16

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	0.883
1082	0.875
2163	0.866
3245	0.858
4327	0.849
5409	0.841
6490	0.833
7572	0.824
8654	0.816
9735	0.808
10817	0.800
11899	0.792
12980	0.784
14062	0.776
15144	0.768
16226	0.760
17307	0.752
18389	0.745
19471	0.737
20552	0.729
21634	0.721

Δt (s) = 1082



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis Cedar Rapids - Clay Cover

TRIAL 2

Test ID: Clay1-NW
Project: Cedar Rapids

Installer: XW
Analyst: CHB

FIXED VARIABLES

d (cm) =	1.905
D (cm) =	29.845
R _a (cm) =	44.45
Final Time:	13:46:20

FITTED VARIABLES

a (s ⁻¹) =	0.0000117
H* (m) =	0.00
H _o (m) =	1.31
MSE (m ²) =	3.30E-04
Bias (m) =	-9.28E-09

SOLUTION -TRIAL 1


K (m/s) = 4.08E-09
Total Time (d) = 0.19 4.5 hrs

TEMPORAL VARIABLES

Time (m/d/yr h:m)	R (cm)
9:18:45	90.5
9:26:45	87.1
9:43:00	84.1
9:52:30	82.3
10:23:30	78.6
11:04:20	75.8
11:50:26	72.8
12:53:33	68.5
13:46:20	66.3

Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	ε (m)	ε ² (m)
1.35	0	1.313	-3.66E-02	1.34E-03
1.32	480	1.306	-9.96E-03	9.92E-05
1.29	1455	1.291	5.19E-03	2.69E-05
1.27	2025	1.282	1.46E-02	2.13E-04
1.23	3885	1.254	2.39E-02	5.71E-04
1.20	6335	1.219	1.64E-02	2.67E-04
1.17	9101	1.180	7.42E-03	5.51E-05
1.13	12888	1.129	-8.63E-04	7.45E-07
1.11	16055	1.087	-2.00E-02	4.02E-04




Chiasson Solution:
Chiasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.

$$Z_t = H_o e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	1.313
803	1.301
1606	1.288
2408	1.276
3211	1.264
4014	1.253
4817	1.241
5619	1.229
6422	1.218
7225	1.206
8028	1.195
8830	1.184
9633	1.173
10436	1.162
11239	1.151
12041	1.140
12844	1.129
13647	1.119
14450	1.108
15252	1.098
16055	1.087



Δt (s) = 803

Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis Cedar Rapids - Clay Cover


Equilibrium Evaluation & Steady Hydraulic Conductivity Determination

Trial	Time (d)	Total Time (d)	K (m/s)
1	0.250	0.250	1.86E-09
2	0.186	0.436	4.08E-09

Clay1 - NW

Field Hydraulic Conductivity

2.97E-09 m/s
2.97E-07 cm/s



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis Cedar Rapids - Clay Cover

TRIAL 1

Test ID: Clay2-NE Installer: XW
Project: Cedar Rapids Analyst: CHB

FIXED VARIABLES


d (cm) = 1.905
D (cm) = 29.845
R_s (cm) = 44.45
Final Time: 14:03:00

FITTED VARIABLES

a (s⁻¹) = 0.0000355
H* (m) = 0.00
H₀ (m) = 1.06
MSE (m²) = 1.62E-03
Bias (m) = -1.26E-08

SOLUTION -TRIAL 1

K (m/s) = 1.23E-08
Total Time (d) = 0.14 3.3 hrs



TEMPORAL VARIABLES

Time (m/d/yr h:m)	R (cm)
10:44:20	69.0
10:44:47	67.0
10:47:00	64.0
10:50:00	61.9
10:53:30	59.7
10:57:00	57.5
11:00:02	55.5
11:04:12	53.0
11:09:45	51.0
11:19:20	48.8
11:33:47	46.2
11:48:50	43.5
12:11:50	40.0
12:33:00	37.8
12:58:30	35.0
13:30:00	31.2
14:03:00	31.6

Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	s (m)	ε ² (m)
1.13	0	1.055	-7.90E-02	6.25E-03
1.11	27	1.054	-6.01E-02	3.61E-03
1.08	160	1.049	-3.50E-02	1.23E-03
1.06	340	1.043	-2.07E-02	4.30E-04
1.04	550	1.035	-6.48E-03	4.20E-05
1.02	760	1.027	7.82E-03	6.11E-05
1.00	942	1.021	2.12E-02	4.49E-04
0.97	1192	1.012	3.72E-02	1.38E-03
0.95	1525	1.000	4.53E-02	2.05E-03
0.93	2100	0.980	4.70E-02	2.21E-03
0.91	2967	0.950	4.33E-02	1.87E-03
0.88	3870	0.920	4.03E-02	1.62E-03
0.84	5250	0.876	3.13E-02	9.77E-04
0.82	6520	0.837	1.46E-02	2.13E-04
0.79	8050	0.793	-1.72E-03	2.94E-06
0.76	9940	0.741	-1.52E-02	2.32E-04
0.76	11920	0.691	-6.96E-02	4.85E-03

Chiaison Solution:

Chiaison, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.


$$Z_t = H_0 e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	1.055
596	1.033
1192	1.012
1788	0.990
2384	0.970
2980	0.949
3576	0.929
4172	0.910
4768	0.891
5364	0.872
5960	0.854
6556	0.836
7152	0.819
7748	0.801
8344	0.785
8940	0.768
9536	0.752
10132	0.736
10728	0.721
11324	0.706
11920	0.691

Δt (s) = 596



**Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis
Cedar Rapids - Clay Cover**

TRIAL 2

Test ID: Clay2-NE Installer: XW
Project: Cedar Rapids Analyst: CHB

FIXED VARIABLES

d (cm) = 1.905
D (cm) = 29.845
R_s (cm) = 44.45
Final Time: 9:37:50

FITTED VARIABLES

a (s⁻¹) = 0.0002579
H* (m) = 0.00
H₀ (m) = 1.01
MSE (m²) = 9.78E-04
Bias (m) = 2.80E-07

TEMPORAL VARIABLES


Time (m/d/yr h:m)	R (cm)
8:39:40	61.6
8:40:40	59.0
8:41:41	56.0
8:43:06	52.5
8:44:35	49.0
8:45:30	47.0
8:47:52	42.5
8:50:00	39.0
8:53:55	33.0
8:56:30	29.6
8:59:59	25.6
9:02:40	23.0
9:06:20	19.5
9:09:53	16.7
9:15:00	13.6
9:20:36	10.5
9:24:28	8.5
9:30:30	5.4
9:37:50	2.7

Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	ε (m)	ε' (m)
1.06	0	1.011	-4.97E-02	2.47E-03
1.03	60	0.995	-3.92E-02	1.54E-03
1.00	121	0.980	-2.48E-02	6.14E-04
0.97	206	0.958	-1.10E-02	1.21E-04
0.93	295	0.937	2.23E-03	4.98E-06
0.91	350	0.924	9.04E-03	8.17E-05
0.87	492	0.890	2.08E-02	4.34E-04
0.83	620	0.861	2.69E-02	7.24E-04
0.77	855	0.811	3.63E-02	1.31E-03
0.74	1010	0.779	3.85E-02	1.48E-03
0.70	1219	0.738	3.76E-02	1.41E-03
0.67	1380	0.708	3.36E-02	1.13E-03
0.64	1600	0.669	2.95E-02	8.71E-04
0.61	1813	0.633	2.18E-02	4.73E-04
0.58	2120	0.585	4.55E-03	2.07E-05
0.55	2456	0.536	-1.30E-02	1.69E-04
0.53	2688	0.505	-2.42E-02	5.84E-04
0.50	3050	0.460	-3.82E-02	1.46E-03
0.47	3490	0.411	-6.06E-02	3.67E-03

SOLUTION - TRIAL 1

K (m/s) = 8.96E-08
Total Time (d) = 0.04 1.0 hrs



Chiasson Solution:

Chiasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.


$$Z_t = H_0 e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	1.011
175	0.966
349	0.924
524	0.883
698	0.844
873	0.807
1047	0.772
1222	0.738
1396	0.705
1571	0.674
1745	0.644
1920	0.616
2094	0.589
2269	0.563
2443	0.538
2618	0.515
2792	0.492
2967	0.470
3141	0.450
3316	0.430
3490	0.411

Δt (s) = 175



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis
Cedar Rapids - Clay Cover

TRIAL 3

Test ID: Clay2-NE Installer: XW
Project: Cedar Rapids Analyst: CHB

FIXED VARIABLES


d (cm) = 1.905
D (cm) = 29.845
R_s (cm) = 44.45
Final Time: 10:18:14

FITTED VARIABLES

a (s⁻¹) = 0.0002809
H* (m) = 0.00
H_o (m) = 0.87
MSE (m²) = 1.47E-04
Bias (m) = 2.70E-07

SOLUTION - TRIAL 1

K (m/s) = 9.76E-08
Total Time (d) = 0.02 0.5 hrs



Chiasson Solution:

Chiasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.

$$Z_t = H_o e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

TEMPORAL VARIABLES

Time (m/d/yr h:m)	R (cm)
9:45:20	44.4
9:47:43	39.6
9:49:30	36.0
9:51:40	32.5
9:56:50	25.0
10:09:41	13.0
10:16:40	7.5
10:18:14	6.4


Z-Z COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	s (m)	s ² (m)
0.89	0	0.869	-1.93E-02	3.73E-04
0.84	143	0.835	-5.54E-03	3.07E-05
0.80	250	0.810	-5.74E-03	3.29E-05
0.77	380	0.781	-1.17E-02	1.36E-04
0.69	690	0.716	2.15E-02	4.64E-04
0.57	1461	0.577	2.10E-03	4.42E-06
0.52	1880	0.513	-6.92E-03	4.79E-05
0.51	1974	0.499	-9.28E-03	8.61E-05

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	0.869
99	0.845
197	0.822
296	0.800
395	0.778
493	0.757
592	0.736
691	0.716
790	0.696
888	0.677
987	0.659
1086	0.641
1184	0.623
1283	0.606
1382	0.590
1481	0.573
1579	0.558
1678	0.543
1777	0.528
1875	0.513
1974	0.499

Δt (s) = 99



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis Cedar Rapids - Clay Cover

TRIAL 5

Test ID: Clay2-NE Installer: XW
Project: Cedar Rapids Analyst: CHB

FIXED VARIABLES


d (cm) = 1.905
D (cm) = 29.845
R_s (cm) = 44.45
Final Time: 11:41:50

FITTED VARIABLES

a (s⁻¹) = 0.0003250
H* (m) = 0.00
H₀ (m) = 1.03
MSE (m²) = 7.45E-04
Bias (m) = 8.53E-07

SOLUTION -TRIAL 1

K (m/s) = 1.13E-07
Total Time (d) = 0.03 0.8 hrs



Chiasson Solution:

Chiasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.

$$Z_t = H_0 e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

TEMPORAL VARIABLES

Time (m/d/yr h:m)	R (cm)
10:56:23	63.0
10:57:20	59.0
10:59:00	54.0
11:01:55	46.5
11:06:30	37.0
11:10:23	31.0
11:14:45	24.3
11:21:40	17.0
11:29:46	10.0
11:36:46	5.0
11:41:50	2.0


Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	s (m)	s ² (m)
1.07	0	1.033	-4.15E-02	1.72E-03
1.03	57	1.014	-2.05E-02	4.20E-04
0.98	157	0.982	-2.92E-03	8.50E-06
0.91	332	0.927	1.78E-02	3.17E-04
0.81	607	0.848	3.35E-02	1.12E-03
0.75	840	0.786	3.17E-02	1.00E-03
0.69	1102	0.722	3.45E-02	1.19E-03
0.61	1517	0.631	1.64E-02	2.69E-04
0.54	2003	0.539	-5.77E-03	3.33E-05
0.49	2423	0.470	-2.45E-02	6.01E-04
0.46	2727	0.426	-3.87E-02	1.50E-03

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	1.033
136	0.988
273	0.945
409	0.904
545	0.865
682	0.828
818	0.792
954	0.757
1091	0.725
1227	0.693
1364	0.663
1500	0.634
1636	0.607
1773	0.581
1909	0.555
2045	0.531
2182	0.508
2318	0.486
2454	0.465
2591	0.445
2727	0.426

Δt (s) = 136



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis
Cedar Rapids - Clay Cover

TRIAL 6

Test ID: Clay2-NE Installer: XW
 Project: Cedar Rapids Analyst: CHB

FIXED VARIABLES


d (cm) = 1.905
 D (cm) = 29.845
 R_s (cm) = 44.45
 Final Time: 12:14:24

FITTED VARIABLES

a (s⁻¹) = 0.0002001
 H* (m) = 0.00
 H₀ (m) = 0.66
 MSE (m²) = 1.45E-05
 Bias (m) = 8.88E-07

SOLUTION -TRIAL 1

K (m/s) = 6.95E-08
 Total Time (d) = 0.02 0.5 hrs



TEMPORAL VARIABLES

Time (m/d/yr h:m)	R (cm)
11:42:48	22.3
11:45:10	20.0
11:48:32	17.0
11:52:15	14.0
11:57:56	10.3
12:03:06	7.6
12:08:21	4.5
12:14:24	1.0

Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	ε (m)	ε ² (m)
0.67	0	0.662	-5.86E-03	3.43E-05
0.64	142	0.643	-1.39E-03	1.94E-06
0.61	344	0.618	3.13E-03	9.83E-06
0.58	567	0.591	6.18E-03	3.83E-05
0.55	908	0.552	4.23E-03	1.79E-05
0.52	1218	0.519	-1.95E-03	3.80E-06
0.49	1533	0.487	-2.62E-03	6.87E-06
0.45	1896	0.453	-1.73E-03	2.98E-06

Chiasson Solution:
 Chiasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.


$$Z_t = H_0 e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	0.662
95	0.649
190	0.637
284	0.625
379	0.613
474	0.602
569	0.590
664	0.579
758	0.568
853	0.558
948	0.547
1043	0.537
1138	0.527
1232	0.517
1327	0.507
1422	0.498
1517	0.488
1612	0.479
1706	0.470
1801	0.461
1896	0.453

Δt (s) = 95



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis Cedar Rapids - Clay Cover

Equilibrium Evaluation & Steady Hydraulic Conductivity Determination


Trial	Time (d)	Total Time (d)	K (m/s)
1	0.138	0.138	1.23E-08
2	0.040	0.178	8.96E-08
3	0.023	0.201	9.76E-08
4	0.025	0.226	1.34E-07
5	0.032	0.258	1.13E-07
6	0.022	0.280	6.95E-08
7	0.025	0.304	6.25E-08

Clay2-NE

Field Hydraulic Conductivity

9.46E-08 m/s

9.46E-06 cm/s



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis

Cedar Rapids - Clay Cover

TRIAL 1

Test ID: Clay3-SW Installer: XW
 Project: Cedar Rapids Analyst: CHB

FIXED VARIABLES

d (cm) = 1.905
 D (cm) = 29.845
 R_s (cm) = 44.45
 Final Time: 16:52:00

FITTED VARIABLES

a (s⁻¹) = 0.0014435
 H* (m) = 0.00
 H_o (m) = 1.29
 MSE (m²) = 2.62E-05
 Bias (m) = -2.30E-07

SOLUTION -TRIAL 1


K (m/s) = 5.01E-07
 Total Time (d) = 0.00 0.1 hrs

TEMPORAL VARIABLES

Time (m/d/yr h:m)	R (cm)
16:47:20	84.0
16:48:06	77.0
16:48:46	70.0
16:49:15	65.0
16:50:08	57.0
16:51:23	47.0
16:52:00	41.0

Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	ε (m)	ε ² (m)
1.28	0	1.292	7.33E-03	5.37E-05
1.21	46	1.209	-5.67E-03	3.21E-05
1.14	86	1.141	-3.49E-03	1.22E-05
1.09	115	1.094	-2.67E-04	7.12E-08
1.01	168	1.014	-8.61E-04	7.41E-07
0.91	243	0.910	-4.87E-03	2.37E-05
0.85	280	0.862	7.82E-03	6.12E-05



Chiaisson Solution:


Chiaisson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.

$$Z_t = H_o e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	1.292
14	1.266
28	1.241
42	1.216
56	1.192
70	1.168
84	1.144
98	1.121
112	1.099
126	1.077
140	1.055
154	1.034
168	1.014
182	0.993
196	0.973
210	0.954
224	0.935
238	0.916
252	0.898
266	0.880
280	0.862



Δt (s) = 14

Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis Cedar Rapids - Clay Cover

TRIAL 2

Test ID: Clay2-NE Installer: XW
Project: Cedar Rapids Analyst: CHB

FIXED VARIABLES

d (cm) = 1.905
D (cm) = 29.845
R_s (cm) = 44.45
Final Time: 16:52:00


FITTED VARIABLES

a (s⁻¹) = 0.0014435
H* (m) = 0.00
H_o (m) = 1.29
MSE (m²) = 2.62E-05
Bias (m) = -2.30E-07

SOLUTION - TRIAL 1

K (m/s) = 5.01E-07

Total Time (d) = 0.00 0.1 hrs



Chiasson Solution:

Chiasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.

$$Z_t = H_o e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

TEMPORAL VARIABLES

Time (m/d/yr h:m)	R (cm)
16:47:20	84.0
16:48:06	77.0
16:48:46	70.0
16:49:15	65.0
16:50:08	57.0
16:51:23	47.0
16:52:00	41.0


Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	e (m)	e ² (m)
1.28	0	1.292	7.33E-03	5.37E-05
1.21	46	1.209	-5.67E-03	3.21E-05
1.14	86	1.141	-3.49E-03	1.22E-05
1.09	115	1.094	-2.67E-04	7.12E-08
1.01	168	1.014	-8.61E-04	7.41E-07
0.91	243	0.910	-4.87E-03	2.37E-05
0.85	280	0.862	7.82E-03	6.12E-05

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	1.292
14	1.266
28	1.241
42	1.216
56	1.192
70	1.168
84	1.144
98	1.121
112	1.099
126	1.077
140	1.055
154	1.034
168	1.014
182	0.993
196	0.973
210	0.954
224	0.935
238	0.916
252	0.898
266	0.880
280	0.862

Δt (s) = 14



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis
Cedar Rapids - Clay Cover

TRIAL 3

Test ID: Clay2-NE Installer: XW
 Project: Cedar Rapids Analyst: CHB

FIXED VARIABLES


d (cm) = 1.905
 D (cm) = 29.845
 R_s (cm) = 44.45
 Final Time: 18:01:10

FITTED VARIABLES

a (s^{-1}) = 0.0000593
 H^* (m) = 0.00
 H_0 (m) = 1.36
 MSE (m^2) = 2.03E-04
 Bias (m) = -5.85E-07

SOLUTION - TRIAL 1

K (m/s) = 2.06E-08
 Total Time (d) = 0.03 0.8 hrs



Chiasson Solution:

Chiasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.

$$Z_t = H_0 e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

TEMPORAL VARIABLES

Time (m/d/yr h:m)	R (cm)
17:13:25	94.0
17:15:15	90.5
17:17:00	89.0
17:20:15	87.0
17:28:40	82.5
17:35:50	79.8
17:45:10	76.6
17:50:45	73.3
18:01:10	72.2


Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	ϵ (m)	ϵ^2 (m)
1.38	0	1.357	-2.79E-02	7.80E-04
1.35	110	1.348	-1.74E-03	3.02E-06
1.33	215	1.339	4.90E-03	2.40E-05
1.31	410	1.324	9.50E-03	9.03E-05
1.27	915	1.285	1.54E-02	2.39E-04
1.24	1345	1.253	1.01E-02	1.02E-04
1.21	1905	1.212	1.19E-03	1.43E-06
1.18	2240	1.188	1.04E-02	1.07E-04
1.17	2865	1.145	-2.18E-02	4.77E-04

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	1.357
143	1.345
287	1.334
430	1.322
573	1.311
716	1.300
860	1.289
1003	1.278
1146	1.267
1289	1.257
1433	1.246
1576	1.236
1719	1.225
1862	1.215
2006	1.204
2149	1.194
2292	1.184
2435	1.174
2579	1.164
2722	1.154
2865	1.145

Δt (s) = 143



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis

Cedar Rapids - Clay Cover

TRIAL 4

Test ID: Clay2-NE Installer: XW
 Project: Cedar Rapids Analyst: CHB

FIXED VARIABLES


d (cm) = 1.905
 D (cm) = 29.845
 R_s (cm) = 44.45
 Final Time: 16:00:45

FITTED VARIABLES

a (s⁻¹) = 0.0000190
 H* (m) = 0.00
 H₀ (m) = 1.33
 MSE (m²) = 1.43E-03
 Bias (m) = 1.21E-07

SOLUTION - TRIAL 1

K (m/s) = 6.59E-09
 Total Time (d) = 0.29 7.1 hrs



TEMPORAL VARIABLES

Time (m/d/yr h:m)	R (cm)
8:57:44	97.0
8:58:40	95.0
9:01:14	92.0
9:04:10	90.0
9:08:46	88.0
9:16:30	85.5
9:26:05	83.0
9:33:10	81.2
9:42:25	79.3
9:55:30	76.8
10:22:41	72.3
10:44:08	69.3
11:06:00	66.3
11:31:50	63.2
11:59:27	60.4
12:17:33	58.7
12:54:16	55.2
13:28:46	52.6
14:15:11	49.4
14:51:10	47.2
15:29:10	45.2
16:00:45	43.7

Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	ε (m)	ε ² (m)
1.41	0	1.331	-8.33E-02	6.93E-03
1.39	56	1.330	-6.47E-02	4.18E-03
1.36	210	1.326	-3.86E-02	1.49E-03
1.34	386	1.322	-2.30E-02	5.28E-04
1.32	662	1.315	-9.87E-03	9.74E-05
1.30	1126	1.303	3.61E-03	1.30E-05
1.27	1701	1.289	1.45E-02	2.09E-04
1.26	2126	1.279	2.21E-02	4.89E-04
1.24	2681	1.265	2.77E-02	7.69E-04
1.21	3466	1.247	3.40E-02	1.16E-03
1.17	5097	1.209	4.11E-02	1.69E-03
1.14	6384	1.179	4.19E-02	1.76E-03
1.11	7696	1.150	4.29E-02	1.84E-03
1.08	9246	1.117	4.06E-02	1.65E-03
1.05	10903	1.083	3.40E-02	1.16E-03
1.03	11989	1.060	2.89E-02	8.37E-04
1.00	14192	1.017	2.05E-02	4.22E-04
0.97	16262	0.978	7.37E-03	5.44E-05
0.94	19047	0.928	-1.09E-02	1.20E-04
0.92	21206	0.890	-2.62E-02	6.85E-04
0.90	23486	0.853	-4.39E-02	1.92E-03
0.88	25381	0.823	-5.90E-02	3.48E-03

Chiasson Solution:

Chiasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.


$$Z_t = H_0 e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	1.331
1269	1.300
2538	1.269
3807	1.238
5076	1.209
6345	1.180
7614	1.152
8883	1.125
10152	1.098
11421	1.072
12691	1.046
13960	1.022
15229	0.997
16498	0.974
17767	0.950
19036	0.928
20305	0.906
21574	0.884
22843	0.863
24112	0.843
25381	0.823

Δt (s) = 1269



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis
Cedar Rapids - Clay Cover

TRIAL 5

Test ID: Clay2-NE Installer: XW
 Project: Cedar Rapids Analyst: CHB

FIXED VARIABLES


d (cm) = 1.905
 D (cm) = 29.845
 R_a (cm) = 44.45
 Final Time: 1/1/2005 17:12

FITTED VARIABLES

a (s⁻¹) = 0.0000112
 H* (m) = 0.00
 H₀ (m) = 1.09
 MSE (m²) = 1.39E-03
 Bias (m) = -8.74E-08

SOLUTION - TRIAL 1

K (m/s) = 3.89E-09
 Total Time (d) = 0.03 0.6 hrs



TEMPORAL VARIABLES

Time (m/d/yr h:m)	R (cm)
1/1/2005 16:36	70.0
1/1/2005 16:41	67.0
1/1/2005 16:49	64.0
1/1/2005 17:01	60.0
1/1/2005 17:12	57.0

Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	s (m)	s ² (m)
1.14	0	1.092	-5.23E-02	2.73E-03
1.11	345	1.088	-2.65E-02	7.01E-04
1.08	799	1.083	-2.00E-03	3.99E-06
1.04	1534	1.074	2.91E-02	8.48E-04
1.01	2160	1.066	5.16E-02	2.66E-03

Chiasson Solution:
 Chiasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.


$$Z_t = H_0 e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	1.092
108	1.091
216	1.090
324	1.088
432	1.087
540	1.086
648	1.084
756	1.083
864	1.082
972	1.080
1080	1.079
1188	1.078
1296	1.076
1404	1.075
1512	1.074
1620	1.073
1728	1.071
1836	1.070
1944	1.069
2052	1.067
2160	1.066

Δt (s) = 108



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis Cedar Rapids - Clay Cover

TRIAL 5

Test ID: Clay2-NE Installer: XW
Project: Cedar Rapids Analyst: CHB

FIXED VARIABLES

d (cm) = 1.905
D (cm) = 29.845
R_s (cm) = 44.45
Final Time: 1/2/2005 10:18

FITTED VARIABLES

a (s⁻¹) = 0.0002434
H* (m) = 0.00
H_o (m) = 0.69
MSE (m²) = 3.35E-07
Bias (m) = -9.80E-07


TEMPORAL VARIABLES

Time (m/d/yr h:m)	R (cm)
1/2/2005 9:56	25.0
1/2/2005 10:09	13.0
1/2/2005 10:16	7.5
1/2/2005 10:18	6.4

Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	ε (m)	ε ² (m)
0.69	0	0.694	-2.92E-04	8.55E-08
0.57	771	0.575	8.89E-04	7.90E-07
0.52	1190	0.520	8.02E-05	6.43E-09
0.51	1284	0.508	-6.78E-04	4.59E-07

SOLUTION - TRIAL 1
K (m/s) = 8.45E-08
Total Time (d) = 0.01 0.4 hrs



Chiasson Solution:
Chiasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.


$$Z_t = H_o e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	0.694
64	0.683
128	0.673
193	0.662
257	0.652
321	0.642
385	0.632
449	0.622
514	0.613
578	0.603
642	0.594
706	0.585
770	0.575
835	0.567
899	0.558
963	0.549
1027	0.541
1091	0.532
1156	0.524
1220	0.516
1284	0.508

Δt (s) = 64



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis

Cedar Rapids - Clay Cover

TRIAL 7

Test ID: Clay2-NE Installer: XW
 Project: Cedar Rapids Analyst: CHB

FIXED VARIABLES

d (cm) = 1.905
 D (cm) = 29.845
 R_s (cm) = 44.45
 Final Time: 11:41:50

FITTED VARIABLES

a (s⁻¹) = 0.0003250
 H* (m) = 0.00
 H₀ (m) = 1.03
 MSE (m²) = 7.45E-04
 Bias (m) = -7.34E-07

SOLUTION - TRIAL 1


K (m/s) = 1.13E-07
 Total Time (d) = 0.03 0.8 hrs

TEMPORAL VARIABLES

Time (m/d/yr h:m)	R (cm)
10:56:23	63.0
10:57:20	59.0
10:59:00	54.0
11:01:55	46.5
11:06:30	37.0
11:10:23	31.0
11:14:45	24.3
11:21:40	17.0
11:29:46	10.0
11:36:46	5.0
11:41:50	2.0

Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	ε (m)	ε ² (m)
1.07	0	1.033	-4.15E-02	1.72E-03
1.03	57	1.014	-2.05E-02	4.20E-04
0.98	157	0.982	-2.92E-03	8.50E-06
0.91	332	0.927	1.78E-02	3.17E-04
0.81	607	0.848	3.35E-02	1.12E-03
0.75	840	0.786	3.17E-02	1.00E-03
0.69	1102	0.722	3.45E-02	1.19E-03
0.61	1517	0.631	1.64E-02	2.69E-04
0.54	2003	0.539	-5.77E-03	3.33E-05
0.49	2423	0.470	-2.45E-02	6.01E-04
0.46	2727	0.426	-3.87E-02	1.50E-03



Chiasson Solution:

Chiasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.


$$Z_t = H_0 e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	1.033
136	0.988
273	0.945
409	0.904
545	0.865
682	0.828
818	0.792
954	0.757
1091	0.725
1227	0.693
1364	0.663
1500	0.634
1636	0.607
1773	0.581
1909	0.555
2045	0.531
2182	0.508
2318	0.486
2454	0.465
2591	0.445
2727	0.426

Δt (s) = 136



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis Cedar Rapids - Clay Cover

TRIAL 8

Test ID: Clay2-NE Installer: XW
Project: Cedar Rapids Analyst: CHB

FIXED VARIABLES


d (cm) = 1.905
D (cm) = 29.845
R_s (cm) = 44.45
Final Time: 12:14:24

FITTED VARIABLES

a (s⁻¹) = 0.0002001
H* (m) = 0.00
H₀ (m) = 0.66
MSE (m²) = 1.45E-05
Bias (m) = 9.02E-07

SOLUTION - TRIAL 1

K (m/s) = 6.95E-08
Total Time (d) = 0.02 0.5 hrs



TEMPORAL VARIABLES

Time (m/d/yr h:m)	R (cm)
11:42:48	22.3
11:45:10	20.0
11:48:32	17.0
11:52:15	14.0
11:57:56	10.3
12:03:06	7.6
12:08:21	4.5
12:14:24	1.0

Z-Z COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	ε (m)	ε ² (m)
0.67	0	0.662	-5.86E-03	3.43E-05
0.64	142	0.643	-1.39E-03	1.94E-06
0.61	344	0.618	3.13E-03	9.83E-06
0.58	567	0.591	6.18E-03	3.83E-05
0.55	908	0.552	4.23E-03	1.79E-05
0.52	1218	0.519	-1.95E-03	3.80E-06
0.49	1533	0.487	-2.62E-03	6.87E-06
0.45	1896	0.453	-1.73E-03	2.98E-06

Chiasson Solution:
Chiasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.


$$Z_t = H_0 e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	0.662
95	0.649
190	0.637
284	0.625
379	0.613
474	0.602
569	0.590
664	0.579
758	0.568
853	0.558
948	0.547
1043	0.537
1138	0.527
1232	0.517
1327	0.507
1422	0.498
1517	0.488
1612	0.479
1706	0.470
1801	0.461
1896	0.453

Δt (s) = 95



**Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis
Cedar Rapids - Clay Cover**

TRIAL 9

Test ID: Clay2-NE Installer: XW
Project: Cedar Rapids Analyst: CHB

FIXED VARIABLES

d (cm) = 1.905
D (cm) = 29.845
R_s (cm) = 44.45
Final Time:

FITTED VARIABLES

a (s⁻¹) = 0.0001799
H* (m) = 0.00
H₀ (m) = 0.67
MSE (m²) = 2.75E-05
Bias (m) = -9.49E-07

TEMPORAL VARIABLES


Time (m/d/yr h:m)	R (cm)
12:14:58	23.2
12:19:53	19.5
12:24:58	15.5
12:29:32	12.3
12:35:58	8.5
12:42:24	5.4
12:50:15	2.3

Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	ε (m)	ε ² (m)
0.68	0	0.672	-5.00E-03	2.50E-05
0.64	295	0.637	-2.70E-03	7.29E-06
0.60	600	0.603	3.30E-03	1.09E-05
0.57	874	0.574	6.31E-03	3.99E-05
0.53	1260	0.535	5.82E-03	3.39E-05
0.50	1646	0.499	9.14E-04	8.35E-07
0.47	2117	0.459	-8.66E-03	7.49E-05

SOLUTION - TRIAL 1

K (m/s) = 6.25E-08
Total Time (d) = 0.02 0.6 hrs




Chiasson Solution:
Chiasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.

$$Z_t = H_0 e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	0.672
106	0.659
212	0.646
318	0.634
423	0.622
529	0.611
635	0.599
741	0.588
847	0.577
953	0.566
1059	0.555
1164	0.545
1270	0.534
1376	0.524
1482	0.514
1588	0.505
1694	0.495
1799	0.486
1905	0.477
2011	0.468
2117	0.459



Δt (s) = 106

Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis Cedar Rapids - Clay Cover

Equilibrium Evaluation & Steady Hydraulic Conductivity Determination


Trial	Time (d)	Total Time (d)	K (m/s)
1	0.003	0.003	5.01E-07
2	0.003	0.006	5.01E-07
3	0.033	0.040	2.06E-08
4	0.294	0.333	6.59E-09
5	0.025	0.358	3.89E-09
6	0.025	0.383	1.28E-07
7	0.032	0.415	1.13E-07
8	0.022	0.437	6.95E-08
9	0.025	0.461	6.25E-08

Clay3-SW

Field Hydraulic Conductivity

9.31E-08 m/s

9.31E-06 cm/s



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis

Cedar Rapids - Clay Cover

TRIAL 1

Test ID: Clay4-SE Installer: XW
 Project: Cedar Rapids Analyst: CHB

FIXED VARIABLES


d (cm) = 1.905
 D (cm) = 29.845
 R_s (cm) = 44.45
 Final Time: 18:00:26

FITTED VARIABLES

a (s⁻¹) = 0.0002284
 H* (m) = 0.00
 H₀ (m) = 1.29
 MSE (m²) = 1.22E-02
 Bias (m) = 6.16E-07

SOLUTION - TRIAL 1

K (m/s) = 7.93E-08
 Total Time (d) = 0.03 0.7 hrs



TEMPORAL VARIABLES

Time (m/d/yr h:m)	R (cm)
17:21:25	66.3
17:28:00	62.0
17:36:15	57.0
17:44:20	52.5
17:50:10	49.4
17:55:30	46.8
18:00:26	45.6

Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	ε (m)	ε ² (m)
1.11	0	1.292	1.84E-01	3.40E-02
1.06	395	1.180	1.16E-01	1.34E-02
1.01	890	1.054	3.97E-02	1.57E-03
0.97	1375	0.944	-2.59E-02	6.71E-04
0.94	1725	0.871	-6.74E-02	4.54E-03
0.91	2045	0.810	-1.03E-01	1.06E-02
0.90	2341	0.757	-1.44E-01	2.07E-02

Chiasson Solution:


Chiasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.

$$Z_t = H_0 e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	1.292
117	1.258
234	1.225
351	1.192
468	1.161
585	1.130
702	1.100
819	1.071
936	1.043
1053	1.016
1171	0.989
1288	0.963
1405	0.937
1522	0.913
1639	0.888
1756	0.865
1873	0.842
1990	0.820
2107	0.798
2224	0.777
2341	0.757



Δt (s) = 117

Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis Cedar Rapids - Clay Cover

TRIAL 2

Test ID: Clay4-SE Installer: XW
Project: Cedar Rapids Analyst: CHB

FIXED VARIABLES

d (cm) = 1.905
D (cm) = 29.845
R_s (cm) = 44.45
Final Time: 12:30:45

FITTED VARIABLES

a (s⁻¹) = 0.0000925
H* (m) = 0.00
H₀ (m) = 1.29
MSE (m²) = 3.63E-02
Bias (m) = 1.35E-07

TEMPORAL VARIABLES


Time (m/d/yr h:m)	R (cm)
8:52:00	67.0
8:52:52	65.0
8:54:35	60.7
8:59:15	58.3
9:07:30	55.3
9:15:50	52.9
9:25:30	50.5
9:32:20	48.7
9:41:50	46.7
9:56:00	44.0
10:22:17	39.7
10:44:40	36.5
11:05:35	33.7
11:32:16	31.4
12:01:21	28.5
12:16:50	27.0
12:30:45	25.5

Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	s (m)	s ² (m)
1.11	0	1.292	1.77E-01	3.14E-02
1.09	52	1.286	1.91E-01	3.65E-02
1.05	155	1.273	2.22E-01	4.93E-02
1.03	435	1.241	2.13E-01	4.55E-02
1.00	930	1.185	1.88E-01	3.53E-02
0.97	1430	1.132	1.58E-01	2.51E-02
0.95	2010	1.073	1.23E-01	1.52E-02
0.93	2420	1.033	1.01E-01	1.03E-02
0.91	2990	0.980	6.82E-02	4.66E-03
0.88	3840	0.906	2.12E-02	4.49E-04
0.84	5417	0.783	-5.87E-02	3.45E-03
0.81	6760	0.691	-1.18E-01	1.40E-02
0.78	8015	0.616	-1.66E-01	2.75E-02
0.76	9616	0.531	-2.28E-01	5.18E-02
0.73	11361	0.452	-2.78E-01	7.71E-02
0.71	12290	0.415	-3.00E-01	9.00E-02
0.70	13125	0.384	-3.16E-01	9.97E-02

SOLUTION - TRIAL 1

K (m/s) = 3.21E-08
Total Time (d) = 0.15 3.6 hrs



Chiasson Solution:

Chiasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.


$$Z_t = H_0 e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	1.292
656	1.216
1313	1.144
1969	1.077
2625	1.013
3281	0.954
3938	0.898
4594	0.845
5250	0.795
5906	0.748
6563	0.704
7219	0.663
7875	0.624
8531	0.587
9188	0.552
9844	0.520
10500	0.489
11156	0.460
11813	0.433
12469	0.408
13125	0.384

Δt (s) = 656



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis

Cedar Rapids - Clay Cover

Equilibrium Evaluation & Steady Hydraulic Conductivity Determination


Trial	Time (d)	Total Time (d)	K (m/s)
1	0.027	0.027	7.93E-08
2	0.152	0.179	3.21E-08

Clay4-SE

Field Hydraulic Conductivity

5.57E-08 m/s

5.57E-06 cm/s



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis

Cedar Rapids - Composite Cover

TRIAL 1

Test ID: CP2-NE Installer: XW
 Project: Cedar Rapids Analyst: CHB

FIXED VARIABLES


d (cm) = 1.905
 D (cm) = 29.845
 R_s (cm) = 52.07
 Final Time: 13:48:00

FITTED VARIABLES

a (s⁻¹) = 0.0005108
 H* (m) = 0.00
 H₀ (m) = 1.39
 MSE (m²) = 7.33E-04
 Bias (m) = -4.43E-08

SOLUTION -TRIAL 1

K (m/s) = 1.77E-07
 Total Time (d) = 0.02 0.4 hrs



Chiasson Solution:

Chiasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.

TEMPORAL VARIABLES

Time (m/d/yr h:m)	R (cm)
13:26:12	92.7
13:27:45	82.7
13:28:30	79.0
13:28:50	77.0
13:29:30	73.5
13:30:30	69.0
13:31:15	65.5
13:32:00	62.0
13:33:30	56.5
13:34:47	52.0
13:35:50	48.5
13:37:06	45.0
13:38:14	42.0
13:39:10	39.5
13:41:00	35.5
13:42:40	32.0
13:45:00	28.5
13:47:10	25.5
13:48:00	24.4

Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	s (m)	e ^s (m)
1.45	0.00	1.392	-5.59E-02	3.12E-03
1.35	93	1.327	-2.04E-02	4.18E-04
1.31	138	1.297	-1.36E-02	1.85E-04
1.29	158	1.284	-6.79E-03	4.61E-05
1.26	198	1.258	2.25E-03	5.05E-06
1.21	258	1.220	9.28E-03	8.62E-05
1.18	303	1.192	1.66E-02	2.74E-04
1.14	348	1.165	2.45E-02	5.99E-04
1.09	438	1.113	2.71E-02	7.36E-04
1.04	515	1.070	2.92E-02	8.53E-04
1.01	578	1.036	3.03E-02	9.20E-04
0.97	654	0.997	2.59E-02	6.70E-04
0.94	722	0.963	2.19E-02	4.78E-04
0.92	778	0.935	1.97E-02	3.89E-04
0.88	888	0.884	8.62E-03	7.43E-05
0.84	988	0.840	-4.14E-04	1.72E-07
0.81	1128	0.782	-2.34E-02	5.48E-04
0.78	1258	0.732	-4.37E-02	1.91E-03
0.76	1308	0.714	-5.11E-02	2.61E-03

$$Z_t = H_0 e^{-at} - H^*$$


$$K = \frac{a \pi d^2}{11 D}$$

9:16:16

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	1.392
65	1.346
131	1.302
196	1.259
262	1.218
327	1.178
392	1.139
458	1.102
523	1.065
589	1.030
654	0.997
719	0.964
785	0.932
850	0.902
916	0.872
981	0.843
1046	0.816
1112	0.789
1177	0.763
1243	0.738
1308	0.714

Δt (s) = 65



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis
Cedar Rapids - Composite Cover

TRIAL 2

Test ID: CP2-NE
 Project: Cedar Rapids

Installer: XW
 Analyst: CHB

FIXED VARIABLES

d (cm) = 1.905
 D (cm) = 29.845
 R₁ (cm) = 52.07
 Final Time: 14:04:19

FITTED VARIABLES

a (s⁻¹) = 0.0005177
 H* (m) = 0.00
 H₀ (m) = 1.43
 MSE (m²) = 1.65E-04
 Bias (m) = 8.37E-08

TEMPORAL VARIABLES


Time (m/d/yr h:m)	R (cm)
13:48:30	93.0
13:49:05	89.0
13:49:35	86.0
13:51:00	79.0
13:53:00	70.5
13:55:24	62.0
13:57:24	55.5
13:59:23	49.5
14:01:04	45.0
14:04:19	37.5

Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	s (m)	s* (m)
1.45	0.00	1.429	-2.17E-02	4.69E-04
1.41	35	1.403	-7.31E-03	5.35E-05
1.38	65	1.382	1.06E-03	1.12E-06
1.31	150	1.322	1.16E-02	1.34E-04
1.23	270	1.243	1.69E-02	2.86E-04
1.14	414	1.153	1.27E-02	1.60E-04
1.08	534	1.084	8.19E-03	6.70E-05
1.02	653	1.019	3.43E-03	1.17E-05
0.97	754	0.967	-3.49E-03	1.22E-05
0.90	949	0.874	-2.14E-02	4.57E-04

SOLUTION - TRIAL 1

K (m/s) = 1.80E-07
 Total Time (d) = 0.01 0.3 hrs



Chlasson Solution:
 Chiasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.


$$Z_t = H_0 e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	1.429
47	1.394
95	1.361
142	1.328
190	1.295
237	1.264
285	1.233
332	1.203
380	1.174
427	1.146
475	1.118
522	1.091
569	1.064
617	1.038
664	1.013
712	0.989
759	0.965
807	0.941
854	0.918
902	0.896
949	0.874

Δt (s) = 47



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis Cedar Rapids - Composite Cover


Equilibrium Evaluation & Steady Hydraulic Conductivity Determination

Trial	Time (d)	Total Time (d)	K (m/s)	
1	0.015	0.015	1.77E-07	CP2-NE
2	0.011	0.011	1.80E-07	

Field Hydraulic Conductivity

1.79E-07 m/s

1.79E-05 cm/s



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis Cedar Rapids - Composite Cover

TRIAL 1

Test ID: CP3-SW Installer: XW
Project: Cedar Rapids Analyst: CHB

FIXED VARIABLES

d (cm) = 1.905
D (cm) = 29.845
R_s (cm) = 52.07
Final Time:

FITTED VARIABLES

a (s⁻¹) = 0.0001774
H* (m) = 0.00
H₀ (m) = 1.41
MSE (m²) = 1.44E-03
Bias (m) = -1.06E-08

SOLUTION - TRIAL 1


K (m/s) = 6.16E-08
Total Time (d) = 0.05 1.2 hrs

TEMPORAL VARIABLES

Time (m/d/yr h:m)	R (cm)
13:54:10	95.0
13:55:00	91.5
13:56:00	88.0
13:57:47	83.0
13:59:40	78.5
14:01:30	74.5
14:04:35	68.5
15:09:00	14.3

Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	s (m)	s ² (m)
1.47	0.00	1.413	-5.79E-02	3.35E-03
1.44	50	1.400	-3.54E-02	1.25E-03
1.40	110	1.385	-1.52E-02	2.31E-04
1.35	217	1.359	8.73E-03	7.62E-05
1.31	330	1.332	2.67E-02	7.15E-04
1.27	440	1.307	4.10E-02	1.68E-03
1.21	625	1.264	5.88E-02	3.46E-03
0.66	4490	0.637	-2.68E-02	7.16E-04



Chlasson Solution:
Chlasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.


$$Z_t = H_0 e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	1.413
225	1.358
449	1.305
673	1.254
898	1.205
1123	1.158
1347	1.112
1572	1.069
1796	1.027
2021	0.987
2245	0.949
2470	0.912
2694	0.876
2919	0.842
3143	0.809
3368	0.777
3592	0.747
3817	0.718
4041	0.690
4266	0.663
4490	0.637

Δt (s) = 225



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis

Cedar Rapids - Composite Cover

TRIAL 2

Test ID: CP3-SW Installer: XW
 Project: Cedar Rapids Analyst: CHB

FIXED VARIABLES


d (cm) = 1.905
 D (cm) = 29.845
 R_a (cm) = 52.07
 Final Time: 16:30:00

FITTED VARIABLES

a (s⁻¹) = 0.0001593
 H* (m) = 0.00
 H₀ (m) = 1.28
 MSE (m²) = 3.01E-03
 Bias (m) = 1.14E-09

SOLUTION - TRIAL 1

K (m/s) = 5.53E-08
 Total Time (d) = 0.05 1.3 hrs



Chlasson Solution:

Chlasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.

$$Z_t = H_0 e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

TEMPORAL VARIABLES

Time (m/d/yr h:m)	R (cm)
15:13:40	89.0
15:15:06	85.5
15:16:14	80.5
15:17:25	74.0
15:18:32	68.0
15:19:56	63.5
15:21:00	62.0
15:23:50	58.5
15:25:07	57.0
15:30:11	51.5
15:36:13	46.0
15:40:20	42.5
15:44:16	39.5
15:49:40	35.7
15:53:10	33.5
15:56:15	31.5
16:00:30	29.0
16:04:10	27.0
16:09:36	24.2
16:17:14	21.6
16:24:25	17.5
16:29:40	15.4
16:30:00	14.9


Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	s (m)	s' (m)
1.41	0.00	1.283	-1.28E-01	1.64E-02
1.38	86	1.265	-1.11E-01	1.22E-02
1.33	154	1.252	-7.42E-02	5.50E-03
1.26	225	1.237	-2.32E-02	5.40E-04
1.20	292	1.224	2.36E-02	5.58E-04
1.16	376	1.208	5.24E-02	2.74E-03
1.14	440	1.196	5.51E-02	3.04E-03
1.11	610	1.164	5.82E-02	3.38E-03
1.09	687	1.150	5.90E-02	3.48E-03
1.04	991	1.095	5.96E-02	3.55E-03
0.98	1353	1.034	5.33E-02	2.84E-03
0.95	1600	0.994	4.84E-02	2.34E-03
0.92	1836	0.957	4.17E-02	1.74E-03
0.88	2160	0.909	3.15E-02	9.94E-04
0.86	2370	0.879	2.36E-02	5.58E-04
0.84	2555	0.854	1.81E-02	3.27E-04
0.81	2810	0.820	9.10E-03	8.28E-05
0.79	3030	0.792	8.71E-04	7.58E-07
0.76	3356	0.752	-1.12E-02	1.25E-04
0.74	3814	0.699	-3.81E-02	1.45E-03
0.70	4245	0.652	-4.34E-02	1.88E-03
0.67	4560	0.620	-5.43E-02	2.95E-03
0.67	4580	0.618	-5.13E-02	2.63E-03

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	1.283
229	1.237
458	1.192
687	1.150
916	1.108
1145	1.069
1374	1.030
1603	0.994
1832	0.958
2061	0.924
2290	0.891
2519	0.859
2748	0.828
2977	0.798
3206	0.770
3435	0.742
3664	0.716
3893	0.690
4122	0.665
4351	0.641
4580	0.618

Δt (s) = 229



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis

Cedar Rapids - Composite Cover

TRIAL 3

Test ID: CP3-SW Installer: XW
 Project: Cedar Rapids Analyst: CHB

FIXED VARIABLES


d (cm) = 1.905
 D (cm) = 29.845
 R₀ (cm) = 52.07
 Final Time: 17:58:55

FITTED VARIABLES

a (s⁻¹) = 0.0001403
 H* (m) = 0.00
 H₀ (m) = 1.42
 MSE (m²) = 1.20E-03
 Bias (m) = 7.30E-09

SOLUTION - TRIAL 1

K (m/s) = 4.87E-08
 Total Time (d) = 0.06 1.5 hrs



Chiasson Solution:

Chiasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.

TEMPORAL VARIABLES

Time (m/d/yr h:m)	R (cm)
16:31:48	96.0
16:32:30	94.0
16:34:30	89.0
16:37:00	84.5
16:39:45	79.5
16:44:30	72.5
16:50:25	69.5
16:53:30	61.8
16:58:10	57.2
17:00:35	55.0
17:04:50	51.3
17:11:14	46.5
17:16:00	43.2
17:26:00	37.0
17:30:20	34.6
17:39:40	29.8
17:47:05	26.4
17:53:30	23.2
17:58:55	21.5

Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	s (m)	s ² (m)
1.48	0.00	1.420	-6.11E-02	3.73E-03
1.46	42	1.411	-4.94E-02	2.44E-03
1.41	162	1.388	-2.30E-02	5.27E-04
1.37	312	1.359	-6.87E-03	4.71E-05
1.32	477	1.328	1.20E-02	1.45E-04
1.25	762	1.276	3.00E-02	9.00E-04
1.22	1117	1.214	-1.98E-03	3.92E-06
1.14	1302	1.183	4.39E-02	1.93E-03
1.09	1582	1.137	4.44E-02	1.97E-03
1.07	1727	1.114	4.35E-02	1.89E-03
1.03	1982	1.075	4.13E-02	1.71E-03
0.99	2366	1.019	3.29E-02	1.08E-03
0.95	2652	0.979	2.59E-02	6.69E-04
0.89	3252	0.900	8.87E-03	7.87E-05
0.87	3512	0.867	6.48E-04	4.19E-07
0.82	4072	0.802	-1.69E-02	2.85E-04
0.78	4517	0.753	-3.14E-02	9.87E-04
0.75	4902	0.714	-3.90E-02	1.52E-03
0.74	5227	0.682	-5.38E-02	2.90E-03


$$Z_t = H_0 e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	1.420
261	1.369
523	1.319
784	1.272
1045	1.226
1307	1.182
1568	1.139
1829	1.098
2091	1.059
2352	1.021
2614	0.984
2875	0.948
3136	0.914
3398	0.881
3659	0.850
3920	0.819
4182	0.790
4443	0.761
4704	0.734
4966	0.707
5227	0.682

Δt (s) = 261



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis

Cedar Rapids - Composite Cover

TRIAL 4

Test ID: CP3-SW Installer: XW
 Project: Cedar Rapids Analyst: CHB

FIXED VARIABLES


d (cm) = 1.905
 D (cm) = 29.845
 R₀ (cm) = 52.07
 Final Time: 10:30:23

FITTED VARIABLES

a (s⁻¹) = 0.0001356
 H* (m) = 0.00
 H₀ (m) = 1.45
 MSE (m²) = 7.84E-04
 Bias (m) = -2.08E-11

SOLUTION -TRIAL 1

K (m/s) = 4.71E-08
 Total Time (d) = 0.05 1.1 hrs



Chiasson Solution:

Chiasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.

TEMPORAL VARIABLES

Time (m/d/yr h:m)	R (cm)
9:25:00	100.0
9:26:00	95.5
9:27:00	92.7
9:30:36	86.7
9:32:50	83.2
9:35:10	80.0
9:37:15	77.3
9:39:13	75.0
9:41:13	72.8
9:44	69.6
9:46:35	67.0
9:52:07	62.0
9:54:27	60.0
9:57:43	57.4
10:02:25	53.7
10:10:18	48.5
10:17:24	44.7
10:21:46	42.4
10:30:23	38.1

Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	ε (m)	ε' (m)
1.52	0.00	1.452	-6.87E-02	4.72E-03
1.48	60	1.440	-3.55E-02	1.26E-03
1.45	120	1.429	-1.91E-02	3.66E-04
1.39	336	1.387	-3.90E-04	1.52E-07
1.35	470	1.362	9.62E-03	9.26E-05
1.32	610	1.337	1.60E-02	2.56E-04
1.29	735	1.314	2.05E-02	4.21E-04
1.27	853	1.293	2.27E-02	5.13E-04
1.25	973	1.272	2.38E-02	5.65E-04
1.22	1140	1.244	2.73E-02	7.43E-04
1.19	1295	1.218	2.74E-02	7.50E-04
1.14	1627	1.164	2.37E-02	5.64E-04
1.12	1767	1.143	2.18E-02	4.77E-04
1.09	1963	1.113	1.79E-02	3.19E-04
1.06	2245	1.071	1.31E-02	1.72E-04
1.01	2718	1.004	-1.44E-03	2.07E-06
0.97	3144	0.948	-1.98E-02	3.93E-04
0.94	3406	0.915	-2.99E-02	8.95E-04
0.90	3923	0.853	-4.89E-02	2.39E-03


$$Z_t = H_0 e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	1.452
196	1.414
392	1.377
588	1.341
785	1.305
981	1.271
1177	1.238
1373	1.205
1569	1.174
1765	1.143
1962	1.113
2158	1.084
2354	1.055
2550	1.027
2746	1.000
2942	0.974
3138	0.949
3335	0.924
3531	0.899
3727	0.876
3923	0.853

Δt (s) = 196




Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis Cedar Rapids - Composite Cover

Equilibrium Evaluation & Steady Hydraulic Conductivity Determination

Trial	Time (d)	Total Time (d)	K (m/s)	
1	0.052	0.052	6.16E-08	CP3-SW
2	0.053	0.105	5.53E-08	
3	0.060	0.165	4.87E-08	
4	0.045	0.211	4.71E-08	

Field Hydraulic Conductivity

5.32E-08 m/s
5.32E-06 cm/s



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis

Cedar Rapids - Composite Cover

TRIAL 1

Test ID: CP4-SE Installer: XW
 Project: Cedar Rapids Analyst: CHB

FIXED VARIABLES


d (cm) = 1.905
 D (cm) = 29.845
 R₀ (cm) = 52.07
 Final Time: 13:48:00

FITTED VARIABLES

a (s⁻¹) = 0.0005108
 H* (m) = 0.00
 H₀ (m) = 1.39
 MSE (m²) = 7.33E-04
 Bias (m) = -1.24E-11

SOLUTION - TRIAL 1

K (m/s) = 1.77E-07
 Total Time (d) = 0.02 0.4 hrs



Chiaison Solution:

Chiaison, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.

TEMPORAL VARIABLES

Time (m/d/yr h:m)	R (cm)
13:26:12	92.7
13:27:45	82.7
13:28:30	79.0
13:28:50	77.0
13:29:30	73.5
13:30:30	69.0
13:31:15	65.5
13:32:00	62.0
13:33:30	56.5
13:34:47	52.0
13:35:50	48.5
13:37:06	45.0
13:38:14	42.0
13:39:10	39.5
13:41:00	35.5
13:42:40	32.0
13:45:00	28.5
13:47:10	25.5
13:48:00	24.4

Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	s (m)	s' (m)
1.45	0.00	1.392	-5.59E-02	3.12E-03
1.35	93	1.327	-2.04E-02	4.18E-04
1.31	138	1.297	-1.36E-02	1.85E-04
1.29	158	1.284	-6.79E-03	4.61E-05
1.26	198	1.258	2.25E-03	5.05E-06
1.21	258	1.220	9.28E-03	8.62E-05
1.18	303	1.192	1.66E-02	2.74E-04
1.14	348	1.165	2.45E-02	5.99E-04
1.09	438	1.113	2.71E-02	7.36E-04
1.04	515	1.070	2.92E-02	8.53E-04
1.01	578	1.036	3.03E-02	9.20E-04
0.97	654	0.997	2.59E-02	6.70E-04
0.94	722	0.963	2.19E-02	4.78E-04
0.92	778	0.935	1.97E-02	3.89E-04
0.88	888	0.884	8.62E-03	7.43E-05
0.84	988	0.840	-4.14E-04	1.72E-07
0.81	1128	0.782	-2.34E-02	5.48E-04
0.78	1258	0.732	-4.37E-02	1.91E-03
0.76	1308	0.714	-5.11E-02	2.61E-03


$$Z_t = H_0 e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	1.392
65	1.346
131	1.302
196	1.259
262	1.218
327	1.178
392	1.139
458	1.102
523	1.065
589	1.030
654	0.997
719	0.964
785	0.932
850	0.902
916	0.872
981	0.843
1046	0.816
1112	0.789
1177	0.763
1243	0.738
1308	0.714

Δt (s) = 65



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis Cedar Rapids - Composite Cover

TRIAL 2

Test ID: CP4-SE Installer: XW
Project: Cedar Rapids Analyst: CHB

FIXED VARIABLES


d (cm) = 1.905
D (cm) = 29.845
R_s (cm) = 52.07
Final Time: 14:04:19

FITTED VARIABLES

a (s⁻¹) = 0.0005177
H* (m) = 0.00
H₀ (m) = 1.43
MSE (m²) = 1.65E-04
Bias (m) = -8.32E-09

SOLUTION - TRIAL 1

K (m/s) = 1.80E-07
Total Time (d) = 0.01 0.3 hrs



Chlasson Solution:

Chiasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.

TEMPORAL VARIABLES

Time (m/d/y r h:m)	R (cm)
13:48:30	93.0
13:49:05	89.0
13:49:35	86.0
13:51:00	79.0
13:53:00	70.5
13:55:24	62.0
13:57:24	55.5
13:59:23	49.5
14:01:04	45.0
14:04:19	37.5

Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	ε (m)	ε ² (m)
1.45	0.00	1.429	-2.17E-02	4.69E-04
1.41	35	1.403	-7.31E-03	5.35E-05
1.38	65	1.382	1.06E-03	1.12E-06
1.31	150	1.322	1.16E-02	1.34E-04
1.23	270	1.243	1.69E-02	2.86E-04
1.14	414	1.153	1.27E-02	1.60E-04
1.08	534	1.084	8.19E-03	6.70E-05
1.02	653	1.019	3.43E-03	1.17E-05
0.97	754	0.967	-3.49E-03	1.22E-05
0.90	949	0.874	-2.14E-02	4.57E-04


$$Z_t = H_0 e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	1.429
47	1.394
95	1.361
142	1.328
190	1.295
237	1.264
285	1.233
332	1.203
380	1.174
427	1.146
475	1.118
522	1.091
569	1.064
617	1.038
664	1.013
712	0.989
759	0.965
807	0.941
854	0.918
902	0.896
949	0.874

Δt (s) = 47



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis Cedar Rapids - Composite Cover

TRIAL 3

Test ID: CP4-SE Installer: XW
Project: Cedar Rapids Analyst: CHB

FIXED VARIABLES


d (cm) = 1.905
D (cm) = 29.845
R_a (cm) = 52.07
Final Time: 15:35:40

FITTED VARIABLES

a (s⁻¹) = 0.0004771
H* (m) = 0.00
H₀ (m) = 1.37
MSE (m²) = 1.74E-04
Bias (m) = 4.66E-09

SOLUTION -TRIAL 1

K (m/s) = 1.66E-07
Total Time (d) = 0.02 0.4 hrs



Chiasson Solution:

Chiasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.

TEMPORAL VARIABLES

Time (m/d/yr h:m)	R (cm)
15:12:10	88.0
15:13:15	82.0
15:14:15	77.5
15:15:35	72.0
15:16:40	68.0
15:18:00	63.0
15:19:10	59.0
15:20:28	55.0
15:21:48	51.0
15:24:20	44.0
15:25:51	40.0
15:29:30	31.5
15:33:40	23.5
15:35:40	20.5

Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	s (m)	s' (m)
1.40	0.00	1.373	-2.74E-02	7.48E-04
1.34	65	1.331	-9.29E-03	8.63E-05
1.30	125	1.294	-1.86E-03	3.46E-06
1.24	205	1.245	4.69E-03	2.20E-05
1.20	270	1.207	6.67E-03	4.44E-05
1.15	350	1.162	1.15E-02	1.31E-04
1.11	420	1.124	1.33E-02	1.77E-04
1.07	498	1.083	1.22E-02	1.50E-04
1.03	578	1.042	1.17E-02	1.36E-04
0.96	730	0.969	8.77E-03	7.69E-05
0.92	821	0.928	7.58E-03	5.75E-05
0.84	1040	0.836	4.91E-04	2.41E-07
0.76	1290	0.742	-1.35E-02	1.83E-04
0.73	1410	0.701	-2.48E-02	6.16E-04


$$Z_t = H_0 e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	1.373
71	1.328
141	1.284
212	1.242
282	1.200
353	1.161
423	1.122
494	1.085
564	1.049
635	1.015
705	0.981
776	0.949
846	0.917
917	0.887
987	0.858
1058	0.829
1128	0.802
1199	0.775
1269	0.750
1340	0.725
1410	0.701

Δt (s) = 71



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis

Cedar Rapids - Composite Cover

TRIAL 4

Test ID: CP4-SE Installer: XW
 Project: Cedar Rapids Analyst: CHB

FIXED VARIABLES


d (cm) = 1.905
 D (cm) = 29.845
 R_s (cm) = 52.07
 Final Time: 15:57:50

FITTED VARIABLES

a (s⁻¹) = 0.0004660
 H* (m) = 0.00
 H₀ (m) = 1.36
 MSE (m²) = 7.70E-05
 Bias (m) = -1.16E-09

SOLUTION - TRIAL 1

K (m/s) = 1.62E-07
 Total Time (d) = 0.02 0.4 hrs



Chlasson Solution:

Chlasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.

TEMPORAL VARIABLES

Time (m/d/yr h:m)	R (cm)
15:35:54	86.0
15:36:34	82.5
15:37:05	80.0
15:39:32	70.5
15:40:50	66.0
15:42:00	62.0
15:43:52	56.0
15:45:14	52.0
15:47:00	47.0
15:48:54	42.0
15:52:00	34.5
15:53:59	30.5
15:55:12	28.0
15:56:45	25.0
15:57:50	23.0

Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	s (m)	s ² (m)
1.38	0.00	1.363	-1.77E-02	3.12E-04
1.35	40	1.338	-7.84E-03	6.14E-05
1.32	71	1.319	-2.02E-03	4.10E-06
1.23	218	1.231	5.67E-03	3.22E-05
1.18	296	1.187	6.72E-03	4.52E-05
1.14	366	1.149	8.62E-03	7.42E-05
1.08	478	1.091	1.02E-02	1.04E-04
1.04	560	1.050	9.28E-03	8.61E-05
0.99	666	0.999	8.68E-03	7.53E-05
0.94	780	0.948	6.98E-03	4.87E-05
0.87	966	0.869	3.30E-03	1.09E-05
0.83	1085	0.822	-3.58E-03	1.28E-05
0.80	1158	0.795	-6.07E-03	3.68E-05
0.77	1251	0.761	-9.77E-03	9.54E-05
0.75	1316	0.738	-1.25E-02	1.56E-04


$$Z_t = H_0 e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	1.363
66	1.322
132	1.282
197	1.243
263	1.206
329	1.169
395	1.134
461	1.100
526	1.067
592	1.034
658	1.003
724	0.973
790	0.943
855	0.915
921	0.887
987	0.861
1053	0.835
1119	0.809
1184	0.785
1250	0.761
1316	0.738

Δt (s) = 66



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis

Cedar Rapids - Composite Cover

TRIAL 5

Test ID: CP4-SE Installer: XW
 Project: Cedar Rapids Analyst: CHB

FIXED VARIABLES


d (cm) = 1.905
 D (cm) = 29.845
 R_a (cm) = 52.07
 Final Time: 9:44:42

FITTED VARIABLES

a (s⁻¹) = 0.0005118
 H* (m) = 0.00
 H₀ (m) = 1.48
 MSE (m²) = 2.21E-04
 Bias (m) = 9.04E-09

SOLUTION -TRIAL 1

K (m/s) = 1.78E-07
 Total Time (d) = 0.01 0.3 hrs



Chlasson Solution:

Chlasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.

TEMPORAL VARIABLES

Time (m/d/yr h:m)	R (cm)
9:24:00	100.0
9:25:00	90.5
9:27:00	83.5
9:28:00	76.5
9:29:30	71.7
9:31:23	64.7
9:32:00	62.5
9:34:15	55.0
9:35:40	50.6
9:36:30	48.3
9:38:23	43.5
9:39:47	40.0
9:40:30	37.8
9:41:34	35.3
9:43:42	29.8
9:44:42	27.7

Z-Z COMPUTATIONS

Z (m)	t (s)	Fitted Z (m)	s (m)	s' (m)
1.52	0.00	1.480	-4.10E-02	1.68E-03
1.43	60	1.435	9.29E-03	8.63E-05
1.36	180	1.350	-6.19E-03	3.83E-05
1.29	240	1.309	2.30E-02	5.29E-04
1.24	330	1.250	1.21E-02	1.46E-04
1.17	443	1.180	1.19E-02	1.41E-04
1.15	480	1.157	1.17E-02	1.38E-04
1.07	615	1.080	9.48E-03	8.98E-05
1.03	700	1.034	7.50E-03	5.62E-05
1.00	750	1.008	4.37E-03	1.91E-05
0.96	863	0.951	-4.27E-03	1.83E-05
0.92	947	0.911	-9.31E-03	8.66E-05
0.90	990	0.892	-7.15E-03	5.11E-05
0.87	1054	0.863	-1.09E-02	1.18E-04
0.82	1182	0.808	-1.06E-02	1.12E-04


$$Z_t = H_0 e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	1.480
62	1.433
124	1.389
186	1.345
248	1.303
310	1.262
373	1.223
435	1.185
497	1.148
559	1.112
621	1.077
683	1.043
745	1.011
807	0.979
869	0.948
931	0.919
994	0.890
1056	0.862
1118	0.835
1180	0.809
1242	0.784

Δt (s) = 62



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis Cedar Rapids - Composite Cover


Equilibrium Evaluation & Steady Hydraulic Conductivity Determination

Trial	Time (d)	Total Time (d)	K (m/s)	
1	0.015	0.015	1.77E-07	CP4-SE
2	0.011	0.026	1.80E-07	
3	0.016	0.042	1.66E-07	
4	0.015	0.058	1.62E-07	
5	0.014	0.072	1.78E-07	

Field Hydraulic Conductivity

1.71E-07 m/s

1.71E-05 cm/s



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis

Cedar Rapids - Composite Cover

TRIAL 1

Test ID: CP5-SE Installer: XW
 Project: Cedar Rapids Analyst: CHB

FIXED VARIABLES


d (cm) = 1.905
 D (cm) = 29.845
 R_s (cm) = 52.07
 Final Time:

FITTED VARIABLES

a (s⁻¹) = 0.0004064
 H* (m) = 0.00
 H₀ (m) = 1.48
 MSE (m²) = 3.40E-04
 Bias (m) = 5.38E-08

SOLUTION -TRIAL 1

K (m/s) = 1.41E-07
 Total Time (d) = 0.03 0.6 hrs



Chlasson Solution:

Chlasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.

TEMPORAL VARIABLES

Time (m/d/yr h:m)	R (cm)
11:06:57	100.0
11:09:02	90.0
11:11:28	80.0
11:14:16	70.0
11:17:30	60.0
11:21:48	49.0
11:25:50	40.0
11:29:21	33.0
11:31:08	30.0
11:32:46	27.0
11:35:00	23.0
11:36:48	20.0
11:40:32	15.0
11:45:10	9.5

Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	s (m)	s' (m)
1.52	0.00	1.484	-3.72E-02	1.38E-03
1.42	125	1.410	-1.07E-02	1.14E-04
1.32	271	1.329	8.11E-03	6.57E-05
1.22	439	1.241	2.04E-02	4.16E-04
1.12	633	1.147	2.63E-02	6.92E-04
1.01	891	1.033	2.21E-02	4.89E-04
0.92	1133	0.936	1.54E-02	2.36E-04
0.85	1344	0.859	8.44E-03	7.13E-05
0.82	1451	0.823	1.88E-03	3.53E-06
0.79	1549	0.790	-2.40E-04	5.76E-08
0.75	1683	0.749	-2.14E-03	4.57E-06
0.72	1791	0.716	-4.29E-03	1.84E-05
0.67	2015	0.654	-1.66E-02	2.76E-04
0.62	2293	0.584	-3.15E-02	9.93E-04


$$Z_t = H_0 e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	1.484
115	1.416
229	1.352
344	1.290
459	1.231
573	1.175
688	1.122
803	1.071
917	1.022
1032	0.975
1147	0.931
1261	0.889
1376	0.848
1490	0.809
1605	0.773
1720	0.737
1834	0.704
1949	0.672
2064	0.641
2178	0.612
2293	0.584

Δt (s) = 115



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis Cedar Rapids - Composite Cover

TRIAL 2

Test ID: CP5-SE Installer: XW
 Project: Cedar Rapids Analyst: CHB

FIXED VARIABLES

d (cm) = 1.905
 D (cm) = 29.845
 R₀ (cm) = 52.07
 Final Time: 12:24:33

FITTED VARIABLES

a (s⁻¹) = 0.0003927
 H* (m) = 0.00
 H₀ (m) = 1.49
 MSE (m²) = 3.92E-04
 Bias (m) = -4.07E-08

TEMPORAL VARIABLES


Time (m/d/yr h:m)	R (cm)
11:46:49	100.0
11:49:12	89.0
11:51:37	80.0
11:56:13	65.0
12:01:26	51.0
12:09:14	35.0
12:18:04	20.0
12:24:33	12.0

Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	s (m)	s ² (m)
1.52	0.00	1.490	-3.03E-02	9.21E-04
1.41	143	1.409	-1.74E-03	3.02E-06
1.32	288	1.331	1.03E-02	1.05E-04
1.17	564	1.194	2.35E-02	5.54E-04
1.03	877	1.056	2.54E-02	6.45E-04
0.87	1345	0.879	8.08E-03	6.54E-05
0.72	1875	0.714	-7.05E-03	4.97E-05
0.64	2264	0.613	-2.82E-02	7.93E-04

SOLUTION - TRIAL 1

K (m/s) = 1.36E-07
 Total Time (d) = 0.03 0.6 hrs



Chlasson Solution:
 Chlasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.


$$Z_t = H_0 e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	1.490
113	1.426
226	1.364
340	1.304
453	1.248
566	1.193
679	1.141
792	1.092
906	1.044
1019	0.999
1132	0.955
1245	0.914
1358	0.874
1472	0.836
1585	0.800
1698	0.765
1811	0.732
1924	0.700
2038	0.669
2151	0.640
2264	0.613

Δt (s) = 113



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis

Cedar Rapids - Composite Cover

TRIAL 3

Test ID: CP5-SE Installer: XW
 Project: Cedar Rapids Analyst: CHB

FIXED VARIABLES

d (cm) = 1.905
 D (cm) = 29.845
 R_a (cm) = 52.07
 Final Time: 12:46:47

FITTED VARIABLES

a (s^{-1}) = 0.0003752
 H^* (m) = 0.00
 H_0 (m) = 1.16
 MSE (m^2) = 4.31E-05
 Bias (m) = 7.91E-08

SOLUTION -TRIAL 1


K (m/s) = 1.30E-07
 Total Time (d) = 0.02 0.4 hrs

TEMPORAL VARIABLES

Time (m/d/yr h:m)	R (cm)
12:24:55	65.0
12:29:45	52.0
12:35:26	39.0
12:40:15	30.0
12:46:47	20.0

Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	s (m)	s^2 (m)
1.17	0.00	1.164	-6.42E-03	4.12E-05
1.04	290	1.044	3.55E-03	1.26E-05
0.91	631	0.919	8.15E-03	6.64E-05
0.82	920	0.824	3.73E-03	1.39E-05
0.72	1312	0.712	-9.02E-03	8.13E-05




Chlasson Solution:
 Chlasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.

$$Z_t = H_0 e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	1.164
66	1.136
131	1.108
197	1.081
262	1.055
328	1.029
394	1.004
459	0.980
525	0.956
590	0.933
656	0.910
722	0.888
787	0.867
853	0.845
918	0.825
984	0.805
1050	0.785
1115	0.766
1181	0.748
1246	0.729
1312	0.712



Δt (s) = 66

Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis

Cedar Rapids - Composite Cover

TRIAL 4

Test ID: CP5-SE
Project: Cedar Rapids

Installer: XW
Analyst: CHB

FIXED VARIABLES


d (cm) = 1.905
D (cm) = 29.845
R_s (cm) = 52.07
Final Time:

FITTED VARIABLES

a (s⁻¹) = 0.0002877
H* (m) = 0.00
H₀ (m) = 0.72
MSE (m²) = 6.34E-06
Bias (m) = -1.02E-11

SOLUTION - TRIAL 1

K (m/s) = 9.99E-08
Total Time (d) = 0.01 0.3 hrs



Chiasson Solution:

Chiasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.

$$Z_t = H_0 e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

TEMPORAL VARIABLES

Time (m/d/yr h:m)	R (cm)
13:50:10	20.0
13:52:15	17.0
13:54:45	14.0
13:57:18	11.0
14:00:12	8.0
14:03:08	5.0
14:06:35	2.0
14:09:05	0.0


Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	s (m)	s ² (m)
0.72	0.00	0.717	-4.15E-03	1.72E-05
0.69	125	0.691	5.46E-04	2.98E-07
0.66	275	0.662	1.35E-03	1.83E-06
0.63	428	0.634	2.85E-03	8.11E-06
0.60	602	0.603	1.92E-03	3.68E-06
0.57	778	0.573	2.17E-03	4.70E-06
0.54	985	0.540	-9.47E-04	8.97E-07
0.52	1135	0.517	-3.74E-03	1.40E-05

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	0.717
57	0.705
114	0.694
170	0.682
227	0.671
284	0.660
341	0.650
397	0.639
454	0.629
511	0.619
568	0.609
624	0.599
681	0.589
738	0.580
795	0.570
851	0.561
908	0.552
965	0.543
1022	0.534
1078	0.525
1135	0.517

Δt (s) = 57




Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis Cedar Rapids - Composite Cover

Equilibrium Evaluation & Steady Hydraulic Conductivity Determination

Trial	Time (d)	Total Time (d)	K (m/s)	
1	0.027	0.027	1.41E-07	CP5-SE
2	0.026	0.053	1.36E-07	
3	0.015	0.068	1.30E-07	
4	0.013	0.081	9.99E-08	
5	0.013	0.094	1.06E-07	

Field Hydraulic Conductivity

1.23E-07 m/s
1.23E-05 cm/s



Single-Stage Constant Head Borehole Test Helena - Store-and-Release Cover

Project: Helena
Date: 08/19/08
Test ID: 1

Installer: XW
Analyst: JS

Fixed Variables:

Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R_s (cm): 10
 L (cm): 60.96



Temporal Variables:

Time	R (cm)
8/19/08 15:00	38.5
8/19/08 16:27	43.3
8/19/08 17:02	45
8/20/08 7:50	89.3
8/20/08 15:00	38.1
8/21/08 8:05	55
8/21/08 12:30	57.3
8/21/08 16:05	58.7
8/22/08 8:27	40
8/22/08 12:40	41.6
8/22/08 16:00	42.6
8/23/08 7:46	47.2
8/23/08 11:57	49.1
8/23/08 15:42	50.5
8/24/08 7:55	49
8/24/08 12:11	51.4
8/24/08 15:37	52.7
8/25/08 8:22	59.0

Computations:

Q (cm ³ /s)	Time (d)	K (cm/s)
7.34E-02	0.060	1.23E-05
6.46E-02	0.085	1.09E-05
6.64E-02	0.701	1.12E-05
-1.58E-01	1.000	
2.19E-02	1.712	3.69E-06
1.15E-02	1.896	1.94E-06
8.66E-03	2.045	1.46E-06
-2.53E-02	2.727	
8.41E-03	2.903	1.41E-06
6.65E-03	3.042	1.12E-06
6.46E-03	3.699	1.09E-06
1.01E-02	3.873	1.69E-06
8.29E-03	4.029	1.39E-06
-2.05E-03	4.705	
1.25E-02	4.883	2.10E-06
8.39E-03	5.026	1.41E-06
8.34E-03	5.724	1.40E-06

Average 1.58E-06



Single-Stage Constant Head Borehole Test Helena - Store-and-Release Cover

Project: Helena
Date: 08/19/08
Test ID: 1

Installer: XW
Analyst: JS



Fixed Variables:

Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R_s (cm): 10
 L (cm): 60.96

Temporal Variables:

Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
8/19/08 14:07	30.5			
8/19/08 15:47	37	8.64E-02	0.069	1.45E-05
8/19/08 17:02	40.5	6.21E-02	0.122	1.04E-05
8/20/08 8:43	60	2.76E-02	0.775	4.63E-06
8/20/08 9:35	61.4	3.58E-02	0.811	6.02E-06
8/20/08 15:00	64.5	1.27E-02	1.037	2.13E-06
8/21/08 8:05	73	1.10E-02	1.749	1.85E-06
8/21/08 12:30	74.6	8.03E-03	1.933	1.35E-06
8/21/08 16:05	76	8.66E-03	2.082	1.46E-06
8/22/08 8:27	40.5	-4.81E-02	2.764	
8/22/08 16:00	42.1	4.70E-03	3.078	7.90E-07
8/22/08 16:00	43	#DIV/0!	3.078	
8/23/08 7:46	47.1	5.76E-03	3.736	9.69E-07
8/23/08 11:57	48.75	8.73E-03	3.910	1.47E-06
8/23/08 15:42	50.3	9.18E-03	4.066	1.54E-06
8/24/08 7:55	55.3	6.83E-03	4.742	1.15E-06
8/24/08 12:11	56.9	8.31E-03	4.920	1.40E-06
8/24/08 15:37	58.2	8.39E-03	5.063	1.41E-06
8/25/08 8:22	63.4	6.88E-03	5.760	1.16E-06

Average 1.28E-06



Single-Stage Constant Head Borehole Test Helena - Store-and-Release Cover

Project: Helena
Date: 08/19/08
Test ID: 1

Installer: XW
Analyst: JS



Fixed Variables:

Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R_a (cm): 10
 L (cm): 60.96

Temporal Variables:

Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
8/19/08 14:08	45.7			
8/19/08 15:47	48.8	4.16E-02	0.069	7.00E-06
8/19/08 17:02	50.8	3.55E-02	0.121	5.96E-06
8/20/08 8:43	67	2.29E-02	0.774	3.85E-06
8/20/08 9:35	68.5	3.84E-02	0.810	6.45E-06
8/20/08 15:00	71.7	1.31E-02	1.036	2.20E-06
8/21/08 8:05	81	1.21E-02	1.748	2.03E-06
8/21/08 12:30	83	1.00E-02	1.932	1.69E-06
8/21/08 16:05	84.5	9.28E-03	2.081	1.56E-06
8/22/08 8:27	38.9	-6.18E-02	2.763	
8/22/08 12:40	40.7	9.46E-03	2.939	1.59E-06
8/22/08 16:00	41.7	6.65E-03	3.078	1.12E-06
8/23/08 7:46	47	7.45E-03	3.735	1.25E-06
8/23/08 11:57	49.4	1.27E-02	3.909	2.14E-06
8/23/08 15:42	50.2	4.74E-03	4.065	7.97E-07
8/24/08 7:55	54.5	5.88E-03	4.741	9.88E-07
8/24/08 12:11	56.6	1.09E-02	4.919	1.83E-06
8/24/08 15:37	58.0	9.03E-03	5.062	1.52E-06
8/25/08 8:22	62.1	5.43E-03	5.760	9.13E-07

Average 1.31E-06



Single-Stage Constant Head Borehole Test Helena - Store-and-Release Cover

Project: Helena
Date: 08/19/08
Test ID: 1

Installer: XW
Analyst: JS


Fixed Variables:

Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R_s (cm): 10
 L (cm): 60.96

Temporal Variables:


Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
8/19/08 17:50	36.5			
8/20/08 8:43	54.2	2.64E-02	0.620	4.43E-06
8/20/08 9:35	56	4.60E-02	0.656	7.74E-06
8/20/08 15:00	58.2	9.00E-03	0.882	1.51E-06
8/21/08 8:05	77.5	2.50E-02	1.594	4.21E-06
8/21/08 12:30	83.5	3.01E-02	1.778	5.06E-06
8/21/08 16:05	87.5	2.47E-02	1.927	4.16E-06
8/22/08 8:35	36.4	-6.86E-02	2.615	
8/22/08 12:40	43.9	4.07E-02	2.785	6.85E-06
8/22/08 16:00	45.3	9.31E-03	2.924	1.57E-06
8/23/08 7:46	88.5	6.07E-02	3.581	1.02E-05
8/23/08 7:47	48.5	-8.63E+01	3.581	
8/23/08 11:57	49.5	5.31E-03	3.755	8.92E-07
8/23/08 15:42	64.5	8.88E-02	3.911	1.49E-05
8/24/08 7:55	51	-1.85E-02	4.587	
8/24/08 12:11	74.5	1.22E-01	4.765	2.05E-05
8/24/08 15:37	86.7	7.87E-02	4.908	1.32E-05

Average 1.62E-05



Bottle leaking from coupler

Still leaking from coupler




Single-Stage Constant Head Borehole Test Monticello - Store-an-Release Cover

Project: Monticello
 Date: 07/23/07
 Test ID: MC-1


Installer: XW
 Analyst: CHB

Fixed Variables:
 Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R_a (cm): 10
 L (cm): 60.96

Temporal Variables:		Computations:		
Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
8:57:00	22.7			
9:12:00	37.1	1.28E+00	0.0104	2.15E-04
9:25:00	40.4	3.38E-01	0.0194	5.68E-05
9:31:00	42.0	3.55E-01	0.0236	5.96E-05
9:44:00	45.5	3.58E-01	0.0326	6.02E-05
9:53:00	47.9	3.55E-01	0.0389	5.96E-05
10:01:00	50.0	3.49E-01	0.0444	5.87E-05
10:07:00	51.3	2.88E-01	0.0486	4.84E-05
10:39:00	59.5	3.41E-01	0.0708	5.73E-05
10:58:00	64.0	3.15E-01	0.0840	5.30E-05
11:13:00	67.8	3.37E-01	0.0944	5.66E-05
11:35:00	73.1	3.20E-01	0.1097	5.39E-05
11:46:00	75.5	2.90E-01	0.1174	4.88E-05
11:58:00	78.5	3.33E-01	0.1257	5.59E-05
12:17:00	83.0	3.15E-01	0.1389	5.30E-05
12:37:00	87.5			



AVG
 5.26E-05



Single-Stage Constant Head Borehole Test Monticello - Store-and-Release Cover

Project: Monticello
Date: 07/23/07
Test ID: MC-2

Installer: XW
Analyst: CHB


Fixed Variables:


Casing Diameter (cm): 30.48
Standpipe Area (cm²): 79.8
R_s (cm): 10
L (cm): 30.48

Temporal Variables:

Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
12:59:00	38.0			
13:00:00	41.5	4.66E+00	0.001	1.37E-03
13:02:00	46.4	3.26E+00	0.002	9.60E-04
13:04:00	50.9	2.99E+00	0.003	8.82E-04
13:06:00	54.9	2.66E+00	0.005	7.84E-04
13:08:00	58.6	2.46E+00	0.006	7.25E-04
13:10:00	62.0	2.26E+00	0.008	6.66E-04
13:12:00	65.4	2.26E+00	0.009	6.66E-04
13:16:00	71.4	1.99E+00	0.012	5.88E-04
13:19:00	75.6	1.86E+00	0.014	5.49E-04
13:22:00	79.7	1.82E+00	0.016	5.36E-04
13:25:00	83.6	1.73E+00	0.018	5.10E-04
13:28:00	87.4	1.68E+00	0.020	4.97E-04
13:31:00	91.0	1.60E+00	0.022	4.70E-04
13:34:00	94.4	1.51E+00	0.024	4.44E-04
13:38:00	39.3	-1.83E+01	0.027	
13:40:00	41.6	1.53E+00	0.028	
13:43:00	45.1	1.55E+00	0.031	
13:46:00	48.4	1.46E+00	0.033	
13:49:00	51.6	1.42E+00	0.035	4.18E-04
13:54:00	56.7	1.36E+00	0.038	4.00E-04
13:58:00	60.7	1.33E+00	0.041	3.92E-04
14:02:00	64.5	1.26E+00	0.044	3.72E-04
14:05:00	67.4	1.29E+00	0.046	3.79E-04
14:09:00	71.1	1.23E+00	0.049	3.63E-04
14:13:00	74.7	1.20E+00	0.051	3.53E-04
14:16:00	77.5	1.24E+00	0.053	3.66E-04
14:19:00	80.0	1.11E+00	0.056	3.27E-04
14:22:00	82.7	1.20E+00	0.058	3.53E-04
14:28:00	87.5	1.06E+00	0.062	3.14E-04
14:34:00	93.0	1.22E+00	0.066	3.59E-04
14:37:00	36.0		0.068	
14:39:00	37.8	1.20E+00	0.069	3.53E-04
14:42:00	40.4	1.15E+00	0.072	3.40E-04
14:46:00	44.0	1.20E+00	0.074	3.53E-04
14:52:00	49.0	1.11E+00	0.078	3.27E-04
14:58:00	53.9	1.09E+00	0.083	3.20E-04
15:07:00	61.1	1.06E+00	0.089	3.14E-04
15:21:00	72.3	1.06E+00	0.099	3.14E-04
15:31:00	80.0	1.02E+00	0.106	3.02E-04
15:52:00	95.7	9.94E-01	0.120	2.93E-04

AVG
3.08E-04





Single-Stage Constant Head Borehole Test

Monitcello - Store-and-Release Cover


Project: Monticello
 Date: 07/24/07
 Test ID: MC-3

Installer: XW
 Analyst: CHB


Fixed Variables:
 Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R_b (cm): 10
 L (cm): 30.48

Temporal Variables:

Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
9:17:00	30.0			
9:24:00	34.6	8.74E-01	0.005	2.58E-04
9:28:00	37.0	7.98E-01	0.008	2.35E-04
9:33:00	39.8	7.45E-01	0.011	2.20E-04
9:43:00	45.1	7.05E-01	0.018	2.08E-04
9:53:00	50.2	6.78E-01	0.025	2.00E-04
10:01:00	53.8	5.98E-01	0.031	1.76E-04
10:06:00	56.6	7.45E-01	0.034	2.20E-04
10:39:00	71.4	5.96E-01	0.057	1.76E-04
10:57:00	78.5	5.25E-01	0.069	1.55E-04
11:13:00	85.0	5.40E-01	0.081	1.59E-04
11:29:00	91.8	5.65E-01	0.092	1.67E-04
11:34:00	36.0	-1.48E+01	0.095	
11:39:00	38.1	5.59E-01	0.099	1.65E-04
11:45:00	40.9	6.21E-01	0.103	1.83E-04
11:57:00	46.1	5.76E-01	0.111	1.70E-04
12:03:00	48.7	5.76E-01	0.115	
12:16:00	54.2	5.63E-01	0.124	
12:36:00	62.5	5.52E-01	0.138	



AVG
 1.70E-04



Single-Stage Constant Head Borehole Test Monitcello - Store-and-Release Cover

Project: Monticello
Date: 07/25/07
Test ID: MC-5

Installer: XW
Analyst: CHB

Fixed Variables:



Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R_a (cm): 10
 L (cm): 60.96

Temporal Variables:

Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
14:22:00	32.7			
14:24:00	36.5	1.68E+04	36.5	2.82E+00
14:29:00	43.1	1.68E+04	79.6	2.82E+00
14:34:00	49.4	1.60E+04	129	2.70E+00
14:36:00	51.7	1.68E+04	180.7	2.82E+00
14:38:00	54.1	2.41E+04	234.8	4.05E+00
14:42:00	58.7	2.48E+04	293.5	4.17E+00

Computations:

AVG
2.79E+00



Single-Stage Constant Head Borehole Test Monitcello - Store-and-Release Cover

Project: Monticello
 Date: 03/30/07
 Test ID: MC-6

Installer: XW
 Analyst: CHB

Fixed Variables:

Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R_s (cm): 10
 L (cm): 30.48



Temporal Variables:

Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
4/3/07 15:03	29.5			
4/3/07 15:51	31.0	3.72E+04	118.000	1.10E+01
4/3/07 16:18	31.8	3.65E+04	232.000	1.07E+01
4/3/07 16:52	32.7	3.72E+04	347.000	1.10E+01
4/3/07 17:13	33.4	3.72E+04	461.000	1.10E+01
4/3/07 17:38	34.0	3.65E+04	591.000	1.07E+01
4/3/07 17:57	34.4	3.35E+04	756.000	9.89E+00

Computations:

AVG

10.9



**Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis
Monticello - Store-and-Release Cover**

TRIAL 1

Test ID: TSB-4 Installer: XW
Project: Monticello Analyst: CHB

FIXED VARIABLES


d (cm) = 30.48
D (cm) = 30.48
R_a (cm) = 0
Final Time: 1/0/00 2:17

FITTED VARIABLES

a (s⁻¹) = 0.0009182
H* (m) = 0.31
H₀ (m) = 0.60
MSE (m²) = 1.87E-05
Bias (m) = -2.89E-08

SOLUTION -TRIAL 1

K (m/s) = 7.99E-05
Total Time (d) = 0.01 0.2 hrs



TEMPORAL VARIABLES

Time (m/d/yr h:m)	R (cm)
1/0/00 2:05	29
1/0/00 2:07	23
1/0/00 2:08	19
1/0/00 2:10	15
1/0/00 2:12	10
1/0/00 2:14	5
1/0/00 2:17	0

Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	ε (m)	ε ² (m)
0.29	0	0.290	-3.69E-04	1.36E-07
0.23	120	0.227	-3.10E-03	9.61E-06
0.19	180	0.198	8.03E-03	6.45E-05
0.15	300	0.145	-5.14E-03	2.64E-05
0.10	420	0.097	-2.77E-03	7.68E-06
0.05	540	0.055	4.57E-03	2.09E-05
0.00	720	-0.001	-1.22E-03	1.49E-06

Chiasson Solution:


Chiasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.

$$Z_t = H_0 e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	0.290
36	0.270
72	0.251
108	0.233
144	0.215
180	0.198
216	0.181
252	0.165
288	0.150
324	0.135
360	0.120
396	0.106
432	0.093
468	0.080
504	0.067
540	0.055
576	0.043
612	0.031
648	0.020
684	0.009
720	-0.001



Δt (s) = 36

Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis
Monticello - Store-and-Release Cover

TRIAL 2

Test ID: TSB-4 Installer: XW
 Project: Monticello Analyst: CHB

FIXED VARIABLES


d (cm) = 30.48
 D (cm) = 30.48
 R_a (cm) = 0
 Final Time: 1/0/00 2:31

FITTED VARIABLES

a (s⁻¹) = 0.0012648
 H* (m) = 0.18
 H_o (m) = 0.49
 MSE (m²) = 3.98E-05
 Bias (m) = 6.33E-08

SOLUTION - TRIAL 1

K (m/s) = 1.10E-04
 Total Time (d) = 0.01 0.2 hrs



Chiasson Solution:

Chiasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90.

$$Z_t = H_o e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

TEMPORAL VARIABLES

Time (m/d/yr h:m)	R (cm)
1/0/00 2:18	30
1/0/00 2:20	25
1/0/00 2:21	20
1/0/00 2:23	15
1/0/00 2:25	10
1/0/00 2:28	5
1/0/00 2:31	0


Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	e (m)	e ² (m)
0.30	0	0.305	4.74E-03	2.24E-05
0.25	120	0.236	-1.36E-02	1.86E-04
0.20	180	0.206	5.89E-03	3.47E-05
0.15	300	0.151	1.45E-03	2.11E-06
0.10	420	0.105	4.68E-03	2.19E-05
0.05	600	0.047	-3.43E-03	1.18E-05
0.00	780	0.000	2.94E-04	8.66E-08

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	0.305
39	0.281
78	0.259
117	0.238
156	0.218
195	0.199
234	0.180
273	0.163
312	0.146
351	0.131
390	0.116
429	0.101
468	0.088
507	0.075
546	0.063
585	0.051
624	0.040
663	0.029
702	0.019
741	0.009
780	0.000

Δt (s) = 39



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis Monticello - Store-and-Release Cover

TRIAL 3

Test ID: TSB-4 Installer: XW
Project: Monticello Analyst: CHB

FIXED VARIABLES

d (cm) = 30.48
D (cm) = 30.48
R_a (cm) = 0
Final Time: 1/0/00 2:56

FITTED VARIABLES

a (s⁻¹) = 0.0012964
H* (m) = 0.05
H_o (m) = 0.35
MSE (m²) = 6.46E-06
Bias (m) = -1.33E-08

TEMPORAL VARIABLES


Time (m/d/yr h:m)	R (cm)
1/0/00 2:32	30
1/0/00 2:34	25
1/0/00 2:36	20
1/0/00 2:39	15
1/0/00 2:43	10
1/0/00 2:48	5
1/0/00 2:56	0

Z-t COMPUTATIONS

Z (m)	t (s)	Fit Z (m)	ε (m)	ε ² (m)
0.30	0	0.299	-1.16E-03	1.35E-06
0.25	120	0.248	-1.81E-03	3.28E-06
0.20	240	0.205	4.84E-03	2.34E-05
0.15	420	0.151	1.23E-03	1.52E-06
0.10	660	0.097	-3.30E-03	1.09E-05
0.05	960	0.049	-1.44E-03	2.08E-06
0.00	1440	0.002	1.64E-03	2.69E-06

SOLUTION - TRIAL 1

K (m/s) = 1.13E-04
Total Time (d) = 0.02 0.4 hrs



Chiasson Solution:

Chiasson, P. (2005), Method of interpretation of borehole falling-head tests performed in compacted clay liners, *Canadian Geotechnical J.*, 42, 79-90


$$Z_t = H_o e^{-at} - H^*$$

$$K = \frac{a \pi d^2}{11 D}$$

SOLUTION FOR GRAPHING

t (s)	Z (m)
0	0.299
72	0.268
144	0.239
216	0.213
288	0.189
360	0.168
432	0.148
504	0.130
576	0.114
648	0.099
720	0.086
792	0.073
864	0.062
936	0.052
1008	0.042
1080	0.034
1152	0.026
1224	0.019
1296	0.013
1368	0.007
1440	0.002

Δt (s) = 72



Borehole Hydraulic Conductivity Test Calculator - Isotropic Analysis Monticello - Store-and-Release Cover

Equilibrium Evaluation & Steady Hydraulic Conductivity Determination


Trial	Time (d)	Total Time (d)	K (m/s)
1	0.008	0.008	7.99E-05
2	0.009	0.017	1.10E-04
3	0.017	0.034	1.13E-04

TSB-4

Field Hydraulic Conductivity

1.13E-04 m/s

1.13E-02 cm/s




Single-Stage Constant Head Borehole Test Omaha - Composite Cover

Project: Omaha **Installer:** XW
Date: 05/19/08 **Analyst:** CHB
Test ID: TS81-composite


Fixed Variables:
Casing Diameter (cm): 30.48
Standpipe Area (cm²): 19.44 (50 mm standpipe)
R_s (cm): 10
L (cm): 60.96

Temporal Variables:		Computations:		
Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
4:05:00	35.5			
4:06:00	38.4	9.40E-01	0.0007	1.58E-04
4:07:00	41.0	8.42E-01	0.0014	1.42E-04
4:08:00	44.0	9.72E-01	0.0021	1.63E-04
4:09:00	46.8	9.07E-01	0.0028	1.53E-04
4:10:00	49.5	8.75E-01	0.0035	1.47E-04
4:11:00	52.2	8.75E-01	0.0042	1.47E-04
4:12:00	55.0	9.07E-01	0.0049	1.53E-04
4:13:00	57.9	9.40E-01	0.0056	1.58E-04
4:14:00	60.2	7.45E-01	0.0063	1.25E-04
4:15:00	62.5	7.45E-01	0.0069	1.25E-04
4:16:00	64.6	6.80E-01	0.0076	1.14E-04
4:17:00	67.3	8.75E-01	0.0083	1.47E-04
4:18:00	70.0	8.75E-01	0.0090	1.47E-04
4:19:00	72.4	7.78E-01	0.0097	1.31E-04
4:20:00	74.7	7.45E-01	0.0104	1.25E-04
4:21:00	77.1	7.78E-01	0.0111	1.31E-04
4:22:00	79.6	8.10E-01	0.0118	1.36E-04
4:23:00	81.5	6.16E-01	0.0125	1.03E-04
4:24:00	83.9	7.78E-01	0.0132	1.31E-04
4:25:00	86.2	7.45E-01	0.0139	1.25E-04
4:26:00	88.5	7.45E-01	0.0146	1.25E-04
4:27:00	90.6	6.80E-01	0.0153	1.14E-04
4:28:00	92.7	6.80E-01	0.0160	1.14E-04
9:16:00	31.5			
9:18:00	35.4	6.32E-01	0.0174	1.06E-04
9:20:00	39.1	5.99E-01	0.0188	1.01E-04
9:22:00	43.2	6.64E-01	0.0201	1.12E-04
9:24:00	47.3	6.64E-01	0.0215	1.12E-04
9:26:00	51.4	6.64E-01	0.0229	1.12E-04
9:28:00	55.5	6.64E-01	0.0243	1.12E-04
9:30:00	59.6	6.64E-01	0.0257	1.12E-04
9:32:00	63.6	6.48E-01	0.0271	1.09E-04
9:34:00	67.6	6.48E-01	0.0285	1.09E-04
9:36:00	71.5	6.32E-01	0.0299	1.06E-04
9:38:00	75.6	6.64E-01	0.0313	1.12E-04
9:40:00	79.7	6.64E-01	0.0326	1.12E-04
9:42:00	83.8	6.64E-01	0.0340	1.12E-04
9:44:00	87.9	6.64E-01	0.0354	1.12E-04
9:46:00	91.1	5.18E-01	0.0368	8.72E-05
9:48:00	95.2	6.64E-01	0.0382	1.12E-04



10:06:00	30.0			
10:08:00	34.6	7.45E-01	0.0368	1.25E-04
10:09:00	36.0	4.54E-01	0.0375	7.63E-05
10:10:00	37.0	3.24E-01	0.0382	5.45E-05
10:11:00	38.1	3.56E-01	0.0389	5.99E-05
10:12:00	39.0	2.92E-01	0.0396	4.90E-05
10:13:00	40.1	3.56E-01	0.0403	5.99E-05
10:14:00	41.5	4.54E-01	0.0410	7.63E-05
10:15:00	43.0	4.86E-01	0.0417	8.17E-05
10:16:00	44.5	4.86E-01	0.0424	8.17E-05
10:17:00	45.9	4.54E-01	0.0431	7.63E-05
10:18:00	47.2	4.21E-01	0.0438	7.08E-05
10:19:00	48.6	4.54E-01	0.0444	7.63E-05
10:20:00	50.1	4.86E-01	0.0451	8.17E-05
10:21:00	51.6	4.86E-01	0.0458	8.17E-05
10:22:00	53.0	4.54E-01	0.0465	7.63E-05
10:23:00	54.5	4.86E-01	0.0472	8.17E-05
10:24:00	55.9	4.54E-01	0.0479	7.63E-05
10:25:00	57.4	4.86E-01	0.0486	8.17E-05
10:26:00	58.8	4.54E-01	0.0493	7.63E-05
10:27:00	60.3	4.86E-01	0.0500	8.17E-05
10:28:00	61.5	3.89E-01	0.0507	6.54E-05
10:29:00	63.0	4.86E-01	0.0514	8.17E-05
10:31:00	65.8	4.54E-01	0.0528	7.63E-05
10:33:00	68.4	4.21E-01	0.0542	7.08E-05
10:35:00	71.3	4.70E-01	0.0556	7.90E-05
10:37:00	74.1	4.54E-01	0.0569	7.63E-05
10:39:00	77.0	4.70E-01	0.0583	7.90E-05

AVG
7.81E-05



Single-Stage Constant Head Borehole Test Omaha - Composite Cover

Project: Omaha
Date: 05/19/08
Test ID: TSB2-composite

Installer: XW
Analyst: CHB


Fixed Variables:

Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 19.44 (50 mm standpipe)
 R₀ (cm): 10
 L (cm): 60.96

Temporal Variables:


Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
3:17:00	32.5			
3:18:00	36.4	1.26E+00	0.001	2.12E-04
3:19:00	40.4	1.30E+00	0.001	2.18E-04
3:20:00	44.4	1.30E+00	0.002	2.18E-04
3:21:00	48.3	1.26E+00	0.003	2.12E-04
3:22:00	52.4	1.33E+00	0.003	2.23E-04
3:23:00	56.2	1.23E+00	0.004	2.07E-04
3:25:00	63.5	1.18E+00	0.006	1.99E-04
3:27:00	71.0	1.21E+00	0.007	2.04E-04
3:29:00	78.5	1.22E+00	0.008	2.04E-04
3:31:00	86.0	1.22E+00	0.010	2.04E-04
3:33:00	93.6	1.23E+00	0.011	2.07E-04
3:37:00	34.5			
3:39:00	42.0	1.22E+00	0.015	2.04E-04
3:41:00	49.0	1.13E+00	0.017	1.91E-04
3:43:00	56.5	1.22E+00	0.018	2.04E-04
3:45:00	63.5	1.13E+00	0.019	1.91E-04
3:47:00	70.3	1.10E+00	0.021	1.85E-04
3:49:00	77.5	1.17E+00	0.022	1.96E-04
3:51:00	83.7	1.00E+00	0.024	1.69E-04
3:53:00	90.4	1.09E+00	0.025	1.82E-04
3:55:00	97.0	1.07E+00	0.026	1.80E-04
9:13:00	31.2			
9:14:00	34.4	1.04E+00	0.027	1.74E-04
9:15:00	37.7	1.07E+00	0.028	1.80E-04
9:17:00	44.2	1.05E+00	0.029	1.77E-04
9:19:00	50.6	1.04E+00	0.031	1.74E-04
9:21:00	57.0	1.04E+00	0.032	1.74E-04
9:23:00	63.5	1.05E+00	0.033	1.77E-04
9:25:00	70.0	1.05E+00	0.035	1.77E-04
9:27:00	76.5	1.05E+00	0.036	1.77E-04
9:29:00	83.0	1.05E+00	0.038	1.77E-04
9:31:00	89.6	1.07E+00	0.039	1.80E-04
9:33:00	96.1	1.05E+00	0.040	1.77E-04

Computations:



9:37:00	31.0			
9:39:00	37.5	1.05E+00	0.042	1.77E-04
9:41:00	44.0	1.05E+00	0.043	1.77E-04
9:43:00	51.5	1.22E+00	0.044	2.04E-04
9:45:00	57.5	9.72E-01	0.046	1.63E-04
9:47:00	63.0	8.91E-01	0.047	1.50E-04
9:49:00	69.5	1.05E+00	0.049	1.77E-04
9:51:00	76.0	1.05E+00	0.050	1.77E-04
9:53:00	83.5	1.22E+00	0.051	2.04E-04
9:55:00	90.0	1.05E+00	0.053	1.77E-04
9:57:00	96.4	1.04E+00	0.054	1.74E-04

AVG
1.77E-04




**Single-Stage Constant Head Borehole Test
Omaha - Composite Cover**

Project: Omaha
Date: 05/19/08
Test ID: T503-composite

Installer: KW
Analyst: CHB


Fixed Variables:
Casing Diameter (cm): 30.48
Standpipe Area (cm²): 79.8
R_s (cm): 10
L (cm): 60.96

Temporal Variables:		Computations:			
Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)	
1:54	34.0				
1:57	36.8	1.24E+00	0.002	2.09E-04	
2:02	42.3	1.46E+00	0.006	2.46E-04	
2:05	45.2	1.29E+00	0.008	2.16E-04	
2:08	48.3	1.37E+00	0.010	2.31E-04	
2:11	51.4	1.37E+00	0.012	2.31E-04	
2:14	54.4	1.38E+00	0.014	2.34E-04	
2:18	58.0	1.20E+00	0.017	2.01E-04	
2:21	60.8	1.24E+00	0.019	2.09E-04	
2:24	63.4	1.15E+00	0.021	1.94E-04	
2:27	65.3	8.42E-01	0.023	1.42E-04	
2:30	68.2	1.29E+00	0.025	2.16E-04	
2:33	71.0	1.24E+00	0.027	2.09E-04	
2:36	73.6	1.15E+00	0.029	1.94E-04	
2:39	76.2	1.15E+00	0.031	1.94E-04	
2:42	78.7	1.11E+00	0.033	1.86E-04	
2:45	81.3	1.15E+00	0.035	1.94E-04	
2:48	84.0	1.20E+00	0.038	2.01E-04	
2:51	86.5	1.11E+00	0.040	1.86E-04	
2:55	89.8	1.10E+00	0.042	1.84E-04	
3:00	93.9	1.09E+00	0.046	1.83E-04	
3:06	99.0	1.13E+00	0.050	1.90E-04	
3:10:00	33.3				
3:12:00	35.0	1.13E+00	0.051	1.90E-04	
3:15:00	37.5	1.11E+00	0.053	1.86E-04	
3:20:00	41.6	1.09E+00	0.057	1.83E-04	
3:25:00	45.5	1.04E+00	0.060	1.74E-04	
3:30:00	49.6	1.09E+00	0.064	1.83E-04	
3:35:00	53.9	1.14E+00	0.067	1.92E-04	
3:40:00	57.7	1.01E+00	0.071	1.70E-04	
3:45:00	61.7	1.06E+00	0.074	1.79E-04	
3:51:00	66.4	1.04E+00	0.078	1.75E-04	
4:00:00	73.5	1.05E+00	0.085	1.76E-04	
4:10:00	81.0	9.97E-01	0.092	1.68E-04	
4:21:00	89.6	1.04E+00	0.099	1.75E-04	
9:04:00	30.3				
9:05:00	31.4	1.46E+00	0.100	2.46E-04	
9:06:00	32.2	1.06E+00	0.101	1.79E-04	
9:07:00	32.9	9.31E-01	0.101	1.57E-04	
9:08:00	33.4	6.65E-01	0.102	1.12E-04	
9:10:00	34.7	5.33E-01	0.103	8.94E-05	
9:11:00	35.0	1.06E+00	0.104	1.79E-04	
9:12:00	35.6	7.98E-01	0.105	1.34E-04	
9:13:00	36.3	9.31E-01	0.106	1.57E-04	
9:14:00	37.0	9.31E-01	0.106	1.57E-04	
9:15:00	37.8	1.06E+00	0.107	1.79E-04	
9:16:00	38.3	6.65E-01	0.108	1.12E-04	
9:17:00	39.2	1.20E+00	0.108	2.01E-04	
9:18:00	39.9	9.31E-01	0.109	1.57E-04	
9:19:00	40.4	6.65E-01	0.110	1.12E-04	
9:20:00	41.1	9.31E-01	0.110	1.57E-04	
9:21:00	41.5	5.33E-01	0.111	8.94E-05	
9:22:00	42.5	1.33E+00	0.112	2.24E-04	
9:23:00	43.2	9.31E-01	0.113	1.57E-04	
9:24:00	43.9	9.31E-01	0.113	1.57E-04	
9:25:00	44.5	7.98E-01	0.114	1.34E-04	
9:26:00	45.3	1.06E+00	0.115	1.79E-04	
9:27:00	45.9	7.98E-01	0.115	1.34E-04	
9:28:00	46.5	7.98E-01	0.116	1.34E-04	
9:29:00	47.2	9.31E-01	0.117	1.57E-04	
9:30:00	48.0	1.06E+00	0.117	1.79E-04	
9:31:00	48.7	9.31E-01	0.118	1.57E-04	
9:32:00	49.3	7.98E-01	0.119	1.34E-04	
9:33:00	50.0	9.31E-01	0.119	1.57E-04	
9:34:00	50.6	7.98E-01	0.120	1.34E-04	
9:35:00	51.3	9.31E-01	0.121	1.57E-04	
9:36:00	52.0	9.31E-01	0.122	1.57E-04	
9:37:00	52.7	9.31E-01	0.122	1.57E-04	
9:38:00	53.2	6.65E-01	0.123	1.12E-04	
9:39:00	54.0	1.06E+00	0.124	1.79E-04	
9:40:00	54.6	7.98E-01	0.124	1.34E-04	
9:41:00	55.4	1.06E+00	0.125	1.79E-04	
9:42:00	55.9	6.65E-01	0.126	1.12E-04	
9:43:00	56.6	9.31E-01	0.126	1.57E-04	
9:44:00	57.2	7.98E-01	0.127	1.34E-04	
9:45:00	57.9	9.31E-01	0.128	1.57E-04	
9:46:00	58.5	7.98E-01	0.128	1.34E-04	
9:47:00	59.2	9.31E-01	0.129	1.57E-04	
9:48:00	59.9	9.31E-01	0.130	1.57E-04	
9:49:00	60.6	9.31E-01	0.131	1.57E-04	
9:50:00	61.2	7.98E-01	0.131	1.34E-04	
9:51:00	61.8	7.98E-01	0.132	1.34E-04	
9:52:00	62.4	7.98E-01	0.133	1.34E-04	
9:53:00	63.0	7.98E-01	0.133	1.34E-04	
9:54:00	63.6	7.98E-01	0.134	1.34E-04	



10:05:00	40.8			
10:06:00	41.5	9.31E-01	0.135	1.57E-04
10:07:00	42.1	7.98E-01	0.135	1.34E-04
10:08:00	42.7	7.98E-01	0.136	1.34E-04
10:09:00	43.4	9.31E-01	0.137	1.57E-04
10:10:00	44.2	1.06E+00	0.138	1.79E-04
10:11:00	44.9	9.31E-01	0.138	1.57E-04
10:12:00	45.6	9.31E-01	0.139	1.57E-04
10:13:00	46.3	9.31E-01	0.140	1.57E-04
10:14:00	46.8	6.65E-01	0.140	1.12E-04
10:15:00	47.5	9.31E-01	0.141	1.57E-04
10:16:00	48.1	7.98E-01	0.142	1.34E-04
10:17:00	48.7	7.98E-01	0.142	1.34E-04
10:18:00	49.4	9.31E-01	0.143	1.57E-04
10:19:00	50.0	7.98E-01	0.144	1.34E-04
10:20:00	50.7	9.31E-01	0.144	1.57E-04
10:21:00	51.3	7.98E-01	0.145	1.34E-04
10:22:00	52.0	9.31E-01	0.146	1.57E-04
10:23:00	52.6	7.98E-01	0.147	1.34E-04
10:24:00	53.3	9.31E-01	0.147	1.57E-04
10:25:00	54.0	9.31E-01	0.148	1.57E-04
10:26:00	54.6	7.98E-01	0.149	1.34E-04
10:28:00	56.0	9.31E-01	0.150	1.57E-04
10:30:00	57.3	8.65E-01	0.151	1.45E-04
10:32:00	58.5	7.98E-01	0.153	1.34E-04
10:34:00	59.7	7.98E-01	0.154	1.34E-04
10:36:00	61.1	9.31E-01	0.156	1.57E-04
10:38:00	62.4	8.65E-01	0.157	1.45E-04
10:40:00	63.8	9.31E-01	0.158	1.57E-04
10:42:00	65.0	7.98E-01	0.160	1.34E-04
10:44:00	66.3	8.65E-01	0.161	1.45E-04

AVG
1.72E-04




Single-Stage Constant Head Borehole Test Omaha - Composite Cover

Project: Omaha Installer: XW
 Date: 05/19/08 Analyst: CHB
 Test ID: TSB4-composite


Fixed Variables:
 Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R_s (cm): 10
 L (cm): 60.96

Temporal Variables:		Computations:		
Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
1:57:00	30.0			
2:00:00	36.0	2.66E+00	0.002	4.47E-04
2:03:00	43.0	3.10E+00	0.004	5.22E-04
2:06:00	49.5	2.88E+00	0.006	4.84E-04
2:09:00	56.1	2.93E+00	0.008	4.92E-04
2:12:00	62.7	2.93E+00	0.010	4.92E-04
2:15:00	68.8	2.70E+00	0.013	4.55E-04
2:19:00	76.5			
2:22:00	82.4	2.62E+00	0.015	4.40E-04
2:25:00	88.1	2.53E+00	0.017	4.25E-04
2:28:00	93.5	2.39E+00	0.019	4.02E-04
2:31:00	99.3	2.57E+00	0.021	4.32E-04
2:37:00	33.3			
2:40:00	39.6	2.79E+00	0.027	4.70E-04
2:43:00	45.5	2.62E+00	0.029	4.40E-04
2:46:00	51.3	2.57E+00	0.031	4.32E-04
2:50:00	59.1	2.59E+00	0.034	4.36E-04
2:53:00	64.6	2.44E+00	0.036	4.10E-04
2:56:00	70.0	2.39E+00	0.038	4.02E-04
2:59:00	75.2	2.31E+00	0.040	3.88E-04
3:02:00	80.4	2.31E+00	0.042	3.88E-04
3:05:00	85.5	2.26E+00	0.044	3.80E-04
3:10:00	94.2	2.31E+00	0.048	3.89E-04
3:13:00	99.0	2.13E+00	0.050	3.58E-04
3:38:00	32.0			
3:41:00	37.2	2.31E+00	0.069	3.88E-04
3:44:00	42.2	2.22E+00	0.072	3.73E-04
3:47:00	46.9	2.08E+00	0.074	3.50E-04
3:50:00	51.5	2.04E+00	0.076	3.43E-04
3:53:00	56.2	2.08E+00	0.078	3.50E-04
3:56:00	60.5	1.91E+00	0.080	3.21E-04
3:59:00	65.2	2.08E+00	0.082	3.50E-04
4:02:00	69.7	2.00E+00	0.084	3.35E-04
4:05:00	73.8	1.82E+00	0.086	3.06E-04
4:08:00	78.3	1.99E+00	0.088	3.35E-04
4:11:00	83.0	2.08E+00	0.090	3.50E-04
04:14:00	87.5	2.00E+00	0.092	3.35E-04
04:17:00	91.5	1.77E+00	0.094	2.98E-04
04:20:00	96.1	2.04E+00	0.097	3.43E-04
08:57:00	30.3			
08:59:00	33.6	2.19E+00	0.098	3.69E-04
09:01:00	35.5	1.76E+00	0.099	2.12E-04
09:03:00	38.2	1.80E+00	0.101	3.02E-04
09:05:00	40.7	1.66E+00	0.102	2.80E-04
09:07:00	43.2	1.66E+00	0.103	2.80E-04
09:09:00	45.5	1.53E+00	0.105	2.57E-04
09:11:00	48.0	1.66E+00	0.106	2.80E-04
09:13:00	50.5	1.66E+00	0.108	2.80E-04
09:15:00	52.9	1.60E+00	0.109	2.68E-04
09:17:00	55.3	1.60E+00	0.110	2.68E-04
09:19:00	57.7	1.60E+00	0.112	2.68E-04
09:21:00	60.0	1.53E+00	0.113	2.57E-04
09:23:00	62.4	1.60E+00	0.115	2.68E-04
09:25:00	64.7	1.53E+00	0.116	2.57E-04
09:27:00	66.9	1.46E+00	0.117	2.46E-04
09:29:00	69.2	1.53E+00	0.119	2.57E-04
09:31:00	71.5	1.53E+00	0.120	2.57E-04
09:33:00	73.8	1.53E+00	0.122	2.57E-04
09:35:00	76.1	1.53E+00	0.123	2.57E-04
09:37:00	78.3	1.46E+00	0.124	2.46E-04
09:39:00	80.6	1.53E+00	0.126	2.57E-04
09:41:00	83.0	1.60E+00	0.127	2.68E-04
09:43:00	85.2	1.46E+00	0.128	2.46E-04
09:45:00	87.5	1.53E+00	0.130	2.57E-04



10:05:00	42.9			
10:06:00	44.1	1.60E+00	0.131	2.68E-04
10:07:00	45.2	1.46E+00	0.131	2.46E-04
10:08:00	46.3	1.46E+00	0.132	2.46E-04
10:09:00	47.5	1.60E+00	0.133	2.68E-04
10:10:00	48.5	1.33E+00	0.133	2.24E-04
10:11:00	49.6	1.46E+00	0.134	2.46E-04
10:12:00	50.7	1.46E+00	0.135	2.46E-04
10:13:00	51.9	1.60E+00	0.135	2.68E-04
10:14:00	52.8	1.20E+00	0.136	2.01E-04
10:15:00	53.9	1.46E+00	0.137	2.46E-04
10:16:00	54.9	1.33E+00	0.138	2.24E-04
10:17:00	56.0	1.46E+00	0.138	2.46E-04
10:18:00	57.0	1.33E+00	0.139	2.24E-04
10:19:00	58.1	1.46E+00	0.140	2.46E-04
10:20:00	59.1	1.33E+00	0.140	2.24E-04
10:21:00	60.2	1.46E+00	0.141	2.46E-04
10:22:00	61.3	1.46E+00	0.142	2.46E-04
10:23:00	62.3	1.33E+00	0.142	2.24E-04
10:24:00	63.5	1.60E+00	0.143	2.68E-04
10:25:00	64.5	1.33E+00	0.144	2.24E-04
10:26:00	65.6	1.46E+00	0.144	2.46E-04
10:28:00	67.8	1.46E+00	0.146	2.46E-04
10:30:00	70.0	1.46E+00	0.147	2.46E-04
10:32:00	72.0	1.33E+00	0.149	2.24E-04
10:34:00	74.0	1.33E+00	0.150	2.24E-04
10:36:00	76.1	1.40E+00	0.151	2.35E-04
10:38:00	78.4	1.53E+00	0.153	2.57E-04
10:40:00	80.6	1.46E+00	0.154	2.46E-04
10:42:00	82.9	1.53E+00	0.156	2.57E-04
10:44:00	84.8	1.26E+00	0.157	2.12E-04

AVG
3.25E-04





Single-Stage Constant Head Borehole Test - Omaha - Thick Store-and-Release Cover

Project: Omaha
 Date: 05/19/08
 Test ID: TSB1-thick-deep
 Installer: XW
 Analyst: CHB

Fixed Variables:
 Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R_s (cm): 10
 L (cm): 60.96

Temporal Variables:		Computations:		
Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
5:22:00	30.0			
5:23:00	32.4	3.19E+00	0.001	5.37E-04
5:25:00	37.7	3.52E+00	0.002	5.93E-04
5:27:00	42.0	2.86E+00	0.003	4.81E-04
5:29:00	46.9	3.26E+00	0.005	5.48E-04
5:32:00	53.5	2.93E+00	0.007	4.92E-04
5:34:00	58.0	2.99E+00	0.008	5.03E-04
5:39:00	69.5	3.06E+00	0.012	5.14E-04
5:41:00	73.8	2.86E+00	0.013	4.81E-04
5:43:00	78.1	2.86E+00	0.015	4.81E-04
5:45:00	82.3	2.79E+00	0.016	4.70E-04
5:47:00	86.6	2.86E+00	0.017	4.81E-04
5:49:00	91.0	2.93E+00	0.019	4.92E-04
9:06:00	30.5			
9:08:00	33.5	2.00E+00	0.020	3.35E-04
9:10:00	35.7	1.46E+00	0.022	2.46E-04
9:12:00	38.3	1.73E+00	0.023	2.91E-04
9:14	41.0	1.80E+00	0.024	3.02E-04
9:16:00	43.4	1.60E+00	0.026	2.68E-04
9:18:00	45.9	1.66E+00	0.027	2.80E-04
9:20:00	48.2	1.53E+00	0.028	2.57E-04
9:25:00	55.9	2.05E+00	0.032	3.44E-04
9:30:00	62.9	1.86E+00	0.035	3.13E-04
9:35:00	67.5	1.22E+00	0.039	2.06E-04
9:40:00	73.7	1.65E+00	0.042	2.77E-04
9:45:00	79.8	1.62E+00	0.046	2.73E-04
9:50:00	86.1	1.68E+00	0.049	2.82E-04
9:55:00	92.3	1.65E+00	0.053	2.77E-04
10:00:00	31.0			0.056
10:06:00	38.9	1.75E+00	0.060	2.94E-04
10:11:00	45.3	1.70E+00	0.064	2.86E-04
10:16:00	51.9	1.76E+00	0.067	2.95E-04
10:21:00	58.4	1.73E+00	0.071	2.91E-04
10:26:00	64.9	1.73E+00	0.074	2.91E-04
10:31:00	71.4	1.73E+00	0.078	2.91E-04
10:36:00	77.9	1.73E+00	0.081	2.91E-04
10:42:00	85.7	1.73E+00	0.085	2.91E-04
10:47:00	92.3	1.76E+00	0.089	2.95E-04

AVG
 2.92E-04



Single-Stage Constant Head Borehole Test - Omaha - Thick Store-and-Release Cover


Project: Omaha
Date: 05/19/08
Test ID: TS82-Thick (Shallow Test)
Installer: XW
Analyst: CHB

Fixed Variables:


Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R₀ (cm): 10
 L (cm): 30.48

Temporal Variables:

Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
1:00:00	35.5			
1:01:00	41.5	7.98E+00	0.0007	2.35E-03
1:02:00	47.5	7.98E+00	0.0014	2.35E-03
1:03:00	53.2	7.58E+00	0.0021	2.23E-03
1:05:00	64.5	7.51E+00	0.0035	2.21E-03
1:07:00	75.0	6.98E+00	0.0049	2.06E-03
1:09:00	85.7	7.12E+00	0.0063	2.10E-03
1:11:00	96.0	6.85E+00	0.0076	2.02E-03
2:00:00	31.5	-1.75E+00	0.0076	
2:01:00	37.0	7.32E+00	0.0083	2.16E-03
2:02:00	42.5	7.32E+00	0.0090	2.16E-03
2:03:00	48.0	7.32E+00	0.0097	2.16E-03
2:04:00	53.2	6.92E+00	0.0104	2.04E-03
2:05:00	58.0	6.38E+00	0.0111	
2:06:00	63.2	6.92E+00	0.0118	2.04E-03
2:07:00	68.2	6.65E+00	0.0125	1.96E-03
2:08:00	73.1	6.52E+00	0.0132	1.92E-03
2:09:00	78.0	6.52E+00	0.0139	1.92E-03
2:10:00	82.5	5.99E+00	0.0146	1.76E-03
2:11:00	87.4	6.52E+00	0.0152	1.92E-03
8:58:00	31.0			
9:00:00	37.8	4.52E+00	0.0166	1.33E-03
9:02:00	43.9	4.06E+00	0.0180	1.20E-03
9:04:00	49.7	3.86E+00	0.0194	1.14E-03
9:06:00	55.5	3.86E+00	0.0208	1.14E-03
9:08:00	61.3	3.86E+00	0.0222	1.14E-03
9:10:00	66.8	3.66E+00	0.0236	1.08E-03
9:12:00	72.5	3.79E+00	0.0250	1.12E-03
9:14:00	77.7	3.46E+00	0.0264	1.02E-03
9:16:00	83.0	3.52E+00	0.0277	1.04E-03
9:18:00	88.2	3.46E+00	0.0291	1.02E-03
9:21:00	34.3		0.0312	
9:23:00	38.9	3.06E+00	0.0326	9.02E-04
9:25:00	44.1	3.46E+00	0.0340	1.02E-03
9:27	49.2	3.39E+00	0.0354	1.00E-03
9:29	54.8	3.72E+00	0.0368	1.10E-03
9:31	59.8	3.32E+00	0.0382	9.80E-04
9:33	64.6	3.19E+00	0.0396	9.41E-04
9:35	69.7	3.39E+00	0.0409	1.00E-03
9:37	74.8	3.39E+00	0.0423	1.00E-03
9:39	79.8	3.33E+00	0.0437	9.80E-04
9:41	85.2	3.59E+00	0.0451	1.06E-03
9:43	90.1	3.26E+00	0.0465	9.60E-04



AVG
 1.00E-03



Single-Stage Constant Head Borehole Test - Omaha - Thick Store-and-Release Cover

Project: Omaha
 Date: 05/19/08
 Test ID: TSB3-thin-shallow

Installer: XW
 Analyst: CHB



Fixed Variables:

Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R_s (cm): 10
 L (cm): 30.48

Temporal Variables:

Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
5:30:00	35.4			
5:31:00	44.0	1.14E+01	0.001	3.37E-03
5:33:00	60.3	1.08E+01	0.002	3.19E-03
5:35:00	75.0	9.78E+00	0.003	2.88E-03
5:37:00	89.0	9.31E+00	0.005	2.74E-03
5:38:00	95.5	8.65E+00	0.006	2.55E-03
8:02:00	30.6			
8:04:00	38.9	5.52E+00	0.007	1.63E-03
8:06:00	46.1	4.79E+00	0.008	1.41E-03
8:08:00	52.8	4.46E+00	0.010	1.31E-03
8:11:00	62.7	4.39E+00	0.012	1.29E-03
8:13:00	69.1	4.26E+00	0.013	1.25E-03
8:15:00	75.3	4.12E+00	0.015	1.22E-03
8:17:00	81.5	4.12E+00	0.016	1.22E-03
8:19:00	87.6	4.06E+00	0.017	1.20E-03
8:21:00	93.5	3.92E+00	0.019	1.16E-03
8:59:30	30.5			
9:02:00	38.0	3.99E+00	0.020	1.18E-03
9:04:00	44.1	4.06E+00	0.022	1.20E-03
9:06:00	50.8	4.46E+00	0.023	1.31E-03
9:08:00	57.0	4.12E+00	0.025	1.22E-03
9:10:00	62.7	3.79E+00	0.026	1.12E-03
9:12:00	68.5	3.86E+00	0.027	1.14E-03
9:14:00	74.8	4.19E+00	0.029	1.23E-03
9:16:00	80.5	3.79E+00	0.030	1.12E-03
9:18:00	86.5	3.99E+00	0.032	1.18E-03
9:20:00	92.2	3.79E+00	0.033	1.12E-03
9:22:00	98.3	4.06E+00	0.034	1.20E-03

average
1.16E-03




Single-Stage Constant Head Borehole Test - Omaha - Thick Store-and-Release Cover

Project: Omaha
 Date: 05/19/08
 Test ID: TSB4-thin


Installer: XW
 Analyst: CHB

Fixed Variables:
 Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R_s (cm): 10
 L (cm): 60.96

Temporal Variables:		Computations:		
Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
5:10:00	32.0			
5:12:00	41.5	6.32E+00	0.001	1.06E-03
5:13:00	50.0	1.13E+01	0.002	1.90E-03
5:14:00	58.0	1.06E+01	0.003	1.79E-03
5:15:00	66.0	1.06E+01	0.003	1.79E-03
5:16:00	74.5	1.13E+01	0.004	1.90E-03
5:17:00	82.5	1.06E+01	0.005	1.79E-03
5:18:00	90.5	1.06E+01	0.006	1.79E-03
5:19:00	98.5	1.06E+01	0.006	1.79E-03
8:00	36.0			
8:02:00	44.7	5.79E+00	0.008	9.73E-04
8:04:00	53.2	5.65E+00	0.009	9.50E-04
8:06:00	61.3	5.39E+00	0.010	9.06E-04
8:08:00	69.5	5.45E+00	0.012	9.17E-04
8:11:00	81.8	5.45E+00	0.014	9.17E-04
8:13:00	90.0	5.45E+00	0.015	9.17E-04
8:15:00	98.1	5.39E+00	0.017	9.06E-04
9:03:00	35.1			
9:05:00	43.4	5.52E+00	0.018	9.28E-04
9:07:00	53.0	6.38E+00	0.019	1.07E-03
9:09:00	61.5	5.65E+00	0.021	9.50E-04
9:11:00	69.7	5.45E+00	0.022	9.17E-04
9:13:00	78.0	5.52E+00	0.024	9.28E-04
9:15:00	86.6	5.72E+00	0.025	9.62E-04
9:17:00	95.0	5.59E+00	0.026	9.39E-04



avg
 9.43E-04



Single-Stage Constant Head Borehole Test Omaha - Thin Store-and-Release Cover

Project: Omaha
 Date: 05/19/08
 Test ID: TSB1-thin

Installer: XW
 Analyst: CHB

Fixed Variables:


Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R_a (cm): 10
 L (cm): 30.48

Temporal Variables:

Time	R (cm)
3:29:00	34.0
3:31:00	36.4
3:33:00	38.7
3:35:00	41.0
3:37:00	43.4
3:39:00	45.6
3:41:00	47.9
3:43:00	50.0
3:45:00	52.1
3:47:00	54.3
3:49:00	56.5
3:51:00	58.6
3:53:00	60.7
3:55:00	62.8
3:57:00	65.0
3:59:00	67.0
4:02:00	70.0
4:06:00	74.0
4:09:00	77.0
4:11:00	79.0
8:50:00	30.0
8:53:00	32.6
8:57:00	36.1
9:00:00	38.7
9:03	41.1
9:06:00	43.7
9:09:00	46.1
9:12:00	48.6
9:19:00	54.5
9:24:00	58.4
9:28:00	61.5
9:32:00	64.8
9:37:00	68.7
9:46:00	76.0
9:52:00	81.0
9:56:00	84.0


Computations:

Q (cm ³ /s)	Time (d)	K (cm/s)
1.60E+00	0.001	4.70E-04
1.53E+00	0.003	4.51E-04
1.53E+00	0.004	4.51E-04
1.60E+00	0.006	4.70E-04
1.46E+00	0.007	4.31E-04
1.53E+00	0.008	4.51E-04
1.40E+00	0.010	4.12E-04
1.40E+00	0.011	4.12E-04
1.46E+00	0.013	4.31E-04
1.46E+00	0.014	4.31E-04
1.40E+00	0.015	4.12E-04
1.40E+00	0.017	4.12E-04
1.40E+00	0.018	4.12E-04
1.46E+00	0.019	4.31E-04
1.33E+00	0.021	3.92E-04
1.33E+00	0.023	3.92E-04
1.33E+00	0.026	3.92E-04
1.33E+00	0.028	3.92E-04
1.33E+00	0.029	3.92E-04
1.15E+00	0.031	3.40E-04
1.16E+00	0.034	3.43E-04
1.15E+00	0.036	3.40E-04
1.06E+00	0.038	3.14E-04
1.15E+00	0.040	3.40E-04
1.06E+00	0.042	3.14E-04
1.11E+00	0.044	3.27E-04
1.12E+00	0.049	3.30E-04
1.04E+00	0.053	3.06E-04
1.03E+00	0.056	3.04E-04
1.10E+00	0.058	3.23E-04
1.04E+00	0.062	3.06E-04
1.08E+00	0.068	3.18E-04
1.11E+00	0.072	3.27E-04
9.98E-01	0.075	2.94E-04



10:30	50.7			
10:36	55.0	9.53E-01	0.079	2.81E-04
10:41	59.0	1.06E+00	0.083	3.14E-04
10:48	64.1	9.69E-01	0.088	2.86E-04
10:56	70.0	9.81E-01	0.093	2.89E-04
11:01	73.5	9.31E-01	0.097	2.74E-04
11:08	78.9	1.03E+00	0.101	3.02E-04
11:17	84.6	8.42E-01	0.108	2.48E-04
11:27	92.0	9.84E-01	0.115	2.90E-04

AVG
3.13E-04



Single-Stage Constant Head Borehole Test Omaha - Thin Store-and-Release Cover

Project: Omaha
Date: 05/19/08
Test ID: TSB2-Thin

Installer: XW
Analyst: CHB

Fixed Variables:


Casing Diameter (cm): 30.48
Standpipe Area (cm²): 79.8
R_a (cm): 10
L (cm): 30.48

Temporal Variables:

Time	R (cm)
2:34:00	45.0
2:35:00	48.8
2:36:00	53.0
2:37:00	57.5
2:38:00	61.5
2:39:00	65.7
2:40:00	69.8
2:41:00	73.8
2:42:00	77.6
2:43:00	81.3
2:45:00	89.0
2:46:00	92.8
2:47:00	96.4
3:07:00	32.0
3:08:00	35.0
3:09:00	38.7
3:10:00	42.0
3:11:00	45.2
3:12:00	48.5
3:13:00	51.7
3:15:00	58.0
3:16:00	61.1
3:17:00	64.0
3:18:00	67.1
3:19:00	70.1
3:20:00	73.2
3:21:00	76.2
3:22:00	79.2
3:23:00	82.0
3:24:00	85.0
3:25:00	87.7
3:26:00	90.5
3:27:00	93.2
3:28:00	96.0


Computations:

Q (cm ³ /s)	Time (d)	K (cm/s)
5.05E+00	0.0007	1.49E-03
5.59E+00	0.0014	1.65E-03
5.99E+00	0.0021	1.76E-03
5.32E+00	0.0028	1.57E-03
5.59E+00	0.0035	1.65E-03
5.45E+00	0.0042	1.61E-03
5.32E+00	0.0049	1.57E-03
5.05E+00	0.0056	1.49E-03
4.92E+00	0.0063	1.45E-03
5.12E+00	0.0076	1.51E-03
5.05E+00	0.0083	1.49E-03
4.79E+00	0.0090	1.41E-03
3.99E+00	0.0097	1.18E-03
4.92E+00	0.0104	1.45E-03
4.39E+00	0.0111	1.29E-03
4.26E+00	0.0118	1.25E-03
4.39E+00	0.0125	1.29E-03
4.26E+00	0.0132	1.25E-03
4.19E+00	0.0146	1.23E-03
4.12E+00	0.0153	1.22E-03
3.86E+00	0.0160	1.14E-03
4.12E+00	0.0167	1.22E-03
3.99E+00	0.0174	1.18E-03
4.12E+00	0.0181	1.22E-03
3.99E+00	0.0188	1.18E-03
3.99E+00	0.0194	1.18E-03
3.72E+00	0.0201	1.10E-03
3.99E+00	0.0208	1.18E-03
3.59E+00	0.0215	1.06E-03
3.72E+00	0.0222	1.10E-03
3.59E+00	0.0229	1.06E-03
3.72E+00	0.0236	1.10E-03



8:46:00	34.0			
8:47:00	36.8	3.72E+00	0.0243	1.10E-03
8:49:00	42.0	3.46E+00	0.0257	1.02E-03
8:50:00	44.2	2.93E+00	0.0264	8.62E-04
8:54:00	53.5	3.09E+00	0.0292	9.11E-04
8:58:00	62.6	3.03E+00	0.0319	8.92E-04
9:01:00	69.1	2.88E+00	0.0340	8.49E-04
9:04:00	76.0	3.06E+00	0.0361	9.02E-04
9:07:00	83.0	3.10E+00	0.0382	9.15E-04
9:10:00	89.0	2.66E+00	0.0403	7.84E-04
9:13:00	95.5	2.88E+00	0.0424	8.49E-04
9:19:00	31.5	-1.42E+01	0.0465	
9:21:00	36.3	3.19E+00	0.0479	9.41E-04
9:25	46.0	3.23E+00	0.0507	9.51E-04
9:29	54.6	2.86E+00	0.0535	8.43E-04
9:34	66.0	3.03E+00	0.0569	8.94E-04
9:38	75.1	3.03E+00	0.0597	8.92E-04
9:40	79.6	2.99E+00	0.0611	8.82E-04
9:43	86.4	3.01E+00	0.0632	8.88E-04
9:45	90.8	2.93E+00	0.0646	8.62E-04

AVG
1.08E-03



Single-Stage Constant Head Borehole Test Omaha - Thin Store-and-Release Cover

Project: Omaha
Date: 05/19/08
Test ID: TS83-thin


Installer: XW
Analyst: CHB

Fixed Variables:


Casing Diameter (cm): 30.48
Standpipe Area (cm²): 79.8
R_s (cm): 10
L (cm): 30.48

Temporal Variables:

Time	R (cm)	Q (cm ² /s)	Time (d)	K (cm/s)
5:32:00	37.0			
5:34:00	43.5	4.32E+00	0.001	1.27E-03
5:36:00	51.0	4.99E+00	0.003	1.47E-03
5:38:00	58.6	5.05E+00	0.004	1.49E-03
5:40:00	65.8	4.79E+00	0.006	1.41E-03
5:42:00	73.1	4.85E+00	0.007	1.43E-03
5:44:00	80.2	4.72E+00	0.008	1.39E-03
5:46:00	87.0	4.52E+00	0.010	1.33E-03
5:48:00	94.0	4.66E+00	0.011	1.37E-03
10:17:00	30.5			
10:20:00	38.8	3.68E+00	0.013	1.08E-03
10:23:00	46.0	3.19E+00	0.015	9.41E-04
10:27:00	56.0	3.33E+00	0.018	9.80E-04
10:31:00	66.1	3.36E+00	0.021	9.90E-04
10:35	76.5	3.46E+00	0.024	1.02E-03
10:39	86.5	3.33E+00	0.026	9.80E-04
10:41	91.5	3.33E+00	0.028	9.80E-04
10:44	99.0	3.33E+00	0.030	9.80E-04
11:35	35.8			
11:37	41.1	3.52E+00	0.031	1.04E-03
11:40	48.8	3.41E+00	0.033	1.01E-03
11:44	59.0	3.39E+00	0.036	1.00E-03
11:47	66.5	3.33E+00	0.038	9.80E-04
11:51	76.5	3.33E+00	0.041	9.80E-04
11:54	84.0	3.32E+00	0.043	9.80E-04
11:57	91.7	3.41E+00	0.045	1.01E-03
12:00	99.0	3.24E+00	0.047	9.54E-04



AVG
9.80E-04



Single-Stage Constant Head Borehole Test Omaha - Thin Store-and-Release Cover

Project: Omaha
Date: 05/19/08
Test ID: TSB4-thin

Installer: XW
Analyst: CHB



Fixed Variables:

Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R₀ (cm): 10
 L (cm): 30.48

Temporal Variables:

Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
3:53:00	37.0			
3:54:00	42.3	7.05E+00	0.001	2.08E-03
3:56:00	52.7	6.92E+00	0.002	2.04E-03
3:58:00	63.0	6.85E+00	0.003	2.02E-03
4:00:00	73.0	6.65E+00	0.005	1.96E-03
4:02:00	82.4	6.25E+00	0.006	1.84E-03
4:05:00	96.5	6.25E+00	0.008	1.84E-03
8:52:00	30.0			
8:55:00	42.8	5.67E+00	0.010	1.67E-03
8:59:00	58.6	5.25E+00	0.013	1.55E-03
9:02:00	70.0	5.05E+00	0.015	1.49E-03
9:05:00	81.4	5.05E+00	0.017	1.49E-03
9:08:00	91.5	4.48E+00	0.019	1.32E-03
9:15:00	32.8	-1.12E+01	0.024	
9:18:00	45.2	5.50E+00	0.026	1.62E-03
9:20:00	53.5	5.52E+00	0.028	1.63E-03
9:22:00	61.5	5.32E+00	0.029	1.57E-03
9:26:00	78.0	5.49E+00	0.032	1.62E-03
9:30:00	94.5	5.49E+00	0.035	1.62E-03

AVG
1.60E-03




Single-Stage Constant Head Borehole Test - Polson - Composite Cover

Project: Polson
Date: 08/21/08
Test ID: Coventional 1


Installer: XW
Analyst: JS

Fixed Variables:
 Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R_a (cm): 10
 L (cm): 60.96



Allowed to flow without measurements for > 24 hrs

Temporal Variables:		Computations:		
Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
9:38	37			
10:03	43	3.19E-01	0.017	5.37E-05
10:21	46.7	2.73E-01	0.030	4.60E-05
10:35	49.8	2.94E-01	0.040	4.95E-05
10:44	51.6	2.66E-01	0.046	4.47E-05
11:06	54	1.45E-01	0.061	2.44E-05
11:34	56.5	1.19E-01	0.081	2.00E-05
11:51	66	7.43E-01	0.092	1.25E-04
12:09	69.9	2.88E-01	0.105	4.84E-05
12:29	74.2	2.86E-01	0.119	4.81E-05
12:52	78.8	2.66E-01	0.135	4.47E-05
13:40	89	2.83E-01	0.168	4.75E-05
Average				4.72E-05




Single-Stage Constant Head Borehole Test - Polson - Composite Cover

Project: Polson
Date: 08/21/08
Test ID: Coventional 2

Installer: XW
Analyst: JS

Fixed Variables:

Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R_a (cm): 10
 L (cm): 60.96




Temporal Variables:

Computations:

Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
9:38	39			
10:03	41.8	1.49E-01	0.017	2.50E-05
10:21	43.7	1.40E-01	0.030	2.36E-05
10:35	45.5	1.71E-01	0.040	2.87E-05
10:44	46.5	1.48E-01	0.046	2.48E-05
10:50	47.7	2.66E-01	0.050	4.47E-05
11:00	49	1.73E-01	0.057	2.91E-05
11:34	52.5	1.37E-01	0.081	2.30E-05
11:51	54	1.17E-01	0.092	1.97E-05
12:09	56.1	1.55E-01	0.105	2.61E-05
12:29	58.5	1.60E-01	0.119	2.68E-05
12:52	60.6	1.21E-01	0.135	2.04E-05
13:40	65.4	1.33E-01	0.168	2.24E-05

Allowed to flow without measurements for > 24 hrs

Average 2.39E-05




Single-Stage Constant Head Borehole Test - Polson - Composite Cover

Project: Polson
Date: 08/21/08
Test ID: Conventional 3


Installer: XW
Analyst: JS

Fixed Variables:
 Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R_a (cm): 10
 L (cm): 60.96



Temporal Variables:		Computations:		
Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
9:38	37.5			
10:03	41.9	2.34E-01	0.017	3.94E-05
10:21	45	2.29E-01	0.030	3.85E-05
10:35	47.5	2.37E-01	0.040	3.99E-05
10:44	49.1	2.36E-01	0.046	3.98E-05
10:56	51	2.11E-01	0.054	3.54E-05
11:00	52.9	6.32E-01	0.057	1.06E-04
11:34	57.8	1.92E-01	0.081	3.22E-05
11:51	60.5	2.11E-01	0.092	3.55E-05
12:09	63.6	2.29E-01	0.105	3.85E-05
12:29	67.1	2.33E-01	0.119	3.91E-05
12:52	71	2.26E-01	0.135	3.79E-05
13:40	79.2	2.27E-01	0.168	3.82E-05
Average				3.84E-05

Allowed to flow without measurements for > 24 hrs




Single-Stage Constant Head Borehole Test - Polson - Composite Cover

Project: Polson
Date: 08/21/08
Test ID: Conventional 4


Installer: XW
Analyst: JS

Fixed Variables:
 Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R_a (cm): 10
 L (cm): 60.96



Temporal Variables:		Computations:		
Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
9:56	36.1			
10:03	37.5	2.66E-01	0.005	4.47E-05
10:21	40.3	2.07E-01	0.017	3.48E-05
10:35	42.5	2.09E-01	0.027	3.51E-05
10:44	43.9	2.07E-01	0.033	3.48E-05
10:56	45.6	1.88E-01	0.042	3.17E-05
11:00	47.1	4.99E-01	0.044	8.39E-05
11:34	51.5	1.72E-01	0.068	2.89E-05
11:51	53.9	1.88E-01	0.080	3.16E-05
12:09	56.5	1.92E-01	0.092	3.23E-05
12:29	59.6	2.06E-01	0.106	3.47E-05
12:52	62.9	1.91E-01	0.122	3.21E-05
13:40	70	1.97E-01	0.156	3.31E-05
Average				3.30E-05

Allowed to flow without measurements for > 24 hrs



Single-Stage Constant Head Borehole Test - Polson - Composite Cover

Project: Polson
Date: 08/21/08
Test ID: Conventional 5

Installer: XW
Analyst: JS


Fixed Variables:
 Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R_a (cm): 10
 L (cm): 60.96

Temporal Variables:


Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
10:34	38			
10:45	39.9	2.30E-01	0.008	3.86E-05
10:57	41.9	2.22E-01	0.016	3.73E-05
11:07	43.5	2.13E-01	0.023	3.58E-05
11:35	48	2.14E-01	0.042	3.59E-05
11:51	50.5	2.08E-01	0.053	3.49E-05
12:09	53.7	2.36E-01	0.066	3.98E-05
12:29	57	2.19E-01	0.080	3.69E-05
12:53	60.8	2.11E-01	0.097	3.54E-05
13:41	68	2.00E-01	0.130	3.35E-05

Computations:

Average 3.64E-05



Allowed to flow without measurements for > 24 hrs




Single-Stage Constant Head Borehole Test - Polson - Store-and-Release Cover

Project: Polson
Date: 08/21/08
Test ID: Alternative 1


Installer: XW
Analyst: JS

Fixed Variables:
 Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R_a (cm): 10
 L (cm): 60.96



Temporal Variables:		Computations:		
Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
16:30	38.3			
16:56	41.1	1.43E-01	0.018	2.41E-05
17:21	45	2.07E-01	0.035	3.49E-05
17:49	48	1.43E-01	0.055	2.40E-05
9:13	31.2	4.33E-02		
9:34	33.4	1.39E-01	0.069	2.34E-05
10:18	37.6	1.27E-01	0.100	2.13E-05
10:38	39.5	1.26E-01	0.114	2.12E-05
11:00	41.6	1.27E-01	0.129	2.13E-05
11:36	45	1.26E-01	0.154	2.11E-05
12:00	47	1.11E-01	0.171	1.86E-05
12:22	49.2	1.33E-01	0.186	2.24E-05
12:41	50.9	1.19E-01	0.199	2.00E-05
14:00	57.9	1.18E-01	0.254	1.98E-05
15:12	64	1.13E-01	0.304	1.89E-05
16:39	71.8	1.19E-01	0.365	2.00E-05
17:41	77.4	1.20E-01	0.408	2.02E-05
18:21	80.6	1.06E-01	0.435	1.79E-05
18:53	83.5	1.21E-01	0.458	2.03E-05
Average				1.96E-05

Allowed to flow without measurements for > 24 hrs




Single-Stage Constant Head Borehole Test - Polson - Store-and-Release Cover

Project: Polson
Date: 08/21/08
Test ID: Alternative 2


Installer: XW
Analyst: JS

Fixed Variables:
 Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R_a (cm): 10
 L (cm): 60.96



Temporal Variables:		Computations:		
Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
16:31	34.5			
16:56	39.5	2.66E-01	0.017	4.47E-05
17:21	43.5	2.13E-01	0.035	3.58E-05
17:49	47.5	1.90E-01	0.054	3.19E-05
9:13	33.5	3.61E-02		
9:34	36.3	1.77E-01	0.069	2.98E-05
10:18	42	1.72E-01	0.099	2.90E-05
10:38	44.4	1.60E-01	0.113	2.68E-05
11:00	47.1	1.63E-01	0.128	2.74E-05
11:36	51.3	1.55E-01	0.153	2.61E-05
12:00	53.8	1.39E-01	0.170	2.33E-05
12:22	56.3	1.51E-01	0.185	2.54E-05
12:41	58.1	1.26E-01	0.199	2.12E-05
14:00	66	1.33E-01	0.253	2.24E-05
15:12	72.5	1.20E-01	0.303	2.02E-05
16:39	79.5	1.07E-01	0.364	1.80E-05
17:41	84.5	1.07E-01	0.407	1.80E-05
18:21	87.6	1.03E-01	0.435	1.73E-05
18:53	90.4	1.16E-01	0.457	1.96E-05
Average				1.82E-05

Allowed to flow without measurements for > 24 hrs




Single-Stage Constant Head Borehole Test - Polson - Store-and-Release Cover

Project: Polson
Date: 08/21/08
Test ID: Alternative 3

Installer: XW
Analyst: JS

Fixed Variables:

Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R_a (cm): 10
 L (cm): 60.96




Temporal Variables:

Computations:

Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
16:50	46			
16:57	47	1.90E-01	0.005	3.19E-05
17:21	49.5	1.39E-01	0.022	2.33E-05
17:49	52	1.19E-01	0.041	2.00E-05
9:12	41.5	2.70E-02		
9:35	44	1.45E-01	0.057	2.43E-05
10:18	48.4	1.36E-01	0.087	2.29E-05
10:38	50.2	1.20E-01	0.101	2.01E-05
11:00	52.3	1.27E-01	0.116	2.13E-05
11:36	55.6	1.22E-01	0.141	2.05E-05
12:00	57.7	1.16E-01	0.158	1.96E-05
12:22	59.4	1.03E-01	0.173	1.73E-05
12:41	61	1.12E-01	0.186	1.88E-05
14:00	66.2	8.75E-02	0.241	1.47E-05
15:12	71	8.87E-02	0.291	1.49E-05
16:39	76.0	7.64E-02	0.351	1.29E-05
17:41	79.8	8.15E-02	0.394	1.37E-05
18:21	82.0	7.32E-02	0.422	1.23E-05
18:53	84.0	8.31E-02	0.444	1.40E-05

Allowed to flow without measurements for > 24 hrs

Average 1.34E-05




Single-Stage Constant Head Borehole Test - Polson - Store-and-Release Cover

Project: Polson
 Date: 08/21/08
 Test ID: 1

Installer: XW
 Analyst: JS


Fixed Variables:
 Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R_s (cm): 10
 L (cm): 60.96



Temporal Variables:		Computations:		
Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
10:13	36.5			
10:15	38.8	1.53E+00	0.001	2.57E-04
10:17	40.5	1.13E+00	0.003	1.90E-04
10:19	42	9.98E-01	0.004	1.68E-04
10:21	43.1	7.32E-01	0.006	1.23E-04
10:25	45.2	6.98E-01	0.008	1.17E-04
10:29	46.7	4.99E-01	0.011	8.39E-05
10:33	48	4.32E-01	0.014	7.27E-05
10:37	49.2	3.99E-01	0.017	6.71E-05
10:51	53.4	3.99E-01	0.026	6.71E-05
10:59	55.5	3.49E-01	0.032	5.87E-05
11:05	56.9	3.10E-01	0.036	5.22E-05
11:15	59	2.79E-01	0.043	4.70E-05
11:26	61.2	2.66E-01	0.051	4.47E-05
11:36	63.1	2.53E-01	0.058	4.25E-05
12:00	67.5	2.44E-01	0.074	4.10E-05
12:22	70.9	2.06E-01	0.090	3.46E-05
12:41	73.7	1.96E-01	0.103	3.30E-05
14:00	84.1	1.75E-01	0.158	2.94E-05
14:50	90.2	1.62E-01	0.192	2.73E-05
15:11	92.7	1.58E-01	0.207	2.66E-05
15:38	95.5	1.38E-01	0.226	2.32E-05
15:45	32.0	-1.21E+01		
16:38	38.8	1.71E-01	0.267	2.87E-05
17:09	42.4	1.54E-01	0.289	2.60E-05
17:41	45.5	1.29E-01	0.311	2.17E-05
18:20	49.5	1.36E-01	0.338	2.29E-05
18:53	52.9	1.37E-01	0.361	2.30E-05
10:20	32.5	5.29E-02		
10:36	34.5	1.66E-01	0.372	2.80E-05
10:46	35.5	1.33E-01	0.379	2.24E-05
10:57	36.6	1.33E-01	0.387	2.24E-05
11:07	37.7	1.46E-01	0.394	2.46E-05
11:35	41.0	1.57E-01	0.413	2.64E-05
11:52	42.7	1.33E-01	0.425	2.24E-05
12:10	44.6	1.40E-01	0.438	2.36E-05
12:30	46.7	1.40E-01	0.451	2.35E-05
12:53	49.0	1.33E-01	0.467	2.24E-05
13:42	53.9	1.33E-01	0.501	2.24E-05

Allowed to flow without measurements for > 24 hrs

Average 2.30E-05



Single-Stage Constant Head Borehole Test - Sacramento - Thin Store-and-Release Cover

Project: Sacramento
 Date: Thin 1
 Test ID: Thin 1

Installer: XW
 Analyst: CB

Fixed Variables:


d = 10.16
 D = 35.56
 Z = 27.94
 R = 45.72

Temporal Variables:

Computations:

Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
12:32	72	145.7		
12:33	68	141.7	60	0.02 3.85E-04
12:38	64	137.7	300	0.1 7.92E-05
12:42	60.8	134.5	240	0.17 8.12E-05
12:50	57.5	131.2	480	0.3 4.29E-05
12:58	54.5	128.2	480	0.43 4.00E-05
13:04	51.6	125.3	360	0.53 5.27E-05
13:10	46.6	120.3	360	0.63 9.38E-05
13:36	40.4	114.1	1560	1.07 2.81E-05
13:33	31.2	104.9	-180	1.02
13:39	21.5	95.2	360	1.12 2.24E-04
13:43	13.5	87.2	240	1.18 3.03E-04
13:52	8.7	82.4	540	1.33 8.70E-05
13:58	83.5	157.2	360	1.43
14:08	78.6	152.3	600	1.6 4.38E-05
14:14	74.5	148.2	360	1.7 6.29E-05
14:22	70.5	144.2	480	1.83 4.73E-05
14:28	66.6	140.3	360	1.93 6.32E-05
14:35	63	136.7	420	2.05 5.13E-05

AVG
 5.62E-05



Single-Stage Constant Head Borehole Test - Sacramento - Thin Store-and-Release Cover

Project: Sacramento
 Date:
 Test ID: Thin 2

Installer: XW
 Analyst: CB

Fixed Variables:


d = 10.16 cm
 D = 35.56 cm
 Z = 33.02 cm
 R = 43.18 cm

Temporal Variables:

Computations:

Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
12:33	81.6	157.8		
12:37	78.6	154.8	0.070	6.63E-05
12:42	76	152.2	0.150	4.68E-05
12:50	71.6	147.8	0.280	5.07E-05
12:58	67.5	143.7	0.420	4.86E-05
13:04	64.5	140.7	0.520	4.86E-05
13:10	61.7	137.9	0.620	4.63E-05
13:26	54.5	130.7	0.880	4.63E-05
13:32	52	128.2	0.980	4.45E-05
13:38	49.5	125.7	1.080	4.54E-05
13:43	47.4	123.6	1.170	4.66E-05
13:52	44	120.2	1.320	4.28E-05
13:58	41.7	117.9	1.420	4.45E-05
1/0/00 14:08	38	114.2	1.580	4.41E-05
1/0/00 14:14	36	112.2	1.680	4.07E-05
1/0/00 14:22	33.2	109.4	1.820	4.36E-05
1/0/00 14:28	31	107.2	1.920	4.68E-05
1/0/00 14:35	28.7	104.9	2.030	4.28E-05
14:40:00	27.2	103.4	2.120	3.98E-05

AVG
 4.33E-05



Single-Stage Constant Head Borehole Test - Sacramento - Thin Store-and-Release Cover

Project: Sacramento
 Date:
 Test ID: Thin 3

Installer: XW
 Analyst: CB

Fixed Variables:


d = 10.16 cm
 D = 35.56 cm
 Z = 55.88 cm
 R = 22.86 cm

Temporal Variables:

Computations:

Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
10:08	81.5	160.2		
10:23	71.5	150.2	9.00E+02	0.250
10:31	67.7	146.4	4.80E+02	0.380
10:39	63.5	142.2	4.80E+02	0.520
10:56	55.5	134.2	1.02E+03	0.800
11:09	50.2	128.9	7.80E+02	1.020
11:22	45	123.7	7.80E+02	1.230
11:37	40	118.7	9.00E+02	1.480
11:48	36	114.7	6.60E+02	1.670
11:59	32.7	111.4	6.60E+02	1.850
12:10	29.5	108.2	6.60E+02	2.030
12:49	18.5	97.2	2.34E+03	2.680
12:55	16.6	95.3	3.60E+02	2.780
1/0/00 13:10	12.4	91.1	9.00E+02	3.03

AVG
 4.04E-05




Single-Stage Constant Head Borehole Test - Sacramento - Thin Store-and-Release Cover

Project: Sacramento Installer: XW
 Date: Analyst: CB
 Test ID: Thin 4

Fixed Variables:
 Casing Diameter (cm): 30.48
 Standpipe Area (cm²): 79.8
 R_s (cm): 10
 L (cm): 60.96

Temporal Variables:		Computations:			
Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)	
10:13	69	145.2			
10:23	67.2	143.4	6.00E+02	0.170	2.01E-05
10:31	65.5	141.7	4.80E+02	0.300	2.40E-05
10:39	64	140.2	4.80E+02	0.430	2.14E-05
10:55	61	137.2	9.60E+02	0.700	2.18E-05
11:09	58.6	134.8	8.40E+02	0.930	2.03E-05
11:23	56.2	132.4	8.40E+02	1.170	2.07E-05
11:38	54.2	130.4	9.00E+02	1.420	1.64E-05
11:49	52.5	128.7	6.60E+02	1.600	1.92E-05
11:59	51.3	127.5	6.00E+02	1.770	1.51E-05
12:10	49.8	126	6.60E+02	1.950	1.73E-05
12:49	45.4	121.6	2.34E+03	2.600	1.47E-05
12:56	44.6	120.8	4.20E+02	2.720	1.52E-05
1/0/00 13:10	43.2	119.4	8.40E+02	2.950	1.34E-05

AVG
1.52E-05



Single-Stage Constant Head Borehole Test - Sacramento - Thick Store-and-Release Cover

Project: Sacramento Installer: XW
 Date: Analyst: CB
 Test ID: Thick 1

Fixed Variables:


d = 10.16 cm
 Q = 35.56 cm
 Z = 60.96 cm
 R = 14.605 cm

Temporal Variables:

Computations:

Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)	
12:16	81	156.6			
12:18	72	147.6	1.20E+02	0.030	4.09E-04
12:21	63.5	139.1	1.80E+02	0.080	2.73E-04
12:23	60.5	136.1	1.20E+02	0.120	1.51E-04
12:27	45	120.6	2.40E+02	0.180	4.18E-04
12:30	52	127.6	1.80E+02	0.230	
12:35	47.5	123.1	3.00E+02	0.320	9.92E-05
12:40	43.7	119.3	3.00E+02	0.400	8.67E-05
12:46	40	115.6	3.60E+02	0.500	7.26E-05
12:53	36.5	112.1	4.20E+02	0.620	6.07E-05
13:00	33.5	109.1	4.20E+02	0.730	5.36E-05
13:05	31	106.6	3.00E+02	0.820	6.41E-05
13:12	28.8	104.4	4.20E+02	0.930	4.12E-05
13:24	24.5	100.1	7.20E+02	1.130	4.84E-05
13:28	23.5	99.1	2.40E+02	1.200	3.47E-05
13:35	21.7	97.3	4.20E+02	1.320	3.62E-05
13:41	20.0	95.6	3.60E+02	1.420	4.06E-05
13:50	17.5	93.1	5.40E+02	1.570	4.07E-05
13:56	16.4	92	3.60E+02	1.670	2.74E-05
14:01:00	15.3	90.9	3.00E+02	1.75	3.33E-05
14:06:00	14.1	89.7	3.00E+02	1.830	3.67E-05
14:12:00	13.0	88.6	3.60E+02	1.930	2.84E-05
14:16:00	12.0	87.6	2.40E+02	2.000	3.92E-05
14:19:00	11.5	87.1	1.80E+02	2.050	2.64E-05
14:20:00	50.4	126	6.00E+01	2.070	
14:24:00	49.0	124.6	2.40E+02	2.130	3.86E-05
14:33:00	45.3	120.9	5.40E+02	2.280	4.63E-05
14:38:00	43.7	119.3	3.00E+02	2.370	3.68E-05
14:47:00	37.8	113.4	5.40E+02	2.520	7.79E-05
15:07:00	35.4	111	1.20E+03	2.850	1.48E-05
15:16:00	33.0	108.6	5.40E+02	3.000	3.36E-05
15:21:00	31.7	107.3	3.00E+02	3.080	3.33E-05
15:31:00	29.3	104.9	6.00E+02	3.250	3.13E-05
15:45:00	26.3	101.9	8.40E+02	3.480	2.86E-05
16:05:00	22.0	97.6	1.20E+03	3.820	2.98E-05

AVG
3.13E-05



Single-Stage Constant Head Borehole Test - Sacramento - Thick Store-and-Release Cover

Project: Sacramento
 Date:
 Test ID: Thick 2

Installer: XW
 Analyst: CB

Fixed Variables:


d = 10.16 cm
 D = 35.56 cm
 Z = 43.18 cm
 R = 33.02 cm

Temporal Variables:

Computations:

Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
1:03	72	148.2		
1:04	68	144.2	0.020	3.78E-04
1:05	64	140.2	0.030	3.89E-04
1:06	60.8	137	0.050	3.19E-04
1:07	57.5	133.7	0.070	3.37E-04
1:08	54.5	130.7	0.080	3.14E-04
1:09	51.6	127.8	0.100	3.10E-04
1:11	46.6	122.8	0.130	2.76E-04
1:14	40.4	116.6	0.180	2.39E-04
1:19	31.2	107.4	0.270	2.27E-04
1:26	21.5	97.7	0.380	1.87E-04
1:33	13.5	89.7	0.500	1.69E-04
1:38	8.7	84.9	0.580	1.52E-04
1:40	83.5	159.7	0.620	
1:42	78.6	154.8	0.650	2.15E-04
1:44	74.5	150.7	0.680	1.85E-04
1:46	70.5	146.7	0.720	1.86E-04
1:48	66.6	142.8	0.750	1.86E-04
1:50	63.0	139.2	0.780	1.76E-04
1:53:00	58.0	134.2	0.83	1.68E-04
2:04:00	42.0	118.2	1.020	1.59E-04
2:11:00	33.6	109.8	1.130	1.46E-04
2:13:00	31.5	107.7	1.170	1.33E-04
2:35:00	12.5	88.7	1.530	1.22E-04

AVG
 1.34E-04



Single-Stage Constant Head Borehole Test - Sacramento - Thick Store-and-Release Cover

Project: Sacramento
 Date: Thick 3
 Test ID: Thick 3

Installer: XW
 Analyst: CB

Fixed Variables:


d = 10.16 cm
 D = 35.56 cm
 Z = 27.94 cm
 R = 44.45 cm

Temporal Variables:

Computations:

Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)	
10:09	82	154.4			
10:14	74.8	147.2	3.00E+02	0.080	1.32E-04
10:20	66.7	139.1	3.60E+02	0.180	1.30E-04
10:25	60	132.4	3.00E+02	0.270	1.36E-04
10:35	48	120.4	6.00E+02	0.430	1.31E-04
10:42	40.4	112.8	4.20E+02	0.550	1.29E-04
10:48	35	107.4	3.60E+02	0.650	1.13E-04
10:53	30	102.4	3.00E+02	0.730	1.32E-04
10:58	26	98.4	3.00E+02	0.820	1.10E-04
11:03	22	94.4	3.00E+02	0.900	1.15E-04
11:08	18	90.4	3.00E+02	0.980	1.20E-04
11:12	14.8	87.2	2.40E+02	1.050	1.25E-04
11:18	10.9	83.3	3.60E+02	1.150	1.05E-04
11:19	9.6	82	6.00E+01	1.170	2.17E-04
11:24	80.4	152.8	3.00E+02	1.250	
11:34	78.7	151.1	6.00E+02	1.420	1.55E-05
11:40	60.5	132.9	3.60E+02	1.520	2.96E-04
11:47	50.3	122.7	4.20E+02	1.630	1.58E-04
11:52	48.0	120.4	3.00E+02	1.720	5.23E-05
11:56:00	43.2	115.6	2.40E+02	1.78	1.41E-04
12:07:00	32.9	105.3	6.60E+02	1.970	1.17E-04
12:22:00	21.0	93.4	9.00E+02	2.220	1.10E-04
12:26:00	18.0	90.4	2.40E+02	2.280	1.13E-04
12:29:00	16.0	88.4	1.80E+02	2.330	1.03E-04
12:34:00	12.5	84.9	3.00E+02	2.420	1.12E-04
12:36:00	11.5	83.9	1.20E+02	2.450	8.19E-05
12:40:00	9.0	81.4	2.40E+02	2.520	1.05E-04

AVG
 1.00E-04



Single-Stage Constant Head Borehole Test - Sacramento - Thick Store-and-Release Cover

Project: Sacramento
Date:
Test ID: Thick 4

Installer: XW
Analyst: CB

Fixed Variables:

d = 10.16 cm
D = 35.56 cm
Z = 60.96 cm
R = 11.43 cm

Temporal Variables:

Computations:

Time	R (cm)	Q (cm ³ /s)	Time (d)	K (cm/s)
3:05	69	141.4		
3:09	65.8	138.2	0.070	7.91E-05
3:16	59.5	131.9	0.180	9.21E-05
3:21	56	128.4	0.270	7.43E-05
3:31	48.7	121.1	0.430	8.09E-05
3:44	40	112.4	0.650	7.92E-05
4:05	28.2	100.6	1.000	7.30E-05
4:26	18.5	90.9	1.350	6.67E-05
4:38	13.5	85.9	1.550	6.52E-05
4:39	54.3	126.7	1.570	
4:45	50.5	122.9	1.670	7.01E-05
4:56	44	116.4	1.850	6.83E-05
5:07	38	110.4	2.030	6.65E-05
5:14	34	106.4	2.150	7.29E-05
5:22	30	102.4	2.280	6.62E-05

AVG
6.84E-05

