

Attachment 8

Peach Bottom Atomic Power Station Units 2 and 3

NRC Docket Nos. 50-277 and 50-278

WCAP-17590, Rev 2, Acoustic Load Definition

Westinghouse Non-Proprietary Class 3

WCAP-17590-NP
Revision 2

February 2014

Peach Bottom Units 2 & 3 Replacement Steam Dryer Acoustic Load Definition



WCAP-17590-NP
Revision 2

Peach Bottom Units 2 & 3 Replacement Steam Dryer Acoustic Load Definition

Gianluca Longoni*
BWR Plant and Stress Analysis

February 2014

Reviewer: David A. Suddaby*
BWR Plant and Stress Analysis

Approved: David R. Forsyth*, Manager
BWR Plant and Stress Analysis

*Electronically approved records are authenticated in the electronic document management system.

Westinghouse Electric Company LLC
1000 Westinghouse Drive
Cranberry Township, PA 16066, USA

© 2014 Westinghouse Electric Company LLC
All Rights Reserved

Record of Revisions		
Rev	Date	Revision Description
0	August 2012	Acoustic load input developed with [] ^{a,c}
1	June 2013	Acoustic load input developed with [] ^{a,c}
2	February 2014	Acoustic load input developed with [] ^{a,c}

TABLE OF CONTENTS

LIST OF TABLES	iv
LIST OF FIGURES	v
LIST OF ACRONYMS/ABBREVIATIONS	vii
1 EXECUTIVE SUMMARY	1-1
2 [] ^{a,c} THE REPLACEMENT STEAM DRYER	2-1
2.1 [] ^{a,c}	2-1
2.2 [] ^{a,c}	2-8
3 [] ^{a,c}	3-1
3.1 [] ^{a,c}	3-3
3.2 [] ^{a,c}	3-5
3.3 [] ^{a,c}	3-11
3.4 [] ^{a,c}	3-14
3.5 [] ^{a,c} ...	3-18
4 REFERENCES	4-1

LIST OF FIGURES

Figure 2-1 [	] ^{a,c}	2-2
Figure 2-2a [		] ^{a,c} 2-3
Figure 2-2b [		] ^{a,c} 2-4
Figure 2-2c [	] ^{a,c}	2-5
Figure 2-3a [		2-6
	] ^{a,c}	2-6
Figure 2-3b [		] ^{a,c}
		2-7
Figure 2-4 [	] ^{a,c}	2-8
Figure 2-5 [	] ^{a,c}	2-9
Figure 3-1 [	] ^{a,c}	3-1
Figure 3-2a [	] ^{a,c}	3-9
Figure 3-2b [	] ^{a,c}	3-9
Figure 3-3a [	] ^{a,c}	3-10
Figure 3-3b [	] ^{a,c}	3-10
Figure 3-4 [	] ^{a,c}	3-13
Figure 3-5 [	] ^{a,c}	3-13
Figure 3-6 [	] ^{a,c}	3-14
Figure 3-7 [	] ^{a,c}	3-14
Figure 3-8 [	] ^{a,c}	3-15
Figure 3-9 [	] ^{a,c}	3-15
Figure 3-10 [	] ^{a,c}	3-16
Figure 3-11 [	] ^{a,c}	3-16
Figure 3-12 [	] ^{a,c}	3-17
Figure 3-13 [	] ^{a,c}	3-17

Figure 3-14 [	] ^{a,c}	3-18
Figure 3-15 [	] ^{a,c}	3-18
Figure 3-16 [	] ^{a,c}	3-19
Figure 3-17 [	] ^{a,c}	3-19
Figure 3-18 [	] ^{a,c}	3-20
Figure 3-19 [	] ^{a,c}	3-20
Figure 3-20 [	] ^{a,c}	3-21
Figure 3-21 [	] ^{a,c}	3-21

LIST OF ACRONYMS/ABBREVIATIONS

Acronym	Definition
3-D	three-dimensional
ACE	acoustic circuit enhanced
CLTP	current licensed thermal power
EPU	extended power uprate
FIV	flow-induced vibration
MSL	main steam line
PBAPS	Peach Bottom Atomic Power Station
PSD	power spectral density
RMS	root mean square
RPV	reactor pressure vessel
RSD	replacement steam dryer
SNR	signal-to-noise ratio
SPM	skirt protection model
SRSS	square root of the sum of the squares
SRV	safety relief valve
SSV	spring safety valve

1 EXECUTIVE SUMMARY

The qualification [Replacement Steam Dryer (RSD) design requires [on the structure. [

] of the Peach Bottom Units 2 & 3
] analysis of the alternating stresses acting

] a,b,c

Table 1-1 ACE Revision 2.0 Differential Pressure Loads at EPU*1.02 Conditions

a,b,c

Table 1-2 ACE+SPM Revision 2.0 Differential Pressure Loads at EPU*1.02 Conditions

a,b,c

2 [DRYER

] ^{a,c} THE REPLACEMENT STEAM

In order to qualify the Peach Bottom Atomic Power Station (PBAPS) Units 2 & 3 replacement steam dryer design for acoustic pressure loads originating from flow-induced vibration (FIV) phenomena, it is necessary to define [

2.1 [

] ^{a,c}

] ^{a,c}

[

] ^{a,c}

[

|

|

] ^{a,c}

] ^{a,c}

Figure 2-1 [

] ^{ac}

a,c

Figure 2-2a [**]**^{a,c}

a,c

Figure 2-2b [**]**^{a,c}

a,c

Figure 2-2c [**] a,c**

a,c

Figure 2-3a [**]**^{a,c}

a,c

Figure 2-3b [

] ^{a,c}

2.2 [

] ^{a,c}

[

] ^{a,c}] ^{a,c}

[

] ^{a,c}] ^{a,c}**Figure 2-4** [] ^{a,c}

[

] ^{a,c}] ^{a,c}

$$]^{a,c}$$

[

$$\}^{a,c}$$

[

a,c

$$J^{a,c}$$

[

a,c

$$\mathbf{J}^{a,c}$$

a,c

Figure 2-5 [

1^{a,c}

[

]^{a,c}

3 []^{a,c}

[

] ^{a,b,c}

a,c

Figure 3-1 [

] ^{a,c}

[

] ^{a,c}

[

] ^{a,c}

[

]

[

^{a,c}] ^{a,c}

[

] ^{a,c}

[

] ^{a,c}

a,c

[

] ^{a,c}

a,c

[

] ^{a,c}

3.1

[

] ^{a,c}

[

] ^{a,c}

Table 3-1 []^{a,c}

a,b,c

Table 3-1a []^{a,c}

a,b,c

3.2 [

] ^{a,c}

[

] ^{ac}

a,b,c

[

] ^{a,c}

Table 3-2a[]^{a,b,c}

a,b,c

Table 3-2b[]^{a,b,c}

a,b,c

Table 3-3[]^{a,b,c}

a,b,c

Table 3-4[]^{a,b,c}

a,b,c

Table 3-5

[

] ^{a,b,c}**Table 3-6**

[

] ^{a,b,c}

a,b,c

Table 3-7] ^{a,b,c}

a,b,c

Table 3-8] ^{a,b,c}

a,b,c

a,b,c

Figure 3-2a [**]^{a,c}**

a,b,c

Figure 3-2b [**]^{a,c}**



a,b,c

Figure 3-3a [

]^{a,c}



a,b,c

Figure 3-3b [

]^{a,c}

3.3 [

] ^{a,c}

[

] ^{a,c}

[

] ^{a,c}] ^{a,b,c}

Table 3-9	[	] ^{a,c}
------------------	---	------------------

a,b,c

Table 3-10	[	] ^{a,c}
-------------------	---	------------------

a,b,c

a,b,c



Figure 3-4 [

]^{a,c}

a,b,c



Figure 3-5 [

]^{a,c}

3.4 [

] ^{a,c}

[

] ^{a,b,c}

a,b,c

Figure 3-6 [] ^{a,c}

a,b,c

Figure 3-7 [] ^{a,c}

a,b,c



Figure 3-8 [

] ^{a,c}

a,b,c



Figure 3-9 [

] ^{a,c}

a,b,c



Figure 3-10 [

] ^{a,c}

a,b,c



Figure 3-11 [

] ^{a,c}

a,b,c



Figure 3-12 [

] ^{a,c}

a,b,c



Figure 3-13 [

] ^{a,c}

3.5 [

] ^{a,c}

[

] ^{a,b,c}

a,b,c

Figure 3-14 [] ^{a,c}

a,b,c

Figure 3-15 [] ^{a,c}

a,b,c



Figure 3-16 [

] ^{a,c}

a,b,c



Figure 3-17 [

] ^{a,c}

a,b,c

Figure 3-18 [

] ^{a,c}

a,b,c

Figure 3-19 [

] ^{a,c}

a,b,c



Figure 3-20 [

] ^{a,c}

a,b,c



Figure 3-21 [

] ^{a,c}

4 REFERENCES

1. Westinghouse Calculation Note CN-A&SA-12-06, Rev. 3, "Acoustic Load Definition for the Peach Bottom Units 2 & 3 Replacement Steam Dryers," January 31, 2014 (Westinghouse Proprietary Class 2).
2. Westinghouse Report, WCAP 17626 Rev. 1, "Processing of Peach Bottom Unit 2 and Unit 3 MSL Strain Gauge Data and Computation of Predicted EPU Signature," February 12, 2014 (Westinghouse Proprietary Class 2).
3. Westinghouse Letter, LTR-A&SA-10-11, Rev. 0, "Field Preparation of Main Steam Lines at Peach Bottom Unit 2 for Strain Gauge Installation," November 4, 2010 (Westinghouse Proprietary Class 2).
4. Westinghouse Letter, LTR-A&SA-11-53, Rev. 0, "Field Preparation of Main Steam Lines at Peach Bottom Unit 3 for Strain Gauge Installation," October 6, 2011 (Westinghouse Proprietary Class 2).
5. Exelon Transmittal of Design Information TODI EPU-MOD-RSD-02-1, "Design Parameters for Replacement Steam Dryer Design," April 17, 2012.
6. Structural Integrity Calculation Package, 1000102.301, Rev. 0, "Peach Bottom Unit 2 Strain Gage Uncertainty Evaluation and Pressure Conversion Factors," Structural Integrity Associates, Inc., November 8, 2010.
7. Structural Integrity Calculation Package, 1000102.303, Rev. 0, "Peach Bottom Unit 3 Strain Gage Uncertainty Evaluation and Pressure Conversion Factors," Structural Integrity Associates, Inc., October 25, 2011.