APP B-9



MAP LEGEND

0

\$

Δ

Water Features

Transportation

-

Background

Spoil Area

Stony Spot

Wet Spot

Other

Rails

US Routes

Major Roads

Local Roads

Very Stony Spot

Special Line Features

Streams and Canals

Interstate Highways


Aerial Photography

Area of Interest (AOI)

Area of Interest (AOI)

Soils

Soil Map Unit Polygons



Soil Map Unit Points

Special Point Features

Blowout

Borrow Pit

Clay Spot

Closed Depression

Gravel Pit

Gravelly Spot

Landfill

A Lava Flow

Marsh or swamp

Mine or Quarry

Miscellaneous Water

Perennial Water

Rock Outcrop

♣ Saline Spot

* Sandy Spot

Severely Eroded Spot

Sinkhole

Slide or Slip

Sodic Spot

MAP INFORMATION

The soil surveys that comprise your AOI were mapped at scales ranging from 1:20,000 to 1:31,700.

Please rely on the bar scale on each map sheet for map measurements.

Source of Map: Natural Resources Conservation Service Web Soil Survey URL: http://websoilsurvey.nrcs.usda.gov Coordinate System: Web Mercator (EPSG:3857)

Maps from the Web Soil Survey are based on the Web Mercator projection, which preserves direction and shape but distorts distance and area. A projection that preserves area, such as the Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required.

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: Andrews County, Texas Survey Area Data: Version 13, Sep 18, 2015

Soil Survey Area: Lea County, New Mexico Survey Area Data: Version 12, Sep 29, 2015

Your area of interest (AOI) includes more than one soil survey area. These survey areas may have been mapped at different scales, with a different land use in mind, at different times, or at different levels of detail. This may result in map unit symbols, soil properties, and interpretations that do not completely agree across soil survey area boundaries.

Soil map units are labeled (as space allows) for map scales 1:50,000 or larger.

Date(s) aerial images were photographed: Data not available.

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.

Map Unit Legend

Andrews County, Texas (TX003)							
Map Unit Symbol	Map Unit Name	Acres in AOI	Percent of AOI				
ВсВ	Blakeney and Conger soils, gently undulating	795.1	28.6%				
FdB	Faskin and Douro soils, gently undulating	40.8	1.5%				
ImB	Ima loamy fine sand, 0 to 3 percent slopes	61.8	2.2%				
JPC	Jalmar-Penwell association, undulating	907.7	32.6%				
KmB	Kimbrough soils, gently undulating	21.2	0.8%				
RaB	Ratliff soils, gently undulating	342.7	12.3%				
TwB	Triomas and Wickett soils, gently undulating	109.6	3.9%				
Subtotals for Soil Survey Area		2,278.8	82.0%				
Totals for Area of Interest		2,780.3	100.0%				

Lea County, New Mexico (NM025)							
Map Unit Symbol	Map Unit Name	Acres in AOI	Percent of AOI				
АВ	Amarillo-Arvana loamy fine sands association	12.5	0.5%				
ВО	Brownfield-Springer association	47.5	1.7%				
BS	Brownfield-Springer association, hummocky	134.3	4.8%				
КМ	Kermit soils and dune land, 0 to 12 percent slopes	11.5	0.4%				
MU	Mixed alluvial land	19.4	0.7%				
PG	Portales and gomez fine sandy loams	17.9	0.6%				
SE	Simona fine sandy loam, 0 to 3 percent slopes	117.0	4.2%				
SR	Simona-Upton association	141.3	5.1%				
Subtotals for Soil Survey Area		501.5	18.0%				
Totals for Area of Interest		2,780.3	100.0%				

Map Unit Descriptions

The map units delineated on the detailed soil maps in a soil survey represent the soils or miscellaneous areas in the survey area. The map unit descriptions, along with the maps, can be used to determine the composition and properties of a unit.

A map unit delineation on a soil map represents an area dominated by one or more major kinds of soil or miscellaneous areas. A map unit is identified and named according to the taxonomic classification of the dominant soils. Within a taxonomic class there are precisely defined limits for the properties of the soils. On the landscape, however, the soils are natural phenomena, and they have the characteristic variability of all natural phenomena. Thus, the range of some observed properties may extend beyond the limits defined for a taxonomic class. Areas of soils of a single taxonomic class rarely, if ever, can be mapped without including areas of other taxonomic classes. Consequently, every map unit is made up of the soils or miscellaneous areas for which it is named and some minor components that belong to taxonomic classes other than those of the major soils.

Most minor soils have properties similar to those of the dominant soil or soils in the map unit, and thus they do not affect use and management. These are called noncontrasting, or similar, components. They may or may not be mentioned in a particular map unit description. Other minor components, however, have properties and behavioral characteristics divergent enough to affect use or to require different management. These are called contrasting, or dissimilar, components. They generally are in small areas and could not be mapped separately because of the scale used. Some small areas of strongly contrasting soils or miscellaneous areas are identified by a special symbol on the maps. If included in the database for a given area, the contrasting minor components are identified in the map unit descriptions along with some characteristics of each. A few areas of minor components may not have been observed, and consequently they are not mentioned in the descriptions, especially where the pattern was so complex that it was impractical to make enough observations to identify all the soils and miscellaneous areas on the landscape.

The presence of minor components in a map unit in no way diminishes the usefulness or accuracy of the data. The objective of mapping is not to delineate pure taxonomic classes but rather to separate the landscape into landforms or landform segments that have similar use and management requirements. The delineation of such segments on the map provides sufficient information for the development of resource plans. If intensive use of small areas is planned, however, onsite investigation is needed to define and locate the soils and miscellaneous areas.

An identifying symbol precedes the map unit name in the map unit descriptions. Each description includes general facts about the unit and gives important soil properties and qualities.

Soils that have profiles that are almost alike make up a *soil series*. Except for differences in texture of the surface layer, all the soils of a series have major horizons that are similar in composition, thickness, and arrangement.

Soils of one series can differ in texture of the surface layer, slope, stoniness, salinity, degree of erosion, and other characteristics that affect their use. On the basis of such differences, a soil series is divided into *soil phases*. Most of the areas shown on the detailed soil maps are phases of soil series. The name of a soil phase commonly indicates a feature that affects use or management. For example, Alpha silt loam, 0 to 2 percent slopes, is a phase of the Alpha series.

Some map units are made up of two or more major soils or miscellaneous areas. These map units are complexes, associations, or undifferentiated groups.

A *complex* consists of two or more soils or miscellaneous areas in such an intricate pattern or in such small areas that they cannot be shown separately on the maps. The pattern and proportion of the soils or miscellaneous areas are somewhat similar in all areas. Alpha-Beta complex, 0 to 6 percent slopes, is an example.

An association is made up of two or more geographically associated soils or miscellaneous areas that are shown as one unit on the maps. Because of present or anticipated uses of the map units in the survey area, it was not considered practical or necessary to map the soils or miscellaneous areas separately. The pattern and relative proportion of the soils or miscellaneous areas are somewhat similar. Alpha-Beta association, 0 to 2 percent slopes, is an example.

An *undifferentiated group* is made up of two or more soils or miscellaneous areas that could be mapped individually but are mapped as one unit because similar interpretations can be made for use and management. The pattern and proportion of the soils or miscellaneous areas in a mapped area are not uniform. An area can be made up of only one of the major soils or miscellaneous areas, or it can be made up of all of them. Alpha and Beta soils, 0 to 2 percent slopes, is an example.

Some surveys include *miscellaneous areas*. Such areas have little or no soil material and support little or no vegetation. Rock outcrop is an example.

Andrews County, Texas

BcB—Blakeney and Conger soils, gently undulating

Map Unit Setting

National map unit symbol: d53f Elevation: 1,500 to 3,600 feet

Mean annual precipitation: 10 to 17 inches Mean annual air temperature: 63 to 68 degrees F

Frost-free period: 210 to 240 days

Farmland classification: Not prime farmland

Map Unit Composition

Blakeney and similar soils: 49 percent Conger and similar soils: 47 percent Minor components: 4 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Blakeney

Setting

Landform: Ridges, divides

Landform position (two-dimensional): Summit

Down-slope shape: Convex

Across-slope shape: Convex, linear

Parent material: Loamy eolian deposits in the blackwater draw formation of pleistocene age overlying calcareous loamy alluvium in the ogallala formation of

miocene-pliocene age

Typical profile

H1 - 0 to 18 inches: fine sandy loam
H2 - 18 to 32 inches: cemented material
H3 - 32 to 68 inches: gravelly loam

Properties and qualities

Slope: 0 to 3 percent

Depth to restrictive feature: 7 to 20 inches to petrocalcic

Natural drainage class: Well drained

Capacity of the most limiting layer to transmit water (Ksat): Moderately low to

moderately high (0.06 to 0.57 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Calcium carbonate, maximum in profile: 70 percent

Salinity, maximum in profile: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Available water storage in profile: Very low (about 2.0 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 6e

Hydrologic Soil Group: D

Ecological site: Shallow 12-17" PZ (R077DY048TX)

Description of Conger

Setting

Landform: Ridges, divides

Landform position (two-dimensional): Summit

Down-slope shape: Convex

Across-slope shape: Convex, linear

Parent material: Loamy eolian deposits in the blackwater draw formation of pleistocene age overlying calcareous loamy alluvium in the ogallala formation of

miocene-pliocene age

Typical profile

H1 - 0 to 17 inches: loam

H2 - 17 to 39 inches: cemented material H3 - 39 to 75 inches: gravelly loam

Properties and qualities

Slope: 0 to 3 percent

Depth to restrictive feature: 8 to 20 inches to petrocalcic

Natural drainage class: Well drained

Capacity of the most limiting layer to transmit water (Ksat): Moderately low to

moderately high (0.06 to 0.57 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Calcium carbonate, maximum in profile: 70 percent

Salinity, maximum in profile: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Available water storage in profile: Very low (about 2.9 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 6e

Hydrologic Soil Group: D

Ecological site: Shallow 12-17" PZ (R077DY048TX)

Minor Components

Unnamed

Percent of map unit: 4 percent

FdB—Faskin and Douro soils, gently undulating

Map Unit Setting

National map unit symbol: d53h Elevation: 2,750 to 3,400 feet

Mean annual precipitation: 13 to 17 inches Mean annual air temperature: 57 to 70 degrees F

Frost-free period: 210 to 240 days

Farmland classification: Not prime farmland

Map Unit Composition

Faskin and similar soils: 63 percent Douro and similar soils: 21 percent Minor components: 16 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Faskin

Setting

Landform: Plains

Down-slope shape: Convex Across-slope shape: Linear

Parent material: Loamy eolian deposits from the blackwater draw formation of

pleistocene age

Typical profile

H1 - 0 to 8 inches: fine sandy loam H2 - 8 to 42 inches: sandy clay loam H3 - 42 to 80 inches: sandy clay loam

Properties and qualities

Slope: 0 to 3 percent

Depth to restrictive feature: More than 80 inches

Natural drainage class: Well drained

Capacity of the most limiting layer to transmit water (Ksat): Moderately high to high

(0.57 to 1.98 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Calcium carbonate, maximum in profile: 50 percent

Salinity, maximum in profile: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Available water storage in profile: Moderate (about 8.5 inches)

Interpretive groups

Land capability classification (irrigated): 3e Land capability classification (nonirrigated): 4e

Hydrologic Soil Group: B

Ecological site: Sandy Loam 12-17" PZ (R077DY047TX)

Description of Douro

Setting

Landform: Plains

Down-slope shape: Convex Across-slope shape: Linear

Parent material: Loamy eolian deposits in the blackwater draw formation of pleistocene age overlying calcareous loamy alluvium in the ogallala formation of

miocene-pliocene age

Typical profile

H1 - 0 to 9 inches: fine sandy loam
H2 - 9 to 30 inches: sandy clay loam
H3 - 30 to 51 inches: cemented material
H4 - 51 to 75 inches: gravelly loam

Properties and qualities

Slope: 0 to 3 percent

Depth to restrictive feature: 20 to 40 inches to petrocalcic

Natural drainage class: Well drained

Capacity of the most limiting layer to transmit water (Ksat): Moderately low to

moderately high (0.06 to 0.57 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Calcium carbonate, maximum in profile: 80 percent

Salinity, maximum in profile: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Available water storage in profile: Low (about 4.3 inches)

Interpretive groups

Land capability classification (irrigated): 3e Land capability classification (nonirrigated): 4e

Hydrologic Soil Group: C

Ecological site: Sandy Loam 12-17" PZ (R077DY047TX)

Minor Components

Unnamed

Percent of map unit: 16 percent

ImB—Ima loamy fine sand, 0 to 3 percent slopes

Map Unit Setting

National map unit symbol: d53j Elevation: 4,000 to 4,600 feet

Mean annual precipitation: 12 to 17 inches Mean annual air temperature: 57 to 63 degrees F

Frost-free period: 180 to 210 days

Farmland classification: Not prime farmland

Map Unit Composition

Ima and similar soils: 100 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Ima

Setting

Landform: Plains

Down-slope shape: Convex Across-slope shape: Linear

Parent material: Sandy alluvium and eolian deposits derived from calcareous

sandstone of triassic and/or permian age

Typical profile

H1 - 0 to 14 inches: loamy fine sand H2 - 14 to 55 inches: fine sandy loam H3 - 55 to 80 inches: very fine sandy loam

Properties and qualities

Slope: 0 to 3 percent

Depth to restrictive feature: More than 80 inches

Natural drainage class: Well drained

Capacity of the most limiting layer to transmit water (Ksat): Moderately high to high

(0.57 to 1.98 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Calcium carbonate, maximum in profile: 15 percent

Salinity, maximum in profile: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Sodium adsorption ratio, maximum in profile: 4.0

Available water storage in profile: Moderate (about 7.1 inches)

Interpretive groups

Land capability classification (irrigated): 4e Land capability classification (nonirrigated): 6c

Hydrologic Soil Group: A

Ecological site: Sandy 12-17" PZ (R077DY046TX)

JPC—Jalmar-Penwell association, undulating

Map Unit Setting

National map unit symbol: d53k Elevation: 2,400 to 3,500 feet

Mean annual precipitation: 10 to 17 inches
Mean annual air temperature: 61 to 70 degrees F

Frost-free period: 210 to 240 days

Farmland classification: Not prime farmland

Map Unit Composition

Jalmar and similar soils: 56 percent Penwell and similar soils: 40 percent

Minor components: 4 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Jalmar

Setting

Landform: Sand sheets
Down-slope shape: Convex
Across-slope shape: Linear

Parent material: Sandy eolian deposits of holocene age over loamy eolian deposits

from the blackwater draw formation of pleistocene age

Typical profile

H1 - 0 to 14 inches: fine sand H2 - 14 to 26 inches: fine sand H3 - 26 to 80 inches: sandy clay loam

Properties and qualities

Slope: 0 to 8 percent

Depth to restrictive feature: More than 80 inches

Natural drainage class: Well drained

Capacity of the most limiting layer to transmit water (Ksat): Moderately high to high

(0.57 to 1.98 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Calcium carbonate, maximum in profile: 25 percent Available water storage in profile: Low (about 6.0 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 6e

Hydrologic Soil Group: B

Ecological site: Sandy 12-17" PZ (R077DY046TX)

Description of Penwell

Setting

Landform: Sand sheets
Down-slope shape: Convex
Across-slope shape: Linear

Parent material: Sandy eolian deposits of holocene age

Typical profile

H1 - 0 to 13 inches: fine sand H2 - 13 to 80 inches: fine sand

Properties and qualities

Slope: 1 to 8 percent

Depth to restrictive feature: More than 80 inches Natural drainage class: Excessively drained

Capacity of the most limiting layer to transmit water (Ksat): High to very high (5.95

to 19.98 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Salinity, maximum in profile: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Available water storage in profile: Low (about 3.6 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 7e

Hydrologic Soil Group: A

Ecological site: Sand Hills 12-17" PZ (R077DY045TX)

Minor Components

Unnamed

Percent of map unit: 4 percent

KmB—Kimbrough soils, gently undulating

Map Unit Setting

National map unit symbol: d53l Elevation: 2,000 to 5,000 feet

Mean annual precipitation: 10 to 17 inches Mean annual air temperature: 57 to 75 degrees F

Frost-free period: 175 to 215 days

Farmland classification: Not prime farmland

Map Unit Composition

Kimbrough and similar soils: 100 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Kimbrough

Setting

Landform: Plains

Down-slope shape: Convex Across-slope shape: Linear

Parent material: Calcareous, loamy alluvium in the ogallala formation of miocene-

pliocene age

Typical profile

H1 - 0 to 8 inches: loam

H2 - 8 to 31 inches: cemented material

Properties and qualities

Slope: 0 to 3 percent

Depth to restrictive feature: 4 to 20 inches to petrocalcic

Natural drainage class: Well drained

Capacity of the most limiting layer to transmit water (Ksat): Moderately high to high

(0.57 to 1.98 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Calcium carbonate, maximum in profile: 10 percent

Salinity, maximum in profile: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Available water storage in profile: Very low (about 1.2 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 7s

Hydrologic Soil Group: D

Ecological site: Shallow 12-17" PZ (R077DY048TX)

RaB—Ratliff soils, gently undulating

Map Unit Setting

National map unit symbol: d53s Elevation: 2,500 to 3,400 feet

Mean annual precipitation: 13 to 17 inches Mean annual air temperature: 63 to 70 degrees F

Frost-free period: 210 to 240 days

Farmland classification: Not prime farmland

Map Unit Composition

Ratliff and similar soils: 100 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Ratliff

Setting

Landform: Plains

Down-slope shape: Convex Across-slope shape: Linear

Parent material: Calcareous, loamy eolian deposits from the blackwater draw

formation of pleistocene age

Typical profile

H1 - 0 to 10 inches: loam H2 - 10 to 25 inches: clay loam H3 - 25 to 80 inches: clay loam

Properties and qualities

Slope: 0 to 3 percent

Depth to restrictive feature: More than 80 inches

Natural drainage class: Well drained

Capacity of the most limiting layer to transmit water (Ksat): Moderately high to high

(0.57 to 1.98 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Calcium carbonate, maximum in profile: 50 percent

Salinity, maximum in profile: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Available water storage in profile: Moderate (about 8.5 inches)

Interpretive groups

Land capability classification (irrigated): 3e Land capability classification (nonirrigated): 4e

Hydrologic Soil Group: B

Ecological site: Limy Upland 12-17" PZ (R077DY042TX)

TwB—Triomas and Wickett soils, gently undulating

Map Unit Setting

National map unit symbol: d53w Elevation: 2,300 to 3,500 feet

Mean annual precipitation: 10 to 17 inches
Mean annual air temperature: 63 to 68 degrees F

Frost-free period: 210 to 240 days

Farmland classification: Not prime farmland

Map Unit Composition

Triomas and similar soils: 78 percent Wickett and similar soils: 16 percent Minor components: 6 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Triomas

Setting

Landform: Plains

Down-slope shape: Convex Across-slope shape: Linear

Parent material: Sandy eolian deposits from the blackwater draw formation of

pleistocene age

Typical profile

H1 - 0 to 16 inches: fine sand H2 - 16 to 68 inches: sandy clay loam H3 - 68 to 80 inches: sandy clay loam

Properties and qualities

Slope: 0 to 5 percent

Depth to restrictive feature: More than 80 inches

Natural drainage class: Well drained

Capacity of the most limiting layer to transmit water (Ksat): Moderately high to high

(0.57 to 1.98 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Calcium carbonate, maximum in profile: 30 percent

Available water storage in profile: Moderate (about 7.5 inches)

Interpretive groups

Land capability classification (irrigated): 4e Land capability classification (nonirrigated): 6e

Hydrologic Soil Group: B

Ecological site: Sandy 12-17" PZ (R077DY046TX)

Description of Wickett

Setting

Landform: Plains

Landform position (three-dimensional): Talf

Down-slope shape: Convex Across-slope shape: Linear

Parent material: Sandy eolian deposits overlying calcareous, loamy alluvium in the

ogallala formation of miocene-pliocene age

Typical profile

H1 - 0 to 16 inches: loamy fine sand H2 - 16 to 33 inches: fine sandy loam H3 - 33 to 53 inches: cemented material H4 - 53 to 67 inches: gravelly loam

Properties and qualities

Slope: 0 to 3 percent

Depth to restrictive feature: 20 to 40 inches to petrocalcic

Natural drainage class: Well drained

Capacity of the most limiting layer to transmit water (Ksat): Moderately low to

moderately high (0.06 to 0.57 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Calcium carbonate, maximum in profile: 85 percent

Salinity, maximum in profile: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Available water storage in profile: Low (about 3.5 inches)

Interpretive groups

Land capability classification (irrigated): 4e Land capability classification (nonirrigated): 6e

Hydrologic Soil Group: B

Ecological site: Sandy 12-17" PZ (R077DY046TX)

Minor Components

Unnamed

Percent of map unit: 6 percent

Lea County, New Mexico

AB—Amarillo-Arvana loamy fine sands association

Map Unit Setting

National map unit symbol: dmnr Elevation: 3,500 to 4,400 feet

Mean annual precipitation: 12 to 16 inches Mean annual air temperature: 58 to 60 degrees F

Frost-free period: 190 to 205 days

Farmland classification: Farmland of statewide importance

Map Unit Composition

Amarillo and similar soils: 50 percent Arvana and similar soils: 40 percent Minor components: 10 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Amarillo

Setting

Landform: Plains

Landform position (three-dimensional): Rise

Down-slope shape: Linear Across-slope shape: Linear

Parent material: Calcareous alluvium and/or calcareous eolian deposits derived

from sedimentary rock

Typical profile

A - 0 to 8 inches: loamy fine sand Bt - 8 to 36 inches: sandy clay loam Bk - 36 to 60 inches: marly loam

Properties and qualities

Slope: 0 to 3 percent

Depth to restrictive feature: More than 80 inches

Natural drainage class: Well drained

Runoff class: Low

Capacity of the most limiting layer to transmit water (Ksat): Moderately high to high

(0.60 to 2.00 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Calcium carbonate, maximum in profile: 50 percent

Gypsum, maximum in profile: 1 percent

Salinity, maximum in profile: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Sodium adsorption ratio, maximum in profile: 2.0

Available water storage in profile: Moderate (about 8.7 inches)

Interpretive groups

Land capability classification (irrigated): 4e Land capability classification (nonirrigated): 4e

Hydrologic Soil Group: B

Ecological site: Sandy Plains (R077CY056NM)

Description of Arvana

Setting

Landform: Plains

Landform position (three-dimensional): Rise

Down-slope shape: Linear Across-slope shape: Linear

Parent material: Calcareous alluvium and/or calcareous eolian deposits derived

from sedimentary rock

Typical profile

A - 0 to 6 inches: loamy fine sand Bt - 6 to 28 inches: sandy clay loam Bkm - 28 to 38 inches: cemented material BCk - 38 to 60 inches: sandy clay loam

Properties and qualities

Slope: 0 to 3 percent

Depth to restrictive feature: 20 to 40 inches to petrocalcic

Natural drainage class: Well drained

Runoff class: Low

Capacity of the most limiting layer to transmit water (Ksat): Low to moderately high

(0.01 to 0.60 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Calcium carbonate, maximum in profile: 50 percent

Gypsum, maximum in profile: 1 percent

Salinity, maximum in profile: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Sodium adsorption ratio, maximum in profile: 2.0

Available water storage in profile: Low (about 3.8 inches)

Interpretive groups

Land capability classification (irrigated): 6e Land capability classification (nonirrigated): 6e

Hydrologic Soil Group: C

Ecological site: Sandy Plains (R077CY056NM)

Minor Components

Portales

Percent of map unit: 2 percent

Ecological site: Limy Upland 16-21" PZ (R077CY028TX)

Brownfield

Percent of map unit: 2 percent

Ecological site: Sandy 12-17" PZ (R077DY046TX)

Patricia

Percent of map unit: 2 percent

Ecological site: Sandy Plains (R077CY056NM)

Gomez

Percent of map unit: 2 percent

Ecological site: Sandy Plains (R077CY056NM)

Mansker

Percent of map unit: 1 percent

Ecological site: Limy Upland 16-21" PZ (R077CY028TX)

Tivoli

Percent of map unit: 1 percent

Ecological site: Sandy 12-17" PZ (R077DY046TX)

BO—Brownfield-Springer association

Map Unit Setting

National map unit symbol: dmpj Elevation: 3,500 to 4,400 feet

Mean annual precipitation: 12 to 16 inches
Mean annual air temperature: 58 to 60 degrees F

Frost-free period: 190 to 205 days

Farmland classification: Farmland of statewide importance

Map Unit Composition

Brownfield and similar soils: 60 percent Springer and similar soils: 30 percent Minor components: 10 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Brownfield

Settina

Landform: Plains

Landform position (three-dimensional): Rise

Down-slope shape: Linear Across-slope shape: Linear

Parent material: Eolian deposits derived from sedimentary rock

Typical profile

A - 0 to 22 inches: fine sand

Bt - 22 to 60 inches: sandy clay loam

Properties and qualities

Slope: 0 to 3 percent

Depth to restrictive feature: More than 80 inches

Natural drainage class: Well drained

Runoff class: Very low

Capacity of the most limiting layer to transmit water (Ksat): Moderately high to high

(0.60 to 2.00 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Salinity, maximum in profile: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Sodium adsorption ratio, maximum in profile: 2.0

Available water storage in profile: Moderate (about 7.0 inches)

Interpretive groups

Land capability classification (irrigated): 6e Land capability classification (nonirrigated): 6e

Hydrologic Soil Group: B

Ecological site: Sandy 12-17" PZ (R077DY046TX)

Description of Springer

Setting

Landform: Plains

Landform position (three-dimensional): Rise

Down-slope shape: Linear Across-slope shape: Linear

Parent material: Eolian deposits derived from sedimentary rock

Typical profile

A - 0 to 14 inches: loamy fine sand Bt - 14 to 60 inches: fine sandy loam Bk - 60 to 79 inches: fine sandy loam

Properties and qualities

Slope: 0 to 3 percent

Depth to restrictive feature: More than 80 inches

Natural drainage class: Well drained

Runoff class: Very low

Capacity of the most limiting layer to transmit water (Ksat): Moderately high to high

(0.60 to 6.00 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Calcium carbonate, maximum in profile: 20 percent

Salinity, maximum in profile: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Sodium adsorption ratio, maximum in profile: 2.0

Available water storage in profile: Moderate (about 7.1 inches)

Interpretive groups

Land capability classification (irrigated): 4e Land capability classification (nonirrigated): 4e

Hydrologic Soil Group: A

Ecological site: Sandy 12-17" PZ (R077DY046TX)

Minor Components

Patricia

Percent of map unit: 4 percent

Ecological site: Sandy Plains (R077CY056NM)

Amarillo

Percent of map unit: 4 percent

Ecological site: Sandy 16-21" PZ (R077CY035TX)

Tivoli

Percent of map unit: 1 percent

Ecological site: Sandy 12-17" PZ (R077DY046TX)

Gomez

Percent of map unit: 1 percent

Ecological site: Sandy Plains (R077CY056NM)

BS—Brownfield-Springer association, hummocky

Map Unit Setting

National map unit symbol: dmpk Elevation: 3,500 to 4,400 feet

Mean annual precipitation: 12 to 16 inches Mean annual air temperature: 58 to 60 degrees F

Frost-free period: 190 to 205 days

Farmland classification: Farmland of statewide importance

Map Unit Composition

Brownfield and similar soils: 65 percent Springer and similar soils: 25 percent Minor components: 10 percent

Minor components: 10 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Brownfield

Setting

Landform: Plains

Landform position (three-dimensional): Rise

Down-slope shape: Linear Across-slope shape: Linear

Parent material: Eolian deposits derived from sedimentary rock

Typical profile

A - 0 to 22 inches: fine sand

Bt - 22 to 60 inches: sandy clay loam

Properties and qualities

Slope: 0 to 3 percent

Depth to restrictive feature: More than 80 inches

Natural drainage class: Well drained

Runoff class: Very low

Capacity of the most limiting layer to transmit water (Ksat): Moderately high to high

(0.60 to 2.00 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Salinity, maximum in profile: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Sodium adsorption ratio, maximum in profile: 2.0

Available water storage in profile: Moderate (about 7.0 inches)

Interpretive groups

Land capability classification (irrigated): 6e Land capability classification (nonirrigated): 6e

Hydrologic Soil Group: B

Ecological site: Sandy 12-17" PZ (R077DY046TX)

Description of Springer

Setting

Landform: Plains

Landform position (three-dimensional): Rise

Down-slope shape: Linear Across-slope shape: Linear

Parent material: Eolian deposits derived from sedimentary rock

Typical profile

A - 0 to 7 inches: loamy fine sand Bt - 7 to 60 inches: fine sandy loam Bk - 60 to 79 inches: fine sandy loam

Properties and qualities

Slope: 0 to 3 percent

Depth to restrictive feature: More than 80 inches

Natural drainage class: Well drained

Runoff class: Very low

Capacity of the most limiting layer to transmit water (Ksat): Moderately high to high

(0.60 to 6.00 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Calcium carbonate, maximum in profile: 20 percent

Gypsum, maximum in profile: 1 percent

Salinity, maximum in profile: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Sodium adsorption ratio, maximum in profile: 2.0

Available water storage in profile: Moderate (about 7.4 inches)

Interpretive groups

Land capability classification (irrigated): 4e Land capability classification (nonirrigated): 4e

Hydrologic Soil Group: A

Ecological site: Sandy 12-17" PZ (R077DY046TX)

Minor Components

Amarillo

Percent of map unit: 4 percent

Ecological site: Sandy 16-21" PZ (R077CY035TX)

Arvana

Percent of map unit: 3 percent

Ecological site: Sandy 16-21" PZ (R077CY035TX)

Tivoli

Percent of map unit: 2 percent

Ecological site: Sandy 12-17" PZ (R077DY046TX)

Dune land

Percent of map unit: 1 percent

KM—Kermit soils and dune land, 0 to 12 percent slopes

Map Unit Setting

National map unit symbol: dmpx Elevation: 3,000 to 4,400 feet

Mean annual precipitation: 10 to 15 inches Mean annual air temperature: 60 to 62 degrees F

Frost-free period: 190 to 205 days

Farmland classification: Not prime farmland

Map Unit Composition

Dune land: 45 percent

Kermit and similar soils: 45 percent Minor components: 10 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Kermit

Setting

Landform: Dunes

Landform position (two-dimensional): Shoulder, backslope, footslope

Landform position (three-dimensional): Side slope Down-slope shape: Convex, linear, concave

Across-slope shape: Convex

Parent material: Calcareous sandy eolian deposits derived from sedimentary rock

Typical profile

A - 0 to 8 inches: fine sand C - 8 to 60 inches: fine sand

Properties and qualities

Slope: 5 to 12 percent

Depth to restrictive feature: More than 80 inches Natural drainage class: Excessively drained

Runoff class: Very low

Capacity of the most limiting layer to transmit water (Ksat): Very high (20.00 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Calcium carbonate, maximum in profile: 3 percent

Gypsum, maximum in profile: 1 percent

Salinity, maximum in profile: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Sodium adsorption ratio, maximum in profile: 2.0

Available water storage in profile: Low (about 3.1 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 7e

Hydrologic Soil Group: A

Ecological site: Sandhills (R042XC022NM)

Description of Dune Land

Setting

Landform: Dunes

Landform position (two-dimensional): Shoulder, backslope, footslope

Landform position (three-dimensional): Side slope Down-slope shape: Convex, linear, concave

Across-slope shape: Convex

Typical profile

A - 0 to 6 inches: fine sand C - 6 to 60 inches: fine sand

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 8e

Hydrologic Soil Group: A

Minor Components

Palomas

Percent of map unit: 3 percent

Ecological site: Loamy Sand (R042XC003NM)

Pyote

Percent of map unit: 3 percent

Ecological site: Loamy Sand (R042XC003NM)

Maljamar

Percent of map unit: 2 percent

Ecological site: Loamy Sand (R042XC003NM)

Wink

Percent of map unit: 2 percent

Ecological site: Loamy Sand (R042XC003NM)

MU—Mixed alluvial land

Map Unit Setting

National map unit symbol: dmqg Elevation: 3,600 to 4,400 feet

Mean annual precipitation: 12 to 16 inches Mean annual air temperature: 58 to 62 degrees F

Frost-free period: 190 to 205 days

Farmland classification: Not prime farmland

Map Unit Composition

Ustifluvents and similar soils: 85 percent

Minor components: 15 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Ustifluvents

Setting

Landform: Drainageways

Landform position (two-dimensional): Toeslope Landform position (three-dimensional): Tread

Down-slope shape: Concave Across-slope shape: Linear

Parent material: Mixed alluvium derived from sedimentary rock

Typical profile

C - 0 to 60 inches: stratified sand to loamy fine sand to loam to sandy clay loam to clay loam to clay

Properties and qualities

Slope: 0 to 7 percent

Depth to restrictive feature: More than 80 inches

Natural drainage class: Well drained

Runoff class: Negligible

Capacity of the most limiting layer to transmit water (Ksat): Moderately low to very

high (0.06 to 20.00 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: Frequent Frequency of ponding: None

Calcium carbonate, maximum in profile: 20 percent

Gypsum, maximum in profile: 5 percent

Salinity, maximum in profile: Nonsaline to moderately saline (0.0 to 8.0 mmhos/cm)

Available water storage in profile: Moderate (about 7.8 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 6e

Hydrologic Soil Group: A

Ecological site: Bottomland (R042XC017NM)

Minor Components

Amarillo

Percent of map unit: 7 percent

Ecological site: Sandy Plains (R077CY056NM)

Portales

Percent of map unit: 7 percent

Ecological site: Limy Upland 16-21" PZ (R077CY028TX)

Playas

Percent of map unit: 1 percent Landform: Flood-plain playas

Landform position (two-dimensional): Toeslope Landform position (three-dimensional): Tread

Down-slope shape: Concave Across-slope shape: Concave

PG—Portales and gomez fine sandy loams

Map Unit Setting

National map unit symbol: dmqm Elevation: 3,600 to 4,400 feet

Mean annual precipitation: 12 to 16 inches Mean annual air temperature: 58 to 60 degrees F

Frost-free period: 190 to 205 days

Farmland classification: Farmland of statewide importance

Map Unit Composition

Portales and similar soils: 45 percent Gomez and similar soils: 45 percent Minor components: 10 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Gomez

Setting

Landform: Plains

Landform position (three-dimensional): Dip

Down-slope shape: Linear Across-slope shape: Linear

Parent material: Calcareous alluvium and/or calcareous lacustrine deposits derived

from sedimentary rock

Typical profile

A - 0 to 6 inches: fine sandy loam

Bk1 - 6 to 22 inches: fine sandy loam

Bk2 - 22 to 60 inches: fine sandy loam

Properties and qualities

Slope: 0 to 3 percent

Depth to restrictive feature: More than 80 inches

Natural drainage class: Well drained

Runoff class: Very low

Capacity of the most limiting layer to transmit water (Ksat): High (2.00 to 6.00 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Calcium carbonate, maximum in profile: 50 percent

Gypsum, maximum in profile: 1 percent

Salinity, maximum in profile: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Sodium adsorption ratio, maximum in profile: 2.0

Available water storage in profile: Moderate (about 6.2 inches)

Interpretive groups

Land capability classification (irrigated): 3e Land capability classification (nonirrigated): 4c

Hydrologic Soil Group: A

Ecological site: Sandy 16-21" PZ (R077CY035TX)

Description of Portales

Setting

Landform: Plains

Landform position (three-dimensional): Dip

Down-slope shape: Linear Across-slope shape: Linear

Parent material: Calcareous alluvium and/or calcareous eolian deposits derived

from sedimentary rock

Typical profile

A - 0 to 8 inches: fine sandy loam Bk - 8 to 60 inches: clay loam

Properties and qualities

Slope: 0 to 3 percent

Depth to restrictive feature: More than 80 inches

Natural drainage class: Well drained

Runoff class: Low

Capacity of the most limiting layer to transmit water (Ksat): Moderately high to high

(0.60 to 2.00 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Calcium carbonate, maximum in profile: 50 percent

Gypsum, maximum in profile: 1 percent

Salinity, maximum in profile: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Sodium adsorption ratio, maximum in profile: 2.0

Available water storage in profile: High (about 11.0 inches)

Interpretive groups

Land capability classification (irrigated): 3e Land capability classification (nonirrigated): 4e

Hydrologic Soil Group: B

Ecological site: Sandy 16-21" PZ (R077CY035TX)

Minor Components

Lea

Percent of map unit: 4 percent

Ecological site: Limy Upland 16-21" PZ (R077CY028TX)

Arvana

Percent of map unit: 3 percent

Ecological site: Sandy 16-21" PZ (R077CY035TX)

Amarillo

Percent of map unit: 2 percent

Ecological site: Sandy Plains (R077CY056NM)

Playas

Percent of map unit: 1 percent

Landform: Playa floors

Landform position (two-dimensional): Toeslope Landform position (three-dimensional): Dip

Down-slope shape: Concave

Across-slope shape: Concave

SE—Simona fine sandy loam, 0 to 3 percent slopes

Map Unit Setting

National map unit symbol: dmr2 Elevation: 3,000 to 4,400 feet

Mean annual precipitation: 10 to 16 inches
Mean annual air temperature: 58 to 62 degrees F

Frost-free period: 190 to 205 days

Farmland classification: Not prime farmland

Map Unit Composition

Simona and similar soils: 85 percent Minor components: 15 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Simona

Setting

Landform: Plains

Landform position (three-dimensional): Rise

Down-slope shape: Linear Across-slope shape: Linear

Parent material: Calcareous eolian deposits derived from sedimentary rock

Typical profile

A - 0 to 8 inches: fine sandy loam

Bk - 8 to 16 inches: gravelly fine sandy loam Bkm - 16 to 26 inches: cemented material

Properties and qualities

Slope: 0 to 3 percent

Depth to restrictive feature: 7 to 20 inches to petrocalcic

Natural drainage class: Well drained

Runoff class: Very high

Capacity of the most limiting layer to transmit water (Ksat): Very low to moderately

low (0.00 to 0.06 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Calcium carbonate, maximum in profile: 35 percent

Gypsum, maximum in profile: 1 percent

Salinity, maximum in profile: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Sodium adsorption ratio, maximum in profile: 2.0

Available water storage in profile: Very low (about 2.0 inches)

Interpretive groups

Land capability classification (irrigated): 6s Land capability classification (nonirrigated): 7s

Hydrologic Soil Group: D

Ecological site: Shallow Sandy (R042XC002NM)

Minor Components

Kimbrough

Percent of map unit: 7 percent

Ecological site: Very Shallow 16-21" PZ (R077CY037TX)

Lea

Percent of map unit: 7 percent

Ecological site: Limy Upland 16-21" PZ (R077CY028TX)

Playas

Percent of map unit: 1 percent

Landform: Playa floors

Landform position (two-dimensional): Toeslope Landform position (three-dimensional): Dip

Down-slope shape: Concave Across-slope shape: Concave

SR—Simona-Upton association

Map Unit Setting

National map unit symbol: dmr3 Elevation: 3,000 to 4,400 feet

Mean annual precipitation: 10 to 16 inches
Mean annual air temperature: 58 to 62 degrees F

Frost-free period: 190 to 205 days

Farmland classification: Not prime farmland

Map Unit Composition

Simona and similar soils: 50 percent Upton and similar soils: 35 percent Minor components: 15 percent

Estimates are based on observations, descriptions, and transects of the mapunit.

Description of Simona

Setting

Landform: Ridges

Landform position (two-dimensional): Shoulder Landform position (three-dimensional): Rise

Down-slope shape: Convex Across-slope shape: Linear

Parent material: Calcareous eolian deposits derived from sedimentary rock

Typical profile

A - 0 to 8 inches: gravelly fine sandy loam Bk - 8 to 16 inches: fine sandy loam Bkm - 16 to 26 inches: cemented material

Properties and qualities

Slope: 0 to 3 percent

Depth to restrictive feature: 7 to 20 inches to petrocalcic

Natural drainage class: Well drained

Runoff class: Very low

Capacity of the most limiting layer to transmit water (Ksat): Very low to moderately

low (0.00 to 0.06 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Calcium carbonate, maximum in profile: 50 percent

Gypsum, maximum in profile: 1 percent

Salinity, maximum in profile: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Sodium adsorption ratio, maximum in profile: 2.0

Available water storage in profile: Very low (about 1.9 inches)

Interpretive groups

Land capability classification (irrigated): None specified

Land capability classification (nonirrigated): 7s

Hydrologic Soil Group: D

Ecological site: Shallow Sandy (R042XC002NM)

Description of Upton

Setting

Landform: Ridges

Landform position (two-dimensional): Shoulder Landform position (three-dimensional): Rise

Down-slope shape: Convex Across-slope shape: Linear

Parent material: Calcareous eolian deposits derived from sedimentary rock

Typical profile

A - 0 to 8 inches: gravelly loam

Bkm - 8 to 18 inches: cemented material BCk - 18 to 60 inches: very gravelly loam

Properties and qualities

Slope: 0 to 3 percent

Depth to restrictive feature: 7 to 20 inches to petrocalcic

Natural drainage class: Well drained

Runoff class: Medium

Capacity of the most limiting layer to transmit water (Ksat): Low to moderately high

(0.01 to 0.60 in/hr)

Depth to water table: More than 80 inches

Frequency of flooding: None Frequency of ponding: None

Calcium carbonate, maximum in profile: 75 percent

Gypsum, maximum in profile: 1 percent

Salinity, maximum in profile: Nonsaline to very slightly saline (0.0 to 2.0 mmhos/cm)

Sodium adsorption ratio, maximum in profile: 2.0

Available water storage in profile: Very low (about 0.9 inches)

Interpretive groups

Land capability classification (irrigated): 6e Land capability classification (nonirrigated): 7s

Hydrologic Soil Group: D

Ecological site: Shallow (R042XC025NM)

Minor Components

Stegall

Percent of map unit: 5 percent

Ecological site: Limy Upland 16-21" PZ (R077CY028TX)

Kimbrough

Percent of map unit: 5 percent

Ecological site: Very Shallow 16-21" PZ (R077CY037TX)

Slaughter

Percent of map unit: 4 percent

Ecological site: Limy Upland 16-21" PZ (R077CY028TX)

Playas

Percent of map unit: 1 percent

Landform: Playa floors

Landform position (two-dimensional): Toeslope Landform position (three-dimensional): Dip

Down-slope shape: Concave Across-slope shape: Concave

References

American Association of State Highway and Transportation Officials (AASHTO). 2004. Standard specifications for transportation materials and methods of sampling and testing. 24th edition.

American Society for Testing and Materials (ASTM). 2005. Standard classification of soils for engineering purposes. ASTM Standard D2487-00.

Cowardin, L.M., V. Carter, F.C. Golet, and E.T. LaRoe. 1979. Classification of wetlands and deep-water habitats of the United States. U.S. Fish and Wildlife Service FWS/OBS-79/31.

Federal Register. July 13, 1994. Changes in hydric soils of the United States.

Federal Register. September 18, 2002. Hydric soils of the United States.

Hurt, G.W., and L.M. Vasilas, editors. Version 6.0, 2006. Field indicators of hydric soils in the United States.

National Research Council. 1995. Wetlands: Characteristics and boundaries.

Soil Survey Division Staff. 1993. Soil survey manual. Soil Conservation Service. U.S. Department of Agriculture Handbook 18. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/national/soils/?cid=nrcs142p2_054262

Soil Survey Staff. 1999. Soil taxonomy: A basic system of soil classification for making and interpreting soil surveys. 2nd edition. Natural Resources Conservation Service, U.S. Department of Agriculture Handbook 436. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/national/soils/?cid=nrcs142p2 053577

Soil Survey Staff. 2010. Keys to soil taxonomy. 11th edition. U.S. Department of Agriculture, Natural Resources Conservation Service. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/national/soils/?cid=nrcs142p2_053580

Tiner, R.W., Jr. 1985. Wetlands of Delaware. U.S. Fish and Wildlife Service and Delaware Department of Natural Resources and Environmental Control, Wetlands Section.

United States Army Corps of Engineers, Environmental Laboratory. 1987. Corps of Engineers wetlands delineation manual. Waterways Experiment Station Technical Report Y-87-1.

United States Department of Agriculture, Natural Resources Conservation Service. National forestry manual. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/soils/home/?cid=nrcs142p2_053374

United States Department of Agriculture, Natural Resources Conservation Service. National range and pasture handbook. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/national/landuse/rangepasture/?cid=stelprdb1043084

United States Department of Agriculture, Natural Resources Conservation Service. National soil survey handbook, title 430-VI. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/soils/scientists/?cid=nrcs142p2 054242

United States Department of Agriculture, Natural Resources Conservation Service. 2006. Land resource regions and major land resource areas of the United States, the Caribbean, and the Pacific Basin. U.S. Department of Agriculture Handbook 296. http://www.nrcs.usda.gov/wps/portal/nrcs/detail/national/soils/?cid=nrcs142p2_053624

United States Department of Agriculture, Soil Conservation Service. 1961. Land capability classification. U.S. Department of Agriculture Handbook 210. http://www.nrcs.usda.gov/Internet/FSE_DOCUMENTS/nrcs142p2_052290.pdf



APPENDIX C CALCULATIONS

WCS\FINAL\15052\
R160308_CISF REPORT

REVISION 0
8 MARCH 2016

APPENDIX C WCS - CISF FLOOD ANALYSIS POST-DEVELOPMENT CURVE NUMBER CALCULATIONS

DES

CHK

WCS File: 15052 - CN CURVE NUMBER

AVV

3/8/2016

DD

3/8/2016

Reference: 1. drawing: S:\CAD\WCS\15052 CISF Floodplain\Engineering\15052 - P CN.dwg

2. Soil information taken from US Department Of Agriculture, Natural Resources Conservation Service Custom Soil Resource Report For Andrews County, Texas, And Lea County, New Mexico, dated December 22, 2015 3. Texas Engineering Technical Note, No. 210-18-TX5, Estimating Runoff for Conservation Practices, 1990

Drainage Area - P DA 1	A=	105.7	Acres	0.16	5 sq mi	ARC I Adjustment**	ARC III Adjustment**
Cover Type & Hydrologic Condition	Soil Type	Hyd. Soil Group	Area	CN*	Area x CN	(60 Min.)	(60 Min.)
Desert Shrub Poor	JPC	B/A***	59.92	77	4614.1	,	,
		Imp. Cover	0.00	98	0.0		
Desert Shrub Poor	TwB	В	12.79	77	985.0		
		Imp. Cover	0.00	98	0.0		
Desert Shrub Poor	BCB	D	13.19	88	1160.8		
		Imp. Cover	0.00	98	0.0		
Desert Shrub Poor	RaB	В	17.80	77	1370.7		
		Imp. Cover	2.00	98	195.6		
Total			105.7		8326.2		
COMPOSITE CN			79			62	91

Drainage Area - P DA 2	A= 46.1 Acres		Acres	0.072 sq mi		ARC I Adjustment**	ARC III Adjustment**
Cover Type & Hydrologic Condition	Soil Type	Hyd. Soil Group	Area	CN*	Area x CN	(60 Min.)	(60 Min.)
Desert Shrub Poor	BcB	D	34.88	88	3069.8	,	,
		Imp. Cover	0.00	98	0.0		
Desert Shrub Poor	SE	D	7.88	88	693.0		
		Imp. Cover	0.00	0	0.0		
Desert Shrub Poor	SR	D	0.84	88	73.7		
		Imp. Cover	0.00	0	0.0		
Desert Shrub Poor	RaB	В	2.50	77	192.2		
		Imp. Cover	0.00	98	0.0		
Total			46.1		4028.7		
COMPOSITE ON							

COMPOSITE CN

87

73

95

Calculations - 14 page



APPENDIX C WCS - CISF FLOOD ANALYSIS POST-DEVELOPMENT CURVE NUMBER CALCULATIONS

Drainage Area - P DA 3	A=	42.8 /	Acres	0.06	7 sq mi	ARC I Adjustment**	ARC III Adjustment**
Cover Type & Hydrologic Condition	Soil Type	Hyd. Soil Group	Area	CN*	Area x CN	(60 Min.)	(60 Min.)
Desert Shrub Poor	RaB	В	2.95	77	227.1		
		Imp. Cover	0.00	0	0.0		
Desert Shrub Poor	BcB	D	34.20	88	3009.6		
		Imp. Cover	5.65	98	553.8		
Total			42.8		3790.5		
COMPOSITE CN			89			76	96
Drainage Area - P DA 4	A=		Acres	1.05	4 sq mi	ARC I Adjustment**	ARC III Adjustment**
Cover Type & Hydrologic Condition	Soil Type	Hyd. Soil Group	Area	CN*	Area x CN	(60 Min.)	(60 Min.)
Stockpile (Bare soil)		D	60.67	94	5703.3		
Desert Shrub Poor	JPC	B/A***	145.83	77	11228.9		
		Imp. Cover	21.88	98	2143.9		
Desert Shrub Poor	RaB	В	215.19	77	16569.4		
		Imp. Cover	4.48	0	0.0		
Desert Shrub Poor	BcB	D	98.43	88	8662.1		
		Imp. Cover	54.29	98	5320.2		
Desert Shrub Poor	TwB	В	25.88	77	1992.8		
		Imp. Cover	47.81	98	4685.8		
Total	•		674.5		56306.4		

COMPOSITE CN

83

67

93

^{*}Taken from Table 2c of Texas Engineering Technical Note, Hydrology, No. 210-18-TX5, Estimating Runoff for Conservation Practices

^{**}Taken from Table 3 of Texas Engineering Technical Note, Hydrology, No. 210-18-TX5, Estimating Runoff for Conservation Practices

^{***}USDA Soil Survey indicates 46% A and 50% B. CN is conservatively calculated to be 100% B



APPENDIX C WCS - CISF FLOOD ANALYSIS POST-DEVELOPMENT DRAINAGE AREA TIME OF CONCENTRATION

DES CHK

WCS AVV 3/8/2016 DD 3/8/2016

Reference: 1. United States Department of Agriculture, Urban Hydrology for Small Watersheds TR-55, 1986

2. Reference Drawing: S:\CAD\WCS\15052 CISF Floodplain\Engineering\15052 - P Hydraulic Calcs PMP.dwg

		P DA 1			P DA 2			P DA 3			P DA 4	
Drainage Area	Α	105.7	(acres)	Α	46.1	(acres)	Α	42.8	(acres)	Α	674.5	(acres)
_		0.165	(sqmi)		0.072	(sqmi)		0.067	(sqmi)		1.054	(sqmi)
Sheet Flow												
Manning's roughness coef.1	n	0.15	n/a	n	0.011	n/a	n	0.011	n/a	n	0.15	n/a
Flow Length	L	300	feet									
2-year, 24-hour rainfall	P2	2.5	inches									
Slope	s	0.015	ft/ft	S	0.003	ft/ft	s	0.003	ft/ft	s	0.01400	ft/ft
Travel time ²	Tt	0.50	hours	Tt	0.11	hours	Tt	0.11	hours	Tt	0.51	hours
		30.0	min.		6.8	min.		6.8	min.		30.8	min.
Shallow Concentrated Flow												
Flow Length	L	1540	feet	L	1656	feet	L	1681	feet	L	3545	feet
Slope	s	0.01650	ft/ft	S	0.00477	ft/ft	s	0.00476	ft/ft	s	0.00555	ft/ft
Surface (1=paved or 2=unpaved)		2	n/a									
Velocity ³	V	2.07	ft/sec	V	1.11	ft/sec	V	1.11	ft/sec	V	1.20	ft/sec
Travel time	Tt	0.21	hours	Tt	0.41	hours	Tt	0.42	hours	Tt	0.82	hours
		12.38	min.		24.77	min.		25.17	min.		49.15	min.
Manning's Equation												
Flow Length	L	1605	feet	L	1196	feet	L	0	feet	L	0	feet
Slope	S	0.00460	ft/ft	S	0.01589	ft/ft	S	0.00000	ft/ft	S	0.00000	ft/ft
roughness ⁴	n	0.028	n/a									
Open Channel												
Bottom Width	BW	150	feet	BW	3.5	feet	BW	0	feet	BW	0	feet
Side Slopes (ft/ft, H:V) Rt.	H:V	125	feet	H:V	5.5	feet	H:V	0	feet	H:V	0	feet
Side Slopes (ft/ft, H:V) Lt.	H:V	125	feet	H:V	2.66	feet	H:V	0	feet	H:V	0	feet
Depth	d	0.5	feet	d	1.5	feet	d	0	feet	d	0	feet
Flow Rate	Q	203	cfs	Q	90	cfs	Q	0	cfs	Q	0	cfs
Velocity	V	1.91	ft/sec	V	6.23	ft/sec	V	1	ft/sec	V	1	ft/sec
Travel time	Tt	0.23	hours	Tt	0.05	hours	Tt	0.00	hours	Tt	0.00	hours
		14.01	min.		3.20	min.		0.00	min.		0.00	min.
Total Travel Time	Т	0.94	hours	T	0.58	hours	Т	0.53	hours	Т	1.33	hours
	Т	56.34	min.	Т	34.73	min.	Т	31.93	min.	Т	79.94	min.
Lag Time (Tc*0.6)	Tlag	0.56	hours	Tlag	0.35	hours	Tlag	0.32	hours	Tlag	0.80	hours
	Tlag	33.80	min.	Tlag	20.84	min.	Tlag	19.16	min.	Tlag	47.97	min.

Notes:

^{1.} Manning's roughness coefficient taken from 'Table 3-1 Roughness coefficients (Manning's n) for sheet flow' - United States Department of Agriculture, *Urban Hydrology for Small Watersheds TR-55*, 1986

^{2.} Equation 3-3, United States Department of Agriculture, Urban Hydrology for Small Watersheds TR-55, 1986

^{3.} Figure 3-1, United States Department of Agriculture, Urban Hydrology for Small Watersheds TR-55, 1986

^{4.} Reference Manning's 'n' calculations in APPDX C: POST-DEVELOPMENT HYDRAULIC CALCULATIONS

S:\Projects\W - Z\WCS (Waste Control Specialists)\draft\15052 Floodplain Analysis CISF\Engineering\15052 - Tc.xls



APPENDIX C WCS - CISF FLOOD ANALYSIS POST-DEVELOPMENT HYDRAULIC CALCULATIONS

DES CHK

WCS AVV 3/8/2016 DD 3/8/2016

Reference: 1. Guide for Selecting Manning's Roughness Coefficients for Natural Channels and Flood Plains, The

U.S. Department of Transportation, 1984

Manning's Roughness Coefficient

Eq. 3 $n = (n_0 + n_1 + n_2 + n_3 + n_4)m$

Where: n_0 = a base value of n for straight, uniform, smooth channel in natural materials

 n_1 = a value added to correct for the effect of surface irregularities

 n_2 = a value for variations in shape and size of the channel cross section

n₃= a value for obstructions

 n_4 = a value for vegetation and flow conditions

m= a correction factor for meandering of the channel

Channel Roughness

 $n_0 =$ 0.020 earth Table1 0.000 smooth Table 2 n₁= 0.000 gradual Table 2 $n_2 =$ 0.000 neglible Table 2 n₃= n₄= 0.008 low Table 2 Table 2 1.0 minor m=

n = (0.02 + 000 + 000 + 000 + 0.008)1.0

= 0.028



APPENDIX C WCS - CISF FLOOD ANALYSIS POST-DEVELOPMENT HYDRAULIC CALCULATIONS

DES CHK

WCS AVV 3/8/2016 DD 3/8/2016

Reference: 1. Topographic aerial survey provided by Dallas Aerial Surveys, Inc., flown 5-29-2014. 10220 Forest Lane, Dallas,

Texas 214-349-2190, 800-862-2190, Fax 214-349-2193.

2. Reference Drawing: S:\CAD\WCS\15052 CISF Floodplain\Engineering\15052 - P Hydraulic Calcs PMP.dwg

Manning's Formula

 $Q = vA = (1.49/n)AR^{2/3}s^{1/2}$

Where:

Q= Flow Rate (cfs) v= velocity, (ft/s) A= Flow Area, (ft²)

n= Manning's Roughness Coefficient

R= Hydraulic Radius, (ft) s= Channel Slope, (ft/ft)

AP-1 Stateline Road

Road Elevation at P AP 1: 3486.5 ft

AMC I

100 YR

Roughness	Channel	Left Side	Right Side	Bottom	Peak	Peak	Peak
Coef	Slope	Slope	Slope	Width	Discharge	Velocity	Depth
n ²	(ft/ft)	(ft/ft) (H:V)	(ft/ft) (H:V)	(ft)	(CFS)	(ft/s)	(ft)
0.028	0.0046	125	125	150	123.6	1.64	0.38

500 YR

Roughness	Channel	Left Side	Right Side	Bottom	Peak	Peak	Peak
Coef	Slope	Slope	Slope	Width	Discharge	Velocity	Depth
n ²	(ft/ft)	(ft/ft) (H:V)	(ft/ft) (H:V)	(ft)	(CFS)	(ft/s)	(ft)
0.028	0.0046	125	125	150	256.3	2.05	0.57

PMP

Roughness	Channel	Left Side	Right Side	Bottom	Peak	Peak	Peak
Coef	Slope	Slope	Slope	Width	Discharge	Velocity	Depth
n ²	(ft/ft)	(ft/ft) (H:V)	(ft/ft) (H:V)	(ft)	(CFS)	(ft/s)	(ft)
0.028	0.0046	125	125	150	428.9	2.38	0.74

AMC II

100 YR

Roughness	Channel	Left Side	Right Side	Bottom	Peak	Peak	Peak
Coef	Slope	Slope	Slope	Width	Discharge	Velocity	Depth
n ²	(ft/ft)	(ft/ft) (H:V)	(ft/ft) (H:V)	(ft)	(CFS)	(ft/s)	(ft)
0.028	0.0046	125	125	150	233.3	1.99	0.54



APPENDIX C WCS - CISF FLOOD ANALYSIS POST-DEVELOPMENT HYDRAULIC CALCULATIONS

500 YR

٠٠.								
	Roughness	Channel	Left Side	Right Side	Bottom	Peak	Peak	Peak
	Coef	Slope	Slope	Slope	Width	Discharge	Velocity	Depth
	n²	(ft/ft)	(ft/ft) (H:V)	(ft/ft) (H:V)	(ft)	(CFS)	(ft/s)	(ft)
	0.028	0.0046	125	125	150	389.6	2.31	0.71

PMP

Roughness	Channel	Left Side	Right Side	Bottom	Peak	Peak	Peak
Coef	Slope	Slope	Slope	Width	Discharge	Velocity	Depth
n ²	(ft/ft)	(ft/ft) (H:V)	(ft/ft) (H:V)	(ft)	(CFS)	(ft/s)	(ft)
0.028	0.0046	125	125	150	440.2	2.4	0.75

AMC III

100 YR

Roughness	Channel	Left Side	Right Side	Bottom	Peak	Peak	Peak
Coef	Slope	Slope	Slope	Width	Discharge	Velocity	Depth
n ²	(ft/ft)	(ft/ft) (H:V)	(ft/ft) (H:V)	(ft)	(CFS)	(ft/s)	(ft)
0.028	0.0046	125	125	150	304.9	2.16	0.62

500 YR

Roughness	Channel	Left Side	Right Side	Bottom	Peak	Peak	Peak
Coef	Slope	Slope	Slope	Width	Discharge	Velocity	Depth
n ²	(ft/ft)	(ft/ft) (H:V)	(ft/ft) (H:V)	(ft)	(CFS)	(ft/s)	(ft)
0.028	0.0046	125	125	150	460.2	2.43	0.77

PMP

Roughness	Channel	Left Side	Right Side	Bottom	Peak	Peak	Peak
Coef	Slope	Slope	Slope	Width	Discharge	Velocity	Depth
n ²	(ft/ft)	(ft/ft) (H:V)	(ft/ft) (H:V)	(ft)	(CFS)	(ft/s)	(ft)
0.028	0.0046	125	125	150	443.0	2.4	0.75

Notes:

- 1. Channel geometry sources from aerial survey provided by Dallas Aerial Surveys, Inc., flown 5-29-2014.
- 2. See Manning's Roughness Coefficient calculation. Manning's n from Guide for Selecting Manning's Roughness Coefficients for Natural Channels and Flood Plains, The U.S. Department of Transportation, 1984



APPENDIX C WCS - CISF FLOOD ANALYSIS POST-DEVELOPMENT ELEVATION-STORAGE TABLES

DES CHK

WCS AVV 2/1/2016 DD 2/4/2016

Elevation-Storage-Discharge

Reference:

- 1. 2008 URS As-Built Rail Drawings R/T Infrastructure Improvements Facilities G.E. Hudson River Project Andrews County, Texas Project No. 29600
- 2. Topographic aerial survey provided by Dallas Aerial Surveys, Inc., flown 5-29-2014. 10220 Forest Lane, Dallas,
- 3. WCS CISF Rail Plans, 1/22/16
- $4. \ Reference\ Drawing: S: \ CAD\ WCS\ 15052\ CISF\ Floodplain\ Engineering\ 15052\ -\ Elevation-Storage\ Calcs. dwg. dwg$

P DA 2

Elevation ¹	Storage	Storage
ft	cu yd	ac-ft
3465	0	0.0000
3468	77	0.0474
3470	295	0.1829
3472	966	0.5987
3474	2112	1.3090
3476	4106	2.5450
3478	7221	4.4756
3480	11613	7.1979
3482	17893	11.0903
3484	27141	16.8228
3486	42007	26.0373
3488	69708	43.2069
3490	124344	77.0723

Notes:

1. Topographic elevations reference aerial survey provided by Dallas Aerial Surveys, Inc., flown 5-29-2014.



APPENDIX C WCS - CISF FLOOD ANALYSIS POST-DEVELOPMENT ELEVATION-STORAGE TABLES

DES CHK

WCS AVV 2/1/2016 DD 2/4/2016

Elevation-Storage-Discharge

Reference:

- $1.\ 2008\ URS\ As-Built\ Rail\ Drawings-R/T\ Infrastructure\ Improvements\ Facilities\ G.E.\ Hudson\ River\ Project$
- Andrews County, Texas Project No. 29600
- 2. Topographic aerial survey provided by Dallas Aerial Surveys, Inc., flown 5-29-2014. 10220 Forest Lane,
- 3. WCS CISF Rail Plans, 1/22/16
- 4. Reference Drawing: S:\CAD\WCS\15052 CISF Floodplain\Engineering\15052 Elevation-Storage

Calcs.dwg.dwg

P DA 3

Elevation ¹	Storage	Storage
ft	cu yd	ac-ft
3484	0	0.0000
3486	12111	7.5068
3488	43926	27.2267
3490	103970	64.4437

Notes:

1. Topographic elevations reference aerial survey provided by Dallas Aerial Surveys, Inc., flown 5-29-2014.



APPENDIX C WCS - CISF FLOOD ANALYSIS POST-DEVELOPMENT ELEVATION-STORAGE TABLES

	DES		CHK	
WCS	AVV	2/1/2016	DD	2/4/2016

Elevation-Storage-Discharge

Reference: 1. 2008 URS As-Built Rail Drawings - R/T Infrastructure Improvements Facilities G.E. Hudson River Project Andrews County, Texas Project No. 29600

- 2. Topographic aerial survey provided by Dallas Aerial Surveys, Inc., flown 5-29-2014. 10220 Forest Lane, Dallas,
- 3. WCS CISF Rail Plans, 1/22/16
- 4. Reference Drawing: S:\CAD\WCS\15052 CISF Floodplain\Engineering\15052 Elevation-Storage Calcs.dwg

Playa

Elevation ¹	Storage	Storage
ft	cu yd	ac-ft
3476.65	0	0
3478	3426	2.123538
3480	33851	20.98187
3482	84169	52.17047
3484	173154	107.326
3486	472351	292.7773
3487	751987	466.1041
3488	1093782	677.9589
3489	1505226	932.9842
3490	1958830	1214.142

Notes:

1. Topographic elevations reference aerial survey provided by Dallas Aerial Surveys, Inc., flown 5-29-2014.



APPENDIX C WCS - CISF FLOOD ANALYSIS POST-DEVELOPMENT NON-LEVEL DAM TOP CROSS SECTIONS

DES CHK

WCS AVV 3/8/2016 DD 3/8/2016

Cross Sections

Reference: 1. WCS CISF Rail Plans, 1/22/16

2. 2008 URS As-Built Rail Drawings - R/T Infrastructure Improvements Facilities G.E.

Hudson River Project Andrews County, Texas Project No. 29600

Non-Level Dam - P DA 2

	Rail	XS	Station	Slope
	Station	Station	Elevation	Ahead
p-rail ¹	1863.4	0.00	3489.35	0.37%
p-rail ¹	1463.4	400.00	3487.87	1.50%
p-rail ¹	700.0	1163.36	3476.42	1.63%
p-rail ¹	0.0	1863.36	3465.02	0.19%
ex-rail ²	3000.0	2243.36	3470.72	1.50%
ex-rail ²	3600.0	2843.36	3479.72	0.98%
ex-rail ²	4400.0	3643.36	3487.52	0.30%
ex-rail ²	4800.0	4043.36	3488.72	-

NOTES:

2. Existing rail stations reference 2008 URS rail as-built drawings - R/T Infrastructure Improvements Facilities G.E. Hudson River Project Andrews County, Texas Project No. 29600 and are approximate

^{1.} Proposed rail stations reference the proposed WCS CISF Rail Plans, 1/22/16



APPENDIX C WCS - CISF FLOOD ANALYSIS POST-DEVELOPMENT NON-LEVEL DAM TOP CROSS SECTIONS

DES CHK

WCS AVV 3/8/2016 DD 3/8/2016

Cross Sections

Reference: 1. WCS CISF Rail Plans, 1/22/16

Non-Level Dam - P DA 3

	Rail XS	Station	Slope
	Station ¹	Elevation	Ahead
p-rail	5477.49	3489.00	-0.16%
p-rail	5489.81	3488.98	-0.13%
p-rail	5689.81	3488.72	-0.13%
p-rail	5889.81	3488.46	-0.13%
p-rail	6089.81	3488.20	-0.12%
p-rail	6262.89	3488.00	0.22%
p-rail	6632.18	3488.80	0.06%
p-rail	7407.91	3489.23	-

NOTES:

1. Proposed rail stations reference the proposed WCS CISF Rail Plans, 1/22/16



APPENDIX C WCS - CISF FLOOD ANALYSIS POST-DEVELOPMENT NON-LEVEL DAM TOP CROSS SECTIONS

DES CHK

WCS AVV 3/8/2016 DD 3/8/2016

Cross Sections

Reference:

1. 2008 URS As-Built Rail Drawings - R/T Infrastructure Improvements Facilities G.E. Hudson River Project Andrews County, Texas Project No. 29600

- 2. Topographic aerial survey provided by Dallas Aerial Surveys, Inc., flown 5-29-2014. 10220 Forest Lane, Dallas, Texas 214-349-2190, 800-862-2190, Fax 214-349-2193.
- 3. Reference Drawing: S:\CAD\WCS\15052 CISF Floodplain\Engineering\15052 P Hydraulic Calcs PMP.dwg

Non-Level Dam - P DA 4

	Rail	XS	Station	Slope
	Station	Station	Elevation	Ahead
ex-rail ¹	8500.00	8500.00	3489.96	-0.12%
ex-rail ¹	9900.00	9900.00	3488.28	-0.15%
ex-rail ¹	10017.67	10017.67	3488.10	-0.20%
ex-rail ¹	10387.00	10387.00	3487.36	-8.00%
topo ²	-	10404.00	3486.00	5.58%
topo ²	-	10439.87	3488.00	0.00%
topo ²	-	10742.10	3488.00	0.65%
topo ²	-	11051.85	3490.00	-

NOTES:

- 1. Existing rail stations reference 2008 URS rail as-built drawings R/T Infrastructure Improvements Facilities G.E. Hudson River Project Andrews County, Texas Project No. 29600 and are approximate
- 2. Topographic elevations come from the topographic aerial survey provided by Dallas Aerial Surveys, Inc., flown 5-29-2014.



APPENDIX C WCS - CISF FLOOD ANALYSIS POST-DEVELOPMENT DRAINAGE AREA TIME OF CONCENTRATION

DES CHK

WCS AVV 3/8/2016 DD 3/8/2016

Reference: 1. Reference Drawing: S:\CAD\WCS\15052 CISF Floodplain\Engineering\15052 - P Hydraulic Calcs

PMP.dwg

Manning Equation

 $v = 1.49/n*R_h^{2/3}*s^{1/2}$

Where,

v= velocity (ft/s) n= Manning's n R_h= hydraulic radius s= slope (ft/ft)

Manning Equation for Sheet Flow

 $q = v*y = 1.49/n*y^{5/3}*s^{1/2}$

Therefore

 $y=(q/(1.49/n*s^{1/2}))^{3/5}$

v = q/y

Where,

q= unit discharge (ft²/s) v= velocity (ft/s)

n= Manning's n y= depth

s= slope (ft/ft)

Max flow

 $q_{Max} = I*L$

Where,

q_{Max}= maximum unit discharge (ft²/s)

I= Rainfaill Intensity
L= Length of Pad

Max depth

 $y_{max} = (q_{max}/(1.49/n*s^{1/2}))^{3/5}$

Where,

y_{max}= Maximum depth of flow (ft)

q_{Max}= Maximum unit discharge

n= Manning's n s= slope (ft/ft)



APPENDIX C WCS - CISF FLOOD ANALYSIS POST-DEVELOPMENT DRAINAGE AREA TIME OF CONCENTRATION

Max velocity

 $v_{max} = q_{max}/y_{max}$

Where,

 q_{Max} = maximum unit discharge (ft²/s) y_{max} = Maximum depth of flow (ft)

Inputs

s= 0.0075 ft/ft phase slope L= 515 ft length of phase

I= 0.210 in/min Max 500 yr-24hr rainfall intensity (HEC-HMS 500 yr SCS Storm)

2.92E-04 ft/s

n= 0.015 manning's n for concrete

Calculation

 $q_{Max} = 1.50E-01 \text{ ft}^2/\text{s}$

IIVIAX	
Max y=	0.088154 ft
	1.1 in
Max v=	1.7 ft/s



APPENDIX D HEC-HMS OUTPUT

WCS\FINAL\15052\
R160308_CISF REPORT

REVISION 0
8 MARCH 2016

Start of Run: 01Jan2016, 00:00 Basin Model: P AP 1 AMC I

End of Run: 02Jan2016, 12:00 Meteorologic Model: 100 yr

Compute Time: 08Mar2016, 12:47:35 Control Specifications:Control 24 HR Storms

Hydrologic	Drainage Area	Peak Discharge	Time of Peak	Volume
Element	(MI2)	(CFS)		(IN)
P DA 1	0.165	123.6	01Jan2016, 12:29	2.09

Start of Run: 01Jan2016, 00:00 Basin Model: P AP 1 AMC I

End of Run: 02Jan2016, 12:00 Meteorologic Model: 500 yr

Compute Time: 08Mar2016, 12:56:57 Control Specifications:Control 24 HR Storms

Hydrologic	Drainage Area	Peak Discharge	Time of Peak	Volume
Element	(MI2)	(CFS)		(IN)
P DA 1	0.165	256.3	01Jan2016, 12:27	4.11

Project: 15052 - CISF Simulation Run: PMP Dist A

Start of Run: 01Jan2016, 00:00 Basin Model: P AP 1 AMC I End of Run: 05Jan2016, 00:00 Meteorologic Model: PMP Distribution A

Compute Time: 08Mar2016, 12:58:19 Control Specifications:Control PMP

Hydrologic	Drainage Area	Peak Discharge	Time of Peak	Volume
Element	(MI2)	(CFS)		(IN)
P DA 1	0.165	428.9	03Jan2016, 06:00	33.97

Start of Run: 01Jan2016, 00:00 Basin Model: P AP 1 AMC II

End of Run: 02Jan2016, 12:00 Meteorologic Model: 100 yr

Compute Time: 08Mar2016, 12:59:23 Control Specifications:Control 24 HR Storms

Hydrologic	Drainage Area	Peak Discharge	Time of Peak	Volume
Element	(MI2)	(CFS)		(IN)
P DA 1	0.165	233.3	01Jan2016, 12:26	3.68

Start of Run: 01Jan2016, 00:00 Basin Model: P AP 1 AMC II

End of Run: 02Jan2016, 12:00 Meteorologic Model: 500 yr

Compute Time: 08Mar2016, 12:59:57 Control Specifications:Control 24 HR Storms

Hydrologic	Drainage Area	Peak Discharge	Time of Peak	Volume
Element	(MI2)	(CFS)		(IN)
P DA 1	0.165	389.6	01Jan2016, 12:26	6.17

Project: 15052 - CISF Simulation Run: PMP Dist A

Start of Run: 01Jan2016, 00:00 Basin Model: P AP 1 AMC II End of Run: 05Jan2016, 00:00 Meteorologic Model: PMP Distribution A

Compute Time: 08Mar2016, 13:00:27 Control Specifications:Control PMP

Hydrologic	Drainage Area	Peak Discharge	Time of Peak	Volume
Element	(MI2)	(CFS)		(IN)
P DA 1	0.165	440.2	03Jan2016, 06:00	37.48

Start of Run: 01Jan2016, 00:00 Basin Model: P AP 1 AMC III

End of Run: 02Jan2016, 12:00 Meteorologic Model: 100 yr

Compute Time: 08Mar2016, 13:02:04 Control Specifications:Control 24 HR Storms

Hydrologic	Drainage Area	Peak Discharge	Time of Peak	Volume
Element	(MI2)	(CFS)		(IN)
P DA 1	0.165	304.9	01Jan2016, 12:25	4.96

Start of Run: 01Jan2016, 00:00 Basin Model: P AP 1 AMC III

End of Run: 02Jan2016, 12:00 Meteorologic Model: 500 yr

Compute Time: 08Mar2016, 13:02:29 Control Specifications:Control 24 HR Storms

Hydrologic	Drainage Area	Peak Discharge	Time of Peak	Volume
Element	(MI2)	(CFS)		(IN)
P DA 1	0.165	460.2	01Jan2016, 12:25	7.63

Project: 15052 - CISF Simulation Run: PMP Dist A

Start of Run: 01Jan2016, 00:00 Basin Model: P AP 1 AMC III End of Run: 05Jan2016, 00:00 Meteorologic Model: PMP Distribution A

Compute Time: 08Mar2016, 13:03:05 Control Specifications:Control PMP

Hydrologic	Drainage Area	Peak Discharge	Time of Peak	Volume
Element	(MI2)	(CFS)		(IN)
P DA 1	0.165	443.0	03Jan2016, 06:00	39.34

Start of Run: 01Jan2016, 00:00 Basin Model: P AP 2 AMC I

End of Run: 02Jan2016, 12:00 Meteorologic Model: 100 yr

Compute Time: 08Mar2016, 14:18:56 Control Specifications:Control 24 HR Storms

Hydrologic Element	Drainage Area (MI2)	Peak Discharge (CFS)	Time of Peak	Volume (IN)
P DA 2	0.072	118.1	01Jan2016, 12:14	3.09
P DA 2 STORAGE	0.072	118.6	01Jan2016, 12:14	3.08

Start of Run: 01Jan2016, 00:00 Basin Model: P AP 2 AMC I

End of Run: 02Jan2016, 12:00 Meteorologic Model: 500 yr

Compute Time: 08Mar2016, 14:21:22 Control Specifications:Control 24 HR Storms

Hydrologic Element	Drainage Area (MI2)	Peak Discharge (CFS)	Time of Peak	Volume (IN)
P DA 2	0.072	209.2	01Jan2016, 12:13	5.44
P DA 2 STORAGE	0.072	209.9	01Jan2016, 12:13	5.42

Project: 15052 - CISF Simulation Run: PMP Dist A

Start of Run: 01Jan2016, 00:00 Basin Model: P AP 2 AMC I End of Run: 05Jan2016, 00:00 Meteorologic Model: PMP Distribution A

Compute Time: 08Mar2016, 14:21:46 Control Specifications:Control PMP

Hydrologic Element	Drainage Area (MI2)	Peak Discharge (CFS)	Time of Peak	Volume (IN)
P DA 2	0.072	191.1	03Jan2016, 06:00	36.38
P DA 2 STORAGE	0.072	191.1	03Jan2016, 06:00	36.37

Start of Run: 01Jan2016, 00:00 Basin Model: P AP 2 AMC II

End of Run: 02Jan2016, 12:00 Meteorologic Model: 100 yr

Compute Time: 08Mar2016, 14:22:36 Control Specifications:Control 24 HR Storms

Hydrologic Element	Drainage Area (MI2)	Peak Discharge (CFS)	Time of Peak	Volume (IN)
P DA 2	0.072	170.8	01Jan2016, 12:13	4.52
P DA 2 STORAGE	0.072	170.9	01Jan2016, 12:13	4.50

Start of Run: 01Jan2016, 00:00 Basin Model: P AP 2 AMC II

End of Run: 02Jan2016, 12:00 Meteorologic Model: 500 yr

Compute Time: 08Mar2016, 14:23:04 Control Specifications:Control 24 HR Storms

Hydrologic Element	Drainage Area (MI2)	Peak Discharge (CFS)	Time of Peak	Volume (IN)
P DA 2	0.072	264.8	01Jan2016, 12:13	7.14
P DA 2 STORAGE	0.072	265.3	01Jan2016, 12:13	7.11

Project: 15052 - CISF Simulation Run: PMP Dist A

Start of Run: 01Jan2016, 00:00 Basin Model: P AP 2 AMC II End of Run: 05Jan2016, 00:00 Meteorologic Model: PMP Distribution A

Compute Time: 08Mar2016, 14:23:26 Control Specifications:Control PMP

Hydrologic Element	Drainage Area (MI2)	Peak Discharge (CFS)	Time of Peak	Volume (IN)
P DA 2	0.072	193.1	03Jan2016, 06:00	38.76
P DA 2 STORAGE	0.072	193.1	03Jan2016, 06:00	38.75

Start of Run: 01Jan2016, 00:00 Basin Model: P AP 2 AMC III

End of Run: 02Jan2016, 12:00 Meteorologic Model: 100 yr

Compute Time: 08Mar2016, 14:24:13 Control Specifications:Control 24 HR Storms

Hydrologic Element	Drainage Area (MI2)	Peak Discharge (CFS)	Time of Peak	Volume (IN)
P DA 2	0.072	193.2	01Jan2016, 12:12	5.41
P DA 2 STORAGE	0.072	194.1	01Jan2016, 12:12	5.40

Start of Run: 01Jan2016, 00:00 Basin Model: P AP 2 AMC III

End of Run: 02Jan2016, 12:00 Meteorologic Model: 500 yr

Compute Time: 08Mar2016, 14:24:59 Control Specifications:Control 24 HR Storms

Hydrologic Element	Drainage Area (MI2)	Peak Discharge (CFS)	Time of Peak	Volume (IN)
P DA 2	0.072	284.4	01Jan2016, 12:12	8.11
P DA 2 STORAGE	0.072	284.6	01Jan2016, 12:13	8.08

Project: 15052 - CISF Simulation Run: PMP Dist A

Start of Run: 01Jan2016, 00:00 Basin Model: P AP 2 AMC III End of Run: 05Jan2016, 00:00 Meteorologic Model: PMP Distribution A

Compute Time: 08Mar2016, 14:25:18 Control Specifications:Control PMP

Hydrologic Element	Drainage Area (MI2)	Peak Discharge (CFS)	Time of Peak	Volume (IN)
P DA 2	0.072	193.5	03Jan2016, 06:00	39.88
P DA 2 STORAGE	0.072	193.5	03Jan2016, 05:59	39.86

Start of Run: 01Jan2016, 00:00 Basin Model: P AP 3 AMC I

End of Run: 02Jan2016, 12:00 Meteorologic Model: 100 yr

Compute Time: 08Mar2016, 14:26:47 Control Specifications:Control 24 HR Storms

Hydrologic Element	Drainage Area (MI2)	Peak Discharge (CFS)	Time of Peak	Volume (IN)
P DA 3	0.067	127.5	01Jan2016, 12:12	3.38
P DA 4	1.054	766.4	01Jan2016, 12:44	2.53
P DA 3 STORAGE	0.067	0.0	01Jan2016, 00:00	0.00
PLAYA	1.121	0.0	01Jan2016, 00:00	0.00

Start of Run: 01Jan2016, 00:00 Basin Model: P AP 3 AMC I

End of Run: 02Jan2016, 12:00 Meteorologic Model: 500 yr

Compute Time: 08Mar2016, 14:27:33 Control Specifications:Control 24 HR Storms

Hydrologic Element	Drainage Area (MI2)	Peak Discharge (CFS)	Time of Peak	Volume (IN)
P DA 3	0.067	218.2	01Jan2016, 12:11	5.81
P DA 4	1.054	1472.6	01Jan2016, 12:42	4.72
P DA 3 STORAGE	0.067	0.0	01Jan2016, 00:00	0.00
PLAYA	1.121	0.0	01Jan2016, 00:00	0.00

Project: 15052 - CISF Simulation Run: PMP Dist A

Start of Run: 01Jan2016, 00:00 Basin Model: P AP 3 AMC I End of Run: 05Jan2016, 00:00 Meteorologic Model: PMP Distribution A

Compute Time: 08Mar2016, 14:27:51 Control Specifications:Control PMP

Hydrologic Element	Drainage Area (MI2)	Peak Discharge (CFS)	Time of Peak	Volume (IN)
P DA 3	0.067	178.4	03Jan2016, 06:00	36.94
P DA 4	1.054	2763.2	03Jan2016, 06:01	35.14
P DA 3 STORAGE	0.067	178.3	03Jan2016, 06:01	29.18
PLAYA	1.121	2845.2	03Jan2016, 06:20	26.60

Start of Run: 01Jan2016, 00:00 Basin Model: P AP 3 AMC II

End of Run: 02Jan2016, 12:00 Meteorologic Model: 100 yr

Compute Time: 08Mar2016, 14:28:38 Control Specifications:Control 24 HR Storms

Hydrologic Element	Drainage Area (MI2)	Peak Discharge (CFS)	Time of Peak	Volume (IN)
P DA 3	0.067	173.8	01Jan2016, 12:11	4.74
P DA 4	1.054	1283.9	01Jan2016, 12:41	4.09
P DA 3 STORAGE	0.067	0.0	01Jan2016, 00:00	0.00
PLAYA	1.121	0.0	01Jan2016, 00:00	0.00

Start of Run: 01Jan2016, 00:00 Basin Model: P AP 3 AMC II

End of Run: 02Jan2016, 12:00 Meteorologic Model: 500 yr

Compute Time: 08Mar2016, 14:29:01 Control Specifications:Control 24 HR Storms

Hydrologic Element	Drainage Area (MI2)	Peak Discharge (CFS)	Time of Peak	Volume (IN)
P DA 3	0.067	265.4	01Jan2016, 12:11	7.38
P DA 4	1.054	2068.0	01Jan2016, 12:40	6.66
P DA 3 STORAGE	0.067	0.0	01Jan2016, 00:00	0.00
PLAYA	1.121	4.0	02Jan2016, 01:57	0.08

Start of Run: 01Jan2016, 00:00 Basin Model: P AP 3 AMC II End of Run: 05Jan2016, 00:00 Meteorologic Model: PMP Distribution A

Compute Time: 08Mar2016, 14:29:19 Control Specifications:Control PMP

Hydrologic Element	Drainage Area (MI2)	Peak Discharge (CFS)	Time of Peak	Volume (IN)
P DA 3	0.067	179.8	03Jan2016, 06:00	39.05
P DA 4	1.054	2818.9	03Jan2016, 06:00	38.14
P DA 3 STORAGE	0.067	179.8	03Jan2016, 06:00	31.29
PLAYA	1.121	2957.6	03Jan2016, 06:14	29.55

Start of Run: 01Jan2016, 00:00 Basin Model: P AP 3 AMC III

End of Run: 02Jan2016, 12:00 Meteorologic Model: 100 yr

Compute Time: 08Mar2016, 14:31:12 Control Specifications:Control 24 HR Storms

Hydrologic Element	Drainage Area (MI2)	Peak Discharge (CFS)	Time of Peak	Volume (IN)
P DA 3	0.067	191.1	01Jan2016, 12:11	5.53
P DA 4	1.054	1564.3	01Jan2016, 12:40	5.18
P DA 3 STORAGE	0.067	0.0	01Jan2016, 00:00	0.00
PLAYA	1.121	0.0	01Jan2016, 00:00	0.00

Start of Run: 01Jan2016, 00:00 Basin Model: P AP 3 AMC III

End of Run: 02Jan2016, 12:00 Meteorologic Model: 500 yr

Compute Time: 08Mar2016, 14:31:32 Control Specifications:Control 24 HR Storms

Hydrologic Element	Drainage Area (MI2)	Peak Discharge (CFS)	Time of Peak	Volume (IN)
P DA 3	0.067	279.9	01Jan2016, 12:11	8.23
P DA 4	1.054	2331.4	01Jan2016, 12:40	7.87
P DA 3 STORAGE	0.067	2.7	02Jan2016, 00:18	0.41
PLAYA	1.121	16.7	02Jan2016, 01:21	0.37

Start of Run: 01Jan2016, 00:00 Basin Model: P AP 3 AMC III End of Run: 05Jan2016, 00:00 Meteorologic Model: PMP Distribution A

Compute Time: 08Mar2016, 14:31:51 Control Specifications:Control PMP

Hydrologic Element	Drainage Area (MI2)	Peak Discharge (CFS)	Time of Peak	Volume (IN)
P DA 3	0.067	180.1	03Jan2016, 06:00	40.00
P DA 4	1.054	2830.9	03Jan2016, 06:00	39.61
P DA 3 STORAGE	0.067	180.0	03Jan2016, 05:58	32.24
PLAYA	1.121	2985.6	03Jan2016, 06:11	30.99

Reservoir: PLAYA

Start of Run: 01Jan2016, 00:00 Basin Model: P AP 3 AMC I

End of Run: 02Jan2016, 12:00 Meteorologic Model: 100 yr

Compute Time: 08Mar2016, 14:32:37 Control Specifications: Control 24 HR Storms

Volume Units: N

Computed Results

Peak Inflow:766.4 (CFS)Date/Time of Peak Inflow:01Jan2016, 12:44Peak Discharge:0.0 (CFS)Date/Time of Peak Discharge:01Jan2016, 00:00Inflow Volume:2.38 (IN)Peak Storage:142.2 (AC-FT)Discharge Volume:0.00 (IN)Peak Elevation:3484.4 (FT)

Reservoir: PLAYA

Start of Run: 01Jan2016, 00:00 Basin Model: P AP 3 AMC I

End of Run: 02Jan2016, 12:00 Meteorologic Model: 500 yr

Compute Time: 08Mar2016, 14:34:06 Control Specifications: Control 24 HR Storms

Volume Units: N

Computed Results

Peak Inflow:1472.6 (CFS)Date/Time of Peak Inflow:01Jan2016, 12:42Peak Discharge:0.0 (CFS)Date/Time of Peak Discharge:01Jan2016, 00:00Inflow Volume:4.44 (IN)Peak Storage:265.2 (AC-FT)Discharge Volume:0.00 (IN)Peak Elevation:3485.7 (FT)

Reservoir: PLAYA

Start of Run: 01Jan2016, 00:00 Basin Model: P AP 3 AMC I End of Run: 05Jan2016, 00:00 Meteorologic Model: PMP Distribution A

Compute Time: 08Mar2016, 14:34:27 Control Specifications: Control PMP

Volume Units: N

Computed Results

Peak Inflow:2941.5 (CFS)Date/Time of Peak Inflow:03Jan2016, 06:01Peak Discharge:2845.2 (CFS)Date/Time of Peak Discharge:03Jan2016, 06:20Inflow Volume:34.78 (IN)Peak Storage:887.4 (AC-FT)Discharge Volume:26.60 (IN)Peak Elevation:3488.8 (FT)

Reservoir: PLAYA

Start of Run: 01Jan2016, 00:00 Basin Model: P AP 3 AMC II

End of Run: 02Jan2016, 12:00 Meteorologic Model: 100 yr

Compute Time: 08Mar2016, 14:37:10 Control Specifications: Control 24 HR Storms

Volume Units: N

Computed Results

Peak Inflow:1283.9 (CFS)Date/Time of Peak Inflow:01Jan2016, 12:41Peak Discharge:0.0 (CFS)Date/Time of Peak Discharge:01Jan2016, 00:00Inflow Volume:3.85 (IN)Peak Storage:230.0 (AC-FT)Discharge Volume:0.00 (IN)Peak Elevation:3485.3 (FT)

Reservoir: PLAYA

Start of Run: 01Jan2016, 00:00 Basin Model: P AP 3 AMC II

End of Run: 02Jan2016, 12:00 Meteorologic Model: 500 yr

Compute Time: 08Mar2016, 14:35:39 Control Specifications: Control 24 HR Storms

Volume Units: N

Computed Results

Peak Inflow:2068.0 (CFS)Date/Time of Peak Inflow:01Jan2016, 12:40Peak Discharge:4.0 (CFS)Date/Time of Peak Discharge:02Jan2016, 01:57Inflow Volume:6.26 (IN)Peak Storage:372.5 (AC-FT)Discharge Volume:0.08 (IN)Peak Elevation:3486.5 (FT)

Reservoir: PLAYA

Start of Run: 01Jan2016, 00:00 Basin Model: P AP 3 AMC II
End of Run: 05Jan2016, 00:00 Meteorologic Model: PMP Distribution A

Compute Time: 08Mar2016, 14:35:56 Control Specifications: Control PMP

Volume Units: N

Computed Results

 Peak Inflow:
 2998.6 (CFS)
 Date/Time of Peak Inflow:
 03Jan2016, 06:00

 Peak Discharge:
 2957.6 (CFS)
 Date/Time of Peak Discharge:
 03Jan2016, 06:14

 Inflow Volume:
 37.73 (IN)
 Peak Storage:
 893.8 (AC-FT)

 Discharge Volume:
 29.55 (IN)
 Peak Elevation:
 3488.8 (FT)

Reservoir: PLAYA

Start of Run: 01Jan2016, 00:00 Basin Model: P AP 3 AMC III

End of Run: 02Jan2016, 12:00 Meteorologic Model: 100 yr

Compute Time: 08Mar2016, 14:39:29 Control Specifications: Control 24 HR Storms

Volume Units: N

Computed Results

Peak Inflow:1564.3 (CFS)Date/Time of Peak Inflow:01Jan2016, 12:40Peak Discharge:0.0 (CFS)Date/Time of Peak Discharge:01Jan2016, 00:00Inflow Volume:4.87 (IN)Peak Storage:291.3 (AC-FT)Discharge Volume:0.00 (IN)Peak Elevation:3486.0 (FT)

Reservoir: PLAYA

Start of Run: 01Jan2016, 00:00 Basin Model: P AP 3 AMC III

End of Run: 02Jan2016, 12:00 Meteorologic Model: 500 yr

Compute Time: 08Mar2016, 14:40:07 Control Specifications: Control 24 HR Storms

Volume Units: N

Computed Results

Peak Inflow:2331.4 (CFS)Date/Time of Peak Inflow:01Jan2016, 12:40Peak Discharge:16.7 (CFS)Date/Time of Peak Discharge:02Jan2016, 01:21Inflow Volume:7.42 (IN)Peak Storage:433.6 (AC-FT)Discharge Volume:0.37 (IN)Peak Elevation:3486.8 (FT)

Reservoir: PLAYA

Start of Run: 01Jan2016, 00:00 Basin Model: P AP 3 AMC III
End of Run: 05Jan2016, 00:00 Meteorologic Model: PMP Distribution A

Compute Time: 08Mar2016, 14:40:29 Control Specifications: Control PMP

Volume Units: N

Computed Results

Peak Inflow:3010.9 (CFS)Date/Time of Peak Inflow:03Jan2016, 06:00Peak Discharge:2985.6 (CFS)Date/Time of Peak Discharge:03Jan2016, 06:11Inflow Volume:39.17 (IN)Peak Storage:895.3 (AC-FT)Discharge Volume:30.99 (IN)Peak Elevation:3488.9 (FT)



APPENDIX E HEC-HMS INPUT (CD)