



BECHTEL PROJECT NO.: 25161				MACTEC PROJECT NO.: 6468-09-2473				COUNTY: Louisa, VA				GEOLOGIST: C. Baldwin			
SITE DESCRIPTION: North Anna Power Station, Unit 3								DRILLER: D. Rhodes				FLUID LEVEL (ft)			
BORING NO.: W-2				DRILL METHOD: Mud Rotary/Rock Core				DRILL MACHINE: CME-45C Track (RAL)				0 HR.		NA	
GROUND ELEV.: 298.4 ft (NAVD88)				NORTHING: 3,909,822 US ft (NAD83)				EASTING: 11,685,864 US ft (NAD83)				24 HR.		16.0	
TOTAL DEPTH: 143.3 ft		SAMPLE METHODS: ASTM D 1586-08a; 2488-09a; 2113-08; 6032-08						ROD TYPE: AWJ		HAMMER (ID): 140-lb. Auto (MEC-12)					
DATE STARTED: 10/27/09		COMPLETED: 10/30/09		HOLE DIA.: 3"		CASING DEPTH: 20.8 ft		CORE SIZE: NQ3		BITS USED: 2-7/8" Tri-Cone					
ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT					SAMP. NO.	LOG	SOIL AND ROCK DESCRIPTION			
		0.5ft	0.5ft	0.5ft	0	20	40	60	80				100		
298.4					Ground Surface							298.4	0.0		
289.9	8.5	5	6	8						SS-1		289.9	8.5		
287.8	10.6	8	10	10						SS-2		287.8			
284.9	13.5	8	15	14						SS-3		284.9			
279.9	18.5	14	12	100/0.3						SS-4		279.9	18.5		
275.6	22.8	50/0.0			SS-5	275.6	22.8								
<p>44.0 ft: complete loss of drill fluid circulation to formation</p> <p>HARD ROCK: Grayish brown to gray with trace orange staining, moderately to slightly weathered, very close to moderately close fracturing, moderately hard to hard, BIOTITE QUARTZ GNEISS</p>													252.3	46.1	

BECHTEL PROJECT NO.: 25161		MACTEC PROJECT NO.: 6468-09-2473		COUNTY: Louisa, VA		GEOLOGIST: C. Baldwin	
SITE DESCRIPTION: North Anna Power Station, Unit 3				DRILLER: D. Rhodes		FLUID LEVEL (ft)	
BORING NO.: W-2		DRILL METHOD: Mud Rotary/Rock Core		DRILL MACHINE: CME-45C Track (RAL)		0 HR.	NA
GROUND ELEV.: 298.4 ft (NAVD88)		NORTHING: 3,909,822 US ft (NAD83)		EASTING: 11,685,864 US ft (NAD83)		24 HR.	16.0
TOTAL DEPTH: 143.3 ft		SAMPLE METHODS: ASTM D 1586-08a; 2488-09a; 2113-08; 6032-08			ROD TYPE: AWJ		HAMMER (ID): 140-lb. Auto (MEC-12)
DATE STARTED: 10/27/09		COMPLETED: 10/30/09	HOLE DIA.: 3"	CASING DEPTH: 20.8 ft	CORE SIZE: NQ3	BITS USED: 2-7/8" Tri-Cone	

ELEV. (ft)	DEPTH (ft)	BLOW COUNT			BLOWS PER FOOT	SAMP. NO.	MOI	LOG	SOIL AND ROCK DESCRIPTION
		0.5ft	0.5ft	0.5ft					
223.6					Continued from previous page				
									HARD ROCK: Grayish brown to gray with trace orange staining, moderately to slightly weathered, very close to moderately close fracturing, moderately hard to hard, BIOTITE QUARTZ GNEISS (continued)
								212.3	86.1 HARD ROCK: Gray and light gray with trace orange staining, slightly to very slightly weathered, very close to wide fracturing, hard to very hard, BIOTITE QUARTZ GNEISS
								155.1	143.3 Boring and coring terminated at 143.3 ft. Note: Boring and coring terminated before 150 feet was reached due to broken core bit in hole. Boring closed by tremie method with cement-bentonite grout.

NORTH ANNA 3 BORE NORTH ANNA 3 PROJECT.GPJ NORTH ANNA 3.GDT 12/3/09



BECHTEL PROJECT NO.: 25161		MACTEC PROJECT NO.: 6468-09-2473		COUNTY: Louisa, VA	GEOLOGIST: C. Baldwin	
SITE DESCRIPTION: North Anna Power Station, Unit 3				DRILLER: D. Rhodes		FLUID LEVEL (ft) 0 HR. NA 24 HR. 16.0
BORING NO.: W-2		DRILL METHOD: Mud Rotary/Rock Core		DRILL MACHINE: CME-45C Track (RAL)		
GROUND ELEV.: 298.4 ft (NAVD88)		NORTHING: 3,909,822 US ft (NAD83)		EASTING: 11,685,864 US ft (NAD83)		
TOTAL DEPTH: 143.3 ft		SAMPLE METHODS: ASTM D 1586-08a; 2488-09a; 2113-08; 6032-08				HAMMER (ID): 140-lb. Auto (MEC-12)
DATE STARTED: 10/27/09		COMPLETED: 10/30/09	CASING DEPTH: 20.8 ft	CORE BARREL TYPE: Wireline NQ3 Triple Tube, series 6 & 10 bits		

ELEV. (ft)	DEPTH (ft)	RUN (ft)	DRILL RATE (Min/ft)	RUN		SAMP. NO.	STRATA		L O G	DESCRIPTION AND REMARKS
				REC. (ft) %	RQD (ft) %		REC. (ft) %	RQD (ft) %		
										Begin Coring @ 22.8 ft
275.6	22.8	3.3	N=50/0.0 1:07/0.3 3:54 4:10	(3.3) 100%	(3.3) 100%	RUN 1	(19.5) 84%	(15.4) 66%	275.6	HARD ROCK: Light gray to grayish brown with orange staining, moderately severe to moderately weathered, very close to close fracturing, medium to moderately hard, BIOTITE QUARTZ GNEISS (1 joint at 10°, tight; 1 joint at 50°, tight; 1 joint at 70°, tight) (3 joints at 0-10°, tight; 1 joint at 30°, open)
272.3	26.1	5.0	6:00	(4.3) 86%	(3.6) 72%	RUN 2				
267.3	31.1	5.0	2:57 1:24 1:54 1:33 1:20	(4.7) 94%	(2.8) 56%	RUN 3				(3 joints at 0-10°, open; 2 joints at 30°, tight; 2 joints at 50°, tight; 2 joints at 70-80°, tight)
262.3	36.1	5.0	1:50 1:28 1:26 1:57 2:40	(2.6) 52%	(1.8) 36%	RUN 4				(2 joints at 0-10°, tight; 3 joints at 20-30°, tight to open)
257.3	41.1	5.0	1:54 1:24 1:41 11:02 2:27	(4.6) 92%	(3.9) 78%	RUN 5				(1 joint at 20°, tight; 1 joint at 20°, open; 1 joint at 40°, open; 1 joint at 80-90°, tight)
252.3	46.1	5.0	2:08 1:52 2:00 2:58 2:29	(5.0) 100%	(4.2) 84%	RUN 6	(38.5) 96%	(32.6) 82%	252.3	44.0 ft: complete loss of drill fluid circulation to formation
247.3	51.1	5.0	3:03 3:00 4:02 4:28 4:20	(5.0) 100%	(4.1) 82%	RUN 7				HARD ROCK: Grayish brown to gray with trace orange staining, moderately to slightly weathered, very close to moderately close fracturing, moderately hard to hard, BIOTITE QUARTZ GNEISS (7 joints at 0-10°, tight; 1 joint at 70°, tight)
242.3	56.1	5.0	3:17 2:52 1:53 2:20 2:46	(5.0) 100%	(5.0) 100%	RUN 8				(6 joints at 0-10°, tight; 1 joint at 30°, tight)
237.3	61.1	5.0	4:16 3:07 4:09 3:07 3:40	(5.0) 100%	(4.2) 84%	RUN 9				(1 joint at 0°, tight; 2 joints at 20°, tight)
232.3	66.1	5.0	2:35 1:33 1:43 2:06 1:37	(4.7) 94%	(3.5) 70%	RUN 10				(10 joints at 20-30°, tight; 1 joint at 50°, tight)
227.3	71.1	5.0	2:42 2:18 2:34 2:12 2:26	(5.0) 100%	(4.4) 88%	RUN 11				(4 joints at 0-10°, tight to open; 2 joints at 20°, tight; 1 joint at 50°, tight; 1 quartz vein 0.1 feet thick at 67.9 ft at 45°)
222.3	76.1	5.0	3:15 3:37 3:10 2:43 2:39	(5.0) 100%	(4.2) 84%	RUN 12				(2 joints at 0-10°, tight; 6 joints at 50-60°, tight)
217.3	81.1	5.0	2:35 2:14 2:40 3:02 3:22	(5.0) 100%	(3.0) 60%	RUN 13				(1 joint at 0°, tight; 4 joints at 20-30°, tight; 1 joint at 70°, tight)
212.3	86.1	5.0	3:23 3:06 1:09 1:17 2:10	(3.8) 76%	(4.9) 98%	RUN 14	(57.1) 100%	(54.4) 95%	212.3	(3 joints at 30°, tight; 3 joints at 50°, tight)
207.3	91.1	5.0	2:11 3:16 3:39 5:36 7:40	(4.9) 98%	(4.3) 86%	RUN 15				HARD ROCK: Gray and light gray with trace orange staining, slightly to very slightly weathered, very close to wide fracturing, hard to very hard, BIOTITE QUARTZ GNEISS (3 joints at 40-50°, tight)
202.3	96.1	5.0	3:24 2:58 3:46 2:16 2:42	(5.0) 100%	(4.4) 88%	RUN 16				(5 joints at 0-10°, tight; 1 joint at 20°, tight; 1 joint at 70°, tight)
		5.0	3:25	(5.0)	(4.4)	RUN 16				(5 joints at 0-10°, tight; 3 joints at 50-60°, tight)

NORTH ANNA 3 CORE NORTH ANNA 3 PROJECT.GPJ NORTH ANNA 3.GDT 12/3/09



SHEET 2 OF 2


BECHTEL PROJECT NO.: 25161	MACTEC PROJECT NO.: 6468-09-2473	COUNTY: Louisa, VA	GEOLOGIST: C. Baldwin
SITE DESCRIPTION: North Anna Power Station, Unit 3		DRILLER: D. Rhodes	FLUID LEVEL (ft)
BORING NO.: W-2	DRILL METHOD: Mud Rotary/Rock Core	DRILL MACHINE: CME-45C Track (RAL)	0 HR. NA
GROUND ELEV.: 298.4 ft (NAVD88)	NORTHING: 3,909,822 US ft (NAD83)	EASTING: 11,685,864 US ft (NAD83)	24 HR. 16.0
TOTAL DEPTH: 143.3 ft	SAMPLE METHODS: ASTM D 1586-08a; 2488-09a; 2113-08; 6032-08		HAMMER (ID): 140-lb. Auto (MEC-12)
DATE STARTED: 10/27/09	COMPLETED: 10/30/09	CASING DEPTH: 20.8 ft	CORE BARREL TYPE: Wireline NQ3 Triple Tube, series 6 & 10 bits

ELEV. (ft)	DEPTH (ft)	RUN (ft)	DRILL RATE (Min/ft)	RUN		SAMP. NO.	STRATA		L O G	DESCRIPTION AND REMARKS
				REC. (ft) %	RQD (ft) %		REC. (ft) %	RQD (ft) %		
										Continued from previous page
197.3	101.1		3:17 3:13 4:45 4:34	100%	88%					HARD ROCK: Gray and light gray with trace orange staining, slightly to very slightly weathered, very close to wide fracturing, hard to very hard, BIOTITE QUARTZ GNEISS (<i>continued</i>)
		5.0	3:46 3:30 3:27 2:30 3:04	(5.0) 100%	(5.0) 100%	RUN 17				(2 joints at 0°, tight; 2 joints at 60-70°, tight)
192.3	106.1	5.0	3:41 3:42 5:08 5:35 6:07	(5.0) 100%	(5.0) 100%	RUN 18				(1 joint at 40°, tight)
187.3	111.1	5.0	6:16 5:29 6:13 6:55 7:50	(5.0) 100%	(4.7) 94%	RUN 19				(1 joint at 30°, tight; 3 joints at 50-60°, tight)
182.3	116.1	5.0	3:35 2:59 3:14 2:47 2:24	(5.0) 100%	(5.0) 100%	RUN 20				(2 joints at 20-30°, tight)
177.3	121.1	5.0	2:40 2:39 1:59 1:54 1:48	(5.0) 100%	(4.7) 94%	RUN 21				(2 joints at 10°, tight; 4 joints at 20-30°, tight)
172.3	126.1	5.0	2:14 2:15 2:33 2:41 3:00	(5.0) 100%	(4.7) 94%	RUN 22				(2 joints at 20°, tight to open; 1 joint at 80°, tight)
167.3	131.1	5.0	3:53 2:48 2:43 2:52 3:09	(5.0) 100%	(4.7) 94%	RUN 23				(2 joints at 40°, tight; 1 joint at 60°, tight)
162.3	136.1	5.0	3:16 3:06 3:23 3:24 2:57	(5.0) 100%	(5.0) 100%	RUN 24				(1 joint at 0°, tight; 1 joint at 50°, tight)
157.3	141.1	2.2	6:37 4:00 3:44/0.2	(2.2) 100%	(2.0) 91%	RUN 25				(2 joints at 30°, open)
155.1	143.3								155.1	143.3 Boring and coring terminated at 143.3 ft. Note: Boring and coring terminated before 150 feet was reached due to broken core bit in hole. Boring closed by tremie method with cement-bentonite grout. 24 hour water level measured on 10/30/2009 prior to drilling. Borehole was at a depth of 141.1 feet.

NORTH ANNA 3 CORE NORTH ANNA 3 PROJECT.GPJ NORTH ANNA 3.GDT 12/3/09




W-2- Box 1




W-2- Box 2




W-2- Box 3




W-2- Box 4



W-2 - Box 5



W-2 - Box 6



W-2 - Box 7