

CHAPTER 2 SITE CHARACTERISTICS

Table of Contents

2.	<i>SITE CHARACTERISTICS.....</i>	<i>2-1</i>
2.1	<i>Geography and Demography of Site Selected.....</i>	<i>2-2</i>
2.2	<i>Nearby Industrial, Transportation and Military Facilities</i>	<i>2-5</i>
2.3	<i>Meteorology.....</i>	<i>2-6</i>
2.3.1	<i>Regional Climatology</i>	<i>2-6</i>
2.3.2	<i>Local Meteorology.....</i>	<i>2-6</i>
2.3.3	<i>Onsite Meteorological Data</i>	<i>2-7</i>
2.3.4	<i>On-Site Meteorological Measurement Program</i>	<i>2-12</i>
2.3.5	<i>Diffusion Estimates</i>	<i>2-12</i>
2.4	<i>Surface Hydrology</i>	<i>2-14</i>
2.4.1	<i>Hydrologic Description</i>	<i>2-14</i>
2.4.2	<i>Floods</i>	<i>2-17</i>
2.4.3	<i>Probable Maximum Flood on Streams and Rivers</i>	<i>2-19</i>
2.4.4	<i>Potential Dam Failures (Seismically Induced).....</i>	<i>2-19</i>
2.4.5	<i>Probable Maximum Surge and Seiche Flooding</i>	<i>2-19</i>
2.4.6	<i>Probable Maximum Tsunami Flooding.....</i>	<i>2-19</i>
2.4.7	<i>Ice Flooding.....</i>	<i>2-19</i>
2.4.8	<i>Flooding Protection Requirements</i>	<i>2-20</i>
2.4.9	<i>Environmental Acceptance of Effluents</i>	<i>2-20</i>
2.5	<i>Subsurface Hydrology.....</i>	<i>2-21</i>
2.5.1	<i>Salt Dissolution and Sink Holes.....</i>	<i>2-25</i>
2.6	<i>Geology And Seismology</i>	<i>2-26</i>
2.6.1	<i>Basic Geologic and Seismic Information.....</i>	<i>2-26</i>
2.6.2	<i>Vibratory Ground Motion.....</i>	<i>2-28</i>
2.6.3	<i>Surface Faulting.....</i>	<i>2-30</i>
2.6.4	<i>Stability of Subsurface Materials.....</i>	<i>2-32</i>
2.6.5	<i>Slope Stability</i>	<i>2-34</i>
2.6.6	<i>Volcanism.....</i>	<i>2-34</i>

2.7	<i>Summary Of Site Conditions Affecting Construction And Operating Requirements.....</i>	<i>2-35</i>
2.8	<i>References</i>	<i>2-36</i>

<i>Attachment A</i>	<i>Meteorological Data from WCS On-Site Weather Stations</i>	<i>A-1</i>
<i>Attachment B</i>	<i>Flood Plain Report.....</i>	<i>B-1</i>
<i>Attachment C</i>	<i>Boring Logs.....</i>	<i>C-1</i>
<i>Attachment D</i>	<i>Seismic Hazard Evaluation for WCS CISF.....</i>	<i>D-1</i>
<i>Attachment E</i>	<i>Geotechnical Investigation for WCS CISF.....</i>	<i>E-1</i>
<i>Attachment F</i>	<i>Evaluation of Halite Dissolution in the Vicinity of Waste Control Specialists Disposal Site, Andrews County, TX</i>	<i>F-1</i>
<i>Attachment G</i>	<i>Technical Specifications for Towers</i>	<i>G-1</i>
<i>Attachment H</i>	<i>Compiled Meteorological and Climatology Data.....</i>	<i>H-1</i>

List of Tables

<i>Table 2-1</i>	<i>Weather Stations Located Near the WCS CISF</i>	<i>2-39</i>
<i>Table 2-2</i>	<i>Summary of Maximum and Minimum Temperatures for Andrews, TX Period of Record: 1962 to 2010.....</i>	<i>2-40</i>
<i>Table 2-3</i>	<i>Andrews, TX Period of Record Precipitation Data (1914-2006)</i>	<i>2-41</i>
<i>Table 2-4</i>	<i>Andrews, TX Period of Record Snow Data (1914-2006).....</i>	<i>2-42</i>
<i>Table 2-5</i>	<i>Average Morning and Afternoon Mixing Heights for Midland-Odessa, Texas</i>	<i>2-43</i>
<i>Table 2-6</i>	<i>EPA National Ambient Air Quality Standards.....</i>	<i>2-44</i>
<i>Table 2-7</i>	<i>Atmospheric Dispersion Coefficients.....</i>	<i>2-45</i>
<i>Table 2-8</i>	<i>Projected Populations Based on Annual Percentage Growth Rate of 0.55%</i>	<i>2-46</i>
<i>Table 2-9</i>	<i>Projected Populations Based on Annual Percentage Growth Rate of 2.4%.....</i>	<i>2-47</i>
<i>Table 2-10</i>	<i>Projected Populations Based on Annual Percentage Growth Rate of 1.2%.....</i>	<i>2-48</i>
<i>Table 2-11</i>	<i>Meteorological Tower Measurements</i>	<i>2-49</i>
<i>Table 2-12</i>	<i>Meteorological Tower Sensors</i>	<i>2-50</i>
<i>Table 2-13</i>	<i>Summary of Maximum, Minimum, and 3-Day Average Temperatures (°F) for Midland-Odessa, TX Period of Record: 2000-2015</i>	<i>2-51</i>

List of Figures

Figure 2-1	WCS Facility Site Plan.....	2-52
Figure 2-2	WCS Facility Site Plan.....	2-53
Figure 2-3	Proposed WCS CISF 1-mile Radius	2-54
Figure 2-4	Wind Rose Location Map.....	2-55
Figure 2-5	WCS Wind Rose Plot: Tower 1	2-56
Figure 2-6	WCS Wind Rose Plot: ER Tower	2-57
Figure 2-7	WCS Wind Rose Plot: WeatherHawk East	2-58
Figure 2-8	WCS Wind Rose Plot: WeatherHawk West.....	2-59
Figure 2-9	Wetlands Inventory	2-60
Figure 2-10	OAG Groundwater Elevation Near the Proposed WCS CISF.....	2-61
Figure 2-11	North to South Geologic Cross Section Showing Relationship of Ogallala Formation to Underlying Strata	2-62
Figure 2-12	West to East Geologic Cross Section Showing Relationship of Ogallala Formation to Underlying Strata	2-63
Figure 2-13	Stratigraphic Column Central Basin Platform.....	2-64
Figure 2-14	Geologic Atlas of Texas, Hobbs Sheet.....	2-65
Figure 2-15	Boring Locations in the Vicinity of the WCS CISF.....	2-72
Figure 2-16	WCS CISF Cross Section West-East.....	2-73
Figure 2-17	WCS CISF Cross Section South-North	2-74
Figure 2-18	Texas Regional Seismicity 1973 to January 31, 2015	2-75
Figure 2-19	Present Population Distribution within 5 Miles of WCS.....	2-76
Figure 2-20	Projected Population Distribution within 5 Miles of WCS.....	2-77
Figure 2-21	Tower 1 Located South of the WCS Guard House.....	2-78
Figure 2-22	ER Tower Located on the North Side of the WCS Federal Waste Facility.....	2-79
Figure 2-23	WeatherHawk East Located on the East Side of the Permitted Area for WCS (North of the Rail Loop).....	2-80
Figure 2-24	WeatherHawk West Located West of the WCs LSA Pad Next to State Line Road	2-81
Figure 2-25	Project Location-Road Base	2-82
Figure 2-26	CJI C-1 Cross Section Layout.....	2-83
Figure 2-27	CJI C-2 Collection Ditches A & B Cross Section.....	2-84
Figure 2-28	CJI C-3 Collection Ditch A Plan & Profile	2-85
Figure 2-29	CJI C-4 Collection Ditch B Plan & Profile STA. 0+00 – STA. 12+25	2-86

<i>Figure 2-30</i>	<i>CJI C-5 Collection Ditch B Plan & Profile STA. 12+25 – STA 23+74.12</i>	<i>2-87</i>
<i>Figure 2-31</i>	<i>CJI C-6 Cross Section A-A' STA. 0+00 – STA. 19+00</i>	<i>2-88</i>
<i>Figure 2-32</i>	<i>CJI C-7 Cross Section A-A' STA. 19+00 – STA. 38+39</i>	<i>2-89</i>
<i>Figure 2-33</i>	<i>CJI C-8 Cross Section B-B' STA. 0+00 – STA.25+25</i>	<i>2-90</i>
<i>Figure 2-34</i>	<i>CJI C9 Cross Section C-C</i>	<i>2-91</i>
<i>Figure 2-35</i>	<i>Developed Drainage Area Map</i>	<i>2-92</i>

2. SITE CHARACTERISTICS

Waste Control Specialists LLC (WCS) controls approximately 14,000 acres of land in northwestern Andrews County. Within this property, WCS currently operates a commercial waste management facility on approximately 1,338 acres of land (the existing facility) and the remaining acreage is mostly undeveloped land. The WCS CISF will be located north and adjacent to the existing facility approximately 300 meters from the north edge of the rail loop as seen in Figure 2-1. The approximate coordinates for Phase I of the WCS CISF site are latitude 32° 27' 08" north longitude 103° 03' 35" west longitude. The existing maximum and minimum elevations of the site are about 3520 feet and 3482 feet mean sea level (msl), respectively. Eunice, the closest *community*, is located approximately 8 kilometers (5 miles) west at the cross-junction of New Mexico Highways 207 and 234. The WCS CISF is about 51 kilometers (32 miles) northwest of Andrews, Texas, and approximately 32 kilometers (20 miles) south of Hobbs, New Mexico. The nearest population center with an international airport is Midland-Odessa, located 103 kilometers (64 miles) southeast of the proposed WCS CISF.

More generally, the WCS CISF site is located at the southwestern edge of the Southern High Plains. This part of Andrews County is a gently southeastward sloping plain with a natural slope of about 8 to 10 feet per mile. A topographic map of the area is shown in Figure 2-2.

The WCS site has two approved Resource Conservation and Recovery Act (RCRA) permits from the TCEQ (HW-50398[2-34] and HW-50397[2-33]) and a Toxic Substances Control Act (TSCA) authorization from the United States Environmental Protection Agency (EPA). WCS also possesses radioactive material license (RML) R04100[2-31] and R05807[2-32] for low-level radioactive wastes (LLRW) and byproduct material, respectively [<https://www.epa.gov/enforcement/toxic-substances-control-act-tsca-and-federal-facilities>].

2.1 Geography and Demography of Site Selected

The WCS CISF is situated in northwest Andrews County on the southwestern edge of the Southern High Plains. The entire WCS site is approximately 14,000 acres with all acreage being *controlled* by WCS. The nearest population center of 25,000 or more is Hobbs, NM about 20 miles northwest of the WCS CISF.

Land uses within a few miles of the WCS CISF include agriculture, cattle ranching, drilling for and production from oil and gas wells, quarrying operations, uranium enrichment, municipal waste disposal, and the surface recovery and land farming of oil field wastes. Surface quarrying of caliche, sand and gravel is conducted in New Mexico, approximately one mile west of the WCS CISF. The oil field waste recovery facility is adjacent to this quarry. The Lea County, New Mexico municipal solid waste landfill is located adjacent to the state line to the immediate south and west of the WCS CISF. Uranium Enrichment Company (URENCO) operates a centrifuge technology, uranium enrichment facility about one mile to the southwest of the HW-50397 RCRA landfill location.

The 15-mile radius area around the WCS CISF is very low population with some industry and mostly ranch land and very little seasonal variation in population. In the Environmental Report, Appendix A, the Socioeconomic Impact Assessment includes 2010 Census data and Figure 1.1-1 in Appendix A shows cities and towns within a 30 mile radius of the WCS CISF.

Except for a historical marker and picnic area approximately 5.5 km (3.3 mi) from the WCS CISF at the intersection of New Mexico Highways 234 and 18, there are no known public recreation areas or state or federal parks within 8 km (5 mi) of the WCS CISF.

The following nonindustrial water resources are located in the proposed WCS CISF vicinity:

- A manmade pond on the adjacent quarry property owned by Permian Basin Materials (Permian, 2016[2-29]).
- Baker Spring, an intermittent surface-water feature situated about 1.6 kilometers (1 mile) northeast of the WCS CISF that contains water seasonally.
- Several cattle-watering holes where groundwater is pumped by windmill and stored in aboveground tanks.
- Monument Draw, a natural shallow drainageway situated several kilometers southwest of the WCS CISF. Local residents indicated that Monument Draw only contains water for a short period of time following a significant rainstorm (LES, 2005[2-19]).

The nearest residential *area is* due west of the WCS CISF in the city of Eunice, New Mexico, which is approximately 8 km (5 mi) away. The closest residence from the center of the WCS CISF is approximately 6 km (3.8 mi) away on the east side of Eunice, New Mexico.

Population centers (more than 25,000 persons) and communities (places less than 25,000 persons) are shown below with distance from the site and 2010 census population (see Figure 2-25):

- *Andrews, Andrews County, Texas: 32 miles southeast: 11,088 persons*
- *Eunice, Lea County, New Mexico: 6 miles west: 2,922 persons*
- *Hobbs, Lea County, New Mexico: 20 miles north; 34,122 persons*
- *Jal, Lea County, New Mexico: 23 miles south; 2,047 persons*
- *Lovington, Lea County, New Mexico: 39 miles north-northwest; 11,009 persons*
- *Seminole, Gaines County, Texas: 32 miles east-northeast; 6,430 persons*
- *Denver City, Gaines County, Texas: 40 miles north-northeast; 4,479 persons*

For additional information regarding the demographics of the general project area and potential socioeconomic impacts associated with the proposed WCS CISF, please refer to the Socioeconomic Impact Assessment in Appendix A of the Environmental Report.

Population within a 5-mile radius centered on the proposed WCS CISF consists of scattered residences located in the eastern portion of the City of Eunice in Lea County, New Mexico. The closest residents to the WCS CISF reside within the 20 homes located approximately 4 to 5 miles west of the project. The locations of these homes with relation to the proposed WCS CISF estimated population counts are shown in Figure 2-19 Present Population Distribution within 5 miles of WCS.

The estimated 2014 population within a 5-mile radius is 55 persons. This estimate assumes 20 households identified based on 2014 aerial photos superimposed with concentric one-mile radius circles. Household size was determined using an average household size of 2.71 persons according to 2010 census data for Census Tract 8/Block Group 2 in Lea County and by applying that average household size to the number of households identified. Because of the remoteness of the proposed WCS CISF and because a majority of the land within the 5-mile radius is controlled by WCS, it is unlikely that the permanent population within a 5-mile radius would change significantly during the proposed license period.

No transient or institutional populations are known within 5 miles of the proposed WCS CISF. There are no known public recreation areas or state or federal parks within the 5-mile radius. Texas State Highway 176, a two-lane highway generally oriented east-west, is the only public transportation facility that provides access to the existing WCS commercial waste management facility. Land uses within a few miles of the WCS CISF include agriculture, cattle ranching, drilling for and production from oil and gas wells, quarrying operations, uranium enrichment, municipal waste disposal, and the surface recovery and land farming of oil field wastes.

Based on U.S. Census Bureau decennial data, Lea County experienced a historical annual percentage growth rate of 0.55% from 1970 to 2010. Applying this historical annual percentage growth rate of 0.55%, the projected 2064 population within the 5-mile radius is 72 persons, an increase of 17 persons from the estimated 2014 population. Table 2-8 provides the population projection calculations for the populated sectors within a 5-mile radius of the proposed WCS CISF. This projection is conservative but appropriate given existing land uses and limited land area available for development. Figure 2-20, Projected Population Distribution within 5 Miles of WCS, illustrates the projected population distribution within the 5-mile radius based on the 0.55% annual percentage growth rate.

Two other possible scenarios were investigated based on 2010-2040 population projections prepared by the Geospatial and Populations Studies Group - University of New Mexico. Applying an annual percentage growth rate of 2.4 percent (based on projected Lea County Populations 2010-2040) results in a 2064 population projection of 177 persons. With a 1.2 percentage annual growth rate, which is half of the projected growth rate for Lea County (2010-2040), projected population by 2064 would be 100 persons. Table 2-9 and Table 2-10 exhibit these calculations for the populated sectors within a 5-mile radius. Ultimately, these growth scenarios were deemed too aggressive given existing land uses and the limited land area available for development within populated sectors.

2.2 Nearby Industrial, Transportation and Military Facilities

The only industrial facilities located within one mile of the WCS CISF boundary are URENCO USA, Permian Basin Materials and Sundance Services, Inc. (Figure 2-3). URENCO USA is a uranium enrichment facility that uses centrifuge technology to provide uranium enrichment services. WCS also operates several permitted and licensed facilities immediately south of the WCS CISF, including a RCRA landfill, a low-level radioactive waste facility and a byproduct materials landfill.

Permian Basin Materials operates a quarry and crushing operation, wherein caliche, sand and gravel are mined, crushed and screened for commercial sales and used in making concrete (Permian, 2016[2-29]). Sundance Services, Inc. provides oilfield waste disposal services. Sundance Services is authorized by the New Mexico Energy, Minerals and Natural Resources Department to operate the waste oil treating plant, and also manages produced water, solids and drilling muds. Sundance Services is also authorized to landfarm solids (Sundance, 2016[2-30]).

The Lea County (New Mexico) Municipal Landfill is located to the southwest and across New Mexico Highway 234 from WCS CISF. The Lea County Landfill is within 1 mile of the WCS *site*; however, it is over a mile from the location of the WCS CISF. This landfill disposes of municipal solid waste for the Lea County Solid Waste Authority under New Mexico Environmental Department Permit Number SW-98-08(P). The landfill services Lea County and its municipalities. The Lea County Municipal Landfill does not generate or receive hazardous waste (Lea, 2016[2-16]).

DD Landfarm, a non-hazardous oilfield waste disposal facility that closed in August 2013 and is undergoing decommissioning and post-closure monitoring, is located approximately 4 km (2.5 miles) west of the proposed WCS CISF.

The closest transportation facility is the Lea County Airport, which is approximately 18 miles from the WCS CISF.

There are no military facilities within a mile of the WCS CISF. *The closest military facility* is Cannon Air Force Base is the closest at a distance of approximately 135 miles.

The existing WCS railroad is generally aligned parallel with and south of the proposed WCS CISF boundary.

Texas State Highway 176 is a two-lane highway with 3.6 m (12 foot) wide driving lanes, 2.4 m (8 foot) wide shoulders and a 61m (200 foot) wide right-of-way easement on each side. Access to the site is directly off of Texas State Highway 176.

2.3 Meteorology

The proposed WCS CISF has been examined with respect to site, local and regional climatological and meteorological conditions and history that demonstrate that the safe operation of the facility would not be affected.

2.3.1 Regional Climatology

The Weather Forecast Office at Midland, Texas covers the High Plains where the proposed WCS CISF is located. The climate of the WCS CISF in Andrews County, TX can best be described as “semi-arid continental” marked with four seasons. Summers are typically hot, dry weather with the relative humidity being generally low. July is the hottest month with high temperatures occasionally reaching above 100 degrees Fahrenheit. January is the coldest month, although the winters are not generally severe. Temperatures occasionally dip below 32 degrees Fahrenheit.

Precipitation levels are generally very low in this arid climate. The precipitation tends to be heavier in the summer and fall.

During the winter, the regional weather is often dominated by a high-pressure system in the central part of the western United States and a low-pressure system in north-central Mexico. The region is affected by a low-pressure system located over Arizona in the summer.

2.3.2 Local Meteorology

The Weather Forecast Office at Midland-Odessa, Texas covers the High Plains where the proposed WCS CISF is located. In addition to the weather forecast office in Midland, climatological data for atmospheric variables such as temperature, pressure, winds, and precipitation are also collected at stations in Jal, New Mexico; Hobbs, New Mexico; and Andrews, Texas. Table 2-1 indicates the distances and directions of these stations from the WCS CISF and the length of record for the reported data *in the application*. Additionally, *WCS compiled meteorological and climatology data from on-site and off-site stations for the WCS Low Level License R04100 (TCEQ 2015) and this data, which includes the period 1914 to 2006, is included in Attachment H. Attachment H includes compiled meteorological and climatology data from four (4) stations within 65 miles of WCS.*

The WCS site and surrounding meteorological stations listed above are all located in a climatic region classified within the Köppen Classification System as BSk or Arid semi-cold. The CISF elevation is approximately 1,044 meters msl and the surrounding meteorological stations range from 947 meters msl to 1,118 meters msl and are listed in Table 3.6-1 in the CISF Environmental Report, Section 3.6.2.

Using a series of tables and wind-rose diagrams from on and off-site stations, Attachment H demonstrates that data collected from within 65 miles of the site can be considered representative of the general climate of the site.

The Midland-Odessa monitoring station is the closest first-order National Weather Service station to the WCS CISF. First-order weather stations record a complete range of meteorological parameters for 24-hour periods, and they are usually fully instrumental and operated by the National Weather Service (<http://www.ncdc.noaa.gov/homr/>).

2.3.3 Onsite Meteorological Data

Meteorological data have been collected on the WCS property from four (4) meteorological tower stations. The towers were located in positions where the measurements will accurately represent overall site meteorology for the WCS site. The map shown in Figure 2-4 illustrates where the stations are located in relation to the WCS facility. The equipment is checked daily and calibrated quarterly. WCS follows a meteorological measurement program that is consistent with Regulatory Guide 1.23, which is cited in NUREG-1567. Details for each station at the WCS site are listed below:

- *WCS stations on-site include Tower 1 (Figure 2-21), which has been collecting data since March 2009, measures temperature, wind direction, wind speed, relative humidity at 2 and 10 meters, barometric pressure, solar radiation, and rain at 2 meters only. Data averages, unless otherwise noted, are based on available historic records from 2009-2015. WCS has sensors at both the 2-meter (lower) and 10-meter (upper) height intervals. Tower 1 was installed using a Met One Model 970666 30-foot guyed fold over tower. Specifications for the instrumentation and install are in Attachment G.*
- *The ER Tower (Figure 2-22), which has been collecting data since July 2009, measures temperature, wind direction, wind speed, relative humidity at 2 and 10 meters, barometric pressure, solar radiation, and rain at 2 meters only. Data averages, unless otherwise noted, are based on available historic records from 2009-2015. WCS has sensors at both the 2-meter (lower) and 10-meter (upper) height intervals. The ER Tower was installed using a Met One Model 970666 30-foot guyed fold over tower. Specifications for the instrumentation and install are in Attachment G.*
- *The WeatherHawk West and East Tower (Figure 2-23 and Figure 2-24) have been collecting data since March 2009. They measure temperature, wind direction, wind speed, relative humidity, barometric pressure, solar radiation, and rain at roughly 4 meters. Data averages, unless otherwise noted, are based on available historic records from 2009-2015. Specifications for the instrumentation and install are in Attachment G.*

Measurements for all parameters, listed in Table 2-11, are taken at 10-minute, 60-minute and 24-hour averages and recorded/stored on a dedicated Campbell Scientific data logger at each station. Routinely the data loggers automatically download their content to a server in Dallas, TX for long-term storage. Data loggers can be remotely accessed via password protected radio telemetry; and the server can be securely accessed via a password protected Internet connection. Table 2-11 lists the meteorological parameters measured and at what heights. Information for the Met One Towers and the WeatherHawk Series regarding range, accuracy, and resolution is listed in Table 2-12.

2.3.3.1 Maximum and Minimum Temperatures

The Western Regional Climate Center (www.wrcc.dri.edu) has historic temperature data for Andrews, TX. The temperature data currently available spans from 1962 until 2010. The average maximum and minimum temperatures, the record high temperature and low temperature for each month, and the annual high and low temperature for these years is shown on Table 2-2. *Table 2-2 was used to provide normal, off-normal, and extreme temperature information for the WCS CISF site.*

Normal Temperature (NUHOMS® System): The normal temperature range is taken as the low and high mean monthly temperature (44.1°F to 81.5°F).

Normal Temperature (NAC System): The normal ambient temperature is taken as the maximum yearly average temperature. In addition to the temperature information provided in Table 2-2, temperature data from the Midland-Odessa monitoring station between 2000 and 2015 was used to provide yearly average temperatures (Table 2-13). The maximum yearly average temperature is 67.1°F.

Off-Normal Temperature (NUHOMS® System): The NUHOMS® System uses the extreme high temperature to evaluate that system for off-normal temperature conditions. That value is taken as the highest temperature recorded over the time period (113°F) in the data set represented in Table 2-2. The off-normal minimum temperature is 30.1°F, which is the minimum mean daily temperature shown in Table 2-2.

Off-Normal Temperature (NAC System): The NAC System uses a rolling average temperature to evaluate that system for the off-normal temperature condition. In addition to the temperature information provided in Table 2-2, temperature data from the Midland-Odessa monitoring station between 2000 and 2015 was used to provide 3-day average ambient temperatures. These temperatures are determined by taking the daily average temperature averaged over three consecutive days for each day of the year. The lowest average 3-day temperature and the highest average 3-day temperature is shown in Table 2-13. The minimum average and maximum average values averaged over the data set represented in Table 2-13 are 27.9°F and 89.4°F.

Extreme Temperature (NUHOMS[®] and NAC Systems): The extreme temperature range is taken as the lowest (-1°F) and highest (113°F) temperatures recorded over the time period as shown in Table 2-2.

2.3.3.2 Extreme Winds and Atmospheric Stability

Regionally wind speeds are usually more moderate, although relatively strong winds often accompany occasional frontal activity during late winter and spring months and sometimes occur just in advance of thunderstorms. Frontal winds may exceed 13 meters per second (30 miles per hour) for several hours and reach peak speeds of more than 22 meters per second (50 miles per hour).

Wind speed and direction data measured at the on-site WCS meteorological stations from 2010 to 2015 is shown on wind rose diagrams in Figure 2-4, Figure 2-5, Figure 2-6, Figure 2-7, and Figure 2-8. The data used to create the wind rose diagrams is located on compact discs in Attachment A. The wind roses show the percent of the time (rings) that the wind blows from each of the 16 directions (N, NNE, NE, NNW) by the length of the bars. The shading of the bars also indicates the frequency of occurrence of wind speeds within the wind speed classes shown on the figures. The on-site data indicates that for this period from 2010 to 2015 the average wind speed ranged from 6.07 knots to 10.53 knots. The wind direction is predominantly from the south. The diagrams indicate that wind gusts in excess of 22 mph generally blow from the southwest or northeast.

The neighboring National Enrichment Facility (NEF) site analyzed wind speed and direction from the Midland-Odessa First Order weather station for the years 1987 to 1991. Calculated annual mean wind speed was 5.1 meters per second (11.4 miles per hour), with prevailing winds from the south and a maximum 5-second wind speed of 31.2 meters per second (70 miles per hour). The Pasquill stability classes range from A to F, with the most stable classes – E and F – occurring 18.9 and 13 atmospheric percent of the time, respectively. The least stable classes, A and B, occur 0.3 and 3.5 percent of the time, respectively. NEF compared this data against data generated at WCS from October 1999 through August 2002, and found similar wind patterns and distribution of wind speed between Midland-Odessa and WCS locations (EIS for NEF, 2005).

2.3.3.3 Tornado and Sever Weather Conditions

Two F2 Class (wind speed from 113 to 157 mph) tornadoes have been recorded in Andrews County, TX from 1950 through 2015 according to data reported by NOAA [www.noaa.gov accessed 2015]. NOAA reports there were eight F1 Class (wind speed 73 to 112 mph) tornadoes recorded in Andrews County since 1950. No F4 or F5 tornados have ever been reported in the vicinity of the WCS CISF.

Tornados are classified using the F-scale with classifications ranging from F0-F5 as follows:

- F0-classified tornados have winds of 64 to 116 kilometers per hour (40 to 72 miles per hour)
- F1-classified tornados have winds of 117 to 181 kilometers per hour (73 to 112 miles per hour)
- F2-classified tornados have winds of 182 to 253 kilometers per hour (113 to 157 miles per hour)
- F3-classified tornados have winds of 254 to 332 kilometers per hour (158 to 206 miles per hour)
- F4-classified tornados have winds of 333 to 419 kilometers per hour (207 to 260 miles per hour)
- F5-classified tornados have winds of 420 to 512 kilometers per hour (261 to 318 miles per hour)

The WCS CISF is located about 805 kilometers (500 miles) from the coast. Because hurricanes lose their intensity quickly once they pass over land, a hurricane would most likely lose its intensity before reaching WCS and dissipate into a tropical depression.

Blowing sand or dust may occur occasionally in the area due to the combination of strong winds, sparse vegetation, and the semi-arid climate. High winds associated with thunderstorms are frequently a source of localized blowing dust. Most episodes of dust prevail for only six hours or less, when visibility is restricted to less than 0.5 mile. Statistical information is lacking on seasonal distribution intensity and duration of dust storms for the region. Recent data in Lubbock, Texas (110 miles northeast of the WCS CISF) indicates blowing dust an average of 12 times in the spring and 9 times during the remainder of the year (Bomar, 1995[2-4]).

2.3.3.4 Precipitation Exposure

The Western Regional Climate Center (www.wrcc.dri.edu) has historic precipitation data for Andrews, TX starting in 1914. The maximum observed 24-hour rainfall (from 1914 until 2012) amount at Andrews, TX is 7.6 inches in *July* 1914. Historic precipitation and snow data for Andrews, TX from 1914 to 2006 can be found in Table 2-3 and Table 2-4.

Rainfall records from the four (4) on-site meteorological stations on-site are included on compact discs in Attachment A.

Summer rains fall almost entirely during brief, but frequently intense thunderstorms. The general southeasterly circulation from the Gulf of Mexico brings moisture from these storms into the State of New Mexico, and strong surface heating combined with orographic lifting as the air moves over higher terrain causes air currents and condensation. Orographic lifting occurs when air is intercepted by a mountain and is forcefully raised up over the mountains, cooling as it rises. If the air cools to its saturation point, the water vapor condenses and a cloud forms.

As these storms move inland, much of the moisture is precipitated over the coastal and inland mountain ranges of California, Nevada, Arizona, and Utah. Much of the remaining moisture falls on the western slope of the Continental Divide and over northern and high-central mountain ranges. Winter is the driest season in New Mexico except for the portion west of the Continental Divide. This dryness is most noticeable in the Central Valley and on eastern slopes of the mountains. In New Mexico, much of the winter precipitation falls as snow in the mountain areas, but it may occur as either rain or snow in the valleys.

Snow loads for the WCS CISF are based on ASCE Design Criteria 7-10 (2010[2-41]) and are 10 pounds per square foot.

Data from the Midland-Odessa Weather Station indicate the relative humidity throughout the year ranges from 51.5 to 65 percent, with the highest humidity occurring during the early morning hours.

2.3.3.5 Thunderstorms and Lightning Strikes

The mean number of annual thunderstorm days for Hobbs, NM and Midland, TX is 25.5 and 36.4, respectively. No records are maintained for the frequency of thunderstorms and lightning at the proposed WCS CISF; however, the actual number of events can be expected to be similar to these regional data. For Andrews County, there are no reported lightning events from 1950 to 2016 that have caused deaths, injury, property damage or crop damage (<http://www.ncdc.noaa.gov/stormevents/>, accessed 2016).

2.3.3.6 Mixing Heights

Mixing height is defined as the height above the earth's surface through which relatively strong vertical mixing of the atmosphere occurs. G.C. Holzworth developed mean annual morning and afternoon mixing heights for the contiguous United States (Holzworth, 1972[2-14]). According to Holzworth's calculations, the mean annual morning and afternoon mixing heights at the WCS CISF are approximately 436 meters (1,430 feet) and 2,089 meters (6,854 feet), respectively. Table 2-5 shows the average morning and afternoon mixing heights for Midland-Odessa, Texas.

2.3.3.7 Air Quality

To assess air quality, the EPA has established maximum concentrations for pollutants that are referred to as the National Ambient Air Quality Standards (<http://www3.epa.gov/ttn/naaqs/criteria>). Table 2-6 presents a list of the NAAQS Air Quality Standards. Six criteria pollutants are used as indicators of air quality: ozone, carbon monoxide, nitrogen dioxide, sulfur dioxide, particulate matter, and lead (EPA, 2016[2-36]). Both Lea and Andrews Counties are in attainment for all of the EPA criteria pollutants [2-36].

2.3.4 On-Site Meteorological Measurement Program

Meteorological data have been collected on the WCS property from four (4) meteorological towers stations shown in Figure 2-4 and listed below:

- WCS stations on-site include Tower 1, which has been collecting data since March 2009, and it measures temperature, wind direction, wind speed, relative humidity at 2 and 10 meters, barometric pressure, solar radiation, and rain at 2 meters only. Data averages, unless otherwise noted, are based on available historic records from 2009-2015. WCS has sensors at both the 2-meter (lower) and 10-meter (upper) height intervals.
- The ER Tower has been collecting data since July 2009 and it measures temperature, wind direction, wind speed, relative humidity at 2 and 10 meters, barometric pressure, solar radiation, and rain at 2 meters only. Data averages, unless otherwise noted, are based on available historic records from 2009-2015. WCS has sensors at both the 2-meter (lower) and 10-meter (upper) height intervals.
- The WeatherHawk West Tower has been collecting data since March 2009 and it measures temperature, wind direction, wind speed, relative humidity, barometric pressure, solar radiation, and rain at roughly 10 feet. Data averages, unless otherwise noted, are based on available historic records from 2009-2015.
- The WeatherHawk East Tower has been collecting data since March 2009 and it measures temperature, wind direction, wind speed, relative humidity, barometric pressure, solar radiation, and rain at roughly 10 feet. Data averages, unless otherwise noted, are based on available historic records from 2009-2015.

2.3.5 Diffusion Estimates

For normal and off-normal conditions, an atmospheric dispersion coefficient is calculated using D-stability and a wind speed of 5 m/sec and a 100 m distance to the controlled area boundary. The controlled area boundary is farther than 100 m from the WCS CISF so use of 100 m is conservative. For accident conditions, a dispersion coefficient is calculated using F-stability and a wind speed of 1 m/sec. These atmospheric conditions are consistent with the guidance of NUREG-1536 [2-38] and NUREG-1567 [2-39]. The smallest vertical plane cross-sectional area of one Horizontal Storage Module (HSM) is conservatively used as the vertical plane cross-sectional area of the building: $\text{area} = \text{HSM Width} * \text{HSM Height} = 9'8'' \times 15' = 20,880 \text{ in}^2 = 13.47 \text{ m}^2$.

The atmospheric dispersion coefficients can be determined through selective use of Equations 1, 2, and 3 of Regulatory Guide 1.145 [2-40] for ground-level relative concentrations at the plume centerline. For D-stability, 5 m/sec wind speed and a distance of 100 m, the horizontal dispersion coefficient, σ_y , is 8 m per Figure 1 of [2-40]. The vertical dispersion coefficient, σ_z , is 4.6 m per Figure 2 of [2-40]. The correction factor at these conditions is determined to be 1.122 per Figure 3 of [2-40].

For F-stability, 1 m/sec wind speed and a distance of 100 m, the horizontal dispersion coefficient, σ_y , is 4 m per Figure 1 of [2-40]. The vertical dispersion coefficient, σ_z , is 2.3 m per Figure 2 of [2-40]. The correction factor at these conditions is 4 per Figure 3 of [2-40].

With the three values of χ/Q determined, the higher χ/Q value of the first two (Equation 1 and Equation 2) is compared with the last one (Equation 3) and the lower of those two is evaluated as the appropriate atmospheric dispersion coefficient per guidance of Regulatory Guide 1.145 [2-40].

The parameters used and the calculated atmospheric dispersion coefficients are summarized in Table 2-7.

2.4 Surface Hydrology

2.4.1 Hydrologic Description

The WCS CISF is located in western Andrews County, Texas nearly at the Texas – New Mexico border, just north of Texas Highway 176 approximately 32 miles west of Andrews, Texas and 5 miles east of Eunice, New Mexico. There are no maps of special flood hazard areas for this location published by the Federal Emergency Management Agency (FEMA). The proposed WCS CISF is not located in wetlands per the National Wetlands Inventory (see Figure 2-9). The Site Location and Surrounding Topography Map, Attachment B Figure 1.1-1, shows the WCS CISF location with respect to the surrounding topography and drainage features and the WCS property boundary.

From a surface water perspective, the general area is characterized by ephemeral drainages, sheet flow, minor gullies and rills, internally-drained playas, and a salt lake basin (identified in Figure 1.1-1 as a Depression Pond in Attachment B). The salt lake basin is the only naturally-occurring, perennial (year-round) water body located near the WCS CISF; the internally drained salt lake basin is located approximately 5 miles from the eastern boundary of the WCS CISF and rarely has more than a few inches of water at scattered locations within the bottom footprint. Surface drainage from the WCS CISF does not flow into this basin. Other perennial surface water features are man-made, including various stock tanks (often replenished by shallow windmill wells) located across the area and the feature denoted as the Fish Pond on Figure 1.1-1, which is located at the Permian Basin Materials quarry (formerly Wallach Concrete) west of the WCS CISF and is also replenished by well water. In addition, Sundance Services, LLC operates the Parabo Disposal Facility for oil and gas waste west of the WCS CISF. Water collects periodically in excavated and/or diked areas at this disposal facility and in the active quarry areas at this property adjacent to and west of the WCS property in New Mexico.

The nearest surface water drainage feature to the WCS CISF is Monument Draw in Lea County, New Mexico, a reasonably well-defined, southward-draining draw about 3 miles west of the WCS CISF. The draw does not have through-going drainage and loses surface expression after it enters Winkler County, Texas. (Note: there are two surface drainage features named Monument Draw in the vicinity: Monument Draw, New Mexico, a south-flowing ephemeral stream in Lea County, New Mexico, and Monument Draw, Texas (same name), an east-flowing ephemeral stream in Andrews County, Texas). East of Monument Draw, New Mexico and south of the WCS CISF is a local topographic high known as Rattlesnake Ridge. This poorly defined ridge parallels the Texas-New Mexico border and crests about 125 feet higher than Monument Draw, New Mexico (Nicholson and Clebsch, 1961[2-27]).

The WCS permitted area is on the southwestern slope of the drainage divide between the Pecos River and the Colorado River. In the immediate vicinity of the WCS CISF, the slope is southwest toward Monument Draw, New Mexico at about 50 feet per mile. The maximum and minimum elevations of the permitted area are about 3490 feet and 3415 feet msl, respectively.

Small surface depressions (buffalo wallows) and a few established playa basins are present within a 6.2-mile radius of the WCS CISF. The largest of the surface depressions within the permitted area is a small playa about 15 acres in size approximately one-half mile northeast of the existing RCRA landfill. Remnant deposits of a filled and now partially covered playa or salt lake basin are found about 3 miles east of the permitted area. Surface drainage from the area north and east of the WCS CISF flows eastward into this basin.

Baker Spring is a manmade feature located at a historic quarry on WCS property about 2,510 feet west of the WCS CISF in Lea County, New Mexico. This feature was formed by excavation of the caliche caprock to the top of the underlying red bed clays. After periods of rainfall, the depression may hold water for an extended period; during dry cycles, the depression may be dry for extended periods.

The National and Oceanic and Atmospheric Administration's National Weather Service Office for Hobbs, New Mexico indicates that the minimum average annual precipitation recorded is 2.01 inches in 2011 and the maximum average annual precipitation recorded is 32.19 inches in 1941[www.noaa.gov]. The annual precipitation on average is approximately 14 inches.

The WCS CISF is located on the southwest-facing slope that transitions from the Southern high Plains to the Pecos Valley physiographic section. The Southern High Plains is an elevated area of undulating plains with low relief encompassing a large area of west Texas and eastern New Mexico. In Andrews County, the southwestern boundary of the Southern High Plains is poorly defined, but in this report is considered to be where the caprock caliche is at or relatively close to the surface, such as on and near the WCS CISF.

The main surface water drainage in the area is Monument Draw, an ephemeral stream about 3 miles west of the WCS CISF, in New Mexico. Ephemeral streams or drainage ways flow briefly only in direct response to precipitation in the immediate locality. Monument Draw is a reasonably well-defined, southward draining feature (although not through-going) that is identified on the USGS topographic maps that serve as the base map source for Attachment B Figure 1.1-1.

An ephemeral drainage feature, referred to as the Ranch House Draw crosses the WCS property from east to west, generally to the south of the WCS CISF, as shown in Figure 1.1-1 in Attachment B. This feature is discernible from the topographic relief depicted on Figure 1.1-1 in Attachment B, although it is much less pronounced than Monument Draw. This drainage feature is a relict drainage way that is choked with windblown sand and is not through-going to Monument Draw. Most of the drainage from the area of the WCS CISF is down slope toward the Ranch House Draw, with a small portion of the drainage from this area toward the southwest. Surface water eventually infiltrates into the windblown sands and dune fields to the south and southwest of the WCS CISF. There are no ephemeral drainages that cross the WCS CISF. Most of the immediate area of the WCS CISF is drained from northwest to southeast by sheet flow. Sheet flow is a term describing overland flow or down slope movement of water taking the form of a thin, continuous film.

Playas, or small, internally-drained basins, occur on the WCS property. The playas are dry most of the time. Some of the playas occasionally hold water after relatively large precipitation events; however, the ponded water rapidly dissipates through infiltration, evaporation, and plant uptake. An established playa basin is present on the eastern edge of the WCS CISF. Surface topography maps indicate approximately 10 feet of relief in the playa.

The combination of low annual precipitation, relatively high potential evapotranspiration, permeable surficial soils down gradient of the WCS CISF, and topographic relief results in well-drained conditions. The engineering design and construction of the WCS CISF will eliminate areas that might promote ponding. Diversion berms and a collection ditch will direct stormwater from upstream drainage areas around the WCS CISF.

There are no public or private surface water drinking-water supplies in the WCS CISF vicinity. Potable water supply for the WCS CISF will tie-in to existing potable water lines at WCS. There are scattered windmills in the general area that take water from isolated pockets of groundwater perched on top of the red bed clay. This water is utilized primarily for livestock watering.

The WCS CISF is located on the southwest-facing slope that transitions from the Southern High Plains to the Pecos Valley physiographic section.

2.4.2 Floods

The WCS CISF storage area, which is within the WCS CISF site, is defined as the area within the protected area fence whose boundary is defined by a rectangle 2360 feet by 2430 feet, as indicated on the Developed Drainage Plan, Figure 2-35. Included in the storage area are the security and administration building, the Cask Handling Building, the storage pads and a portion of the WCS CISF rail side track. The WCS CISF storage area is approximately 132 acres and is graded for surface drainage with slopes of approximately 0.8 % from the northwest to the southeast. Developed elevations across the WCS CISF storage area range from 3506 ft msl at the northwest corner to 3486 ft msl near the southeast corner.

All of the surface water runoff from the storage area will drain into the large playa southeast of the site. Flow arrows on Figure 2-35, Developed Drainage Area Map, provide the detailed drainage patterns for the WCS CISF site.

The WCS CISF is not located in the 100-year floodplain, the 500-year floodplain or the floodplain resulting from the probable maximum precipitation (PMP)/ probable maximum flood (PMF). Attachment B presents the Flood Plain Study for the WCS CISF. Attachment B also includes a copy of a floodplain study performed in 2006 for the operational area south of the WCS CISF, which includes a playa area near the southeast corner of the WCS CISF.

2.4.2.1 Flood History

The climate of the area is classified as semiarid, characterized by dry summers and mild, dry winters. Annual precipitation on average is approximately 14 inches and annual evaporation exceeds annual precipitation by nearly five times. The area is subject to occasional winter storms, which produce snowfall events of short duration.

Rainfall records from July 2009 through December 2015, provided by WCS from a weather station near the WCS CISF, indicate an average annual rainfall of 12.6 inches and a maximum twenty-four hour rainfall total of 3.62 inches (Attachment A). According to WCS personnel, surface water runoff has not overflowed roads or existing drainage features at the WCS site during this time frame.

2.4.2.2 Flood Design Considerations

There has been no history of flooding at the WCS CISF site and the WCS CISF is not located in the 100-year floodplain. All surface water runoff from the storage area/protected area will leave the WCS CISF just north of the southeast corner of the storage area and will drain into a large playa southeast of the WCS CISF. A small amount of surface water runoff from the west side of the WCS CISF storage area will drain southwest. Flow arrows on Figure 2-35, Developed Drainage Area Map, provide the detailed drainage patterns for the WCS CISF.

The WCS CISF Drainage Evaluation and Floodplain Analysis (Attachment B) models the 100-year flood, the 500-year flood and the PMF to evaluate the effects on the WCS CISF.

The only analysis of significance from a flooding standpoint is the water level in the playa area resulting from the PMP event. The result is that the WCS CISF storage area is above the maximum water level elevation resulting from that storm event as demonstrated in Attachment B. The area west of the WCS CISF drains freely and does not result in any ponded water to create a flood area near the WCS CISF.

As noted previously, a stormwater collection ditch and berm are to be constructed up-gradient from the WCS CISF storage area. The ditch and berm are to be constructed as a matter of operational convenience to minimize (not prevent) run-on of stormwater during precipitation events by diverting it around the operational storage area. Figure 2-26 (CJI Drawing C-1) show the location of the Collection Ditch and Berm. Figure 2-27 through Figure 2-30 (CJI Drawings C-2, C-3, C-4, and C-5) show plan and profile of the collection ditch and berm. The storage area is sloped to promote drainage across the area, which will result in short-term overland flow of stormwater falling directly on the storage area during some precipitation events. The overland flow across the storage area will be temporary in nature. Compromise of the ditch and berm may result in increased flow across the storage area as a result of some precipitation events, but again, it would be short term and temporary. The storage pad area is approximately three times the area from which run-on might emanate, thus the majority of the overland flow results from the stormwater that falls directly on the pad. The area upgradient of the storage area is predominately a sand dune area with little to no developed drainage paths, which has the effect of lessening the overland flow of water from that area during the storm events. In order to provide a conservative analysis of the flood effects, the flood events are modeled without including the collection ditch and berms, which provides the greatest possible area contributing runoff into the playa.

As indicated in Section 4.0 of the December 2016 revision of the March 2016 report entitled Centralized Interim Storage Facility Drainage Evaluation and Floodplain Analysis (Attachment B of SAR Chapter 2):

“The local PMP [probable maximum precipitation] floodplain analysis yielded the PMF elevation near the CISF site of 3488.9 ft msl. Elevations of the storage pads vary from 3489 ft msl to 3504 msl. Elevations of the foundations of the security/administration building and the Cask Handling Building are 3496 ft msl and 3493 ft msl, respectively.”

The finish floor elevations of the Security and Administration building and the Cask Handling Building are 7 feet and 4 feet, respectively, above the PMF elevation and will not be impacted by the PMF. The detailed calculations for determining the water level elevations in the playa can be found in Attachment B.

2.4.2.3 Effects of Local Intense Precipitation

The Flood Plain Study in Attachment B includes calculations for a PMP using a 500-year frequency storm event and the limits of the floodplain. The results from these additional storms that were modeled describe a floodplain that is still shallow and wide that is too distant from the WCS CISF to ever be any threat.

2.4.3 Probable Maximum Flood on Streams and Rivers

There are no streams or rivers on or in the vicinity of the WCS CISF. Monument Draw, an ephemeral stream, is the closest main surface water drainage and is about 3 miles west of the WCS CISF in New Mexico, so the WCS CISF would be unaffected by flooding on streams or rivers. While Monument Draw is typically dry, the maximum historical flow occurred on June 10, 1972 and measured 36.2 cubic meters per second (1,280 cubic feet per second).

2.4.4 Potential Dam Failures (Seismically Induced)

There are no dams on or in the vicinity of the WCS CISF. The WCS RCRA and LLRW facilities currently have five (5) manmade evaporation ponds which are partially above-grade. If a seismic event were to cause slope failure the ponds are designed to have the south wall fail and all water released would flow south away from the WCS CISF.

2.4.5 Probable Maximum Surge and Seiche Flooding

Surges and seiches are typically observed on lakes or seas. There are no surface bodies of water on or near the WCS CISF where such a phenomenon would be a safety concern at the WCS CISF. There are currently five evaporation ponds at the WCS site and they are designed with spillways on the south side so any seiche or surge would flow south away from the WCS CISF.

2.4.6 Probable Maximum Tsunami Flooding

The WCS CISF is located about 805 kilometers (500 miles) from the coast. The WCS CISF is sufficient distance from the coastline that tsunami flooding is not a hazard.

2.4.7 Ice Flooding

The WCS CISF is not located in an area where ice flooding is a concern. There are no streams or rivers on or in the vicinity of the WCS CISF. Monument Draw, an ephemeral stream, is the closest main surface water drainage and is about 3 miles west of the WCS CISF in New Mexico, so the WCS CISF would be unaffected by ice blockage and ice flooding.

2.4.8 Flooding Protection Requirements

The WCS CISF is not located in an area where flooding protection is required. There are no maps of special flood hazard areas for this location published by the Federal Emergency Management Agency (FEMA).

2.4.9 Environmental Acceptance of Effluents

There are no radioactive or other effluent releases associated with the proposed WCS CISF.

Stormwater runoff is not expected to contain any radiological effluents and WCS CISF stormwater runoff will be directed to the natural drainage system. Domestic wastes will be directed to above ground tanks on-site and the tanks will be periodically drained and all wastes will be transported off-site for disposal.

2.5 Subsurface Hydrology

The High Plains aquifer of west Texas, the principal aquifer in west Texas, consists of water-bearing units within the Tertiary Ogallala Formation and underlying Cretaceous rocks (Nativ and Gutierrez, 1988[2-26]). Hydrogeologically, the High Plains aquifer is viewed as a single, hydraulically connected aquifer system, and groundwater exists under both unconfined and confined conditions. The term Ogallala aquifer is used interchangeably with the High Plains aquifer, since regionally, the Ogallala Formation is the primary component of the High Plains aquifer (Dutton and Simpkins, 1986[2-8]). Regionally the sands, gravels and sandstones that have been variously ascribed to the Tertiary Ogallala Formations, the Tertiary aged sections of the Gatuña Formation, and the Cretaceous Antlers Formation are distinct and independent. Locally, these units are situated in the same stratigraphic interval and hydrogeologically they represent a single hydrostratigraphic unit overlying the Triassic red beds, the distinctive red and purple mudstones, siltstones, and sandstones of the Triassic Dockum Group. The hydrostratigraphic unit of undifferentiated sands and sandstones of the Ogallala/Antlers/Gatuña is locally referred to as the OAG unit. However, the Ogallala and Cretaceous aquifers are evaluated independently in the literature and will be addressed individually in the discussion below.

The Cenozoic Alluvium aquifer and the Triassic Dockum Group aquifer are considered either major (Cenozoic Alluvium) or minor (Dockum Group) aquifers in this part of west Texas (Mace, 2001[2-20]) and will also be addressed below.

The shallowest water bearing zone is about 225 feet deep at the WCS CISF. Figure 2-10 is a groundwater contour map indicating the OAG unit is largely unsaturated beneath the WCS CISF. The nearest downgradient drinking water well identified in the hydrogeologic unit is located approximately 6.5 miles to the east of the proposed WCS CISF at a residence on the Letter B Ranch. The method of storage (dry cask), the nature of the canisters, the extremely low permeability of the red bed clay and the depth to groundwater beneath the WCS CISF preclude the possibility of groundwater contamination from the operation of the WCS CISF.

Ogallala Aquifer

The Ogallala Formation aquifer is the primary freshwater aquifer within the regional study area and serves as the principal source of groundwater in the Southern High Plains (Cronin, 1969[2-6]). The southern and eastern limits of the Ogallala aquifer lie to the north and east of the WCS CISF.

Regionally, the Ogallala aquifer thickens to the north and east of the currently permitted WCS facility (Blandford et al., 2003[2-3]) as shown on cross sections in Figure 2-11 and Figure 2-12. The saturated thickness of the Ogallala aquifer ranges from a few feet to approximately 300 feet in the Southern High Plains (Nativ, 1988[2-25]). Groundwater within the Ogallala aquifer is typically under water table conditions, with a regional hydraulic gradient toward the southeast ranging from approximately 10 feet/mile to 15 feet/mile. The average hydraulic conductivity of the Ogallala *aquifer* is about 10 feet/day with higher values preferentially distributed in depositional channels. Assuming an average hydraulic gradient of 12.5 feet/mile and a porosity of 0.20, the average rate of flow in the regional Ogallala aquifer is 43 feet/year.

The primary sources of recharge to the Ogallala aquifer are playas, headwater creeks, and irrigation return flow (Blandford et al., 2003[2-3]). Regionally, the recharge rate to the Ogallala aquifer is estimated to be of the order of 0.35 inches/year (Mullican et al., 1997[2-24]). Blandford et al., (2003)[2-3] estimated predevelopment recharge at less than 0.083 inches/year. In a 2003 numerical model of the Ogallala aquifer, prescribed recharge beneath irrigated lands was on the order of 1.25 to 2.25 inches/year, and recharge beneath non-irrigated agricultural lands ranged from 0.25 to 2.0 inches/year (Blandford et al., 2003[2-3]). Groundwater discharge from the Ogallala aquifer occurs naturally through springs, underflow, evaporation, and transpiration, but is also removed artificially through pumping. Throughout much of the Southern High Plains, groundwater discharge from the Ogallala aquifer exceeds recharge, and water levels have consistently declined. In some regions, however, water levels remained reasonably stable between 1960 and 2000 or even increased, indicating that recharge is the same or greater than discharge/pumping (Blandford et al., 2003[2-3]).

Water quality data for three Ogallala aquifer wells, located within two miles of the WCS CISF, were obtained from a review of Texas and New Mexico state records for western Andrews County, Texas and eastern Lea County, New Mexico.

Review of the water quality data indicates that the local Ogallala aquifer contains fresh to slightly saline water ($\text{TDS} \leq 3000 \text{ mg/L}$). The Ogallala Formation, if present, is not water bearing in the WCS area.

Cretaceous Aquifer (Antlers Formation)

The Cretaceous aquifer of the Southern High Plains is also considered to be part of the High Plains Aquifer (Nativ and Gutierrez, 1988[2-26]). The regional hydraulic gradient of the Cretaceous aquifer is toward the southeast, similar to the overlying and often hydraulically interconnected Ogallala aquifer.

The Cretaceous aquifer of the Southern High Plains consists of a basal unit (Trinity or Antlers Formation sandstone), an intermediate unit (Edwards Formation limestone), and an upper unit (Kiamichi/Duck Creek Formation sandstone and limestone). Where present and water bearing in the subsurface, the Cretaceous aquifer in the Southern High Plains is used as a source of groundwater (Nativ and Gutierrez, 1988[2-26]). The Cretaceous Antlers Formation has been identified in the vicinity of the WCS CISF and in the subsurface immediately below the WCS CISF; however, it is unsaturated but for a few isolated perched lenses.

Triassic Dockum Group Aquifer

The Dockum Group regionally consists of Triassic fluvial and lacustrine clays, shales, siltstones, sandstones and conglomerates. The Dockum Group consists of five formations, the lowermost of which is the Santa Rosa Formation, followed by the Tecovas, the Trujillo, the Cooper Canyon, and the Redonda Formations. Only the Santa Rosa, Tecovas, Trujillo and Cooper Canyon Formations are present in the vicinity of the WCS CISF. Water from the Dockum Group aquifer is used as a replacement for, or in combination with, the Ogallala aquifer as a regional source for irrigation, stock and municipal water (Dutton and Simpkins, 1986[2-8]).

There are two water-bearing sandstone formations in the Dockum Group in the vicinity of the WCS CISF. Both yield non-potable water with less than 5,000 mg/L total dissolved solids. The Santa Rosa Formation sandstone at the base of the Dockum Group is about 250 feet thick and is considered the best aquifer within the Dockum Group (Bradley and Kalaswad, 2003[2-5]). The top of the Santa Rosa Formation sandstone is at 1,140 feet below ground surface at the WCS CISF (Figure 2-13). The Trujillo Formation sandstone, the other Dockum Group water-bearing formation in the area, is about 100 feet thick. The top of the Trujillo Formation is about 600 feet below ground surface (Figure 2-13). About 450 feet of very low permeability Dockum Group fluvial and lacustrine clays separate the two formations.

The lower Dockum Group aquifer is recharged by precipitation where Dockum Group sediments are exposed at land surface (Bradley and Kalaswad, 2003[2-5]). However, most of the recharge to the sandstones in the lower Dockum Group (comprising the Santa Rosa and Trujillo Formation sandstones) is considered to have occurred during the Pleistocene (Dutton, 1995[2-7]; Dutton and Simpkins, 1986[2-8]) some 15,000 to 35,000 years before present. Topographically controlled groundwater basin divides were developed during the Pleistocene by the erosion of the Pecos and Canadian River valleys. Prior to the development of these groundwater basin divides, the lower Dockum aquifer was recharged by precipitation on its outcrop area in eastern New Mexico. However, since the development of the Pecos and Canadian River valleys, the lower Dockum aquifer in Texas has been cut-off from its recharge area. Without recharge, the lower Dockum aquifer experiences a net loss of groundwater from withdrawal by wells and by seepage (Dutton and Simpkins, 1986[2-8]). The regional hydraulic gradient of the lower Dockum aquifer, which is toward the southeast, is approximately 15 feet/mile. Based on water levels encountered during logging of the two deep wells at the WCS site, water levels in the lower Dockum aquifer range from 2,852 feet msl (Santa Rosa Formation) to 3,172 feet msl (Trujillo Formation). Transmissivity of the lower Dockum aquifer ranges from 3180 ft²/day to about 10 ft²/day and storativity, based on two values, is 0.0001 and 0.002 (Dutton and Simpkins, 1986[2-8]). Based on the transmissivity values noted above, an average thickness of 350 feet of combined Santa Rosa and Trujillo Formation sandstones, a porosity of 0.15, and a gradient of 15 feet/mile, the rate of groundwater flow is estimated to be between 17 feet/year and 0.6 feet/year.

The upper portion of the Dockum Group (Cooper Canyon Formation) serves as an aquitard in the regional and local study area (Nicholson and Clebsch, 1961[2-27]; Dutton and Simpkins, 1986[2-8]). This is supported by the fact that the hydraulic head of the lower Dockum aquifer is significantly lower than that of the overlying Ogallala aquifer throughout much of the regional study area. This relative head difference, approximately 200 to 300 feet in western Andrews County, suggests that the lower Dockum aquifer is receiving essentially no recharge from cross-formational flow (Nativ, 1988[2-25]). The primary limiting factors on recharge to the Dockum Group aquifer include the low-permeability aquitard characteristics of the upper Dockum Group and cut-off by the Pecos River Valley of historical recharge areas in eastern New Mexico.

Cenozoic Alluvium Aquifer

The Cenozoic Alluvium aquifer, also referred to as the Cenozoic Pecos Alluvium aquifer (Jones, 2001[2-15]), is regional in extent, but it is not present in the vicinity of the WCS CISF.

2.5.1 Salt Dissolution and Sink Holes

The proposed WCS CISF is located over Permian-age halite-bearing formations, and the possibility of dissolution and its effects on the long-term performance of the WCS CISF have to be considered. Robert M. Holt, PhD and Dennis W. Powers, PhD developed three conceptual hydrologic models of dissolution processes (shallow, deep and stratabound) based on experience and features found in the Delaware Basin west of the WCS CISF. Investigations showed that no features in the study area at and around the WCS CISF indicated any past dissolution, and the hydrologic systems at the site limit the potential for future dissolution and/or sinkholes. The full discussion and results of the study are detailed in “Evaluation of Halite Dissolution in the Vicinity of Waste Control Specialists Disposal Site, Andrews County, TX” and the report is located in Attachment F.

2.6 Geology And Seismology

2.6.1 Basic Geologic and Seismic Information

This section discusses the regional geology ascending from a depth of approximately 1400 feet, which includes the lowermost underground source of drinking water (USDW), to the ground surface. Figure 2-14 presents the Hobbs Sheet of the Geologic Atlas of Texas, 1:250,000 scale. The map shows surficial lithologic exposures, topography infrastructure and governmental boundaries in the area surrounding the WCS permitted area.

Two cross sections in the vicinity of the WCS CISF were created using boring logs from former site investigations. The locations of the cross sections are shown on Figure 2-15. Two cross sections in the vicinity of the WCS CISF are included as Figure 2-16 and Figure 2-17 and the associated boring logs are included in Attachment C.

The geologic formations of concern, beneath of the WCS CISF comprise, from oldest to youngest, the Triassic Dockum Group, the Cretaceous Trinity Group Antlers Formation, the Late Tertiary stratigraphic equivalent of the Ogallala Formation, the Late Tertiary/Quaternary Gatuña Formation or Cenozoic Alluvium (note that the Gatuña Formation and Cenozoic Alluvium are sometimes used interchangeably), the Pleistocene windblown sands of the Blackwater Draw Formation, Holocene windblown sands and playa deposits. A regional hard caliche pedisol, termed the Caprock caliche, developed on all pre-Quaternary formations before the Blackwater Draw sands were deposited.

A stratigraphic column for the above units is provided in Figure 2-13. This stratigraphic column adopts the nomenclature of Lehman (1994a[2-17], 1994b[2-18]) for the Dockum Group and includes the entire stratigraphic sequence typical of the Central Basin Platform of the west Texas Permian Basin (Bebout and Meador, 1985[2-2]).

The WCS CISF is located over the north-central portion of a prominent subsurface structural feature known as the Central Basin Platform. The Central Basin Platform is a deep-seated horst-like structure that extends northwest to southeast from southeastern New Mexico to eastern Pecos County, Texas. The Central Basin Platform is flanked on three sides by regional structural depressions known as the Delaware Basin to the southwest and the Midland Basin to the northeast, and by the Val Verde Basin to the south.

From the Cambrian to late Mississippian, west Texas and southeast New Mexico experienced mild structural deformation that produced broad regional arches and shallow depressions (Wright, 1979[2-37]). The Central Basin Platform served intermittently as a slightly positive feature during the early Paleozoic (Galley, 1958[2-9]). During the Mississippian and Pennsylvanian, the Central Basin Platform uplifted between ancient lines of weakness (Hills, 1985[2-13]), and the Delaware, Midland, and Val Verde Basins began to subside, forming separate basins.

Late Mississippian tectonic events uplifted and folded the platform and were followed by more intense late Pennsylvanian and early Permian deformation that compressed and faulted the area (Hills, 1963[2-12]). Highly deformed local structures formed ranges of mountains oriented generally parallel to the main axis of the platform (Wright, 1979[2-37]).

This period of intense late Paleozoic deformation was followed by a long period of gradual subsidence and erosion that stripped the Central Basin Platform and other structures to near base-level (Wright, 1979[2-37]) forming the Permian Basin. The expanding sea gradually encroached over broad eroded surfaces and truncated edges of previously deposited sedimentary strata. New layers of arkose, sand, chert pebble conglomerate and shale deposits accumulated as erosional products along the edges and on the flanks of both regional and local structures. Throughout the remainder of the Permian, the Permian Basin slowly filled with several thousand feet of evaporites, carbonates, and shales.

From the end of the Permian until late Cretaceous, there was relatively little tectonic activity except for periods of slight regional uplifting and downwarping. During the early Triassic, the region was slowly uplifted and slightly eroded. These conditions continued until the late Triassic, when gentle downwarping formed a large land-locked basin in which terrigenous deposits of the Dockum Group accumulated in alluvial floodplains and as deltaic and lacustrine deposits (McGowen, et al., 1979[2-21]). In Jurassic time, the area was again subject to erosion.

During Cretaceous time, a large part of the western interior of North America (including west Texas and southeastern New Mexico) was submerged by a large continental shelf sea. A thick sequence of Cretaceous rocks was deposited over most of the area. Locally, the Cretaceous sequence of sediments was comprised of a basal clastic unit (the Trinity, Antlers, or Paluxy sands) and overlying shallow marine carbonates.

Uplift from the west and southward and eastward–retreating Cretaceous seas were coincident with the Laramide Orogeny, which formed the Cordilleran Range west of the Permian Basin. The Laramide Orogeny uplifted the region to essentially its present position, supplying sediments for the nearby late Tertiary Ogallala Formation. The major episode of Laramide folding and faulting occurred in the late Paleocene. There have been no major tectonic events in North America since the Laramide Orogeny, except for a brief period of minor volcanism during the late Tertiary in northeastern New Mexico and in the Trans-Pecos area. Hills (1985)[2-13] suggests that slight Tertiary movement along Precambrian lines of weakness may have opened joint channels which allowed the circulation of groundwater into Permian evaporite layers. The near-surface regional structural controls may be locally modified by differential subsidence related to groundwater dissolution of Permian salt deposits (Gustavson, 1980[2-10]).

The Central Basin Platform is an area of moderate, low intensity seismic activity based on data obtained from the U.S. Geological Survey (USGS) Earthquake Data Base available from the National Earthquake Information Center (<http://neic.usgs.gov/>). Typical of the central U.S., there is a marked absence of mapped Quaternary faults and few of the known earthquakes can be associated with a specific geologic structure. In the 2014 U.S.G.S. National Hazard Maps, the site area was characterized as one of relatively low seismic hazard.

2.6.2 Vibratory Ground Motion

The WCS CISF lies in a region with crustal properties that indicate minimum risk due to faulting and seismicity. Crustal thickness is the most reliable predictor of seismic activity and faulting in intracratonic regions. Crustal thickness in the vicinity of the WCS CISF is approximately 30 miles (50 km), one of the three thickest crustal regions in North America (Mooney and Braile, 1989[2-22]). In comparison, the crustal thickness of the Rio Grande Rift is as little as 7.5 miles (12 km) in places.

In 2016, WCS completed a Probabilistic Seismic Hazard Evaluation using Nuclear Regulatory Commission (NRC) guidance for the WCS CISF. The Seismic Hazard Evaluation (Attachment D) was prepared under the technical supervision of Dr. Ivan Wong, head of Seismic Hazards Group, AECOM, Oakland, CA and the analysis was performed consistent with the professional standards of the Texas Board of Professional Geoscientists.

The objectives of the Seismic Hazard Analysis were to (1) estimate the levels of ground motions that could be exceeded at a specific annual frequency (or return period) at the site by performing a probabilistic seismic hazard analysis (PSHA), (2) incorporate the site-specific effects of the near-surface geology on the ground motions, and (3) develop Design Response Spectra (DRS) at the ground surface for the site and corresponding histories.

Significant earthquakes (moment magnitude [M] > 5.0), however have occurred in the site region including the 1992 M 5.0 Rattlesnake Canyon earthquake about 30 km from the WCS CISF. Some occurrences of induced seismicity have also proven to be spatially correlated to active hydrocarbon production in the region. Typical of the central U.S., there is a marked absence of Quaternary faults and few of the known earthquakes can be associated with a specific geologic structure. In the 2014 U.S. Geological Survey (USGS) National Hazard Maps, the site area was characterized as one of relatively low seismic hazard.

Spectral-analysis-of-surface-wave (SASW) surveys were performed at the WCS CISF by the University of Texas at Austin to obtain shear-wave velocity (V_s) profiles down to the Trujillo sandstone at a depth of about 600 feet.

To estimate ground motions, four Next Generation of Attenuation (NGA)-West2 ground motion prediction models for the western U.S. (WUS) and the EPRI (2013) [2-36] models for the central and eastern U.S. (CEUS) were utilized. For the NGA-West2 models, a time-averaged shear wave velocity (V_s) in the top 100 feet (V_{s30}) of 760 m/sec was used. The EPRI (2013) [2-36] ground motion models are defined for hard rock or a V_{s30} of 2,830 m/sec and greater. To address the epistemic uncertainty on which models are appropriate, both the NGA-West2 and EPRI (2013) [2-36] models were used in the PSHA weighted 0.60 and 0.40, respectively.

Based on the PSHA and the inputs of the seismic source model and ground motion models, seismic hazard curves for both firm and hard rock were calculated. The absence of late-Quaternary faulting and the low to moderate rate of background seismicity, even that associated with petroleum recovery activities, results in relatively low seismic hazard at the WCS site. The largest contributor to the hazard at the WCS CISF is the background seismicity (the Southern Great Plains seismic source zone and Gaussian smoothing).

A site response analysis was performed to estimate ground motions at the WCS CISF incorporating the site-specific geology. The hazard curves were weighted based on the weights assigned to the NGA-West2 and EPRI (2013) [2-36] ground motion models and a 10,000 year return period horizontal Uniform Hazard Spectrum (UHS) was calculated. A 10,000-year return period vertical UHS was also calculated using the NRC V/H ratios. On Table 3 in Attachment D is the horizontal and vertical UHS for a return period of 10,000 years. The ground surface design response spectrum peak horizontal acceleration for 0.01 seconds is 0.25 g and the vertical is 0.175 g.

Historic and recent seismic activity for the Texas regional area from 1973 to 2015 can be seen on Figure 2-18.

2.6.3 Surface Faulting

Two types of faulting were associated with early Permian deformation. Most of the faults were long, high-angle reverse faults with several hundred feet of vertical displacement that often involved the Precambrian basement rocks (Hills, 1985[2-13]; Bebout and Meador, 1985[2-2]). The second type of faulting is found along the western margin of the Central Basin Platform where long strike-slip faults, with displacements of tens of miles, are found (Hills, 1985[2-13]). All of the major faulting in the vicinity of the Central Basin Platform occurred in response to tectonic forces active before the global plate tectonic reorganization that created the North American continent (Bally et al., 1989[2-1]). The Paleozoic faults exhibit low natural microseismicity as a result of passive response to relatively low levels of tectonic stress in the trailing edge of the westward-drifting North American plate. The closest Quaternary faults are in the Guadalupe Mountains (Muehlberger, 1979[2-23]), about 100 miles southwest of the WCS CISF.

The large structural features of the Permian Basin are reflected only indirectly in the Mesozoic and Cenozoic rocks, as there has been virtually no tectonic movement within the basin since the Permian (Nicholson and Clebsch, 1961[2-27]). The Central Basin Platform is located approximately 7000 feet beneath the present land surface and the Permian and Triassic sediments drape over the top of the Platform structure. The faults that uplifted the platform do not appear to displace the younger Permian sediments. The northernmost fault, located at the Matador Uplift, terminates in lower Wolfcampian sediments.

The regional geologic and tectonic information does not indicate the presence of significant post-Permian faulting within the regional study area. Permian period with basin subsidence matching sediment accumulation. Post-Permian activity in the entire Permian Basin consisted of localized tectonic pulses. The basin has remained stable for the last 200 million years (Seismic Hazard Evaluation Attachment D).

Two regional stratigraphic cross section constructed in the vicinity of the WCS CISF using oil and gas well logs are shown as Figure 2-11 and Figure 2-12. The locations of the cross sections are also shown on the figures. These cross sections depict the major stratigraphic units that occur within about 2000 feet below ground surface in the vicinity of the WCS CISF. The stratigraphic units depicted on Figure 2-11 and Figure 2-12 include the upper Ogallala Antlers Gapuña unit of a few tens of feet in thickness, the underlying Triassic red beds of the Dockum Group with a thickness of 1,000 to 1,500 feet, the underlying Permian Dewey Lake Formation red beds, and the Permian evaporates of the Rustler and Salado Formations. These cross sections do not indicate the presence of significant faulting in the upper 2,000 feet of sediments within 3 to 4 miles of the WCS CISF.

The closest areas of faulting that affect Quaternary strata are faults associated with the Basin and Range physiographic province. Tectonically, Basin and Range faulting is associated with crustal extension and thinning in southwestern North America due to right lateral shear between the Pacific plate and the North American plate. This extension is the cause of the Rio Grande Rift, which is an area with numerous Quaternary faults located approximately 200 miles west of the WCS CISF.

The closest Quaternary faults listed in the United States Geological Survey (USGS) Quaternary Fault and Fold Database (<http://earthquakes.usgs.gov/qfaults>) are faults that are associated with the range-front of the Guadalupe Mountains and are located along the southwestern base of the mountain range. The closest Quaternary fault is an unnamed fault at the base of the Guadalupe Mountains, listed as fault No. 907 in the database and located approximately 104 miles southwest of the WCS CISF in Guadalupe Mountains National Park in Culberson County, Texas. This fault is a down-to-the-west range-bounding normal fault, with the most recent deformation estimated at less than 1.6 million years ago (Ma) (<http://earthquakes.usgs.gov/qfaults>). A second fault associated with this region is the Guadalupe Fault listed as fault No. 2058 and located 108 miles west of the WCS CISF in Chaves and Otero Counties, New Mexico. This fault may be the re-activation of a late Tertiary Basin and Range fault. The age of the faulted deposits have not been studied, but the oldest faulted strata are believed to be as old as the penultimate glaciation based on the stratigraphic sequence present, placing the oldest age of deformation at approximately 130 thousand years ago (ka). The most recent deformation of this fault is believed to be less than 15 ka. There are additional Quaternary faults located south of the two faults listed, along the southwestern base of the Guadalupe Mountains in Texas.

The next closest area of Quaternary faulting listed on the USGS Quaternary Fault and Fold Database is the Alamogordo fault, which is divided into three sections. The sections of the Alamogordo fault closest to the WCS CISF are fault Nos. 2045b and 2045c on the USGS Quaternary Fault and Fold Database. These faults are located approximately 170 miles west of the WCS CISF in Otero County, New Mexico. The Alamogordo fault is the range-bounding structure of the Sacramento Mountains. The faults are down-to-the west faults, much like those associated with the Guadalupe Mountain range. The most recent deformation is listed as less than 130 ka in the USGS Quaternary Fault and Fold Database. There is no surface evidence of quaternary faulting within the WCS property.

During landfill excavation activities at WCS an apparent southward-dipping reverse fault in a sandstone in the upper portion of the Triassic red beds of the original RCRA landfill excavation were located in 2004. Since regulatory criteria address the age of faults and the age of any geologic units affected or displaced by faulting, a geologic investigation of the fault was undertaken. The southeast wall of the RCRA landfill was extended about 200 feet to the southeast in May and June 2004, yielding about 60 feet of vertical geologic exposure along a length of about 400 feet. Two benches with subvertical walls were exposed. The relationship between faulting in the Triassic red beds and the overlying Cretaceous Antlers Formation was carefully evaluated to determine if any displacement of the younger Cretaceous deposits had occurred. The Triassic red beds are separated from the overlying Cretaceous Antlers Formation sands and gravels and from a layer of reworked altered clay by a distinct and mappable parting near the top of the gray altered layer of red beds. None of the observed fault planes or slip surfaces in the Triassic red beds in the extensively mapped section cross or offset the parting. In addition, the bedding in the Antlers Formation is continuous where observable and not calichified, and in particular, there are no indications that the Cretaceous-aged Antlers Formation was affected by the faulting in the Triassic red beds. Photos, figures and further details are included in the WCS LLRW License [2-31].

2.6.4 Stability of Subsurface Materials

In the area of the WCS CISF, surficial materials consist of topsoil, recent windblown sand and sands of the Blackwater Draw. A thin veneer of two feet or less of topsoil and windblown sand is present at the surface. The topsoil consists of brown silty sand that contains sparse vegetation debris and roots. The Blackwater Draw consists of sand that is reddish brown, fine to very fine grained, with minor amounts of clay and nodules of soft sandy caliche. Surficial material is underlain by a variable sequence of calcium carbonate-cemented caliche referred to as the caprock caliche. The caprock caliche forms the resistant beds of the Caprock escarpment along the western and eastern margins of the Southern High Plains (Gustavson and Finley, 1985[2-11]). A local surface exposure of the caprock was observed at Baker Spring. At this location, the caliche consists of: approximately six feet of white, highly fractured calcium carbonate cemented feldspathic and quartzitic silt and very fine grained sand; overlying approximately 12 feet of white and pinkish white, massive caliche with extensive concretionary nodule growths (i.e., pisolites) and feldspathic and quartzitic silt and very fine grained sand; resting on top of approximately six feet of pinkish white, calcium carbonate-cemented feldspathic and quartzitic silt, sand and gravel which becomes less cemented with depth. The lower six feet of caliche appears to be well-to-poorly cemented calcium carbonate. The caliche has an irregular basal contact and indicates a gradational transition into primarily uncemented sands and gravels below. The caliche horizon contains varying amounts of feldspathic and quartzitic silt, sand and gravel fragments with a general trend of decreased cementation and increased silt, sand and gravel content with depth.

The WCS CISF subsurface conditions were explored with eighteen soil borings (Geotechnical Engineering report from Geoservices in Attachment E). The boring locations and depths were selected by GEOservices and surveyed by WCS personnel (Attachment E Figures 3, 4, and 5). The soil test borings were advanced using a Cannon skid rig (air rotary) and a CME-55 track rig. N-values were recorded in the field and noted on the boring logs. Soil samples collected during drilling were sent to a lab for visual classification and laboratory testing including: Atterberg Limits; Natural Moisture Content; Particle Size Analysis; Resistivity of Soil; Consolidated Undrained Triaxial Test; Standard Proctor Moisture-Density Tests; California Bearing Ratio; and Consolidation.

At the surface of each of the eighteen soil test borings, residual soils were encountered to auger refusal and/or boring termination depths ranging from 25 to 45 feet below the existing surface elevation. The N-values of the standard penetration resistance test (SPT) were used to evaluate the relative consistency or density of the subsurface. The N-values for the subsurface materials ranged from 4 bpf to 100 blows per 1 inch of penetration, indicating a relative density of very loose to very dense. The relative density of the subsurface materials were most commonly medium dense to very dense. The standard penetration resistance values have likely been inflated due to the caliche.

The natural moisture content of the subsurface materials ranged from 2.5 to 9 percent. Atterberg limits testing on three selected residual samples revealed liquid limits (LL) ranging from 26 to 20 percent and each sample was non-plastic. Wash 200 tests performed on eight soil samples revealed 24 to 45 percent finer than the 200 sieve.

Shear wave velocities for the upper 100 feet below ground surface (bgs) range from 820.3 ft/sec to 23,383 ft/sec. The upper 10 feet of the site is a loose fill material and shear wave velocities for 0-10 feet bgs ranged from 820.3 ft/sec to 1,107 ft/sec. For 15 to 35 feet bgs, the shear wave velocities were 1302 to 1940 feet per second for a stratigraphic unit of silty sands, gravels, and caliche referred to as the Ogallala/Antlers/Gatuna formation (OAG). The Dockum Formation (dense clay) starts at 35 to 40 feet bgs beneath the OAG and shear wave velocities ranged from 2,058 feet/s to 3,383 ft/s. The results of the shear wave studies are located in Table 4 of the Geotechnical Exploration Report (Attachment E). The plot plan of the linear array is shown in Figure 12 of Appendix E of the Geotechnical Report (Attachment E). The engineering properties of site materials by strata, based on the geophysical survey investigation, are contained in Table 8 located in Appendix C of Attachment E.

During the geotechnical investigation, no water was encountered in any of the borings. There are no water table conditions anticipated beneath the site during facility construction and operations. Several monitor wells in the area are installed in the uppermost transmissive zone, and have been dry since installation in 2005 or 2008. The site is underlain by a northerly dipping lower confining unit. Since groundwater was not encountered in any of the 18 soil test borings and given that some of the borings penetrated as deep as 45 feet below the ground surface, it can be concluded that a liquefaction hazard does not exist for the proposed CISF.

The recommended allowable bearing capacity for design of the foundations is 3,000 pounds per square foot (psf) or less. A one-third increase in the allowable bearing capacity for all load conditions that include transient loads (wind, seismic, other short term loads) is permitted. The 33% increase in allowable bearing capacity (stress) can be applied to load combinations that consider transient loads in conjunction with dead loads. Calculations can be found in Appendix G of Attachment E. Calculations indicate a higher bearing capacity is possible; however, it is recommended to use a more conservative 3,000 pounds psf to avoid long term settlement. A summary table for the site characteristics geotechnical-related parameters can be found in Table 9 in Appendix D of Attachment E. Plans and profiles showing the extent of excavations and backfill are shown in Figure 2-26, Figure 2-31, Figure 2-32, and Figure 2-33.

2.6.5 Slope Stability

The WCS CISF site and surrounding area is nearly flat, so there is little possibility of landslides. Settling or slumping is unlikely because the geologic strata are well consolidated and surface soils have low moisture content. The semi-arid climate helps maintain low moisture content of the soils. Surface water is absent except during infrequent rainstorms.

2.6.6 Volcanism

There is minimal seismic and no volcanic activity near the WCS CISF. There is no evidence of tectonic or volcanic activity near the WCS CISF in the recent past.

2.7 Summary Of Site Conditions Affecting Construction And Operating Requirements

The WCS CISF site is located on the southwestern edge of the Southern High Plains, approximately 32 miles northwest of the City of Andrews. This part of Andrews County is a gently southeastward sloping plain with a natural slope of about 8 to 10 feet per mile. The finished grade of the WCS CISF is expected to be sloped gently with an anticipated elevation of 3,485 feet above msl. The WCS CISF site is currently undeveloped and the existing land surface is fairly flat with an average slope of 0.8 percent (%). The existing maximum and minimum elevations of the site are about 3520 feet and 3482 feet msl, respectively. The cover type is desert shrub. The existing WCS railroad is generally aligned parallel with and south of the proposed WCS CISF site boundary.

The entire WCS CISF, including the access road, is above the 100-year flood elevation. The northern most limit of the 100-year floodplain is approximately 4,000 feet southeast of the WCS CISF while the northernmost limits of the 500-year and PMP floodplains are 3965 feet and 3895 feet southeast of the WCS CISF, respectively.

A probabilistic seismic hazard analysis was performed to determine the design basis ground motion at the WCS CISF. The peak ground acceleration for a 10,000 year return period is 0.26 g.

Subsurface soils at the WCS CISF are suitable for supporting conventional foundations under both the static and dynamic loading conditions. There is no potential for liquefaction, collapse, or excessive settlement of these soils. There are no slopes, natural or manmade, close enough to the proposed WCS CISF facilities that their failure would adversely affect these facilities.

Storage overpacks will be used to store canisters containing spent fuel and GTCC waste. The canisters are drained of all liquid prior to being shipped to the WCS CISF. Therefore, liquid releases cannot result from operation of the WCS CISF.

The shallowest water bearing zone is about 225 feet deep at the WCS CISF. The method of storage (dry cask), the nature of the storage casks, the extremely low permeability of the red bed clay and the depth to groundwater beneath the WCS CISF preclude the possibility of groundwater contamination from the operation of the WCS CISF.

2.8 References

- 2-1 Bally, A.W., C.R. Scotese, and M.I. Ross, 1989, North America; Plate-Tectonic Setting and Tectonic Elements in The Geology of North America-An Overview: Volume A, Decade of North American Geology, p. 1-15, Geological Society of America, Boulder, Colorado.
- 2-2 Bebout, D.G., and K.J. Meador, 1985, Regional Cross Sections — Central Basin Platform, West Texas: The University of Texas at Austin, Bureau of Economic Geology, 4 p., 11 plates.
- 2-3 Blandford, T.N., D.J. Blazer, K.C. Calhoun, A.R. Dutton, T. Naing, R.C. Reedy, and B.R. Scanlin, 2003, Groundwater Availability of the Southern Ogallala Aquifer in Texas and New Mexico Numerical Simulations through 2050: Texas Water Development Board Draft Report, 160 p.
- 2-4 Bomar, G.W., 1995, Texas Weather, 2nd edition, University of Texas Press, Austin, Texas.
- 2-5 Bradley, R.G., and S. Kalaswad, 2003, The Groundwater Resources of the Dockum Aquifer in Texas: Texas Water Development Board Report 359, 73 p.
- 2-6 Cronin, J.G., 1969, Groundwater in the Ogallala Formation in the Southern High Plains of Texas and New Mexico: U.S. Geological Survey Hydrological Investigations HA-330, 9 p.
- 2-7 Dutton, A.R., 1995, Groundwater Isotopic Evidence for Paleorecharge in U.S. High Plains Aquifers: Quaternary Research 43, p. 221-231.
- 2-8 Dutton, A.R., and W.W. Simpkins, 1986, Hydrogeochemistry and Water Resources of the Triassic Lower Dockum Group in the Texas Panhandle and Eastern New Mexico: University of Texas at Austin, Bureau of Economic Geology Report of Investigations No. 161, 51 p.
- 2-9 Galley, J.E., 1958, Oil and Geology in the Permian Basin of Texas and New Mexico, in Habitat of Oil: American Association of Petroleum Geologists, p. 395-446.
- 2-10 Gustavson, T.C., 1980, Faulting and Salt Dissolution, in Geology and Geohydrology of the Palo Duro Basin, Texas Panhandle, A Report on the Progress of Nuclear Waste Isolation Feasibility Studies (1979): The University of Texas at Austin, Bureau of Economic Geology Circular 80-7, p.83-87.
- 2-11 Gustavson, T.C., and R.J. Finley, 1985, Late Cenozoic Geomorphic Evolution of the Texas Panhandle and Northeastern New Mexico: The University of Texas at Austin, Bureau of Economic Geology Report of Investigations No. 148, 42 p.
- 2-12 Hills, J.M., 1963, Late Paleozoic Tectonics and Mountain Ranges, Western Texas to Southern Colorado, American Association of Petroleum Geologists Bulletin, vol. 47, p. 1709-1724.
- 2-13 Hills, J.M., 1985, Structural Evolution of the Permian Basin of West Texas and New Mexico, in Structure and Tectonics of Trans-Pecos Texas: West Texas Geological Society, Field Conference Publication 85-81, p. 89-99.

- 2-14 Holzworth, G.C. "Mixing Heights, Wind Speeds, and Potential for Urban Air Pollution Throughout the Contiguous United States." U.S. Environmental Protection Agency, Office of Air Programs. January 1972.
- 2-15 Jones, I.C., 2001, Cenozoic Pecos Alluvium Aquifer, in *Aquifers of West Texas: Texas Water Development Board Report 356*, ed. R.E. Mace, W.F. Mullican III, and E.S. Angle, p. 120-134.
- 2-16 Lea County Solid Waste Authority. "Lea County Solid Waste Authority." <http://www.leacounty.net/SWA.html> (Accessed 2/16/2016).
- 2-17 Lehman, T.M, 1994a, The Saga of the Dockum Group and the Case of the Texas/New Mexico Boundary Fault: New Mexico Bureau of Mines and Mineral Resources, Bulletin 150, p. 37-51.
- 2-18 Lehman, T.M, 1994b, Save the Dockum Group!: West Texas Geological Society Bulletin 34(4), p. 5-10.
- 2-19 Louisiana Energy Services (LES). "National Enrichment Facility Environmental Report." Revision 4. NRC Docket No. 70-3103. April 2005.
- 2-20 Mace, R.E., 2001, Aquifers of West Texas: An Overview, in *Aquifers of West Texas: Texas Water Development Board Report 356*, ed. R.E. Mace, W.F. Mullican III, and E.S. Angle, p. 1-16.
- 2-21 McGowen, J.H., G.E. Granata, and S.J. Seni, 1979, Depositional Framework of the Lower Dockum Group (Triassic) Texas Panhandle: The University of Texas at Austin, Bureau of Economic Geology Report of Investigations No. 97, 60 p.
- 2-22 Mooney, W.D. and L.W. Braile, 1989, The Seismic Structure of the Continental Crust and Upper Mantel of North America in *The Geology of North America – An Overview: Volume A, Decade of North American Geology: Geological Society of America*, Boulder, CO, p. 39-52.
- 2-23 Muehlberger, W.R., 1979, The Areal Extent of Cenozoic Faulting in Trans-Pecos Texas. In *Cenozoic Geology of the Trans-Pecos Volcanic Field of Texas*, p 19-21.
- 2-24 Mullican, W.F., Ill, N.D. Johns, and A.E. Fryar, 1997, Playas and Recharge of the Ogallala Aquifer on the Southern High Plains of Texas — An Examination using Numerical Techniques: The University of Texas at Austin, Bureau of Economic Geology Report of Investigations No. 242, 72 p.
- 2-25 Nativ, R., 1988, Hydrogeology and Hydrochemistry of the Ogallala Aquifer, Southern High Plains, Texas Panhandle and Eastern New Mexico: The University of Texas at Austin, Bureau of Economic Geology Report of Investigations No. 177, 64 p.
- 2-26 Nativ, R. and G.N. Gutierrez, 1988, Hydrogeology and Hydrochemistry of Cretaceous Aquifers, Texas Panhandle and Eastern New Mexico: The University of Texas at Austin, Bureau of Economic Geology Geological Circular 88-3, 32 p.
- 2-27 NEF. (2005). *National Enrichment Facility. URENCO Environmental Report. Published in April 2005.*

- 2-28 Nicholson, A., Jr., and A. Clebsch, Jr., 1961, *Geology and Ground-Water Conditions in Southern Lea County, New Mexico*: New Mexico Bureau of Mines and Mineral Resources Ground-Water Report 6, Socorro, New Mexico, 123 p.
- 2-29 Permian Basin Materials. Personal communications between B.J. Oden, Permian Basin Materials, and J. Caldwell, Waste Control Specialists LLC February 16, 2016.
- 2-30 Sundance Services, Inc. Personal communications between A. Carrillo, Permian Basin Materials, and J. Caldwell, Waste Control Specialists LLC February 16, 2016.
- 2-31 Texas Commission on Environmental Quality Radioactive Material License No. R04100 Low Level. Amendment 29. *Radioactive Material License Amendment 29*. Issued in December 2015.
- 2-32 Texas Commission on Environmental Quality Radioactive Material License No. R05807. Amendment 09. Issued in January 2015.
- 2-33 Texas Commission on Environmental Quality Radioactive Material Permit No. 50397. Permit for Industrial Solid Waste Management Site. Issued in December 2008.
- 2-34 Texas Commission on Environmental Quality Radioactive Material Permit No. 50398. *Permit for Industrial Solid Waste Management Site*. Issued in October 2005.
- 2-35 Title 10, Code of Federal Regulations, Part 100, “Reactor Site Criteria.”
- 2-36 U.S. Environmental Protection Agency. “Green Book – Nonattainment Areas for Criteria Pollutants.” February 18, 2016.
- 2-37 Wright, W.F., 1979, *Petroleum Geology of the Permian Basin*: West Texas Geological Society Publication.
- 2-38 NUREG-1536, Revision 1, “Standard Review Plan for Spent Fuel Dry Cask Storage Systems at a General License Facility,” U.S. 200 Regulatory Commission, Office of Nuclear Material Safety and Safeguards.
- 2-39 NUREG-1567, “Standard Review Plan for Spent Fuel Dry Storage Facilities,” Revision 0, U.S. Nuclear Regulatory Commission, Office of Nuclear Material Safety and Safeguards, March 2000.
- 2-40 U.S. NRC Regulatory Guide 1.145, “Atmospheric Dispersion Models for Potential Accident Consequence Assessments at Nuclear Power Plants,” Revision 1, November 1982.
- 2-41 ASCE 7-10, “Minimum Design Loads for Buildings and Other Structures,” American Society of Civil Engineers (2010).

Table 2-1
Weather Stations Located Near the WCS CISF

Station	Distance and Direction from Proposed WCS CISF	Length of Record ⁽¹⁾	Station Elevation (meters)
Hobbs, New Mexico	32 kilometers (20 miles) north of WCS CISF	29 (1981-2010)	1,115
Jal, New Mexico	50 kilometers (31 miles) south of WCS CISF	29 (1981-2010)	947
Andrews, Texas	51 kilometers (32 miles) east of WCS CISF	29 (1981-2010)	967
Midland-Odessa, Texas	103 kilometers (64 miles) southeast of WCS CISF	29 (1981-2010)	1,118

Note:

1. Years of compiled data for climatological analysis.

Table 2-2
Summary of Maximum and Minimum Temperatures for Andrews, TX
Period of Record: 1962 to 2010

MONTH	MEAN MONTHLY TEMPERATURE		MEAN DAILY MAX. TEMPERATURE		MEAN DAILY MIN. TEMPERATURE		HIGHEST DAILY MAX. TEMPERATURE		LOWEST DAILY MIN TEMPERATURE	
	°C	°F	°C	°F	°C	°F	°C	°F	°C	°F
January	6.7	44.1	14.5	58.1	-1.1	30.1	29.4	85.0	-17.8	0.0
February	9.2	48.6	17.2	63.1	1.1	33.9	31.7	89.0	-18.3	-1.0
March	13.3	56.0	21.8	71.3	4.8	40.6	36.1	97.0	-13.3	8.0
April	18.2	64.7	26.8	80.2	9.4	49.0	37.2	99.0	-5.0	23.0
May	22.7	72.9	31.0	87.8	14.5	58.1	41.7	107.0	0.6	33.0
June	26.6	79.8	34.3	93.8	18.7	65.7	45.0	113.0	8.3	47.0
July	27.5	81.5	34.8	94.6	20.2	68.3	43.9	111.0	13.9	57.0
August	26.7	80.0	33.9	93.0	19.5	67.1	41.1	106.0	12.2	54.0
September	23.3	73.9	30.4	86.8	16.1	61.0	40.0	104.0	3.3	38.0
October	18.3	64.9	26.1	79.0	10.4	50.8	38.3	101.0	-5.6	22.0
November	11.8	53.2	19.4	67.0	4.1	39.4	33.9	93.0	-11.7	11.0
December	7.6	45.6	15.3	59.5	-0.2	31.7	27.2	81.0	-17.2	1.0
Annual	17.5	63.5	25.3	77.5	9.7	49.4	45.0	113.0	-18.3	-1.0

Source: www.wrcc.dri.edu

Table 2-3
Andrews, TX Period of Record Precipitation Data (1914-2006)

Precipitation CM (INCHES)	JANUARY	FEBRUARY	MARCH	APRIL	MAY	JUNE	JULY	AUGUST	SEPTEMBER	OCTOBER	NOVEMBER	DECEMBER	ANNUAL
Average	1.24 (0.49)	1.50 (0.59)	1.70 (0.67)	2.41 (0.95)	4.19 (1.65)	4.88 (1.92)	5.74 (2.26)	4.78 (1.88)	5.72 (2.25)	3.78 (1.49)	1.58 (0.62)	1.35 (0.53)	38.86 (15.30)
Maximum	11.40 (4.49)	6.40 (2.52)	8.46 (3.33)	13.67 (5.38)	14.91 (5.87)	18.06 (7.11)	30.23 (11.90)	14.00 (5.51)	20.17 (7.94)	16.16 (6.36)	8.00 (3.15)	7.80 (3.07)	78.66 (30.97)
Minimum	0.00 (0.00)	0.00 (0.00)	0.00 (0.00)	0.00 (0.00)	0.00 (0.00)	0.00 (0.00)	0.00 (0.00)	0.36 (0.14)	0.00 (0.00)	0.00 (0.00)	0.00 (0.00)	0.00 (0.00)	0.36 (0.14)
Max 24 Hr	5.61 (2.21)	2.54 (1.00)	4.70 (1.85)	6.30 (2.48)	7.62 (3.00)	9.40 (3.70)	19.30 (7.60)	6.10 (2.40)	8.90 (3.50)	5.21 (2.05)	5.33 (2.10)	3.94 (1.55)	19.30 (7.60)

Source: Reference [2-3/]

Table 2-4
Andrews, TX Period of Record Snow Data (1914-2006)

Snow CM (INCHES)	JANUARY	FEBRUARY	MARCH	APRIL	MAY	JUNE	JULY	AUGUST	SEPTEMBER	OCTOBER	NOVEMBER	DECEMBER	ANNUAL
Average	3.33 (1.31)	1.52 (0.60)	0.08 (0.03)	0.15 (0.06)	0.00 (0.00)	0.00 (0.00)	0.00 (0.00)	0.00 (0.00)	0.00 (0.00)	0.08 (0.03)	1.45 (0.57)	1.98 (0.78)	8.59 (3.38)
Maximum	25.40 (10.00)	17.78 (7.00)	2.54 (1.00)	6.35 (2.50)	0.00 (0.00)	0.00 (0.00)	0.00 (0.00)	0.00 (0.00)	0.00 (0.00)	2.54 (1.00)	35.56 (14.00)	13.97 (5.50)	52.07 (20.50)
Minimum	0.00 (0.00)	0.00 (0.00)	0.00 (0.00)	0.00 (0.00)	0.00 (0.00)	0.00 (0.00)	0.00 (0.00)	0.00 (0.00)	0.00 (0.00)	0.00 (0.00)	0.00 (0.00)	0.00 (0.00)	0.00 (0.00)
Max 24 Hr	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

Source: Reference [2-31]

Table 2-5
Average Morning and Afternoon Mixing Heights for Midland-Odessa, Texas

	Winter	Spring	Summer	Fall	Annual
Morning	290 meters (951 feet)	429 meters (1,407 feet)	606 meters (1,988 feet)	419 meters (1,375 feet)	436 meters (1,430 feet)
Afternoon	1,276 meters (4,186 feet)	2,449 meters (8,035 feet)	2,744 meters (9,003 feet)	1,887 meters (6,191 feet)	2,089 meters (6,854 feet)

Source: Reference [2-14]

Table 2-6
EPA National Ambient Air Quality Standards

Pollutant	EPA Standard Value	Standard Type
Carbon Monoxide (CO)		
8-hour Average	9 ppm	Primary
1-hour Average	35 ppm	Primary
Nitrogen Dioxide (NO₂)		
Annual Arithmetic Mean	0.053 ppm ⁽²⁾	Primary and Secondary
Ozone (O₃)		
8-hour Average	0.070 ppm ⁽³⁾	Primary and Secondary
Lead (Pb)		
Quarterly Average	1.5 g/m ³ ⁽¹⁾	Primary and Secondary
Particulate (PM₁₀)		
24-hour Average	150 µg/m ³	Primary and Secondary
Particulate (PM_{2.5})		
Annual Arithmetic Mean ⁽⁵⁾	12.0 µg/m ³	Primary
Annual Arithmetic Mean ⁽⁵⁾	15.0 µg/m ³	Secondary
24-hour average ⁽⁵⁾	35 µg/m ³	Primary and Secondary
Sulfur Dioxide (SO₂)		
3-hour Average	0.5 ppm	Secondary
1-hour Average	75 ppb ⁽⁴⁾	Primary

Notes

1. In areas designated nonattainment for the Pb standards prior to the promulgation of the current (2008) standards, and for which implementation plans to attain or maintain the current (2008) standards have not been submitted and approved, the previous standards (1.5 µg/m³ as a calendar quarter average) also remain in effect.
2. The level of the annual NO₂ standard is 0.053 ppm. It is shown here in terms of ppb for the purposes of clearer comparison to the 1-hour standard level.
3. Final rule signed October 1, 2015, and effective December 28, 2015. The previous (2008) O₃ standards additionally remain in effect in some areas. Revocation of the previous (2008) O₃ standards and transitioning to the current (2015) standards will be addressed in the implementation rule for the current standards.
4. The previous SO₂ standards (0.14 ppm 24-hour and 0.03 ppm annual) will additionally remain in effect in certain areas: (1) any area for which it is not yet 1 year since the effective date of designation under the current (2010) standards, and (2) any area for which implementation plans providing for attainment of the current (2010) standard have not been submitted and approved and which is designated nonattainment under the previous SO₂ standards or is not meeting the requirements of a SIP call under the previous SO₂ standards (40 CFR 50.4(3)). A SIP call is an EPA action requiring a state to resubmit all or part of its State Implementation Plan to demonstrate attainment of the require NAAQS.
5. Averaged over 3 years

Table 2-7
Atmospheric Dispersion Coefficients

Parameter	Normal/Off-Normal	Accident
Stability	D	F
$\overline{U_{10}}$ (m/sec)	5	1
A (m ²)	13.47	13.47
σ_y (m)	8	4
σ_z (m)	4.6	2.3
M	1.122	4
Equation 1 of [2-40] (sec/m ³)	1.635E-03	2.806E-02
Equation 2 of [2-40] (sec/m ³)	5.766E-04	1.153E-02
Equation 3 of [2-40] (sec/m ³)	1.542E-03	8.650E-03
χ/Q (sec/m ³)	1.542E-03	8.650E-03

Table 2-8
Projected Populations Based on Annual Percentage Growth Rate of 0.55%

Sector	2014 Estimated Residences¹	2014 Estimated Population²	Projected Population³				
			2024	2034	2044	2054	2064
<i>WNW</i>	2	6	6	7	7	7	8
<i>WSW</i>	18	49	52	55	58	61	64
Total		55	58	62	65	68	72

Source/Note:

- 1 Residences were identified based on 2014 aerial photos superimposed with concentric one-mile radius circles.
- 2 The 2014 estimated population was calculated by applying the average household size of 2.71 persons (based on 2010 Census data representing Census Tract 8/Block Group 2 in Lea County) to the number of residences identified on 2014 aerial.
- 3 The following projected population calculation was utilized: $[(0.55/100)+1]^{10} \times [(2014, 2024, 2034, 2044, \text{ or } 2054) \text{ Population}]$.

Table 2-9
Projected Populations Based on Annual Percentage Growth Rate of 2.4%

Sector	2014 Estimated Residences¹	2014 Estimated Population²	Projected Population³				
			2024	2034	2044	2054	2064
<i>WNW</i>	2	6	8	10	12	15	19
<i>WSW</i>	18	49	62	78	99	125	158
Total		55	70	88	111	140	177

Source/Note:

- 1 Residences were identified based on 2014 aerial photos superimposed with concentric one-mile radius circles.
- 2 The 2014 estimated population was calculated by applying the average household size of 2.71 persons (based on 2010 Census data representing Census Tract 8/Block Group 2 in Lea County) to the number of residences identified on 2014 aerial.
- 3 The following projected population calculation was utilized: $[(2.4/100)+1]^{10} \times [(2014, 2024, 2034, 2044, \text{ or } 2054) \text{ Population}]$.

Table 2-10
Projected Populations Based on Annual Percentage Growth Rate of 1.2%

Sector	2014 Estimated Residences¹	2014 Estimated Population²	Projected Population³				
			2024	2034	2044	2054	2064
<i>WNW</i>	2	6	7	8	9	10	11
<i>WSW</i>	18	49	55	62	70	79	89
<i>Total</i>		55	62	70	79	89	100

Source/Note:

- 1 Residences were identified based on 2014 aerial photos superimposed with concentric one-mile radius circles.
- 2 The 2014 estimated population was calculated by applying the average household size of 2.71 persons (based on 2010 Census data representing Census Tract 8/Block Group 2 in Lea County) to the number of residences identified on 2014 aerial.
- 3 The following projected population calculation was utilized: $[(1.2/100)+1]^{10} \times [(2014, 2024, 2034, 2044, \text{ or } 2054) \text{ Population}]$.

Table 2-11
Meteorological Tower Measurements

Parameter (Ht above Grnd)	Weather Station				Instrument Manufacturer
	Tower 1	ER Tower	WH East	WH West	
<i>Wind Spd (2 Meters)</i>	<i>X</i>	<i>X</i>			<i>Met One</i>
<i>Wind Spd (10 Meters)</i>	<i>X</i>	<i>X</i>			<i>Met One</i>
<i>Wind Spd (4 Meters)</i>			<i>X</i>	<i>X</i>	<i>Weather Hawk*</i>
<i>Wind Dir (2 Meters)</i>	<i>X</i>	<i>X</i>			<i>Met One</i>
<i>Wind Dir (10 Meters)</i>	<i>X</i>	<i>X</i>			<i>Met One</i>
<i>Wind Dir (4 Meters)</i>			<i>X</i>	<i>X</i>	<i>Weather Hawk*</i>
<i>Air Temp [°F] (2 Meters)</i>	<i>X</i>	<i>X</i>			<i>Met One</i>
<i>Air Temp [°F] (10 Meters)</i>	<i>X</i>	<i>X</i>			<i>Met One</i>
<i>Air Temp [°F] (4 Meters)</i>			<i>X</i>	<i>X</i>	<i>Weather Hawk*</i>
<i>Relative Humidity (2 Meters)</i>	<i>X</i>	<i>X</i>			<i>Met One</i>
<i>Relative Humidity (10 Meters)</i>	<i>X</i>	<i>X</i>			<i>Met One</i>
<i>Relative Humidity (4 Meters)</i>			<i>X</i>	<i>X</i>	<i>Weather Hawk*</i>
<i>Barometric Press (2 Meters)</i>	<i>X</i>	<i>X</i>			<i>Met One</i>
<i>Barometric Press (4 Meters)</i>			<i>X</i>	<i>X</i>	<i>Weather Hawk*</i>
<i>Solar Radiation (2 Meters)</i>	<i>X</i>	<i>X</i>			<i>Met One</i>
<i>Solar Radiation (4 Meters)</i>			<i>X</i>	<i>X</i>	<i>Weather Hawk*</i>
<i>Rain [Tip Bucket] (Ground)</i>	<i>X</i>	<i>X</i>			<i>Met One</i>
<i>Rain [Tip Bucket] (Ground)</i>			<i>X</i>	<i>X</i>	<i>Weather Hawk*</i>

Table 2-12
Meteorological Tower Sensors

Parameter	Sensor	Range	Accuracy	Resolution
WeatherHawk Series 500				
<i>Air Temperature</i>	<i>Capacitive Ceramic</i>	<i>-60 - +140 F</i>	<i>+/-0.9 F @ -40 to 125 F</i>	<i>0.1 F</i>
<i>Relative Humidity</i>	<i>Capacitive thin-film polymer</i>	<i>0-100%</i>	<i>+/- 3% @ 0-90%RH; +/-5% @ 90-100%RH</i>	<i>0.1%</i>
<i>Barometric Pressure</i>	<i>Capacitive Silicon</i>	<i>17.72-32.48 inHg (60-110 kPa)</i>	<i>0.15 inHg @ +32 to +86 F (+-.05 kPa @0-32 C)</i>	<i>.03 inHg @-60 to +140 F (+-.1 kPa @-52 to +60 C)</i>
<i>Solar Radiation</i>	<i>Silicon Pyranometer</i>	<i>300 to 1100 nm (Spectral Range)</i>	<i>Reproducibility +/-2%</i>	<i>Infinite</i>
<i>Rain</i>	<i>Piezoelectric</i>	<i>9.3 in² (collecting area)</i>	<i><5% (weather dependent)</i>	<i>.001 in</i>
<i>Wind Direction</i>	<i>Ultrasonic</i>	<i>0-360 deg (Azimuth)</i>	<i>+/- 2 deg</i>	<i>1 deg</i>
<i>Wind Speed</i>	<i>Ultrasonic</i>	<i>0-134 mph</i>	<i>+/- .67 mph (+/- 0.3m/s) or +/- 2% whichever is greater</i>	<i>.22 mph (0.1 m/s)</i>
Met One Towers				
<i>Air Temperature</i>	<i>Thermistor</i>	<i>-50 to +50 C</i>	<i>+/- 0.10 C</i>	<i>Analog Output with Infinite Resolution</i>
<i>Relative Humidity</i>	<i>Capacitive thin-film polymer</i>	<i>0-100%</i>	<i>+/-3% @ 0-10% and 90-100%; +/- 2% @ 10-90%</i>	<i>Analog Output with Infinite Resolution</i>
<i>Barometric Pressure</i>	<i>Active Solid-State Device</i>	<i>0-100%</i>	<i>+/-0.125% FS</i>	<i>Analog Output with Infinite Resolution</i>
<i>Solar Radiation</i>	<i>Pyranometer</i>	<i>0.4 to 0.7 micrometers</i>	<i>+/- 5%</i>	<i>Analog Output with Infinite Resolution</i>
<i>Rain</i>	<i>Dual-chambered tipping bucket that activates a reed switch</i>	<i>8 in² (collecting area)</i>	<i>@ 0.5 in/hour +/- 0.5%; @ 1 in to 3 in/hour +/- 1.0%</i>	<i>0.01 in</i>
<i>Wind Direction</i>	<i>Wire-wound potentiometer</i>	<i>0-360 deg</i>	<i>+/-5 deg</i>	<i>Analog Output with Infinite Resolution</i>
<i>Wind Speed</i>	<i>3-cup anemometer</i>	<i>0-125 mph</i>	<i>+/-1.5% or 0.25 mph</i>	<i>1.79 mph @ 1 sec; 0.03 mph @ 1 min</i>

Table 2-13
Summary of Maximum, Minimum, and 3-Day Average Temperatures (°F) for
Midland-Odessa, TX Period of Record: 2000-2015

<i>Year</i>	<i>Average Daily Temperature</i>	<i>Maximum 3-Day Average Temperature</i>	<i>Minimum 3-Day Average Temperature</i>	<i>Maximum Temperature</i>	<i>Minimum Temperature</i>
2000	65.4	90.3	27.5	108	16
2001	64.8	90.3	26.8	105	16
2002	63.8	90.3	31.8	106	17
2003	65.1	91.0	30.2	106	17
2004	63.6	85.8	25.8	103	16
2005	63.8	87.8	26.7	106	6
2006	65.4	88.7	30.7	105	14
2007	63.0	84.3	25.8	102	16
2008	64.2	89.5	31.5	106	14
2009	64.6	89.8	31.0	104	12
2010	63.9	88.2	28.5	109	15
2011	66.7	93.5	14.7	111	5
2012	67.1	90.0	35.3	107	18
2013	64.9	91.2	26.7	109	16
2014	65.5	89.0	26.3	105	13
2015	65.1	90.5	27.5	104	19
Avg.	64.8	89.4	27.9	106	14.4
Max	67.1	93.5	-	111	-
Min	63.0	-	14.7	-	5



Figure 2-1
WCS Facility Site Plan